

TEST REPORT

For

Mobile Phone

Model Number: RMX3261

FCC ID: 2AUYFRMX3261

Report Number : WT218001270

Test Laboratory : Shenzhen Academy of Metrology and Quality Inspection
Site Location : NETC Building, No.4 Tongfa Rd., Xili, Nanshan, Shenzhen, China
Tel : 0086-755-86928965
Fax : 0086-755-86009898-31396
Web : www.smq.com.cn
E-mail : emcrf@smq.com.cn

TEST REPORT DECLARATION

Applicant : Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address : No.178 Yulong Avenue, Yufengshan, Yubei District,
Chongqing, China
Manufacturer : Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address : No.178 Yulong Avenue, Yufengshan, Yubei District,
Chongqing, China
EUT Description : Mobile Phone
Model No. : RMX3261
Trade mark : realme
Serial Number : /
FCC ID : 2AUYFRMX3261

Test Standards:

FCC Part 15 Subpart C 15.247 (2019)

The EUT described above is tested by Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory to determine the maximum emissions from the EUT. Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory is assumed full responsibility for the accuracy of the test results.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.




Project Engineer:  Date: May.24, 2021
(Zhou Fangai 周芳媛)
Checked by:  Date: May.24, 2021
(Shi Changda 施昌达)
Approved by:  Date: May.24, 2021
(Lin Yixiang 林奕翔)

TABLE OF CONTENTS

| | |
|--|-----------|
| TEST REPORT DECLARATION | 2 |
| 1. TEST RESULTS SUMMARY | 5 |
| 2. GENERAL INFORMATION | 6 |
| 2.1. Report Information | 6 |
| 2.2. Laboratory Accreditation and Relationship to Customer | 6 |
| 2.3. Measurement Uncertainty..... | 7 |
| 3. PRODUCT DESCRIPTION | 8 |
| 3.1. EUT Description | 8 |
| 3.2. Related Submittal(s) / Grant (s) | 8 |
| 3.3. Block Diagram of EUT Configuration | 8 |
| 3.4. Operating Condition of EUT | 8 |
| 3.5. Directional Antenna Gain | 9 |
| 3.6. Support Equipment List..... | 9 |
| 3.7. Test Conditions..... | 9 |
| 3.8. Special Accessories..... | 9 |
| 3.9. Equipment Modifications..... | 9 |
| 4. TEST EQUIPMENT USED | 10 |
| 5. 6DB BANDWIDTH MEASUREMENT | 11 |
| 5.1. Limits of 6dB Bandwidth Measurement..... | 11 |
| 5.2. Test Procedure | 11 |
| 5.3. Test Setup | 11 |
| 5.4. Test Data | 11 |
| 6. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT | 14 |
| 6.1. Limits of Maximum Conducted Output Power Measurement | 14 |
| 6.2. Test Procedure | 14 |
| 6.3. Test Setup | 14 |
| 6.4. Test Data | 14 |
| 7. MAXIMUM POWER SPECTRAL DENSITY LEVEL MEASUREMENT | 17 |
| 7.1. Limits of Maximum Power Spectral Density Level Measurement | 17 |
| 7.2. Test Procedure | 17 |
| 7.3. Test Data | 17 |
| 8. CONDUCTED BANDEDGE AND SPURIOUS MEASUREMENT | 20 |
| 8.1. Limits of Conducted Bandedge and Spurious Measurement | 20 |
| 8.2. Test Procedure | 20 |
| 8.3. Test Data | 20 |
| 9. RADIATED BANDEDGE AND SPURIOUS MEASUREMENT | 29 |
| 9.1. Limits of Radiated Bandedge and Spurious Measurement | 29 |
| 9.2. Test Procedure | 29 |
| 9.3. Test Data | 29 |
| 10. CONDUCTED EMISSION TEST FOR AC POWER PORT MEASUREMENT | 47 |
| 10.1. Test Standard and Limit..... | 47 |
| 10.2. Test Procedure | 47 |

| | | |
|------------|-----------------------------------|-----------|
| 10.3. | Test Arrangement | 47 |
| 10.4. | Test Data | 47 |
| 11. | ANTENNA REQUIREMENTS | 50 |
| 11.1. | Applicable Requirements | 50 |
| 11.2. | Antenna Connector | 50 |
| 11.3. | Antenna Gain | 50 |

1. TEST RESULTS SUMMARY

Table 1 Test Results Summary

| Test Items | FCC Rules | Test Results |
|---|--------------------------------|--------------|
| 6dB DTS Bandwidth | 15.247 (a) (2) | Pass |
| Maximum Peak Conducted Power | 15.247 (b) (3) | Pass |
| Maximum Power Spectral Density Level | 15.247 (e) | Pass |
| Conducted Bandedge and Spurious | 15.247 (d) | Pass |
| Radiated Bandedge and Spurious | 15.247 (d) 15.209 15.205 | Pass |
| Conducted Emission Test for AC Power Port | 15.207 | Pass |
| Antenna Requirements | 15.203 | Pass |

Remark: "N/A" means "Not applicable."

2. GENERAL INFORMATION

2.1. Report Information

This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that SMQ approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that SMQ in any way guarantees the later performance of the product/equipment.

The sample/s mentioned in this report is/are supplied by Applicant, SMQ therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through SMQ, unless the applicant has authorized SMQ in writing to do so.

The lab will not be liable for any loss or damage resulting for false, inaccurate, inappropriate or incomplete product information provided by the applicant/manufacturer.

2.2. Laboratory Accreditation and Relationship to Customer

The testing report were performed by the Shenzhen Academy of Metrology and quality Inspection EMC Laboratory (Guangdong EMC compliance testing center), in their facilities located at NETC Building, No.4 Tongfa Rd., Xili, Nanshan, Shenzhen, China. At the time of testing, Laboratory is accredited by the following organizations:

China National Accreditation Service for Conformity Assessment (CNAS) accredits the Laboratory for conformance to FCC standards, EMC international standards and EN standards. The Registration Number is CNAS L0579.

The Laboratory is Accredited Testing Laboratory of FCC with Designation number CN1165 and Site registration number 582918.

The Laboratory is registered to perform emission tests with Innovation, Science and Economic Development (ISED), and the registration number is 11177A.

The Laboratory is registered to perform emission tests with VCCI, and the registration number are C-20048, G20076, R-20077, R-20078 and T-20047.

The Laboratory is Accredited Testing Laboratory of American Association for Laboratory Accreditation (A2LA) and certificate number is 3292.01.

2.3. Measurement Uncertainty

Conducted Emission

9 kHz~150 kHz 3.7dB

150 kHz~30MHz 3.3dB

Radiated Emission

30MHz~1000MHz 4.3dB

1GHz~6GHz 4.6 dB

6GHz~18GHz 5.1dB

18GHz~26.5GHz 5.1dB

3. PRODUCT DESCRIPTION

NOTE: The extreme test conditions for temperature and antenna gain were declared by the manufacturer.

3.1. EUT Description

- Description : Mobile Phone
- Manufacturer : Realme Chongqing Mobile Telecommunications Corp., Ltd.
- Model Number : RMX3261
- Operate Frequency : 2.402GHz~2.480GHz
- Antenna Designation : PIFA Antenna
- Operating voltage : DC3.6V (Low)/DC3.87V (Nominal)/DC4.45V (Max)
- Software Version : Android11
- Hardware Version : 11

Remark: 1. There are three adapters, only the worst data of OP52YAUH (1#) shown in this report.

2. There are three batteries, only the worst data of BLP729 (2#) shown in this report.

Bluetooth Low Energy:

Table 2 Working Frequency List

| Regulatory Range | RF Channels |
|------------------|------------------------------|
| 2.400-2.4835 GHz | f=2402+k*2 MHz, k=0, ... ,39 |

3.2. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **2AUYFRMX3261** filing to comply with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

3.3. Block Diagram of EUT Configuration



Figure 1 EUT setup

3.4. Operating Condition of EUT

Worst-case mode and channel used for 30-1000 MHz radiated and power line conducted emissions was the mode and channel with the highest output power.

Worst-case data rates as provided by the client were:

Bluetooth low energy

Test mode is configured to be with duty cycle >98%

3.5. Directional Antenna Gain

The EUT does NOT support a WIFI MIMO function.
Directional gain need NOT to be considered.

3.6. Support Equipment List

Table 3 Support Equipment List

| Name | Model No | S/N | Manufacturer |
|---|----------|-----|--------------------------------------|
| Adaptor 1# for EUT | OP52YAUH | -- | Jiangsu Chenyang Electron CO.,Ltd. |
| Adaptor 2# for EUT | OP52KAUH | -- | ShenZhen KunXing Technology Co., Ltd |
| Adaptor 3# for EUT | OP52JAUH | -- | Ten Pao Industrial Co., Ltd. |
| Rechargeable Li-Ion Polymer Battery 1# for EUT | BLP729 | --- | Huizhou Desay Battery Co., Ltd |
| Rechargeable Li-Ion Polymer Battery 2# for EUT | BLP729 | --- | SUNWODA Electronic Co., Ltd. |
| Rechargeable Li-Ion Polymer Battery 3# for EUT | BLP729 | --- | TWS Technology (Guangzhou) Limited |
| USB for EUT | DL122 | --- | -- |

3.7. Test Conditions

Date of test : Apr.30, 2021- May.20, 2021
Date of EUT Receive : Apr.29, 2021
Temperature: 20°C-21°C
Relative Humidity: 42%-52%

3.8. Special Accessories

Not available for this EUT intended for grant.

3.9. Equipment Modifications

Not available for this EUT intended for grant.

4. TEST EQUIPMENT USED

Table 4 Test Equipment

| No. | Equipment | Manufacturer | Model No. | Last Cal. | Cal. Interval |
|-----------|-------------------|--------------|-----------|-------------|---------------|
| SB9058/05 | Test Receiver | R&S | ESCI 3 | Sep.25,2020 | 1 Year |
| SB4357 | AMN | R&S | ENN216 | Aug.26,2020 | 1 Year |
| SB17366 | Test Receiver | R&S | ESR26 | Jul.09,2020 | 1 Year |
| SB3955 | Broadband Antenna | Schwarzbeck | VULB9163 | Jan.05,2021 | 1 Year |
| SB8501/09 | Test Receiver | R&S | ESU40 | Feb.05,2021 | 1 Year |
| SB3435 | Horn Antenna | R&S | HF906 | Dec.16,2020 | 1 Year |
| SB9054/08 | Broadband Antenna | Schwarzbeck | VULB 9163 | Jan.05,2021 | 1 Year |
| SB9058/03 | Pre-Amplifier | R&S | SCU 18 | Feb.05,2021 | 1 Year |
| SB8501/10 | Horn Antenna | R&S | 3160-09 | Mar.10,2020 | 3 Years |
| SB8501/11 | Horn Antenna | R&S | 3160-09 | Mar.09,2020 | 3 Years |
| SB8501/12 | Horn Antenna | R&S | 3160-10 | Mar.17,2020 | 3 Years |
| SB8501/13 | Horn Antenna | R&S | 3160-10 | Mar.10,2020 | 3 Years |
| SB8501/14 | Pre-Amplifier | R&S | SCU-03 | Feb.05,2021 | 1 Year |
| SB8501/15 | Pre-Amplifier | R&S | SCU-03 | Feb.05,2021 | 1 Year |
| SB8501/16 | Pre-Amplifier | R&S | SCU 26 | Feb.05,2021 | 1 Year |
| SB8501/17 | Pre-Amplifier | R&S | SCU-18 | Feb.05,2021 | 1 Year |
| SB8501/17 | Pre-Amplifier | R&S | SCU-18 | Feb.14,2020 | 1 Year |
| SB7941/02 | Spectrum Analyzer | R&S | FSU26 | May.18,2020 | 1 Year |

Table 5 Test software

| Name | Manufacturer | Version |
|--------------------------------|------------------------------|-------------|
| Bluetooth and WiFi Test System | Shenzhen JS tonscond co.,ltd | 2.6.88.0330 |

5. 6DB BANDWIDTH MEASUREMENT

5.1.Limits of 6dB Bandwidth Measurement

CFR 47 (FCC) part 15.247 (a) (2), 558074 D01 DTS Meas Guidance v05r02

5.2.Test Procedure

The transmitter output was connected to the spectrum analyzer.

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.Test Setup




5.4.Test Data

Table 6 6dB Bandwidth Test Data BLE


| Test Mode | Channel Frequency [MHz] | 6dB Bandwidth [MHz] | Limit [MHz] | Result |
|---------------|-------------------------|---------------------|-------------|--------|
| BLE_5.0_1Mbps | 2402 | 0.672 | ≥ 0.50 | Pass |
| | 2440 | 0.668 | ≥ 0.50 | Pass |
| | 2480 | 0.668 | ≥ 0.50 | Pass |
| BLE_5.0_2Mbps | 2402 | 1.140 | ≥ 0.50 | Pass |
| | 2440 | 1.140 | ≥ 0.50 | Pass |
| | 2480 | 1.128 | ≥ 0.50 | Pass |

BLE_5.0_1Mbps_2402 MHz




Date: 11.MAY.2021 12:32:23

BLE_5.0_1Mbps_2440 MHz




Date: 11.MAY.2021 12:36:17

BLE_5.0_1Mbps_2480 MHz




Date: 11.MAY.2021 12:38:42

BLE_5.0_2Mbps_2402 MHz




Date: 11.MAY.2021 12:40:55

BLE_5.0_2Mbps_2440 MHz



Date: 11.MAY.2021 12:43:07

BLE_5.0_2Mbps_2480 MHz



Date: 11.MAY.2021 12:44:56

6. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT

6.1.Limits of Maximum Conducted Output Power Measurement


CFR 47 (FCC) part 15.247 (b) (3), 558074 D01 DTS Meas Guidance v05r02

6.2. Test Procedure

The transmitter output was connected to the spectrum analyzer.

- a)Set the RBW \geq DTS bandwidth.
- b)Set VBW \geq 3 x RBW.
- c)Set span \geq 3 x RBW
- d)Sweep time = auto couple.
- e)Detector = peak.
- f)Trace mode = max hold.
- g)Allow trace to fully stabilize.
- h)Use peak marker function to determine the peak amplitude level.

6.3. Test Setup




6.4. Test Data

Table 7 Maximum Conducted Output Power Test Data BLE


| Test Mode | Center Freq. [MHz] | Meas. Level (Cond.) [dBm] | Limit [dBm] | Result |
|---------------|--------------------|---------------------------|-------------|--------|
| BLE_5.0_1Mbps | 2402 | 5.99 | ≤ 30 | Pass |
| | 2440 | 5.73 | ≤ 30 | Pass |
| | 2480 | 5.17 | ≤ 30 | Pass |
| BLE_5.0_2Mbps | 2402 | 6.06 | ≤ 30 | Pass |
| | 2440 | 5.73 | ≤ 30 | Pass |
| | 2480 | 5.19 | ≤ 30 | Pass |

BLE_5.0_1Mbps_2402 MHz




Date: 11.MAY.2021 12:32:43

BLE_5.0_1Mbps_2440 MHz




Date: 11.MAY.2021 12:36:37

BLE_5.0_1Mbps_2480 MHz




Date: 11.MAY.2021 12:39:03

BLE_5.0_2Mbps_2402 MHz




Date: 11.MAY.2021 12:41:16

BLE_5.0_2Mbps_2440 MHz



Date: 11.MAY.2021 12:43:27

BLE_5.0_2Mbps_2480 MHz



Date: 11.MAY.2021 12:45:16

7. MAXIMUM POWER SPECTRAL DENSITY LEVEL MEASUREMENT

7.1.Limits of Maximum Power Spectral Density Level Measurement

CFR 47 (FCC) part 15.247 (e) , 558074 D01 DTS Meas Guidance v05r02

7.2.Test Procedure

The transmitter output was connected to the spectrum analyzer.


- a)Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h)Allow trace to fully stabilize.
- i)Use the peak marker function to determine the maximum amplitude level within the RBW.
- j)If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.3.Test Data

Table 8 Maximum Power Spectral Density Level Test Data BLE


| Test Mode | Freq.[MHz] | PSD [dBm] | Limit [dBm] | Result |
|---------------|------------|-----------|-------------|--------|
| BLE_5.0_1Mbps | 2402 | -3.34 | ≤ 8 | Pass |
| | 2440 | -3.62 | ≤ 8 | Pass |
| | 2480 | -4.15 | ≤ 8 | Pass |
| BLE_5.0_2Mbps | 2402 | -5.85 | ≤ 8 | Pass |
| | 2440 | -6.11 | ≤ 8 | Pass |
| | 2480 | -6.61 | ≤ 8 | Pass |

BLE_5.0_1Mbps_2402 MHz




Date: 11.MAY.2021 12:33:03

BLE_5.0_1Mbps_2440 MHz




Date: 11.MAY.2021 12:36:56

BLE_5.0_1Mbps_2480 MHz




Date: 11.MAY.2021 12:39:22

BLE_5.0_2Mbps_2402 MHz




Date: 11.MAY.2021 12:41:35

BLE_5.0_2Mbps_2440 MHz



Date: 11.MAY.2021 12:43:46

BLE_5.0_2Mbps_2480 MHz



Date: 11.MAY.2021 12:45:35

8. CONDUCTED BANDEDGE AND SPURIOUS MEASUREMENT

8.1.Limits of Conducted Bandedge and Spurious Measurement

CFR 47 (FCC) part 15.247 (d) and 558074 D01 DTS Meas Guidance v05r02

8.2. Test Procedure

The transmitter output was connected to the spectrum analyzer.

Establish a reference level by using the following procedure:

- a)Set instrument center frequency to DTS channel center frequency.
- b)Set the span to ≥ 1.5 times the DTS bandwidth.
- c)Set the RBW = 100 kHz.
- d)Set the VBW $\geq 3 \times$ RBW.
- e)Detector = peak.
- f)Sweep time = auto couple.
- g)Trace mode = max hold.
- h)Allow trace to fully stabilize.
- i)Use the peak marker function to determine the maximum PSD level.


Emission level measurement

- a)Set the center frequency and span to encompass frequency range to be measured.
- b)Set the RBW = 100 kHz.
- c)Set the VBW $\geq 3 \times$ RBW.
- d)Detector = peak.
- e)Ensure that the number of measurement points \geq span/RBW
- f)Sweep time = auto couple.
- g)Trace mode = max hold.
- h)Allow trace to fully stabilize.
- i)Use the peak marker function to determine the maximum amplitude level.

8.3. Test Data


BLE_5.0_1Mbps

Band Edge




BLE_5.0_2Mbps

Band Edge




Conducted Spurious Emission


BLE_5.0_1Mbps
Low Channel



Mid. Channel




High Channel




Conducted Spurious Emission


BLE_5.0_2Mbps
Low Channel



Mid. Channel



High Channel



9. RADIATED BANDEDGE AND SPURIOUS MEASUREMENT

9.1.Limits of Radiated Bandedge and Spurious Measurement

CFR 47 (FCC) part 15.247 (d) and 558074 D01 DTS Meas Guidance v05r02

9.2.Test Procedure

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. For measurement below 1GHz, the EUT was placed on a turntable with 0.8meter, above ground. For measurement above 1 GHz, test at FAR, the EUT is placed on a non-conductive table, which is 1.5 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f > 1$ GHz for peak measurement. Set RBW = 1 MHz, and 1/T (on time) for average measurement.

9.3.Test Data

9 kHz-30 MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Table 9 Radiated Emission Test Data 9k Hz-30MHz

| Frequency (MHz) | Cable Loss +preamp (dB) | Antenna Factor (dB) | Reading (dBµV/m) | Level (dBµV/m) | Polarity (H/V) | Limit (dBµV/m) | Margin (dB) | Note |
|-----------------|-------------------------|---------------------|------------------|----------------|----------------|----------------|-------------|------|
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |

30 MHz-1 GHz

Worst case is shown below for 30MHz-1GHz only.

The emissions don't show in following result tables are more than 20dB below the limits.


Table 10 Radiated Emission Test Data 30MHz-1GHz

| Frequency (MHz) | Cable Loss +preamp (dB) | Antenna Factor (dB) | Reading (dBµV/m) | Level (dBµV/m) | Polarity (Horizontal/ Vertical) | Limit (dBµV/m) | Margin (dB) | Note |
|-----------------|-------------------------|---------------------|------------------|----------------|---------------------------------|----------------|-------------|------|
| 30.099 | 0.6 | 12.3 | 20.3 | 33.2 | Vertical | 40 | 6.8 | QP |
| 32.910 | 0.7 | 12.3 | 14.6 | 27.6 | Vertical | 40 | 12.4 | QP |
| 66.181 | 0.9 | 10.7 | 13.7 | 25.3 | Vertical | 40 | 14.7 | QP |
| 175.500 | 1.5 | 9.0 | 20.6 | 31.1 | Vertical | 43.5 | 12.4 | QP |
| 185.006 | 1.5 | 9.7 | 20.7 | 31.9 | Vertical | 43.5 | 11.6 | QP |
| 198.489 | 1.6 | 10.6 | 19.2 | 31.4 | Vertical | 43.5 | 12.1 | QP |
| 30.097 | 0.6 | 12.3 | 17.0 | 29.9 | Horizontal | 40 | 10.1 | QP |
| 55.705 | 0.9 | 13.0 | 8.5 | 22.4 | Horizontal | 40 | 17.6 | QP |
| 184.036 | 1.5 | 9.7 | 16.0 | 27.2 | Horizontal | 43.5 | 16.3 | QP |
| 196.937 | 1.7 | 10.6 | 14.6 | 26.9 | Horizontal | 43.5 | 16.6 | QP |
| 292.579 | 2.0 | 12.7 | 11.7 | 26.4 | Horizontal | 46 | 19.6 | QP |
| 211.681 | 1.8 | 10.6 | 13.7 | 26.1 | Horizontal | 43.5 | 17.4 | QP |


Remark: Emission level (dBµV)=Read Value(dBµV/m) + Antenna Factor(dB)+ Cable Loss +preamp(dB)

30MHz-1GHz

Horizontal




Vertical




1-18 GHz

BLE_5.0_1Mbps CH0
Horizontal




Vertical




1-18 GHz

BLE_5.0_1Mbps BLE CH19
Horizontal




Vertical




1-18 GHz

BLE_5.0_1Mbps BLE CH39
Horizontal




Vertical




1-18 GHz

BLE_5.0_2Mbps CH0
Horizontal




Vertical




1-18 GHz

BLE_5.0_2Mbps CH19
Horizontal




Vertical




1-18 GHz

BLE_5.0_2Mbps CH39
Horizontal




Vertical




18-26.5 GHz

No Peak found in pre-scan, only worst case result is listed in this report.
Horizontal





Vertical





Band Edge
BLE_5.0_1Mbps BLE CH0

Horizontal





Vertical





Band Edge
BLE_5.0_1Mbps BLE CH39

Horizontal





Vertical





Band Edge
BLE_5.0_2Mbps BLE CH0

Horizontal





Vertical





Band Edge
BLE_5.0_2Mbps BLE CH39

Horizontal



Vertical



10. CONDUCTED EMISSION TEST FOR AC POWER PORT MEASUREMENT

10.1. Test Standard and Limit

10.1.1. Test Standard

FCC Part 15.207

10.1.2. Test Limit

Table 11 Conducted Emission Test Limit

| Frequency | Maximum RF Line Voltage (dB μ V) | |
|---------------|--------------------------------------|---------------|
| | Quasi-peak Level | Average Level |
| 150kHz~500kHz | 66 ~ 56 * | 56 ~ 46 * |
| 500kHz~5MHz | 56 | 46 |
| 5MHz~30MHz | 60 | 50 |

* Decreasing linearly with logarithm of the frequency

* The lower limit shall apply at the transition frequency.

10.2. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver is used to test the emissions from both sides of AC line. According to the requirements of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

The bandwidth of EMI test receiver is set at 9 kHz.

10.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

10.4. Test Data


The emissions don't show in below are too low against the limits. Refer to the test curves.

Table 12 Conducted Emission Test Data


| Test mode: Charging and Transmitting | | | | | | | | |
|--------------------------------------|-----------------|------------------------|----------------------|-----------------------------|--------------------|----------------------|-----------------------------|--------------------|
| | Frequency (MHz) | Correction Factor (dB) | Quasi-Peak | | | Average | | |
| | | | Reading (dB μ V) | Emission Level (dB μ V) | Limit (dB μ V) | Reading (dB μ V) | Emission Level (dB μ V) | Limit (dB μ V) |
| Line | 0.150 | 9.7 | 36.2 | 45.9 | 66 | 21.0 | 30.7 | 56 |
| | 0.191 | 9.7 | 32.7 | 42.4 | 64.0 | 18.5 | 28.2 | 54.0 |
| | 0.159 | 9.7 | 37.0 | 46.7 | 65.5 | 17.5 | 27.2 | 55.5 |
| | 0.429 | 9.7 | 29.8 | 39.5 | 57.3 | 21.9 | 31.6 | 47.3 |
| | 0.474 | 9.7 | 30.6 | 40.3 | 56.4 | 23.5 | 33.2 | 46.4 |
| | 0.515 | 9.8 | 30.8 | 40.6 | 56 | 21.3 | 31.1 | 46 |
| Neutral | 0.150 | 9.7 | 36.3 | 46.0 | 66 | 20.7 | 30.4 | 56 |
| | 0.186 | 9.7 | 32.7 | 42.4 | 64.2 | 16.2 | 25.9 | 54.2 |
| | 0.195 | 9.7 | 31.7 | 41.4 | 63.8 | 19.5 | 29.2 | 53.8 |
| | 0.438 | 9.7 | 23.0 | 32.7 | 57.1 | 9.7 | 19.4 | 47.1 |
| | 0.474 | 9.7 | 27.1 | 36.8 | 56.4 | 20.6 | 30.3 | 46.4 |
| | 0.533 | 9.8 | 27.1 | 36.9 | 56 | 13.9 | 23.7 | 46 |

- REMARKS: 1. Emission level (dB μ V) =Read Value (dB μ V) + Correction Factor (dB)
 2. Correction Factor (dB) =LISN Factor (dB) + Cable Factor (dB) +Limiter Factor (dB)
 3. The other emission levels were very low against the limit.

Line



Neutral



11. ANTENNA REQUIREMENTS

11.1. Applicable Requirements

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

11.2. Antenna Connector

Antenna Connector is on the PCB within enclosure and not accessible to user.

11.3. Antenna Gain

The antenna gain of EUT is less than 6 dBi.

-----End of Report-----