

FCC RF EXPOSURE REPORT

FCC ID: 2AUYFRMX3286

Project No. : 2110C043A
Equipment : Mobile Phone
Brand Name : realme
Test Model : RMX3286
Series Model : N/A
Applicant : Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address : No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China
Manufacturer : Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address : No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China
Date of Receipt : Oct. 25, 2021
Date of Test : Oct. 26, 2021 ~ Nov. 17, 2021
Issued Date : Dec. 02, 2021
Report Version : R00
Test Sample : Engineering Sample No.: DG20211022144 for conducted,
DG20211022145 for radiated.
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & KDB447498 D01

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Vincent Tan

Prepared by : Vincent Tan

Ethan Ma

Approved by : Ethan Ma



TESTING CERT #5123.02

Add: No. 3 Jinshagang 1st Rd. Shixia, Dalang Town, Dongguan City, Guangdong, People's Republic of China

Tel: +86-769-8318-3000

Web: www.newbtl.com

GENERAL CONCLUSION:

Maximum measured transmitter power:

Max. H-field strength(dBuV/m)	Output Power (dBm)	Output Power (mW)	Limit(mW)
44.54	-50.76	0.0000084	10

According to FCC KDB447498 D01 V06, Appendix A, SAR Test Exclusion Thresholds for 100MHz-6GHz and ≤ 50 mm

The maximum measured output peak power of this EUT is 0.0000084 mW, less than 10mW at 20cm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold.

End of Test Report