



TEST REPORT

APPLICANT : Realme Chongqing Mobile
Telecommunications Corp., Ltd.

PRODUCT NAME : Mobile Phone

MODEL NAME : RMX3363

BRAND NAME : realme

FCC ID : 2AUYFRMX3363

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2021-05-19

TEST DATE : 2021-05-27 to 2021-06-30

ISSUE DATE : 2021-07-23

Edited by: Peng Mi
Peng Mi (Rapporteur)

Approved by: Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

- 1. Technical Information 3**
- 1.1. Applicant and Manufacturer Information 3**
- 1.2. Equipment Under Test (EUT) Description 3**
- 1.3. The Channel Number and Frequency 5**
- 1.4. Test Standards and Results 6**
- 1.5. Environmental Conditions 7**
- 2. 47 CFR Part 15C Requirements 8**
- 2.1. Antenna Requirement 8**
- 2.2. Duty Cycle of Test Signal 9**
- 2.3. Maximum Peak Conducted Output Power 10**
- 2.4. Maximum Average Conducted Output Power 20**
- 2.5. 6 dB Bandwidth 22**
- 2.6. Conducted Spurious Emissions and Band Edge 31**
- 2.7. Power Spectral Density (PSD) 44**
- 2.8. Conducted Emission 53**
- 2.9. Restricted Frequency Bands 57**
- 2.10. Radiated Emission 70**
- Annex A Test Uncertainty 86**
- Annex B Testing Laboratory Information 87**

Change History		
Version	Date	Reason for change
1.0	2021-07-23	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Applicant Address:	No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China
Manufacturer:	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Manufacturer Address:	No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China

1.2. Equipment Under Test (EUT) Description

Product Name:	Mobile Phone	
Sample No.:	54#	
Hardware Version:	11	
Software Version:	realme UI V2.0	
Equipment Type:	Bluetooth LE	
Bluetooth Version:	5.2	
Modulation Type:	GFSK	
Data Rate:	1Mbps, 2Mbps	
Operating Frequency Range:	2402MHz-2480MHz	
Antenna Type:	PIFA Antenna	
Antenna Gain:	ANT 0: -3.5dBi; ANT 1: -5.0dBi	
Accessory Information:	Battery	
	Brand Name:	realme
	Model No.:	BLP809
	Serial No.:	(N/A, marked #1 by test site)
	Capacity:	Typical: 2150mAh, Rated: 2100mAh
	Rated Voltage:	7.74V
	Charge Limit:	8.90V
	Manufacturer:	SUNWODA Electronic Co., Ltd.



Accessory Information:	AC Adapter 1	
	Brand Name:	realme
	Model No.:	VCA7JAUH
	Serial No.:	(N/A, marked #1 by test site)
	Rated Output:	5V \Rightarrow 2A; 10V \Rightarrow 5A
	Rated Input:	100-130V \sim 50/60Hz, 1.8A
	Rated Output:	5V \Rightarrow 2A; 10V \Rightarrow 6.5A
	Rated Input:	200-240V \sim 50/60Hz, 1.8A
	Manufacturer:	HUIZHOU GOLDEN LAKE INDUSTRIAL CO., LTD
	AC Adapter 2	
	Brand Name:	realme
	Model No.:	VCA7JDUH
	Serial No.:	(N/A, marked #1 by test site)
	Rated Output:	5V \Rightarrow 2A; 10V \Rightarrow 5A
	Rated Input:	100-130V \sim 50/60Hz, 1.8A
	Rated Output:	5V \Rightarrow 2A; 10V \Rightarrow 6.5A
	Rated Input:	200-240V \sim 50/60Hz, 1.8A
	Manufacturer:	HUIZHOU GOLDEN LAKE INDUSTRIAL CO., LTD
	AC Adapter 3	
	Brand Name:	realme
	Model No.:	VCA7HAUH
	Serial No.:	(N/A, marked #1 by test site)
	Rated Output:	5V \Rightarrow 2A; 10V \Rightarrow 5A
	Rated Input:	100-130V \sim 50/60Hz, 1.8A
	Rated Output:	5V \Rightarrow 2A; 10V \Rightarrow 6.5A
	Rated Input:	200-240V \sim 50/60Hz, 1.8A
	Manufacturer:	SHENZHEN HUNTKEY ELECTRIC CO., LTD.
USB Cable		
Model No.:	DL129	
Earphone		
Model No.:	MH156	
Length:	1.2m	

Note 1: We use the dedicated software to control the EUT continuous transmission.

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



1.3. The Channel Number and Frequency

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Note 1: The black bold channels were selected for test.



1.4. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle of Test Signal	Jun 03&11, 2021	Su Xiaoxian	PASS	No deviation
3	15.247(b)	Maximum Peak Conducted Output Power	Jun 03&11, 2021	Su Xiaoxian	PASS	No deviation
4	15.247(b)	Maximum Average Conducted Output Power	Jun 03&11, 2021	Su Xiaoxian	PASS	No deviation
5	15.247(a)	Bandwidth	Jun 03&11, 2021	Su Xiaoxian	PASS	No deviation
6	15.247(d)	Conducted Spurious Emission and Band Edge	Jun 03&11, 2021	Su Xiaoxian	PASS	No deviation
7	15.247(e)	Power Spectral Density	Jun 03&11, 2021	Su Xiaoxian	PASS	No deviation
8	15.207	Conducted Emission	May 27, 2021	Wu Runfeng	PASS	No deviation
9	15.247(d)	Restricted Frequency Bands	Jun 03&30, 2021	Huang Zhiye	PASS	No deviation
10	15.209, 15.247(d)	Radiated Emission	Jun 03&30, 2021	Huang Zhiye	PASS	No deviation

Note 1: The tests were performed according to the method of measurements prescribed in



ANSIC63.10-2013 and KDB558074 D01 v05r02.

Note 2: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The Ref offset 1.5dB means the cable loss is 1.5dB.

Note 3: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 4: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106



2. 47 CFR Part 15C Requirements

2.1. Antenna Requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Test Result: Compliant

Inside of the EUT has a PIFA antenna coupled with the metal shrapnel. Please refer to the EUT internal photos.

2.2. Duty Cycle of Test Signal


2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

2.2.2. Test Description

Test Setup:



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.



2.2.3. Test Result

ANT 0:

Test Mode	Data Rate	Duty Cycle (%) (D)	Duty Factor (10*lg[1/D])
GFSK	1Mbps	62.02	2.07
	2Mbps	32.69	4.86

ANT 1:

Test Mode	Data Rate	Duty Cycle (%) (D)	Duty Factor (10*lg[1/D])
GFSK	1Mbps	62.02	2.07
	2Mbps	32.69	4.86

2.3. Maximum Peak Conducted Output Power


2.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.3.2. Test Description

The measured output power was calculated by the reading of the spectrum analyzer and calibration.

Test Setup:



The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

2.3.3. Test Procedure

The measured output power was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for Peak Output Power test on the spectrum analyzer:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 1MHz
- c) Set VBW to 3MHz
- d) Set span to 3MHz
- e) Sweep time = auto couple
- f) Detector = peak
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use peak marker function to determine the peak amplitude level



2.3.4. Test Result

ANT 0:

1Mbps

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	8.07	0.0064	30	1	PASS
19	2440	8.26	0.0067			
39	2480	7.47	0.0056			

B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)




2Mbps

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	8.30	0.0068	30	1	PASS
19	2440	8.55	0.0072			PASS
39	2480	7.69	0.0059			PASS

B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)



ANT 1:

1Mbps

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	6.93	0.0049	30	1	PASS
19	2440	6.86	0.0049			
39	2480	7.32	0.0054			


B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)




2Mbps

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	7.17	0.0052	30	1	PASS
19	2440	7.13	0.0052			PASS
39	2480	7.60	0.0058			PASS

B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)

2.4. Maximum Average Conducted Output Power


2.4.1. Requirement

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

2.4.2. Test Description

The measured output power was calculated by the reading of the spectrum analyzer and calibration.

Test Setup:



The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

2.4.3. Test Procedure

KDB 558074 Section 8.3.2 was used in order to prove compliance.



2.4.4. Test Result

ANT 0:

1Mbps

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty Factor Calculated		dBm	W	
		dBm		dBm	W			
0	2402	5.49	2.07	7.56	0.0057	30	1	PASS
19	2440	5.65		7.72	0.0059			PASS
39	2480	4.83		6.90	0.0049			PASS

2Mbps

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty Factor Calculated		dBm	W	
		dBm		dBm	W			
0	2402	2.81	4.86	7.67	0.0058	30	1	PASS
19	2440	3.19		8.05	0.0064			PASS
39	2480	2.33		7.19	0.0052			PASS

ANT 1:

1Mbps

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty Factor Calculated		dBm	W	
		dBm		dBm	W			
0	2402	4.17	2.07	6.24	0.0042	30	1	PASS
19	2440	4.12		6.19	0.0042			PASS
39	2480	4.60		6.67	0.0046			PASS

2Mbps

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty Factor Calculated		dBm	W	
		dBm		dBm	W			
0	2402	1.75	4.86	6.61	0.0046	30	1	PASS
19	2440	1.62		6.48	0.0044			PASS
39	2480	2.02		6.88	0.0049			PASS


2.5. 6 dB Bandwidth

2.5.1. Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

2.5.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.5.3. Test Procedure

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission



The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW ≥ 3 × RBW, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥6 dB.

2.5.4. Test Result

ANT 0:

1Mbps

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
0	2402	0.670	≥500	PASS
19	2440	0.667	≥500	PASS
39	2480	0.671	≥500	PASS

B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440 MHz)



(Channel 39, 2480MHz)



2Mbps

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
0	2402	1.143	≥500	PASS
19	2440	1.144	≥500	PASS
39	2480	1.149	≥500	PASS

B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440 MHz)



(Channel 39, 2480MHz)



ANT 1:

1Mbps

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
0	2402	0.668	≥500	PASS
19	2440	0.669	≥500	PASS
39	2480	0.669	≥500	PASS

B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440 MHz)



(Channel 39, 2480MHz)



2Mbps

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
0	2402	1.222	≥500	PASS
19	2440	1.229	≥500	PASS
39	2480	1.222	≥500	PASS

B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440 MHz)



(Channel 39, 2480MHz)


2.6. Conducted Spurious Emissions and Band Edge

2.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.6.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.6.3. Test Procedure

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.



2.6.4. Test Result


ANT 0:

1Mbps


A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
0	2402	-47.95	7.36	-12.64	PASS
19	2440	-46.55	6.95	-13.05	PASS
39	2480	-48.20	6.46	-13.54	PASS


B. Test Plot:




(30MHz to 25GHz, Channel 0)




(Band Edge, Channel 0)



(30MHz to 25GHz, Channel 19)



(30MHz to 25GHz, Channel 39)



(Band Edge, Channel 39)




2Mbps

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
0	2402	-48.35	6.89	-13.11	PASS
19	2440	-48.30	5.00	-15.00	PASS
39	2480	-48.19	3.55	-16.45	PASS


B. Test Plot:




(30MHz to 25GHz, Channel 0)



(Band Edge, Channel 0)



(30MHz to 25GHz, Channel 19)



(30MHz to 25GHz, Channel 39)



(Band Edge, Channel 39)




ANT 1:

1Mbps


A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
0	2402	-52.69	6.28	-13.72	PASS
19	2440	-52.89	6.25	-13.75	PASS
39	2480	-52.94	6.99	-13.01	PASS


B. Test Plot:




(30MHz to 25GHz, Channel 0)



(Band Edge, Channel 0)



(30MHz to 25GHz, Channel 19)



(30MHz to 25GHz, Channel 39)



(Band Edge, Channel 39)




2Mbps

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
0	2402	-52.92	1.91	-18.09	PASS
19	2440	-52.64	6.67	-13.33	PASS
39	2480	-52.53	5.79	-14.21	PASS


B. Test Plot:




(30MHz to 25GHz, Channel 0)



(Band Edge, Channel 0)



(30MHz to 25GHz, Channel 19)



(30MHz to 25GHz, Channel 39)



(Band Edge, Channel 39)


2.7. Power Spectral Density

2.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

2.7.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.7.3. Test Procedure

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW



2.7.4. Test Result

ANT 0:

1Mbps

A. Test Verdict:

Spectral Power Density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
0	2402	-6.79	8	PASS
19	2440	-6.62	8	PASS
39	2480	-7.38	8	PASS

B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)



2Mbps


A.Test Verdict:

Spectral Power Density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
0	2402	-9.52	8	PASS
19	2440	-9.31	8	PASS
39	2480	-10.08	8	PASS

B.Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)



ANT 1:

1Mbps

A. Test Verdict:

Spectral Power Density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
0	2402	-3.13	8	PASS
19	2440	-3.10	8	PASS
39	2480	-2.68	8	PASS


B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)



2Mbps

A.Test Verdict:

Spectral Power Density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
0	2402	-8.40	8	PASS
19	2440	-8.37	8	PASS
39	2480	-8.01	8	PASS

B.Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)

2.8. Conducted Emission

2.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).


Frequency Range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.8.2. Test Description

Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.



2.8.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+ Adapter + Earphone + BT TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.4424	35.96	31.48	57.02	47.02	Line	PASS
2	0.5277	32.01	23.48	56.00	46.00		PASS
3	0.6677	31.82	23.78	56.00	46.00		PASS
4	0.9063	31.87	23.91	56.00	46.00		PASS
5	1.1003	32.04	23.26	56.00	46.00		PASS
6	1.4728	31.04	21.71	56.00	46.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.4429	35.90	31.54	57.01	47.01	Neutral	PASS
2	0.7258	32.60	24.05	56.00	46.00		PASS
3	0.8826	31.94	22.70	56.00	46.00		PASS
4	1.1002	31.90	23.26	56.00	46.00		PASS
5	1.3161	30.96	22.33	56.00	46.00		PASS
6	1.5104	31.21	23.41	56.00	46.00		PASS


2.9. Restricted Frequency Bands

2.9.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.9.2. Test Description

Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.



2.9.3. Test Procedure

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

2.9.4. Test Result

The lowest and highest channels are tested to verify the Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.


ANT 0:

1Mbps


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV	U_R (dB μ V)					
0	2378.00	PK	26.93	6.74	27.20	60.87	74	PASS
0	2390.00	AV	14.43	6.74	27.20	48.37	54	PASS
39	2483.98	PK	26.56	6.74	27.20	60.50	74	PASS
39	2485.33	AV	14.08	6.74	27.20	48.02	54	PASS

B. Test Plot:




(PEAK, Channel 0)



(AVERAGE, Channel 0)



(PEAK, Channel 39)



(AVERAGE, Channel 39)




2Mbps


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
0	2387.46	PK	26.50	6.74	27.20	60.44	74	PASS
0	2390.00	AV	14.46	6.74	27.20	48.40	54	PASS
39	2485.88	PK	27.01	6.74	27.20	60.95	74	PASS
39	2485.99	AV	14.10	6.74	27.20	48.04	54	PASS


B. Test Plot:



(PEAK, Channel 0)



(AVERAGE, Channel 0)



(PEAK, Channel 39)



(AVERAGE, Channel 39)




ANT 1:

1Mbps


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
0	2388.82	PK	22.44	6.74	27.20	56.38	74	PASS
0	2390.00	AV	10.43	6.74	27.20	44.37	54	PASS
39	2484.78	PK	22.18	6.74	27.20	56.12	74	PASS
39	2483.50	AV	10.10	6.74	27.20	44.04	54	PASS


B. Test Plot:



(PEAK, Channel 0)



(AVERAGE, Channel 0)



(PEAK, Channel 39)



(AVERAGE, Channel 39)



2Mbps


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
0	2390.00	PK	23.04	6.74	27.20	56.98	74	PASS
0	2390.00	AV	10.42	6.74	27.20	44.36	54	PASS
39	2485.30	PK	22.98	6.74	27.20	56.92	74	PASS
39	2484.47	AV	10.08	6.74	27.20	44.02	54	PASS


B. Test Plot:



(PEAK, Channel 0)



(AVERAGE, Channel 0)



(PEAK, Channel 39)



(AVERAGE, Channel 39)



2.10. Radiated Emission

2.10.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).


2.10.2. Test Description

Test Setup:


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.



2.10.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V}/\text{m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.


Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 40GHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.



ANT 0: 1Mbps

Plot for Channel 0



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
101.780	27.78	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1459.733	42.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2406.400	44.66	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4438.760	45.60	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5680.000	46.95	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12551.480	47.47	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
235.640	28.20	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1330.133	43.37	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3982.920	46.79	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4796.040	46.65	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8402.720	47.32	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12613.080	48.05	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 19



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
98.870	28.54	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2588.800	44.86	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4525.000	46.19	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5670.760	46.52	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9055.680	47.34	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10897.520	47.12	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
94.020	27.79	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
3656.440	45.60	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3995.240	49.06	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5310.400	48.27	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8944.800	47.06	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12157.240	47.72	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 39



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
97.900	27.86	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2562.667	44.53	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5701.560	46.54	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8991.000	48.16	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12148.000	47.23	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
14054.520	46.77	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
244.370	26.72	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1330.133	43.69	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3493.200	46.48	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4786.800	46.67	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8852.400	46.92	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12138.760	47.96	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)



2Mbps

Plot for Channel 0



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
99.840	27.60	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1917.867	45.07	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3865.880	44.58	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5587.600	47.03	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8889.360	47.63	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12517.600	49.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
93.050	28.30	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1331.200	44.11	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2409.600	45.44	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4561.960	46.58	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5667.680	46.71	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8569.040	47.49	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 19



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
95.960	27.26	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2024.000	44.32	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2462.933	44.24	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3899.760	45.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5673.840	46.79	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8448.920	47.15	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
77.530	26.47	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
1177.067	41.72	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3499.360	45.65	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3989.080	44.99	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5766.240	47.13	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10192.200	46.81	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 39



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
99.840	27.58	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1404.267	43.12	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2387.200	44.05	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4518.840	45.84	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5784.720	47.09	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8415.040	47.21	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
314.210	28.72	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1645.333	45.14	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2991.160	44.23	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3656.440	45.82	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5658.440	47.08	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8328.800	46.57	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




ANT 1: 1Mbps

Plot for Channel 0



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
108.570	29.19	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
720.640	33.13	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1919.467	45.13	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5184.120	48.04	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8421.200	47.00	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12157.240	47.75	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
94.990	28.89	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
567.380	31.70	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1806.933	44.69	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3986.000	46.68	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5316.560	48.05	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8464.320	47.76	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 19



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
111.480	30.45	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
756.530	32.71	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2047.467	44.63	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4531.160	45.71	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8439.680	47.23	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12588.440	47.73	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
96.930	28.27	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
773.990	32.78	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1921.600	44.70	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3585.600	46.07	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4796.040	48.11	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
10882.120	47.88	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 39



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
112.450	28.87	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
719.670	32.78	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2003.200	45.13	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5646.120	46.56	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8452.000	47.01	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12135.680	48.46	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
93.050	28.13	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
638.190	31.65	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1761.067	45.67	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4789.880	48.11	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8935.560	47.55	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12166.480	47.36	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




2Mbps

Plot for Channel 0



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
94.020	27.96	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
719.670	33.04	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1760.533	45.39	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5689.240	47.08	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8439.680	47.11	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12896.440	48.78	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
93.050	28.26	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
830.250	35.25	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1940.800	46.22	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4457.240	46.08	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7863.720	46.78	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13090.480	47.64	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 19



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
93.050	27.83	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
604.240	32.08	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2060.800	46.32	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4568.120	46.60	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8926.320	47.37	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
13047.360	47.28	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBµV/m)	QP (dBµV/m)	AV (dBµV/m)	Limit-PK (dBµV/m)	Limit-QP (dBµV/m)	Limit-AV (dBµV/m)	Antenna	Verdict
113.420	29.75	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
606.180	31.37	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1896.533	44.69	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3665.680	46.69	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4789.880	49.56	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8901.680	47.09	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 39



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
94.990	28.00	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
830.250	33.54	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1860.267	44.32	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4463.400	46.04	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8957.120	47.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10857.480	47.78	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
94.990	28.14	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
486.870	30.43	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2172.800	45.02	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3656.440	48.22	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4792.960	48.89	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8294.920	46.54	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)



Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test Items	Uncertainty
Peak Output Power	$\pm 2.22\text{dB}$
Power Spectral Density	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{dB}$
Restricted Frequency Bands	$\pm 5\%$
Radiated Emission	$\pm 2.95\text{dB}$
Conducted Emission	$\pm 2.44\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2021.03.25	2022.03.24
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial Cable	CB02	RF02	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNE R	N/A	N/A
Computer	T430i	Think Pad	Lenovo	N/A	N/A

4.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY5640009 3	N9038A	KEYSIGHT	2021.03.09	2022.03.08
LISN	8127449	NSLK 8127	Schwarzbeck	2021.03.09	2022.03.08
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2020.07.24	2021.07.23
Coaxial Cable(BNC) (30MHz-26GHz)	CB01	EMC01	Morlab	N/A	N/A
Laptop	2016AP5012	ThinkPad E470c	Lenovo (Beijing) Co., Ltd.	N/A	N/A
Laptop Adapter	N/A	ADLX45DL C3A	Lite-On Technology Co., Ltd.	N/A	N/A

4.3 List of Software Used

Description	Manufacturer	Software Version
Test System	Tonscend	V2.6
Power Panel	Agilent	V3.8
Morlab EMCR V1.2	Morlab	V1.0
TS+ -[JS32-CE]	Tonscend	V2.5.0.0

**4.4 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY54130016	N9038A	Agilent	2020.07.21	2021.07.20
Test Antenna - Bi-Log	9163-520	VULB 9163	Schwarzbeck	2019.05.24	2022.05.23
Test Antenna - Loop	1520-022	FMZB1520	Schwarzbeck	2019.02.14	2022.02.13
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2019.07.26	2022.07.25
Test Antenna – Horn	BBHA9170 #774	BBHA 9170	Schwarzbeck	2019.07.26	2022.07.25
Coaxial Cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial Cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial Cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
Coaxial Cable (N male) (30MHz-40GHz)	CB05	EMC05	Morlab	N/A	N/A
1-18GHz pre-Amplifier	61171/61172	S020180L32 03	Tonscend	2020.07.21	2021.07.20
18-26.5GHz pre-Amplifier	46732	S10M100L38 02	Tonscend	2020.07.21	2021.07.20
26-40GHz pre-Amplifier	56774	S40M400L40 02	Tonscend	2020.07.21	2021.07.20
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2020.07.21	2021.07.20
Anechoic Chamber	N/A	9m*6m*6m	CRT	2020.01.06	2023.01.05

END OF REPORT