



# TEST REPORT

No. I21N03262-BT

for

**Realme Chongqing Mobile Telecommunications Corp., Ltd.**

**Mobile Phone**

**Model Name: RMX3393**

with

**Hardware Version: 11**

**Software Version: ColorOS 12.1**

**FCC ID: 2AUYFRMX3393**

**Issued Date: 2021-11-29**

**Designation Number: CN1210**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of SAICT.

**Test Laboratory:**

**SAICT, Shenzhen Academy of Information and Communications Technology**

Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518000.

Tel:+86(0)755-33322000, Fax:+86(0)755-33322001

Email: yewu@caict.ac.cn www.saict.ac.cn

©Copyright. All rights reserved by SAICT.



## **CONTENTS**

<b>CONTENTS .....</b>	<b>2</b>
<b>1. SUMMARY OF TEST REPORT.....</b>	<b>3</b>
1.1. TEST ITEMS.....	3
1.2. TEST STANDARDS .....	3
1.3. TEST RESULT .....	3
1.4. TESTING LOCATION .....	3
1.5. PROJECT DATA .....	3
1.6. SIGNATURE .....	3
<b>2. CLIENT INFORMATION.....</b>	<b>4</b>
2.1. APPLICANT INFORMATION .....	4
2.2. MANUFACTURER INFORMATION .....	4
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>5</b>
3.1. ABOUT EUT .....	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....	5
3.4. GENERAL DESCRIPTION.....	6
<b>4. REFERENCE DOCUMENTS.....</b>	<b>7</b>
4.1. DOCUMENTS SUPPLIED BY APPLICANT .....	7
4.2. REFERENCE DOCUMENTS FOR TESTING .....	7
<b>5. TEST RESULTS .....</b>	<b>8</b>
5.1. TESTING ENVIRONMENT.....	8
5.2. TEST RESULTS .....	8
5.3. STATEMENTS.....	8
<b>6. TEST EQUIPMENTS UTILIZED .....</b>	<b>9</b>
<b>7. LABORATORY ENVIRONMENT.....</b>	<b>10</b>
<b>8. MEASUREMENT UNCERTAINTY .....</b>	<b>11</b>
<b>ANNEX A: DETAILED TEST RESULTS.....</b>	<b>12</b>
TEST CONFIGURATION.....	12
A.0 ANTENNA REQUIREMENT .....	15
A.1 MAXIMUM PEAK OUTPUT POWER .....	16
A.2 BAND EDGES COMPLIANCE .....	17
A.3 CONDUCTED EMISSION.....	24
A.4 RADIATED EMISSION.....	39
A.5 20dB BANDWIDTH.....	51
A.6 TIME OF OCCUPANCY (DWELL TIME) .....	57
A.7 NUMBER OF HOPPING CHANNELS.....	61
A.8 CARRIER FREQUENCY SEPARATION .....	64
A.9 AC POWER LINE CONDUCTED EMISSION .....	67



## 1. Summary of Test Report

### 1.1. Test Items

Product Name	Mobile Phone
Model Name	RMX3393
Applicant's name	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Manufacturer's Name	Realme Chongqing Mobile Telecommunications Corp., Ltd.

### 1.2. Test Standards

FCC CFR 47, Part 15, Subpart C 2019

### 1.3. Test Result

**Pass**

Please refer to "5.2.Test Results"

### 1.4. Testing Location

Address: Building G, Shenzhen International Innovation Center, No.1006 Shennan Road,  
Futian District, Shenzhen, Guangdong, P. R. China

### 1.5. Project data

Testing Start Date:	2021-10-26
Testing End Date:	2021-11-25

### 1.6. Signature

---

Lin Zechuang  
(Prepared this test report)

---

An Ran  
(Reviewed this test report)

---

Zhang Bojun  
(Approved this test report)



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: Realme Chongqing Mobile Telecommunications Corp., Ltd.  
Address: No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China.  
Contact Person Yang LiangPing  
E-Mail ylp@realme.net  
Telephone: (86)13798864426  
Fax: /

### **2.2. Manufacturer Information**

Company Name: Realme Chongqing Mobile Telecommunications Corp., Ltd.  
Address: No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China.  
Contact Person Yang LiangPing  
E-Mail ylp@realme.net  
Telephone: (86)13798864426  
Fax: /

**3. Equipment Under Test (EUT) and Ancillary Equipment (AE)****3.1. About EUT**

Product Name	Mobile Phone
Model Name	RMX3393
Frequency Band	2400MHz~2483.5MHz
Type of Modulation	GFSK/ $\pi/4$ DQPSK/8DPSK
Number of Channels	79
Antenna Type	PIFA antenna
Antenna Gain	0.10dBi
Power Supply	3.87V DC by Battery
FCC ID	2AJOTRMX3393
Condition of EUT as received	No abnormality in appearance

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Shenzhen Academy of Information and Communications Technology.

**3.2. Internal Identification of EUT used during the test**

EUT ID*	IMEI	HW Version	SW Version	Receive Date
UT03aa	868912050020558	11	ColorOS 12.1	2021-10-21
	868912050020541			
UT04aa	868912050020590	11	ColorOS 12.1	2021-10-25
	868912050020582			
UT20aa	868912050020632	11	ColorOS 12.1	2021-10-25
	868912050020624			

\*EUT ID: is used to identify the test sample in the lab internally.

UT03aa is used for conduction test, UT04aa is used for radiation test, and UT20aa is used for AC Power line Conducted Emission test.

**3.3. Internal Identification of AE used during the test**

AE ID*	Description	AE ID*
AE1	Battery	/
AE2	Charger	/
AE3	USB Cable	/
AE4	Headset	/

**AE1**

Model	BLP837
Manufacturer	Sunwoda Electronic Co., Ltd.
Capacity	4400mAh
Nominal Voltage	3.87V

**AE2**

Model	VCA7JAUH
-------	----------



No. I21N03262-BT

Manufacturer	Huizhou Golden Lake Industrial Co., Ltd.
Specification	American Standard Charger
AE3	
Model	DL129
Manufacturer	/
AE4	
Model	MH156
Manufacturer	/

\*AE ID: is used to identify the test sample in the lab internally.

### **3.4. General Description**

The Equipment under Test (EUT) is a model of Mobile Phone with PIFA antenna and battery.

It consists of normal options: Lithium Battery and Charger, USB Cable and Headset.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.



#### **4. Reference Documents**

##### **4.1. Documents supplied by applicant**

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

##### **4.2. Reference Documents for testing**

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
FCC Part 15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz	2019
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	2013



## 5. Test Results

### 5.1. Testing Environment

Normal Temperature: 15~35°C

Relative Humidity: 20~75%

### 5.2. Test Results

No	Test cases	Sub-clause of Part 15C	Verdict
0	Antenna Requirement	15.203	P
1	Maximum Peak Output Power	15.247 (b)	P
2	Band Edges Compliance	15.247 (d)	P
3	Conducted Spurious Emission	15.247 (d)	P
4	Radiated Spurious Emission	15.247,15.205,15.209	P
5	Occupied 20dB bandwidth	15.247(a)	/
6	Time of Occupancy(Dwell Time)	15.247(a)	P
7	Number of Hopping Channel	15.247(a)	P
8	Carrier Frequency Separation	15.247(a)	P
9	AC Power line Conducted Emission	15.107,15.207	P

See **ANNEX A** for details.

### 5.3. Statements

SAICT has evaluated the test cases requested by the applicant/manufacture as listed in section 5.2 of this report, for the EUT specified in section 3, according to the standards or reference documents listed in section 4.2.

Disclaimer:

A. After confirmation with the customer, the sample information provided by the customer may affect the validity of the measurement results in this report, and the impact and consequences arising therefrom shall be borne by the customer.

B. The samples in this report are provided by the customer, and the test results are only applicable to the samples received.



**6. Test Equipments Utilized****Conducted test system**

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date	Calibration Period
1	Vector Signal Analyzer	FSV40	100903	Rohde & Schwarz	2021-12-30	1 year
2	Power Sensor	U2021XA	MY55430013	Agilent	2022-01-13	1 year
3	Data Acquisition	U2531A	TW55443507	Agilent	/	/
4	RF Control Unit	JS0806-2	21C8060398	Tonscend	2022-05-09	1 year
5	Wireless Connective Tester	CMW270	100540	Rohde & Schwarz	2022-03-14	1 year
6	Test Receiver	ESCI	100702	Rohde & Schwarz	2022-01-13	1 year
7	LISN	ENV216	102067	Rohde & Schwarz	2022-07-15	1 year

**Radiated test system**

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date	Calibration Period
1	Loop Antenna	HLA6120	35779	TESEQ	2022-04-25	3 years
2	BiLog Antenna	3142E	0224831	ETS-Lindgren	2024-05-27	3 years
3	Horn Antenna	3117	00066577	ETS-Lindgren	2022-04-02	3 years
4	Horn Antenna	QSH-SL-18 -26-S-20	17013	Q-par	2023-01-06	3 years
5	Test Receiver	ESR7	101676	Rohde & Schwarz	2022-11-24	1 year
6	Spectrum Analyser	FSV40	101192	Rohde & Schwarz	2022-01-13	1 year
7	Chamber	FACT3-2.0	1285	ETS-Lindgren	2023-05-29	2 years

**Test software**

No.	Equipment	Manufacturer	Version
1	JS1120-3	Tonscend	2.6
2	EMC32	Rohde & Schwarz	10.50.40

EUT is engineering software provided by the customer to control the transmitting signal.

The EUT was programmed to be in continuously transmitting mode.

**Anechoic chamber**

Fully anechoic chamber by ETS-Lindgren



## 7. Laboratory Environment

### Semi-anechoic chamber

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB
Electrical insulation	> 2M $\Omega$
Ground system resistance	< 4 $\Omega$
Normalised site attenuation (NSA)	< $\pm$ 4 dB, 3 m distance, from 30 to 1000 MHz

### Shielded room

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-1000MHz>90 dB
Electrical insulation	> 2M $\Omega$
Ground system resistance	< 4 $\Omega$

### Fully-anechoic chamber

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB
Electrical insulation	> 2M $\Omega$
Ground system resistance	< 4 $\Omega$
Voltage Standing Wave Ratio (VSWR)	$\leq$ 6 dB, from 1 to 18 GHz, 3 m distance
Uniformity of field strength	Between 0 and 6 dB, from 80 to 6000 MHz



**8. Measurement Uncertainty**

Test Name	Uncertainty ( $k=2$ )	
1. Maximum Peak Output Power	1.32dB	
2. Band Edges Compliance	1.92dB	
3. Transmitter Spurious Emission - Conducted	30MHz≤f<1GHz	1.41dB
	1GHz≤f<7GHz	1.92dB
	7GHz≤f<13GHz	2.31dB
	13GHz≤f≤26GHz	2.61dB
4.. Transmitter Spurious Emission - Radiated	9kHz≤f<30MHz	1.79dB
	30MHz≤f<1GHz	4.86dB
	1GHz≤f<18GHz	4.82dB
	18GHz≤f≤40GHz	2.90dB
5. 20dB Bandwidth	66Hz	
6. Time of Occupancy (Dwell Time) & Number of Hopping Channels	0.58ms	
7. Carrier Frequency Separation	66Hz	
8. AC Power line Conducted Emission	150kHz≤f≤30MHz	2.62dB


## **ANNEX A: Detailed Test Results**

### **Test Configuration**

The measurement is made according to ANSI C63.10.

#### **1) Conducted Measurements**

1. Connect the EUT to the test system correctly.
2. Set the EUT to the required work mode.
3. Set the EUT to the required channel.
4. Set the EUT hopping mode (hopping on or hopping off).
5. Set the spectrum analyzer to start measurement.
6. Record the values.




#### **2) Radiated Measurements**

**Test setup:**


**9kHz-30MHz:**

The EUT are measured in a semi-anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 3m from the receiving antenna. The center of the receiving loop antenna is 1.0 meter above the ground. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT and adjusting the receiver antenna polarization.



**30MHz-1GHz:**


The EUT are measured in a semi-anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 3m from the receiving antenna. The center of the receiving antenna is 1.0 meter to 4.0 meter above the ground. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT and adjusting the receiver antenna polarization.




**Above 1GHz:**

EUT was placed on a 1.5 meter high non-conductive table at a 3 meter test distance from the receive antenna. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT and adjusting the receiving antenna polarization.

**1GHz-3GHz**




**3GHz-40GHz**



**3) AC Power line Conducted Emission Measurement**

The EUT is working as Bluetooth terminal. A communication link of Bluetooth is set up with a System Simulator (SS). The EUT is commanded to operate at maximum transmitting power.





**A.0 Antenna requirement**

**Measurement Limit:**

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

**Conclusion: The Directional gains of antenna used for transmitting is 0.10dBi.  
The RF transmitter uses an integrate antenna without connector.**



### A.1 Maximum Peak Output Power

**Method of Measurement: See ANSI C63.10-clause 7.8.5.**

A peak responding power meter may be used, where the power meter and sensor system video bandwidth is greater than the occupied bandwidth of the unlicensed wireless device, rather than a spectrum analyzer.

**Measurement Limit:**

Standard	Limit (dBm)
FCC CRF Part 15.247(b)	< 30

**Measurement Results:**

Mode	Peak Conducted Output Power (dBm)		
	2402MHz (Ch0)	2441MHz (Ch39)	2480MHz (Ch78)
GFSK	11.91	12.19	11.35
$\pi/4$ DQPSK	11.42	11.70	11.21
8DPSK	11.97	12.21	11.52

**Conclusion: Pass**





### A.2 Band Edges Compliance

Method of Measurement: See ANSI C63.10-clause 7.8.6.

Measurement Limit:

Standard	Limit (dBm)
FCC 47 CFR Part 15.247 (d)	> 20

Measurement Result:

Mode	Channel	Hopping	Test Results	Conclusion
GFSK	0	OFF	Fig.1	<b>P</b>
	78	OFF	Fig.2	<b>P</b>
	0	ON	Fig.3	<b>P</b>
	78	ON	Fig.4	<b>P</b>
$\pi/4$ DQPSK	0	OFF	Fig.5	<b>P</b>
	78	OFF	Fig.6	<b>P</b>
	0	ON	Fig.7	<b>P</b>
	78	ON	Fig.8	<b>P</b>
8DPSK	0	OFF	Fig.9	<b>P</b>
	78	OFF	Fig.10	<b>P</b>
	0	ON	Fig.11	<b>P</b>
	78	ON	Fig.12	<b>P</b>

See below for test graphs.

Conclusion: Pass




Fig. 1 Band Edges (GFSK, CH0, Hopping OFF)




Fig. 2 Band Edges (GFSK, CH78, Hopping OFF)




Fig. 3 Band Edges (GFSK, CH0, Hopping ON)




Fig. 4 Band Edges (GFSK, CH78, Hopping ON)




Fig. 5 Band Edges ( $\pi/4$  DQPSK, CH0, Hopping OFF)




Fig. 6 Band Edges ( $\pi/4$  DQPSK, CH78, Hopping OFF)




Fig. 7 Band Edges ( $\pi/4$  DQPSK, CH0, Hopping ON)




Fig. 8 Band Edges ( $\pi/4$  DQPSK, CH78, Hopping ON)




Fig. 9 Band Edges (8DPSK, CH0, Hopping OFF)




Fig. 10 Band Edges (8DPSK, CH78, Hopping OFF)




Fig. 11 Band Edges (8DPSK, CH0, Hopping ON)




Fig. 12 Band Edges (8DPSK, CH78, Hopping ON)



### A.3 Conducted Emission

Method of Measurement: See ANSI C63.10-clause 7.8.8.

Measurement Limit:

Standard	Limit (dBm)
FCC 47 CFR Part 15.247 (d)	20dBm below peak output power in 100kHz bandwidth

Measurement Results:

MODE	Channel	Frequency Range	Test Results	Conclusion
GFSK	0	2.402 GHz	Fig.13	<b>P</b>
		30MHz -1GHz	Fig.14	<b>P</b>
		1GHz-26.5GHz	Fig.15	<b>P</b>
	39	2.441 GHz	Fig.16	<b>P</b>
		30MHz -1GHz	Fig.17	<b>P</b>
		1GHz-26.5GHz	Fig.18	<b>P</b>
	78	2.480 GHz	Fig.19	<b>P</b>
		30MHz -1GHz	Fig.20	<b>P</b>
		1GHz-26.5GHz	Fig.21	<b>P</b>
$\pi/4$ DQPSK	0	2.402 GHz	Fig.22	<b>P</b>
		30MHz -1GHz	Fig.23	<b>P</b>
		1GHz-26.5GHz	Fig.24	<b>P</b>
	39	2.441 GHz	Fig.25	<b>P</b>
		30MHz -1GHz	Fig.26	<b>P</b>
		1GHz-26.5GHz	Fig.27	<b>P</b>
	78	2.480 GHz	Fig.28	<b>P</b>
		30MHz -1GHz	Fig.29	<b>P</b>
		1GHz-26.5GHz	Fig.30	<b>P</b>
8DPSK	0	2.402 GHz	Fig.31	<b>P</b>
		30MHz -1GHz	Fig.32	<b>P</b>
		1GHz-26.5GHz	Fig.33	<b>P</b>
	39	2.441 GHz	Fig.34	<b>P</b>
		30MHz -1GHz	Fig.35	<b>P</b>
		1GHz-26.5GHz	Fig.36	<b>P</b>
	78	2.480 GHz	Fig.37	<b>P</b>
		30MHz -1GHz	Fig.38	<b>P</b>
		1GHz-26.5GHz	Fig.39	<b>P</b>

See below for test graphs.

Conclusion: Pass






Fig. 13 Conducted Spurious Emission (GFSK, CH0, 2.402GHz)




Fig. 14 Conducted Spurious Emission (GFSK, CH0, 30MHz -1GHz)




Fig. 15 Conducted Spurious Emission (GFSK, CH0, 1GHz-26.5GHz)




Fig. 16 Conducted Spurious Emission (GFSK, CH39, 2.441GHz)




Fig. 17 Conducted Spurious Emission (GFSK, CH39, 30MHz -1GHz)




Fig. 18 Conducted Spurious Emission (GFSK, CH39, 1GHz-26.5GHz)




Fig. 19 Conducted Spurious Emission (GFSK, CH78, 2.480GHz)




Fig. 20 Conducted Spurious Emission (GFSK, CH78, 30MHz -1GHz)




Fig. 21 Conducted Spurious Emission (GFSK, CH78, 1GHz-26.5GHz)




Fig. 22 Conducted Spurious Emission ( $\pi/4$  DQPSK, CH0, 2.402GHz)




Fig. 23 Conducted Spurious Emission ( $\pi/4$  DQPSK, CH0, 30MHz -1GHz)




Fig. 24 Conducted Spurious Emission ( $\pi/4$  DQPSK, CH0, 1GHz-26.5GHz)




Fig. 25 Conducted Spurious Emission ( $\pi/4$  DQPSK, CH39, 2.441GHz)




Fig. 26 Conducted Spurious Emission ( $\pi/4$  DQPSK, CH39, 30MHz -1GHz)




Fig. 27 Conducted Spurious Emission ( $\pi/4$  DQPSK, CH39, 1GHz-26.5GHz)




Fig. 28 Conducted Spurious Emission ( $\pi/4$  DQPSK, CH78, 2.480GHz)






Fig. 29 Conducted Spurious Emission ( $\pi/4$  DQPSK, CH78, 30MHz -1GHz)




Fig. 30 Conducted Spurious Emission ( $\pi/4$  DQPSK, CH78, 1GHz-26.5GHz)




Fig. 31 Conducted Spurious Emission (8DPSK, CH0, 2.402GHz)




Fig. 32 Conducted Spurious Emission (8DPSK, CH0, 30MHz -1GHz)




Fig. 33 Conducted Spurious Emission (8DPSK, CH0, 1GHz-26.5GHz)




Fig. 34 Conducted Spurious Emission (8DPSK, CH39, 2.441GHz)




Fig. 35 Conducted Spurious Emission (8DPSK, CH39, 30MHz -1GHz)




Fig. 36 Conducted Spurious Emission (8DPSK, CH39, 1GHz-26.5GHz)




Fig. 37 Conducted Spurious Emission (8DPSK, CH78, 2.480GHz)




Fig. 38 Conducted Spurious Emission (8DPSK, CH78, 30MHz -1GHz)




Fig. 39 Conducted Spurious Emission (8DPSK, CH78, 1GHz-26.5GHz)



**A.4 Radiated Emission**

**Method of Measurement: See ANSI C63.10-clause 6.3.**

**Measurement Limit:**

Standard	Limit (dBm)
FCC 47 CFR Part 15.247, 15.205, 15.209	20dBm below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

**Limit in restricted band:**

Frequency of emission (MHz)	Field strength(μV/m)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**Test Condition:**

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	120kHz/300kHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

**Note:** According to the performance evaluation, the radiated emission margin of EUT is over 20dB in the band from 9kHz to 30MHz. Therefore, the measurement starts from 30MHz to tenth harmonic.

The measurement results include the horizontal polarization and vertical polarization measurements.



**Measurement Results:**

Mode	Channel	Frequency Range	Test Results	Conclusion
GFSK	0	1 GHz ~18 GHz	Fig.40	P
	39	1 GHz ~18 GHz	Fig.41	P
	78	1 GHz ~18 GHz	Fig.42	P
	Restricted Band(CH0)	2.38 GHz ~ 2.45 GHz	Fig.43	P
	Restricted Band (CH78)	2.45 GHz ~ 2.5 GHz	Fig.44	P
π/4 DQPSK	0	1 GHz ~18 GHz	Fig.45	P
	39	1 GHz ~18 GHz	Fig.46	P
	78	1 GHz ~18 GHz	Fig.47	P
	Restricted Band (CH0)	2.38 GHz ~ 2.45 GHz	Fig.48	P
	Restricted Band (CH78)	2.45 GHz ~ 2.5 GHz	Fig.49	P
8DPSK	0	1 GHz ~18 GHz	Fig.50	P
	39	1 GHz ~18 GHz	Fig.51	P
	78	1 GHz ~18 GHz	Fig.52	P
	Restricted Band (CH0)	2.38 GHz ~ 2.45 GHz	Fig.53	P
	Restricted Band (CH78)	2.45 GHz ~ 2.5 GHz	Fig.54	P
/	All channels	9 kHz ~30 MHz	Fig.55	P
		30 MHz ~1 GHz	Fig.56	P
		18 GHz ~26.5 GHz	Fig.57	P

**Worst Case Result**

**GFSK CH39 (1-18GHz)**

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
2966.000000	45.5	74.0	28.5	H	9.0
5022.000000	39.0	74.0	35.0	H	-8.9
7291.200000	45.2	74.0	28.8	V	-1.7
11379.600000	47.4	74.0	26.6	V	1.5
14817.200000	51.1	74.0	22.9	H	6.4
17985.200000	54.4	74.0	19.6	H	14.1

Frequency (MHz)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
2966.000000	32.6	54.0	21.4	H	9.0
5022.000000	26.0	54.0	28.0	H	-8.9
7291.200000	32.1	54.0	21.9	V	-1.7
11379.600000	34.4	54.0	19.6	V	1.5
14817.200000	38.6	54.0	15.4	H	6.4
17985.200000	42.9	54.0	11.1	H	14.1





**π/4 DQPSK CH39 (1-18GHz)**

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
2951.200000	45.5	74.0	28.5	H	9.0
3920.100000	36.3	74.0	37.7	V	-12.4
4996.200000	38.5	74.0	35.5	V	-8.6
7319.200000	43.3	74.0	30.7	V	-1.7
14424.800000	49.4	74.0	24.6	V	5.6
17976.800000	54.4	74.0	19.6	H	14.3

Frequency (MHz)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
2951.200000	34.1	54.0	19.9	H	9.0
3920.100000	23.6	54.0	30.4	V	-12.4
4996.200000	25.9	54.0	28.1	V	-8.6
7319.200000	31.5	54.0	22.5	V	-1.7
14424.800000	37.8	54.0	16.2	V	5.6
17976.800000	42.7	54.0	11.3	H	14.3

**8DPSK CH39 (1-18GHz)**

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
2956.000000	45.1	74.0	28.9	H	9.0
3912.900000	36.0	74.0	38.0	H	-12.5
4717.200000	38.3	74.0	35.7	H	-9.3
6256.000000	40.5	74.0	33.5	V	-6.0
14807.600000	51.6	74.0	22.4	V	6.5
17988.400000	54.9	74.0	19.1	V	14.1

Frequency (MHz)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
2956.000000	33.3	54.0	20.7	H	9.0
3912.900000	23.4	54.0	30.6	H	-12.5
4717.200000	25.2	54.0	28.8	H	-9.3
6256.000000	27.5	54.0	26.5	V	-6.0
14807.600000	39.3	54.0	14.7	V	6.5
17988.400000	42.8	54.0	11.2	V	14.1

**Note:**

A "reference path loss" is established and the  $A_{Rpl}$  is the attenuation of "reference path loss", and Antenna Factor, the gain of the preamplifier, the cable loss.  $P_{Mea}$  is the field strength recorded from the instrument. The measurement results are obtained as described below:

Result=  $P_{Mea}$  +Cable Loss +Antenna Factor-Gain of the preamplifier.

**See below for test graphs.**

**Conclusion: Pass**




Fig. 40 Radiated Spurious Emission (GFSK, CH0, 1 GHz ~18 GHz)




Fig. 41 Radiated Spurious Emission (GFSK, CH39, 1 GHz ~18 GHz)




Fig. 42 Radiated Spurious Emission (GFSK, CH78, 1 GHz ~18 GHz)




Fig. 43 Radiated Band Edges (GFSK, CH0, 2380GHz~2450GHz)




Fig. 44 Radiated Band Edges (GFSK, CH78, 2450GHz~2500GHz)




Fig. 45 Radiated Spurious Emission ( $\pi/4$  DQPSK, CH0, 1 GHz ~18 GHz)




Fig. 46 Radiated Spurious Emission ( $\pi/4$  DQPSK, CH39, 1 GHz ~18 GHz)




Fig. 47 Radiated Spurious Emission ( $\pi/4$  DQPSK, CH78, 1 GHz ~18 GHz)




Fig. 48 Radiated Band Edges ( $\pi/4$  DQPSK, CH0, 2380GHz~2450GHz)




Fig. 49 Radiated Band Edges ( $\pi/4$  DQPSK, CH78, 2450GHz~2500GHz)




Fig. 50 Radiated Spurious Emission (8DPSK, CH0, 1 GHz ~18 GHz)




Fig. 51 Radiated Spurious Emission (8DPSK, CH39, 1 GHz ~18 GHz)




Fig. 52 Radiated Spurious Emission (8DPSK, CH78, 1 GHz ~18 GHz)




Fig. 53 Radiated Band Edges (8DPSK, CH0, 2380GHz~2450GHz)






Fig. 54 Radiated Band Edges (8DPSK, CH78, 2450GHz~2500GHz)






Fig. 55 Radiated Spurious Emission (All Channels, 9 kHz ~30 MHz)



**Fig. 56 Radiated Spurious Emission (All Channels, 30 MHz ~1 GHz)**



**Fig. 57 Radiated Spurious Emission (All Channels, 18 GHz ~26.5 GHz)**



**A.5 20dB Bandwidth**

**Method of Measurement:** See ANSI C63.10-clause 7.8.7.

**Measurement Limit:**

Standard	Limit (kHz)
FCC 47 CFR Part 15.247 (a)	/

**Measurement Result:**

Mode	Channel	20dB Bandwidth (kHz)		Conclusion
		Fig.	Value	
GFSK	0	Fig.58	940.00	/
	39	Fig.59	940.00	
	78	Fig.60	940.00	
$\pi/4$ DQPSK	0	Fig.61	1290.00	/
	39	Fig.62	1290.00	
	78	Fig.63	1270.00	
8DPSK	0	Fig.64	1270.00	/
	39	Fig.65	1270.00	
	78	Fig.66	1270.00	

See below for test graphs.

**Conclusion: PASS**




Fig. 58 20dB Bandwidth (GFSK, CH0)




Fig. 59 20dB Bandwidth (GFSK, CH39)




Fig. 60 20dB Bandwidth (GFSK, CH78)




Fig. 61 20dB Bandwidth ( $\pi/4$  DQPSK, CH0)




Fig. 62 20dB Bandwidth ( $\pi/4$  DQPSK, CH39)




Fig. 63 20dB Bandwidth ( $\pi/4$  DQPSK, CH78)




Fig. 64 20dB Bandwidth (8DPSK, CH0)




Fig. 65 20dB Bandwidth (8DPSK, CH39)



Fig. 66 20dB Bandwidth (8DPSK, CH78)





**A.6 Time of Occupancy (Dwell Time)**

**Method of Measurement:** See ANSI C63.10-clause 7.8.4.

**Measurement Limit:**

Standard	Limit (ms)
FCC 47 CFR Part 15.247(a)	< 400

**Measurement Results:**

Mode	Channel	Packet	BurstWidth (ms)		TotalHops (Num)		Result (ms)	Conclusion
			Fig.	ms	Fig.	Num		
GFSK	39	DH5	Fig.67	2.86	Fig.68	120	343.00	<b>P</b>
$\pi/4$ DQPSK	39	2-DH5	Fig.69	2.87	Fig.70	120	344.00	<b>P</b>
8DPSK	39	3-DH5	Fig.71	2.87	Fig.72	80	229.00	<b>P</b>

See below for test graphs.

**Conclusion: Pass**




Fig. 67 BurstWidth (Dwell Time) (GFSK, CH39)




Fig. 68 Number of Burst in Observation Period (Dwell Time) (GFSK, CH39)




Fig. 69 BurstWidth (Dwell Time) ( $\pi/4$  DQPSK, CH39)




Fig. 70 Number of Burst in Observation Period (Dwell Time) ( $\pi/4$  DQPSK, CH39)




Fig. 71 BurstWidth (Dwell Time) (8DPSK, CH39)




Fig. 72 Number of Burst in Observation Period (Dwell Time) (8DPSK, CH39)



**A.7 Number of Hopping Channels**

**Method of Measurement:** See ANSI C63.10-clause 7.8.3.

**Measurement Limit:**

Standard	Limit (Num)
FCC 47 CFR Part 15.247(a)	At least 15 non-overlapping channels

**Measurement Results:**

Mode	Packet	Number of Hopping Channels	Test results (Num)	Conclusion
GFSK	DH5	Fig.73	79	<b>P</b>
$\pi/4$ DQPSK	2-DH5	Fig.74	79	<b>P</b>
8DPSK	3-DH5	Fig.75	79	<b>P</b>

**See below for test graphs.**

**Conclusion: Pass**




Fig. 73 Number of Hopping Channels (GFSK, Hopping)





Fig. 74 Number of Hopping Channels ( $\pi/4$  DQPSK, Hopping)



**Fig. 75** Number of Hopping Channels (8DPSK, Hopping)



### A.8 Carrier Frequency Separation

Method of Measurement: See ANSI C63.10-clause 7.8.2.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)	By a minimum of 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater

Measurement Results:

Mode	Channel	Packet	Separation of hopping channels	Test result (kHz)	Conclusion
GFSK	39	DH5	Fig.76	1003.00	P
$\pi/4$ DQPSK	39	2-DH5	Fig.77	1000.00	P
8DPSK	39	3-DH5	Fig.78	1000.00	P

See below for test graphs.

Conclusion: Pass






Fig. 76 Carrier Frequency Separation (GFSK, CH39)




Fig. 77 Carrier Frequency Separation ( $\pi/4$  DQPSK, CH39)




Fig. 78 Carrier Frequency Separation (8DPSK, CH39)



### A.9 AC Power line Conducted Emission

Method of Measurement: See ANSI C63.10-clause 6.2

Test Condition:

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:

BT- AE2, AE3, AE4

Frequency range (MHz)	Quasi-peak Limit (dB $\mu$ V)	Average-peak Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
			Traffic	Idle	
0.15 to 0.5	66 to 56	56 to 46	Fig.79	Fig.80	<b>P</b>
0.5 to 5	56	46			
5 to 30	60	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

**Note:** The measurement results include the L1 and N measurements.

See below for test graphs.

**Conclusion: Pass**




Fig. 79 AC Power line Conducted Emission (Traffic)

**Measurement Results: Quasi Peak**

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	40.24	66.00	25.76	L1	ON	10
0.430000	39.35	57.25	17.90	N	ON	10
0.466000	45.39	56.59	11.20	L1	ON	10
0.878000	33.81	56.00	22.19	L1	ON	10
1.250000	33.19	56.00	22.81	L1	ON	10
12.674000	38.61	60.00	21.39	N	ON	10

**Measurement Results: Average**

Frequency (MHz)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.414000	34.57	47.57	13.00	L1	ON	10
0.462000	40.26	46.66	6.40	N	ON	10
0.882000	28.28	46.00	17.72	N	ON	10
1.270000	28.38	46.00	17.62	L1	ON	10
10.102000	31.60	50.00	18.40	N	ON	10
12.906000	34.21	50.00	15.79	L1	ON	10




Fig. 80 AC Power line Conducted Emission (Idle)

Measurement Results: Quasi Peak

Frequency (MHz)	Quasi Peak (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	43.73	66.00	22.27	N	ON	10
0.430000	46.55	57.25	10.70	L1	ON	10
0.434000	43.85	57.18	13.32	L1	ON	10
1.034000	33.27	56.00	22.73	L1	ON	10
1.286000	29.50	56.00	26.50	L1	ON	10
13.326000	39.78	60.00	20.22	N	ON	10

Measurement Results: Average

Frequency (MHz)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.426000	41.00	47.33	6.33	N	ON	10
0.462000	40.45	46.66	6.21	L1	ON	10
1.022000	24.29	46.00	21.71	N	ON	10
1.278000	26.16	46.00	19.84	N	ON	10
2.758000	26.93	46.00	19.07	N	ON	10
12.898000	34.77	50.00	15.23	N	ON	10

\*\*\*END OF REPORT\*\*\*