Quick Guide RMX3785	гealme		Hi-Res This p		ormed t under lic
Greetings from realme mobile This guide will show you how to use the phone and its important functions. You	 When charging, please place the device in an environment that has a normal 		612804000xxx	V0.1	
may also visit realme official website to get more information about the phone.	room temperature and good ventilation. It is recommended to charge the device in an environment with temperature ranging from 5°C~35°C.	English	Product		RMX
Front Camera	How to reboot the phone Press and hold the Power Button and Volume Up Button at the same time until the realme boot animation is displayed to reboot the phone.		Main screen pa	rameter	17.0
Power Key / Fingerprint Scanner	How to Transfer Old Mobile Content to a New Mobile You can use realme Clone Phone to easily transfer photos, videos, music, contacts, messages, apps, etc from your old phone to the new one. 1. If you have an old Android phone, first scan the QR code below, then download and install Clone Phone, next open Clone Phone on both the new and old phones,		Dimension		165
	and follow the on-screen instructions to complete the operation.		Battery		500
 Warning Do not place the phone or battery near or inside heating equipment, cooking equipments, high pressure vessels (such as microwave ovens, induction cooker, electric oven, heater, pressure cooker, water heater, gas stove, etc.) to prevent the battery overheating which may lead to an 	https://i.clonephone.coloros.com/download 2. If you have an old iPhone, open Clone Phone on the new phone directly, and		Camera		16 / 64 /
 explosion. The original charger, data cable and battery shall be used. Unapproved 	follow on-screen instructions to sign in to iCloud account and sync the files.			perature	0°C
 chargers, data cables, or batteries that are not certified by the manufacturer may result in electric shock, fire, explosion, or other hazards. Back cover can't be removed. 	Standard accessories You are provided with the following standard accessories: 1 Phone, 1 Charger, 1 USB data cable, 1 Safety Guide, 1 Quick Guide, 1 SIM Ejector Tool, 1 Protective Case.		SAR Values	FCC SAR	1.1 0.6

demark or registered trademark of NFC Forum, Inc. in the United States and in other countries.

formed to High-Resolution Audio standard defined by Japan Audio Society. The High-Resolution under license from Japan Audio Society.

m your device depending on the region, service provider, or software version, and t prior notice.

₿ (€ 🗍

	Radio Waves Specifications			
RMX3785	Radio	Frequency	Max. Output Powe	
	GSM	850MHz/900MHz	33.5dBm	
17.07cm(6.72")		1800MHz/1900MHz	30.5dBm	
	WCDMA	Bands 1/5/6/8/19	24.5dBm	
		Bands 2/4	24dBm	
165.7×76.0×7.89(mm)	LTE FDD	Bands 1/3	24.8dBm	
		Bands 2/4/7	23.5dBm	
		Bands 5/8/12/13/17/18/19/20/28	24.5dBm	
4880mAh/18.88Wh(Min) 5000mAh/19.35Wh(Typ)		Bands 26/66	24dBm	
	LTETDD	Bands 38/39/40	24dBm	
		Band 41	24.5dBm	
16 Megapixels Front 64 Megapixels+2 Megapixels Rear	5G NR	n1/n3/n5/n8/n20/n28/n66	24.2dBm	
		n7/n40	23.7dBm	
		n38/n41/n77/n78	24.2dBm	
	Bluetooth	2.4-2.4835GHz	13.5dBm(EIRP)	
0°C-35°C	2.4G Wi-Fi	2.4-2.4835GHz	18.5dBm(EIRP)	
	5G Wi-Fi	5.15-5.25GHz	21dBm(EIRP)	
		5.25-5.35GHz	21.5dBm(EIRP)	
1.16 W/kg(Head) 0.64 W/kg(Body)	5G WI-FI	5.47-5.725GHz	20dBm(EIRP)	
		5.725-5.85GHz	18dBm(EIRP)	
	NFC	13.56MHz	42dBuA/m @10m	