

TEST REPORT

Applicant: Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address: No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China
Equipment Type: Mobile Phone
Model Name: RMX3785
Brand Name: realme
FCC ID: 2AUYFRMX3785
Test Standard: 47 CFR Part 15 Subpart C
ANSI C63.10-2013
Sample Arrival Date: May 24, 2023
Test Date: Jun. 01, 2023 – Jul. 11, 2023
Date of Issue: Jul. 21, 2023

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Zhang Guoxi

Checked by: Xia Long

Approved by: Liao Jianming
(Technical Director)

Zhang Guoxi

Xia Long

Liao Jianming

Revision History		
Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Jul. 21, 2023</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information.....	5
2.3	Factory Information.....	5
2.4	General Description for Equipment under Test (EUT).....	5
2.5	Technical Information	6
3	SUMMARY OF TEST RESULTS	7
3.1	Test Standards	7
3.2	Verdict	7
3.3	Test Uncertainty	7
4	GENERAL TEST CONFIGURATIONS	8
4.1	Test Environments.....	8
4.2	Test Equipment List.....	8
4.3	Description of Test Setup	10
5	TEST ITEMS	12
5.1	Antenna Requirements	12
5.2	Emission Bandwidth	14
5.3	Field Strength of Fundamental Emissions and Radiated Emissions.....	16
5.4	Frequency Tolerance.....	18
5.5	Conducted Emission.....	19
ANNEX A	TEST RESULT	20

A.1	Emission Bandwidth	20
A.2	Field Strength of Fundamental Emissions.....	21
A.3	Radiated Emissions	22
A.4	Frequency Stability	25
A.5	Conducted Emissions	26
ANNEX B	TEST SETUP PHOTOS	28
ANNEX C	EUT EXTERNAL PHOTOS.....	28
ANNEX D	EUT INTERNAL PHOTOS.....	28

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	<input checked="" type="checkbox"/> Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	<input type="checkbox"/> 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address	No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China

2.2 Manufacturer Information

Manufacturer	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address	No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China

2.3 Factory Information

Factory	N/A
Address	N/A

2.4 General Description for Equipment under Test (EUT)

EUT Name	Mobile Phone
Model Name Under Test	RMX3785
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	11
Software Version	realme UI 4.0
Dimensions (Approx.)	165.66*75.98*7.94mm
Weight (Approx.)	189.2 g
EUT ID	S20, S21
IMEI Number	S20: IMEI1:865046060054837, IMEI2:865046060054829 S21: IMEI1:865046060054613, IMEI2:865046060054605

2.5 Technical Information

Network and Wireless connectivity	2G Network GSM/GPRS/EDGE 850/1900 MHz 3G Network WCDMA/HSDPA/HSUPA Band 2/4/5 4G Network LTE FDD Band 2/4/5/7/12/13/17/26/66 LTE TDD Band 38/41 LTE CA Uplink (UL): CA_7C, CA_38C, CA_41C 5G Network SA: NR n5/n7/n38/n41/n66 NSA(EN-DC): DC_2A_n7A, DC_2A_n38A, DC_2A_n41A, DC_2A_n66A, DC_4A_n7A, DC_4A_n38A, DC_5A_n7A, DC_5A_n38A, DC_5A_n66A, DC_7A_n66A, DC_26A_n41A, DC_41A_n41A, DC_66A_n5A, DC_66A_n7A, DC_66A_n38A, DC_66A_n41A Bluetooth (BR+EDR+BLE) 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20/40), VHT20/40 5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80) U-NII-1/2A/2C/3, GPS, GLONASS, BDS, Galileo, NFC
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Modulation Type	ASK
Product Type	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Frequency Range	13.56 MHz
Receiver Categorization	3
Number of channel	1
Tested Channel	1
Antenna Type	FPC Antenna

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Miscellaneous Wireless Communications Services
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC Part No.	Test Result	Verdict
1	Antenna Requirement	15.203	--	Pass ^{Note}
2	Emissions Bandwidth	15.215	ANNEX A.1	Pass
3	Field Strength of Fundamental Emissions	15.225(a)	ANNEX A.2	Pass
4	Radiated Emissions	15.225(d) / 15.209	ANNEX A.3	Pass
5	Frequency Stability	15.225(e)	ANNEX A.4	Pass
6	Conducted Emission	15.207	ANNEX A.5	Pass

Note 1: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note 2: Compared with the EUT of test report BL-SZ2350513-402, the changes of the EUT of this report as below:

1. Update Model Name, front camera, rear camera, battery, adapter, motor, charge management system, circuit.

Therefore, all test data please refer to report BL-SZ2350513-402, which was issued by Shenzhen BALUN Technology Co., Ltd. on Jul. 12, 2023.

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions (9 kHz-30 MHz)	4.28 dB
Radiated emissions (9 kHz-30 MHz)	3.22 dB
Radiated emissions (30 MHz-1 GHz)-10m	4.80 dB
Radiated emissions (30 MHz-1 GHz)-3m	4.76 dB
Radiated emissions (1 GHz-18 GHz)-3m	4.88 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	50% to 53%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+23.6°C to +24.7°C
Working Voltage of the EUT	NV (Normal Voltage)	3.87 V

4.2 Test Equipment List

Emissions Bandwidth						
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2022.09.09	2023.09.08	<input checked="" type="checkbox"/>
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2021.04.16	2024.04.15	<input checked="" type="checkbox"/>
Anechoic Chamber	EMC TECHNOLOGY LTD	20.1m*11.6m*7.35m	130	2021.08.15	2024.08.14	<input checked="" type="checkbox"/>

Field Strength Of Fundamental Emissions						
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2022.09.09	2023.09.08	<input checked="" type="checkbox"/>
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B2018054558	2022.12.07	2023.12.06	<input type="checkbox"/>
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2021.04.16	2024.04.15	<input checked="" type="checkbox"/>
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9168	9168-01162	2020.08.12	2023.08.11	<input type="checkbox"/>
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	130	2021.08.15	2024.08.14	<input checked="" type="checkbox"/>


Radiated Emissions						
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	ROHDE&SCHWARZ RZ	ESRP	101036	2022.09.09	2023.09.08	<input checked="" type="checkbox"/>
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B201805455 8	2022.12.07	2023.12.06	<input checked="" type="checkbox"/>
Test Antenna- Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2021.04.16	2024.04.15	<input checked="" type="checkbox"/>
Test Antenna- Bi-Log	SCHWARZBECK	VULB 9168	9168-01162	2020.08.12	2023.08.11	<input checked="" type="checkbox"/>
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60* 7.35m	130	2021.08.15	2024.08.14	<input checked="" type="checkbox"/>
Description	Manufacturer	Name		Version		Use
Test Software	BALUN	BL410-E		V22.930		<input checked="" type="checkbox"/>

Frequency Stability						
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	ROHDE&SCHWARZ RZ	ESRP	101036	2022.09.09	2023.09.08	<input checked="" type="checkbox"/>
Test Antenna- Loop(9 kHz- 30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2021.04.16	2024.04.15	<input checked="" type="checkbox"/>
Temperature Chamber	AHK	SP20	1412	2022.09.20	2023.09.19	<input checked="" type="checkbox"/>
DC Power Supply	ROHDE&SCHWARZ RZ	HMP2020	018141664	2023.05.15	2024.05.14	<input checked="" type="checkbox"/>
Anechoic Chamber	EMC TECHNOLOGY LTD	20.1m*11.6m *7.35m	130	2021.08.15	2024.08.14	<input checked="" type="checkbox"/>

Conducted disturbance Test						
Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2022.09.09	2023.09.08	<input checked="" type="checkbox"/>
LISN	SCHWARZBECK	NSLK 8127	8127-687	2023.05.16	2024.05.15	<input checked="" type="checkbox"/>
ISN	TESEQ	ISN T800	34449	2022.11.11	2023.11.10	<input type="checkbox"/>
ISN	TESEQ	ISN T8-Cat6	53561	2023.04.23	2024.04.22	<input type="checkbox"/>
Shielded Room	YiHeng Electronic Co., Ltd	3.5m*3.1m*2. 8m	112	2022.02.19	2025.02.18	<input checked="" type="checkbox"/>
Description	Manufacturer	Name		Version		Use
Test Software	BALUN	BL410-E		V22.930		<input checked="" type="checkbox"/>


4.3 Description of Test Setup

4.3.1 For Radiated Test (Below 30 MHz)




(Diagram 1)

4.3.2 For Radiated Test (30 MHz-1 GHz)



(Diagram 2)

4.3.3 For AC Power Supply Port Test



(Diagram 3)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer EUT internal photos.

5.2 Emission Bandwidth

5.2.1 Definition

15.215(c);

Intentional radiators operating under the alternative provisions to the general emission limits must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

5.2.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

The 20dB bandwidth is measured with a spectrum analyzer connected via a receiver antenna placed near the EUT while the EUT is operating in transmission mode.

Use the following spectrum analyzer settings:

Span = between 2 to 5 times the OBW

RBW = 1% to 5% the OBW

VBW \geq 3RBW

Sweep = auto

Detector function = peak

Trace = max hold

The 99% emission bandwidth is measured with a spectrum analyzer connected via a receiver antenna placed near the EUT while the EUT is operating in transmission mode.

Use the following spectrum analyzer settings:

Span = between 1.5 to 5 times the OBW

RBW = 1% to 5% OBW

VBW \geq 3RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.2.4 Test Result

Please refer to ANNEX A.1

5.3 Field Strength of Fundamental Emissions and Radiated Emissions

5.3.1 Limit

FCC §15.225(a), (b), (c)

According to FCC section 15.225, for <30 MHz, Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set 10 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the center of the loop. The measuring bandwidth was set to 10 kHz. (Note: During testing the receive antenna was rotated about its axis to maximize the emission from the EUT)

There was no detected Restricted bands and Radiated spurious emission below 30MHz. The 30m limit was converted to 3m Limit using square factor(x) as it was found by measurements as follows; 3 m Limit(dBμV/m) = 20log(X)+40log(30/3)= 20log(15848)+40log(30/3) = 124dBμV

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency range (MHz)	Field Strength@30m		Field Strength@10m	Field Strength@3m
	μV/m	dBμV/m	dBμV/m	dBμV/m
Below 13.110	30	29.5	48.58	69.5
13.110 ~ 13.410	106	40.5	59.58	80.5
13.410 ~ 13.553	334	50.5	69.58	90.5
13.553 ~13.567	15848	84	103.08	124
13.567 ~ 13.710	334	50.5	69.58	90.5
13.710 ~14.010	106	40.5	59.58	80.5
Above 14.010	30	29.5	48.58	69.5

NOTE:

1. Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.

FCC §15.225(d)

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dB μ V/m@3m (AV) and 74dB μ V/m@3m (PK).

5.3.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented. The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.3.4 Test Result

Please refer to ANNEX A.2 and A.3

NOTE:

1. Results (dB μ V/m) = Reading (dB μ V/m) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)

3. Over limit = Results – Limit.

5.4 Frequency Tolerance

5.4.1 Limit

FCC §15.225(e)

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

If the frequency stability limits are only met within a temperature range that is smaller than the -30°C to $+50^{\circ}\text{C}$ range specified in (a), the frequency stability requirement will be deemed to be met if the transmitter is automatically prevented from operating outside this smaller temperature range and if the published operating characteristics for the equipment are revised to reflect this restricted temperature range.

5.4.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

1. The test is performed in a Temperature Chamber.
2. The EUT is configured as MS + DC Power Supply.

5.4.4 Test Result

Please refer to ANNEX A.4.

5.5 Conducted Emission

5.5.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.5.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.5.4 Test Result

Please refer to ANNEX A.5.

NOTE:

1. Results (dB μ V) = Reading (dB μ V) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Over limit = Results – Limit.

ANNEX A TEST RESULT


A.1 Emission Bandwidth

Test Data


Frequency (MHz)	Emission Bandwidth(20dB down) (kHz)	Occupied Bandwidth(99%) (kHz)
13.56	0.768	0.628

Test plots

Emission Bandwidth



99% Occupied Bandwidth



A.2 Field Strength of Fundamental Emissions


Note: Field Strength of Fundamental Emissions tests were performed in X, Y, Z axis direction of EUT. And only the worst axis test condition was recorded in this test report.

Test Data

Field Strength of Fundamental Emissions Value					
Frequency (MHz)	Detector	Field Strength (dB μ V/m)	Limit @3m (dB μ V/m)	EUT	Margin (dB)
13.560	PEAK	56.06	124.0	X axis	67.94

Test Plot

Test Antenna-LOOP, EUT X axis



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	13.560	56.06	20.86	124.0	67.94	Peak	199.00	100	Vertical	N/A


A.3 Radiated Emissions

Note 1: This frequency which near 13.560 MHz with circle should be ignored because they are NFC carrier frequency.

Note 2: All Radiated Emissions tests were performed in X, Y, Z axis direction of EUT. And only the worst axis test condition was recorded in this test report.

The Data and Plots (9 kHz ~ 30 MHz)(at 3m chamber)


Below 30 MHz, Test Antenna LOOP, EUT X axis



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	0.016	57.47	20.13	123.5	66.03	Peak	343.00	100	Vertical	Pass
2	0.024	56.97	20.23	120.0	63.03	Peak	360.00	100	Vertical	Pass
3	0.165	51.64	20.10	103.3	51.66	Peak	311.00	100	Vertical	Pass
4	0.329	46.93	20.15	97.3	50.37	Peak	245.00	100	Vertical	Pass
5	6.665	39.82	20.82	69.5	29.68	Peak	54.00	100	Vertical	Pass
6	13.560	58.98	20.86	69.5	10.52	Peak	196.00	100	Vertical	N/A


Test Data and Plots (30 MHz ~ 10th Harmonic)

30 MHz to 1 GHz, Test Antenna Vertical, EUT X axis



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	41.880	14.88	-26.51	30.0	15.12	Peak	320.00	100	Vertical	Pass
2	67.578	22.30	-29.10	30.0	7.70	Peak	165.00	100	Vertical	Pass
3	83.822	16.63	-31.20	30.0	13.37	Peak	143.00	100	Vertical	Pass
4	185.404	21.04	-29.21	33.5	12.46	Peak	239.00	100	Vertical	Pass
5	282.379	16.11	-25.73	36.0	19.89	Peak	239.00	100	Vertical	Pass
6	892.599	25.13	-12.53	36.0	10.87	Peak	193.00	100	Vertical	Pass

30 MHz to 1 GHz, Test Antenna Horizontal, EUT X axis



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	48.910	12.74	-26.33	30.0	17.26	Peak	230.00	100	Horizontal	Pass
2	127.946	12.21	-31.06	33.5	21.29	Peak	25.00	100	Horizontal	Pass
3	287.956	16.13	-25.19	36.0	19.87	Peak	360.00	100	Horizontal	Pass
4	610.400	21.53	-17.85	36.0	14.47	Peak	84.00	100	Horizontal	Pass
5	793.442	24.11	-14.42	36.0	11.89	Peak	102.00	100	Horizontal	Pass
6	953.452	26.40	-11.88	36.0	9.60	Peak	264.00	100	Horizontal	Pass

A.4 Frequency Stability

Note 1: Because the 85%(3.2895V) and 115% (4.4505V)of the rated supply voltage value exceeds the cut-off voltage upper(4.45V) and lower(3.6V) limit of the manufacturer, the cut-off voltage of EUT is test here.

OPERATING FREQUENCY:	13560000 Hz
REFERENCE VOLTAGE:	3.87 V
DEVIATION LIMIT:	±0.01%


VOLTAGE (%)	Test Conditions		Frequency(Hz)	Deviation(%)	Verdict
	Power (VDC)	Temperature (°C)			
100	3.87	-20	13559961	-0.000516	
100		-10	13559958	-0.000516	
100		0	13559964	-0.000951	
100		+10	13559961	0.000265	
100		+20	13559961	-0.004417	
100		+25	13559964	0.001578	
100		+30	13559958	0.002839	
100		+40	13560013	0.000376	
100		+50	13559961	0.001512	
100		+20	13559958	0.001136	
MAX(Battery End Point, 85)		3.6	-20	13559961	
MIN(Battery End Point, 115)	4.45	+20	13559958	-0.000310	

A.5 Conducted Emissions

Note 1: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.


Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.152	39.12	9.84	65.89	26.77	Peak	L	Pass
1**	0.152	20.91	9.84	55.89	34.98	AV	L	Pass
2	0.176	36.54	9.81	64.67	28.13	Peak	L	Pass
2**	0.176	21.25	9.81	54.67	33.42	AV	L	Pass
3	0.354	32.35	9.76	58.87	26.52	Peak	L	Pass
3**	0.354	19.76	9.76	48.87	29.11	AV	L	Pass
4	4.076	28.86	10.35	56.00	27.14	Peak	L	Pass
4**	4.076	15.24	10.35	46.00	30.76	AV	L	Pass
5	12.474	29.98	10.29	60.00	30.02	Peak	L	Pass
5**	12.474	18.20	10.29	50.00	31.80	AV	L	Pass
6	20.830	28.95	10.59	60.00	31.05	Peak	L	Pass
6**	20.830	13.25	10.59	50.00	36.75	AV	L	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.160	34.60	9.83	65.46	30.86	Peak	N	Pass
1**	0.160	23.26	9.83	55.46	32.20	AV	N	Pass
2	0.224	31.63	9.78	62.67	31.04	Peak	N	Pass
2**	0.224	20.20	9.78	52.67	32.47	AV	N	Pass
3	0.396	33.58	10.33	57.94	24.36	Peak	N	Pass
3**	0.396	19.90	10.33	47.94	28.04	AV	N	Pass
4	1.300	29.29	10.22	56.00	26.71	Peak	N	Pass
4**	1.300	15.76	10.22	46.00	30.24	AV	N	Pass
5	12.356	30.90	10.51	60.00	29.10	Peak	N	Pass
5**	12.356	19.24	10.51	50.00	30.76	AV	N	Pass
6	29.946	29.40	10.87	60.00	30.60	Peak	N	Pass
6**	29.946	15.17	10.87	50.00	34.83	AV	N	Pass

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2361029-AE-2.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2361029-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2361029-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--