



TEST REPORT

No.I23N01711-WLAN 5GHz

for

Realme Chongqing Mobile Telecommunications Corp., Ltd.

Mobile Phone

Model Name: RMX3840

with

Hardware Version: 11

Software Version: realme UI 5.0

FCC ID: 2AUYFRMX3840

Issued Date: 2023-12-06

Designation Number: CN1210

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of SAICT.

Test Laboratory:

SAICT, Shenzhen Academy of Information and Communications Technology

Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518000.

Tel:+86(0)755-33322000, Fax:+86(0)755-33322001

Email: yewu@caict.ac.cn. www.saict.ac.cn



REPORT HISTORY

Report Number	Revision	Description	Issue Date
I23N01711-WLAN 5GHz	Rev.0	1st edition	2023-12-06

Note: the latest revision of the test report supersedes all previous versions.



CONTENTS

CONTENTS	3
1. SUMMARY OF TEST REPORT	4
1.1. TEST ITEMS	4
1.2. TEST STANDARDS	4
1.3. TEST RESULT	4
1.4. TESTING LOCATION	4
1.5. PROJECT DATA	4
1.6. SIGNATURE	4
2. CLIENT INFORMATION	5
2.1. APPLICANT INFORMATION	5
2.2. MANUFACTURER INFORMATION	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1. ABOUT EUT	6
3.2. INTERNAL IDENTIFICATION OF EUT	6
3.3. INTERNAL IDENTIFICATION OF AE	7
3.4. GENERAL DESCRIPTION	7
4. REFERENCE DOCUMENTS	8
4.1. DOCUMENTS SUPPLIED BY APPLICANT	8
4.2. REFERENCE DOCUMENTS FOR TESTING	8
5. TEST RESULTS	9
5.1. TESTING ENVIRONMENT	9
5.2. TEST RESULTS	9
5.3. STATEMENTS	9
6. TEST EQUIPMENTS UTILIZED	10
7. LABORATORY ENVIRONMENT	11
8. MEASUREMENT UNCERTAINTY	12
ANNEX A: DETAILED TEST RESULTS	13
A.1. MEASUREMENT METHOD	13
A.2. MAXIMUM OUTPUT POWER	16
A.3. PEAK POWER SPECTRAL DENSITY (CONDUCTED)	21
A.4. OCCUPIED 26dB BANDWIDTH (CONDUCTED)	23
A.5. OCCUPIED 6dB BANDWIDTH (CONDUCTED)	28
A.6. 99% OCCUPIED BANDWIDTH (CONDUCTED)	32
A.7. DYNAMIC FREQUENCY SELECTION	37
A.8. BAND EDGES COMPLIANCE	41
A.9. TRANSMITTER SPURIOUS EMISSION	57
A.10. RADIATED SPURIOUS EMISSIONS < 30MHZ	84
A.11. AC POWER LINE CONDUCTED EMISSION	86
A.12. POWER CONTROL	89



1. Summary of Test Report

1.1. Test Items

Description	Mobile Phone
Model Name	RMX3840
Applicant's name	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Manufacturer's Name	Realme Chongqing Mobile Telecommunications Corp., Ltd.

1.2. Test Standards

FCC Part15-2021; FCC 06-96-2006; ANSI C63.10-2013; KDB789033-V02r01; KDB 905462-D02; KDB 662911-V02r01.

1.3. Test Result

Pass

Please refer to "5.2. Test Results"

1.4. Testing Location

Address: Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 51800

1.5. Project data

Testing Start Date: 2023-10-25
Testing End Date: 2023-11-24

1.6. Signature

Lin Zechuang
(Prepared this test report)

An Ran
(Reviewed this test report)

Zhang Bojun
(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address: No.178 Yulong Avenue,Yufengshan,Yubei District,Chongqing,China
Contact Person Yang LiangPing
E-Mail ylp@realme.net
Telephone: (86)13798864426
Fax: /

2.2. Manufacturer Information

Company Name: Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address: No.178 Yulong Avenue,Yufengshan,Yubei District,Chongqing,China
Contact Person Yang LiangPing
E-Mail ylp@realme.net
Telephone: (86)13798864426
Fax: /



3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Mobile Phone
Model Name	RMX3840
RF Protocol	IEEE 802.11a/n-HT20/n-HT40/ac-VHT20/ac-VHT40/ac-VHT80/ ac-VHT160/ax-HE20/ax-HE40/ax-HE80/ax-HE160
WLAN Frequency Range	ISM Bands: 5150MHz~5250MHz; 5250MHz~5350MHz; 5470MHz~5725MHz; 5725MHz~5850MHz.
Type of modulation	OFDM/OFDMA
Antenna Type	Integrated antenna
Antenna Gain	5150MHz~5250MHz: SISO: ANT9: 0.4dBi; ANT2: -1.4dBi; Directional Gain: 2.6dBi (see Note1) 5250MHz~5350MHz: SISO: ANT9: 0.6dBi; ANT2: 0.1dBi; Directional Gain: 3.4dBi (see Note1) 5470MHz~5725MHz: SISO: ANT9: 0.1dBi; ANT2: 0.0dBi; Directional Gain: 3.1dBi (see Note1) 5725MHz~5850MHz: SISO: ANT9: -2.6dBi; ANT2: 1.4dBi; Directional Gain: 2.54dBi (see Note1)
Power Supply	3.89V DC by Battery
FCC ID	2AUYFRMX3840
Device Type (DFS)	Client without radar detection(only support client mode)
Condition of EUT as received	No abnormality in appearance

Note1: Directional gain(correlated) = $10\log [(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / NANT]$ dBi.

For 5150MHz~5250MHz: Directional gain= $10\log [(10^{0.4/20} + 10^{-1.4/20})^2 / 2]$ dBi=2.6dBi;

For 5250MHz~5350MHz: Directional gain= $10\log [(10^{0.6/20} + 10^{0.1/20})^2 / 2]$ dBi=3.4dBi;

For 5470MHz~5725MHz: Directional gain= $10\log [(10^{0.1/20} + 10^{0.0/20})^2 / 2]$ dBi=3.1dBi;

For 5725MHz~5850MHz: Directional gain= $10\log [(10^{-2.6/20} + 10^{1.4/20})^2 / 2]$ dBi=2.6dBi.

Note2: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Shenzhen Academy of Information and Communications Technology.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of Receipt
UT10aa	863994060028495	11	realme UI 5.0	2023-10-17
	863994060028487			
UT07aa	867815060019513	11	realme UI 5.0	2022-10-19
	867815060019505			
UT06aa	867815060019497	11	realme UI 5.0	2022-10-19
	867815060019489			

*EUT ID: is used to identify the test sample in the lab internally.



UT10aa is used for conduction test, UT07aa is used for radiation test, and UT06aa is used for AC Power line Conducted Emission test.

3.3. Internal Identification of AE used during the test

AE No.	Description	AE ID*
AE1	Battery	/
AE2	Charger	/
AE3	USB Cable	/

AE1

Model	BLPA35
Manufacturer	Sunwoda Electronic Co.,Ltd.
Capacity	4880mAh
Nominal Voltage	3.91 V

AE2

Model	VCB70AUH
Manufacturer	HUIZHOU GOLDEN LAKE INDUSTRIAL CO., LTD
Specification	American Standard Charger

AE3

Model	DL129
Manufacturer	/

*AE ID and AE Label: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment under Test (EUT) is a model of Smart Phone with PIFA antenna and battery. It consists of normal options: Lithium Battery, Charger and USB Cable. Manual and specifications of the EUT were provided to fulfil the test. Samples undergoing test were selected by the client.



4. REFERENCE DOCUMENTS

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47,Part 15,Subpart C FCC CFR 47,Part 15,Subpart E	2021
FCC 06-96	Revision of Parts 2 and 15 of the Commission's Rules to Permit Unlicensed National Information Infrastructure (U-NII) devices in the 5 GHz band	2006
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	2013
KDB 789033	GUIDELINES FOR COMPLIANCE TESTING OF UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE (U-NII) DEVICES PART 15, SUBPART E	V02r01
KDB 905462	Compliance Measurement Procedures for Unlicensed-national Information Infrastructure Devices Operating in the 5250-5350 MHz and 5470-5725 MHz Bands Incorporating Dynamic Frequency Selection	D02
KDB 662911	Emissions Testing of Transmitters with Multiple Outputs in the Same Band (e.g., MIMO, Smart Antenna, etc)	V02r01



5. Test Results

5.1. Testing Environment

Normal Temperature: 15~35°C

Relative Humidity: 20~75%

5.2. Test Results

No.	Test cases	Sub-clause of Part15E	Verdict
0	Maximum Output Power	15.407(a)	P
1	Power Spectral Density	15.407(a)	P
2	Occupied 26dB Bandwidth	15.403(i)	/
3	Occupied 6dB Bandwidth	15.407(e)	P
4	99% Occupied Bandwidth	15.403	/
5	Dynamic Frequency Selection	15.407 (h)	P
6	Band edge compliance	15.209	P
7	Radiated Spurious Emissions	15.209	P
8	AC Power line Conducted	15.207	P
9	Transmit Power Control	15.407	NA

See **ANNEX A** for details.

Note: According to the definition of the application description, the device will automatically discontinue transmission in case of either absence of information to transmit or operational failure.

5.3. Statements

SAICT has evaluated the test cases requested by the applicant/manufacturer as listed in section 5.2 of this report, for the EUT specified in section 3, according to the standards or reference documents listed in section 4.2

Disclaimer:

A. After confirmation with the customer, the sample information provided by the customer may affect the validity of the measurement results in this report, and the impact and consequences arising therefrom shall be borne by the customer.

B. The samples in this report are provided by the customer, and the test results are only applicable to the samples received.



6. Test Equipments Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date	Calibration Period
1	Vector Signal Analyzer	FSV40	100903	Rohde & Schwarz	2023-12-28	1 year
2	Power Sensor	U2021XA	MY55430013	Keysight	2023-12-28	1 year
3	Data Acquisition	U2531A	TW55443507	Keysight	/	/
4	RF Control Unit	JS0806-2	21C8060398	Tonscend	2024-05-07	1 year
5	Vector Signal General	SMU200A	104096	Rohde & Schwarz	2023-12-28	1 year
6	Shielding Room	S81	CT000986-1344	ETS-Lindgren	2026-09-12	5 years
No.	Equipment	Model	FCC ID	Manufacturer	Calibration Due date	Calibration Period
7	Master AP	RT-AX86U	MSQ-RTAXI600	ASUS	/	/

Radiated test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Due date	Calibration Period
1	Test Receiver	ESR7	101676	Rohde & Schwarz	2024-11-22	1 year
2	Spectrum Analyzer	FSV40	101192	Rohde & Schwarz	2024-01-11	1 year
3	BiLog Antenna	3142E	0224831	ETS-Lindgren	2024-05-27	3 years
4	Horn Antenna	3117	00066577	ETS-Lindgren	2025-04-17	3 years
5	Horn Antenna	QSH-SL-1 8-26-S-20	17013	Q-par	2026-02-01	3 years
6	Horn Antenna	QSH-SL-2 6-40-K-20	17014	Q-par	2026-01-30	3 years
7	Anechoic Chamber	FACT3-2.0	1285	ETS-Lindgren	2025-05-28	2 years
8	Loop Antenna	HLA6120	35779	TESEQ	2025-05-12	3 years
9	Test Receiver	ESCI	100702	Rohde & Schwarz	2024-01-11	1 year
10	LISN	ENV216	102067	Rohde & Schwarz	2024-10-07	1 year

Test software

No.	Equipment	Manufacturer	Version
1	JS1120-3	Tonscend	3.3
2	EMC32	Rohde & Schwarz	10.50.40

EUT is engineering software provided by the customer to control the transmitting signal. The EUT was programmed to be in continuously transmitting mode.

7. Laboratory Environment

Shielded room

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω

Anechoic chamber

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz> 60 dB; 1MHz-18000MHz>90 dB
Electrical insulation	> 2MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	<±4 dB, 3 m distance, from 30 to 1000 MHz
Voltage Standing Wave Ratio (VSWR)	≤ 6 dB, from 1 to 18 GHz, 3m distance
Uniformity of field strength	Between 0 and 6 dB, from 80 to 6000 MHz

**8. Measurement Uncertainty**


Test Name	Uncertainty ($k=2$)	
1. Maximum output Power	1.36dB	
2. Peak Power Spectral Density	1.36dB	
3. Occupied 26dB Bandwidth	4.56kHz	
4. Occupied 6dB Bandwidth	4.56kHz	
5. 99% Occupied Bandwidth	4.56kHz	
6. Band Edges Compliance	4.68dB	
7. Transmitter Spurious Emission - Radiated	$9\text{kHz} \leq f < 30\text{MHz}$	1.70dB
	$30\text{MHz} \leq f < 1\text{GHz}$	4.80dB
	$1\text{GHz} \leq f < 18\text{GHz}$	4.62dB
	$18\text{GHz} \leq f \leq 40\text{GHz}$	2.36dB
8. AC Power line Conducted Emission	$150\text{kHz} \leq f \leq 30\text{MHz}$	2.68dB

ANNEX A: Detailed Test Results


A.1. Measurement Method

1) Conducted Measurements

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode.
- 3). Set the EUT to the required channel.
- 4). Set the spectrum analyzer to start measurement.
- 5). Record the values.



6). The below figure shows the DFS setup, where the EUT is a WLAN device operating in slave mode, without Radar Interference Detection function. This setup also contains a device operating in master mode. The radar test signals are injected into the master device. The EUT (slave device) is associated with the master device. WLAN traffic is generated by streaming the mpeg file from the master to the slave in full monitor video mode using the media player.




2) Radiated Emission Measurements

Test setup:

9kHz-30MHz:


The EUT are measured in a anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 3m from the receiving antenna. The center of the receiving loop antenna is 1.0 meter above the ground. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT and adjusting the receiver antenna polarization.




30MHz-40GHz:

The EUT are measured in a anechoic chamber. The EUT is placed on a non-conductive stand of 80cm high, and at a measurement distance of 3m from the receiving antenna. The center of the receiving antenna is 1.0 meter to 4.0 meter above the ground. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT and adjusting the receiver antenna polarization.


30MHz-1GHz:



1GHz-3GHz:




3GHz-40GHz:



3) AC Power line Conducted Emission Measurement

For WLAN, the EUT is working under test mode. The EUT is commanded to operate at maximum transmitting power.





A.2. Maximum output Power

Measurement Limit and Method:

Standard	Frequency (MHz)	Limit (dBm)
FCC CRF Part 15.407(a)	5150MHz~5250MHz	24
	5250MHz~5350MHz	24 or 11+10logB
	5470MHz~5725MHz	24 or 11+10logB
	5725MHz~5850MHz	30

Limit use the less value, and B is the 26dB bandwidth.

Measurement of method: See ANSI C63.10-2013-Clause 12.3.3.2.

Method PM-G is a measurement using a gated RF average power meter.

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

Measurement Results:

SISO:

Mode	Frequency (MHz)	RF output power (dBm)		Conclusion
		Antenna 9	Antenna 2	
802.11a	5180MHz(CH36)	12.16	11.85	P
	5200MHz(CH40)	14.80	14.10	P
	5240MHz(CH48)	12.44	11.22	P
	5260MHz(CH52)	14.95	14.15	P
	5280MHz(CH56)	14.81	14.18	P
	5320MHz(CH64)	14.33	13.98	P
	5500MHz(CH100)	15.95	15.80	P
	5580MHz(CH116)	16.58	16.53	P
	5700MHz(CH140)	14.48	14.44	P
	5745MHz(CH149)	15.64	15.57	P
	5785MHz(CH157)	15.60	15.36	P
802.11n-HT20	5825MHz(CH165)	15.80	15.04	P
	5180MHz(CH36)	11.88	11.67	P
	5200MHz(CH40)	14.36	13.78	P
	5240MHz(CH48)	12.18	10.80	P
	5260MHz(CH52)	14.52	13.72	P
	5280MHz(CH56)	14.35	13.79	P
	5320MHz(CH64)	13.98	13.56	P
	5500MHz(CH100)	15.72	15.58	P
	5580MHz(CH116)	16.27	16.25	P
	5700MHz(CH140)	13.60	13.56	P
5745MHz(CH149)	15.39	15.25	P	



	5785MHz(CH157)	15.33	15.08	P
	5825MHz(CH165)	15.52	14.68	P
802.11ac-VHT20	5180MHz(CH36)	11.85	11.70	P
	5200MHz(CH40)	14.35	13.78	P
	5240MHz(CH48)	12.16	10.84	P
	5260MHz(CH52)	14.53	13.73	P
	5280MHz(CH56)	14.37	13.76	P
	5320MHz(CH64)	14.01	13.55	P
	5500MHz(CH100)	15.75	15.55	P
	5580MHz(CH116)	16.34	16.28	P
	5700MHz(CH140)	13.66	13.47	P
	5745MHz(CH149)	15.41	15.21	P
	5785MHz(CH157)	15.32	15.09	P
	5825MHz(CH165)	15.44	14.66	P
802.11ax-HE20	5180MHz(CH36)	12.14	11.87	P
	5200MHz(CH40)	14.64	14.03	P
	5240MHz(CH48)	12.27	11.11	P
	5260MHz(CH52)	14.86	13.96	P
	5280MHz(CH56)	14.70	14.04	P
	5320MHz(CH64)	14.29	13.77	P
	5500MHz(CH100)	15.91	15.79	P
	5580MHz(CH116)	16.40	16.45	P
	5700MHz(CH140)	14.26	14.18	P
	5745MHz(CH149)	15.62	15.47	P
	5785MHz(CH157)	15.49	15.27	P
5825MHz(CH165)	15.78	14.92	P	
802.11n-HT40	5190MHz(CH38)	12.04	11.67	P
	5230MHz(CH46)	14.94	14.23	P
	5270MHz(CH54)	14.79	14.19	P
	5310MHz(CH62)	11.52	11.11	P
	5510MHz(CH102)	14.01	13.73	P
	5550MHz(CH110)	16.70	16.55	P
	5670MHz(CH134)	15.62	15.27	P
	5755MHz(CH151)	15.49	15.43	P
	5795MHz(CH159)	15.55	15.43	P
802.11ac-VHT40	5190MHz(CH38)	14.88	13.87	P
	5230MHz(CH46)	14.88	14.20	P
	5270MHz(CH54)	14.78	14.16	P
	5310MHz(CH62)	11.47	11.07	P
	5510MHz(CH102)	13.94	13.70	P
	5550MHz(CH110)	16.67	16.51	P
	5670MHz(CH134)	15.49	15.23	P
	5755MHz(CH151)	15.46	15.40	P



	5795MHz(CH159)	15.54	15.39	P
802.11ax-HE40	5190MHz(CH38)	14.62	13.63	P
	5230MHz(CH46)	14.75	13.91	P
	5270MHz(CH54)	14.65	14.17	P
	5310MHz(CH62)	11.28	11.00	P
	5510MHz(CH102)	13.68	13.64	P
	5550MHz(CH110)	16.55	16.51	P
	5670MHz(CH134)	15.49	15.17	P
	5755MHz(CH151)	15.31	15.24	P
802.11ac-VHT80	5795MHz(CH159)	15.33	15.15	P
	5210MHz(CH42)	11.92	11.18	P
	5290MHz(CH58)	10.35	9.87	P
	5530MHz(CH106)	11.17	11.16	P
	5610MHz(CH122)	14.80	14.70	P
802.11ax-HE80	5775MHz(CH155)	15.54	15.27	P
	5210MHz(CH42)	11.82	11.08	P
	5290MHz(CH58)	10.22	9.85	P
	5530MHz(CH106)	11.14	11.12	P
	5610MHz(CH122)	14.71	14.65	P
802.11ac-VHT160	5775MHz(CH155)	15.52	15.22	P
	5250MHz(CH50)	10.72	10.02	P
802.11ax-HE160	5570MHz(CH114)	10.57	10.72	P
	5250MHz(CH50)	10.75	10.10	P
802.11ax-HE160	5570MHz(CH114)	10.60	10.79	P

MIMO:

Mode	Frequency (MHz)	RF output power (dBm)	Conclusion
802.11n-HT20	5180MHz(CH36)	14.30	P
	5200MHz(CH40)	16.79	P
	5240MHz(CH48)	14.29	P
	5260MHz(CH52)	16.67	P
	5280MHz(CH56)	16.61	P
	5320MHz(CH64)	16.36	P
	5500MHz(CH100)	18.12	P
	5580MHz(CH116)	18.85	P
	5700MHz(CH140)	16.40	P
	5745MHz(CH149)	17.76	P
	5785MHz(CH157)	17.62	P
	5825MHz(CH165)	17.56	P
802.11ac-VHT20	5180MHz(CH36)	14.28	P
	5200MHz(CH40)	16.78	P
	5240MHz(CH48)	14.27	P
	5260MHz(CH52)	16.68	P



	5280MHz(CH56)	16.59	P
	5320MHz(CH64)	16.30	P
	5500MHz(CH100)	18.09	P
	5580MHz(CH116)	18.82	P
	5700MHz(CH140)	16.41	P
	5745MHz(CH149)	17.74	P
	5785MHz(CH157)	17.61	P
	5825MHz(CH165)	17.53	P
802.11ax-HE20	5180MHz(CH36)	14.47	P
	5200MHz(CH40)	16.99	P
	5240MHz(CH48)	14.56	P
	5260MHz(CH52)	16.95	P
	5280MHz(CH56)	16.86	P
	5320MHz(CH64)	16.59	P
	5500MHz(CH100)	18.36	P
	5580MHz(CH116)	19.09	P
	5700MHz(CH140)	16.64	P
	5745MHz(CH149)	17.96	P
	5785MHz(CH157)	17.84	P
5825MHz(CH165)	17.76	P	
802.11n-HT40	5190MHz(CH38)	14.51	P
	5230MHz(CH46)	17.11	P
	5270MHz(CH54)	17.02	P
	5310MHz(CH62)	13.85	P
	5510MHz(CH102)	16.51	P
	5550MHz(CH110)	19.21	P
	5670MHz(CH134)	18.16	P
	5755MHz(CH151)	17.91	P
	5795MHz(CH159)	17.78	P
802.11ac-VHT40	5190MHz(CH38)	17.13	P
	5230MHz(CH46)	17.09	P
	5270MHz(CH54)	17.00	P
	5310MHz(CH62)	13.79	P
	5510MHz(CH102)	16.48	P
	5550MHz(CH110)	19.15	P
	5670MHz(CH134)	18.14	P
	5755MHz(CH151)	17.90	P
	5795MHz(CH159)	17.74	P
802.11ax-HE40	5190MHz(CH38)	16.84	P
	5230MHz(CH46)	16.79	P
	5270MHz(CH54)	16.70	P
	5310MHz(CH62)	13.62	P
	5510MHz(CH102)	16.13	P



	5550MHz(CH110)	18.91	P
	5670MHz(CH134)	17.84	P
	5755MHz(CH151)	17.61	P
	5795MHz(CH159)	17.47	P
802.11ac-VHT80	5210MHz(CH42)	14.22	P
	5290MHz(CH58)	12.75	P
	5530MHz(CH106)	13.57	P
	5610MHz(CH122)	17.06	P
	5775MHz(CH155)	17.68	P
802.11ax-HE80	5210MHz(CH42)	14.15	P
	5290MHz(CH58)	12.60	P
	5530MHz(CH106)	13.46	P
	5610MHz(CH122)	16.99	P
	5775MHz(CH155)	17.61	P
802.11ac-VHT160	5250MHz(CH50)	12.93	P
	5570MHz(CH114)	13.35	P
802.11ax-HE160	5250MHz(CH50)	13.00	P
	5570MHz(CH114)	13.39	P

Note:

The data rate 1Mbps (11b mode), 6Mbps (11g mode), MCS0 (11n mode), MCS0 (VHT mode) and MCS0 (11ax mode) are selected as the Worst-Case. 11ax-HE20(RU242), 11ax-HE40(RU484), 11ax-HE80(RU996) and 11ax-HE160(996*2RU) are the type with maximum outpower level. 802.11a(ax-HE20), 11n-HT40, 11ac-VHT80 and 11ax-HE160 are selected as the worst-case (SISO(Antenna 9) and MIMO). The following cases and test graphs are mostly performed with this condition.

The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

Conclusion: PASS



A.3. Peak Power Spectral Density (conducted)

Measurement of method: See KDB 789033 D02 v02r01, Section F.

Measurement Limit:

Standard	Frequency (MHz)	Limit
FCC CRF Part 15.407(a)	5150MHz~5250MHz	11dBm/MHz
	5250MHz~5350MHz	11dBm/MHz
	5470MHz~5725MHz	11dBm/MHz
	5725MHz~5850MHz	30dBm/500kHz

The PPSD measurement method SA-1 is made according to KDB 789033.

Measurement Results:

SISO:

Mode	Frequency (MHz)	Power Spectral Density(dBm/MHz)	Conclusion
802.11a	5180MHz(CH36)	1.15	P
	5200MHz(CH40)	3.24	P
	5240MHz(CH48)	1.59	P
	5260MHz(CH52)	2.95	P
	5280MHz(CH56)	3.03	P
	5320MHz(CH64)	2.90	P
	5500MHz(CH100)	4.96	P
	5580MHz(CH116)	5.30	P
802.11n-HT40	5700MHz(CH140)	3.13	P
	5190MHz(CH38)	-2.21	P
	5230MHz(CH46)	0.67	P
	5270MHz(CH54)	-0.23	P
	5310MHz(CH62)	-2.93	P
	5510MHz(CH102)	-0.03	P
	5550MHz(CH110)	2.57	P
802.11ac-VHT80	5670MHz(CH134)	0.55	P
	5210MHz(CH42)	-5.45	P
	5290MHz(CH58)	-7.19	P
	5530MHz(CH106)	-5.66	P
802.11ax-HE160	5610MHz(CH122)	-2.94	P
	5250MHz(CH50)	-9.16	P
	5570MHz(CH114)	-9.38	P
Mode	Frequency (MHz)	Power Spectral Density (dBm/500kHz)	Conclusion
802.11a	5745MHz(CH149)	1.13	P
	5785MHz(CH157)	1.55	P
	5825MHz(CH165)	1.16	P
802.11n-HT40	5755MHz(CH151)	-1.92	P
	5795MHz(CH159)	-2.27	P



802.11ac-VHT80	5775MHz(CH155)	-4.55	P
----------------	----------------	-------	----------

MIMO:

Mode	Frequency (MHz)	Power Spectral Density(dBm/MHz)	Conclusion
802.11ax-HE20	5180MHz(CH36)	2.38	P
	5200MHz(CH40)	4.15	P
	5240MHz(CH48)	2.15	P
	5260MHz(CH52)	3.93	P
	5280MHz(CH56)	3.92	P
	5320MHz(CH64)	3.84	P
	5500MHz(CH100)	6.19	P
	5580MHz(CH116)	6.95	P
802.11n-HT40	5700MHz(CH140)	4.24	P
	5190MHz(CH38)	0.00	P
	5230MHz(CH46)	3.09	P
	5270MHz(CH54)	2.38	P
	5310MHz(CH62)	0.06	P
	5510MHz(CH102)	2.75	P
	5550MHz(CH110)	4.60	P
802.11ac-VHT80	5670MHz(CH134)	3.88	P
	5210MHz(CH42)	-3.75	P
	5290MHz(CH58)	-5.05	P
	5530MHz(CH106)	-3.64	P
802.11ax-HE160	5610MHz(CH122)	-0.29	P
	5250MHz(CH50)	-7.67	P
802.11ax-HE20	5570MHz(CH114)	-6.46	P
	5745MHz(CH149)	2.90	P
	5785MHz(CH157)	2.98	P
802.11n-HT40	5825MHz(CH165)	2.79	P
	5755MHz(CH151)	1.13	P
802.11n-HT40	5795MHz(CH159)	0.23	P
	802.11ac-VHT80	5775MHz(CH155)	-2.42

Conclusion: PASS



A.4. Occupied 26dB Bandwidth (conducted)

Measurement of method: See KDB 789033 D02 v02r01, Section C.1.

Measurement Limit:

Standard	Limit (MHz)
FCC 47 CFR Part 15.403 (i)	/

The measurement is made according to KDB 789033

Measurement Result:

Mode	Frequency (MHz)	Occupied 26dB Bandwidth (MHz)		Conclusion
		Fig.	Value	
802.11a	5180MHz(CH36)	Fig.1	18.64	/
	5200MHz(CH40)	Fig.2	18.68	/
	5240MHz(CH48)	/	18.44	/
	5260MHz(CH52)	/	18.48	/
	5280MHz(CH56)	/	18.48	/
	5320MHz(CH64)	/	18.36	/
	5500MHz(CH100)	/	18.44	/
	5580MHz(CH116)	/	18.52	/
	5700MHz(CH140)	/	18.84	/
	5745MHz(CH149)	/	18.52	/
	5785MHz(CH157)	/	18.40	/
	5825MHz(CH165)	/	18.56	/
802.11n-HT40	5190MHz(CH38)	Fig.3	39.76	/
	5230MHz(CH46)	Fig.4	40.00	/
	5270MHz(CH54)	/	40.16	/
	5310MHz(CH62)	/	39.84	/
	5510MHz(CH102)	/	39.84	/
	5550MHz(CH110)	/	40.08	/
	5670MHz(CH134)	/	40.32	/
	5755MHz(CH151)	/	40.56	/
	5795MHz(CH159)	/	40.32	/
802.11ac-VHT80	5210MHz(CH42)	Fig.5	81.28	/
	5290MHz(CH58)	Fig.6	81.28	/
	5530MHz(CH106)	/	81.28	/
	5610MHz(CH122)	/	81.44	/
	5775MHz(CH155)	/	81.12	/
802.11ax-HE160	5250MHz(CH50)	Fig.7	163.84	/
	5570MHz(CH114)	Fig.8	165.76	/

See below for test graphs.

Conclusion: **PASS**




Fig. 1 Occupied 26dB Bandwidth (802.11a, 5180MHz)




Fig. 2 Occupied 26dB Bandwidth (802.11a, 5200MHz)




Fig. 3 Occupied 26dB Bandwidth (802.11n-HT40, 5190MHz)




Fig. 4 Occupied 26dB Bandwidth (802.11n-HT40, 5230MHz)




Fig. 5 Occupied 26dB Bandwidth (802.11ac-VHT80, 5210MHz)




Fig. 6 Occupied 26dB Bandwidth (802.11ac-VHT80, 5290MHz)




Fig. 7 Occupied 26dB Bandwidth (802.11ax-HE160, 5250MHz)




Fig. 8 Occupied 26dB Bandwidth (802.11ax-HE160, 5570MHz)



A.5. Occupied 6dB Bandwidth (conducted)

Measurement of method: See KDB 789033 D02 v02r01, Section C.2.

Measurement Limit:

Standard	Limit (MHz)
FCC 47 CFR Part 15.407 (e)	≥ 0.5

The measurement is made according to KDB 789033.

Measurement Result:

Mode	Frequency (MHz)	Occupied 6dB Bandwidth (MHz)		Conclusion
		Fig.	Value	
802.11a	5745MHz(CH149)	Fig.9	15.12	P
	5785MHz(CH157)	Fig.10	14.48	P
	5825MHz(CH165)	Fig.11	15.12	P
802.11n-HT40	5755MHz(CH151)	Fig.12	35.04	P
	5795MHz(CH159)	Fig.13	35.04	P
802.11ac-VHT80	5775MHz(CH155)	Fig.14	61.44	P

See below for test graphs.

Conclusion: PASS




Fig. 9 Occupied 6dB Bandwidth (802.11a, 5745MHz)




Fig. 10 Occupied 6dB Bandwidth (802.11a, 5785MHz)




Fig. 11 Occupied 6dB Bandwidth (802.11a, 5825MHz)




Fig. 12 Occupied 6dB Bandwidth (802.11n-HT40, 5755MHz)




Fig. 13 Occupied 6dB Bandwidth (802.11n-HT40, 5795MHz)




Fig. 14 Occupied 6dB Bandwidth (802.11ac-VHT80, 5775MHz)



A.6. 99% Occupied Bandwidth (conducted)

Measurement of method: See KDB 789033 D02 v02r01, Section D.

Measurement Limit:

Standard	Limit (MHz)
FCC 47 CFR Part 15.403	/

The measurement is made according to KDB 789033.

Measurement Result:

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)		Conclusion
		Fig.	Value	
802.11a	5180MHz(CH36)	Fig.15	16.50	/
	5200MHz(CH40)	Fig.16	16.50	/
	5240MHz(CH48)	/	16.50	/
	5260MHz(CH52)	/	16.50	/
	5280MHz(CH56)	/	16.50	/
	5320MHz(CH64)	/	16.50	/
	5500MHz(CH100)	/	16.50	/
	5580MHz(CH116)	/	16.54	/
	5700MHz(CH140)	/	16.50	/
	5745MHz(CH149)	/	16.54	/
	5785MHz(CH157)	/	16.46	/
	5825MHz(CH165)	/	16.50	/
802.11n-HT40	5190MHz(CH38)	Fig.17	36.04	/
	5230MHz(CH46)	Fig.18	35.88	/
	5270MHz(CH54)	/	36.04	/
	5310MHz(CH62)	/	35.96	/
	5510MHz(CH102)	/	35.96	/
	5550MHz(CH110)	/	35.96	/
	5670MHz(CH134)	/	36.04	/
	5755MHz(CH151)	/	36.04	/
	5795MHz(CH159)	/	36.04	/
802.11ac-VHT80	5210MHz(CH42)	Fig.19	74.97	/
	5290MHz(CH58)	Fig.20	75.13	/
	5530MHz(CH106)	/	74.81	/
	5610MHz(CH122)	/	74.81	/
	5775MHz(CH155)	/	75.13	/
802.11ax-HE160	5250MHz(CH50)	Fig.21	155.68	/
	5570MHz(CH114)	Fig.22	156.00	/

See below for test graphs.

Conclusion: PASS




Fig. 15 99% Occupied Bandwidth (802.11a, 5180MHz)




Fig. 16 99% Occupied Bandwidth (802.11a, 5200MHz)




Fig. 17 99% Occupied Bandwidth (802.11n-HT40, 5190MHz)




Fig. 18 99% Occupied Bandwidth (802.11n-HT40, 5230MHz)




Fig. 19 99% Occupied Bandwidth (802.11ac-VHT80, 5210MHz)




Fig. 20 99% Occupied Bandwidth (802.11ac-VHT80, 5290MHz)




Fig. 21 99% Occupied Bandwidth (802.11ax-HE160, 5250MHz)




Fig. 22 99% Occupied Bandwidth (802.11ax-HE160, 5570MHz)

A.7. Dynamic Frequency Selection

The EUT is Client without radar detection (only support client mode).

Measurement of method: See KDB 905462-D02.

Measurement Limit:

Standard	Test Items	Limit
FCC 47 CFR Part 15.407 (h)	Channel Move Time	< 10 s
	Channel Closing Transmission Time	< 200 ms + 60 ms
	Non-Occupancy Period	> 1800 s

The measurement is made according to KDB 905462.

1). Parameters of DFS test signal:


Interference threshold values, master or client incorporation in service monitoring. For device Power less than 23dBm (E.I.R.P.), the threshold level is -62 dBm at the antenna port after Correction for antenna gain and procedural adjustments.

Because of conducted measurement performed, the calibration power from radar signal generator to antenna port of DFS test equipment is -62 dBm.

Maximum Transmit Power	Value
> 200 mW	-64 dBm
< 200 mW	-62 dBm

2). Parameters of the reference DFS test signal:

Pulse width W (µs)	Pulse repetition frequency PRF (PPS)	Pulses per burst (PPB)
1	700	18



Radar Signal (Type 0)



Measurement Results:

Channel Move Time & Channel Closing Transmission Time:

Mode	Frequency (MHz)	Test Results	Conclusion
802.11a	5320MHz(Ch64)	Fig.23	P
802.11ax-HE160	5570MHz(Ch114)	Fig.24	P

Non-Occupancy Period:

Mode	Frequency (MHz)	Test Results	Conclusion
802.11a	5320MHz(Ch64)	Fig.25	P
802.11ax-HE160	5570MHz(Ch114)	Fig.26	P

See below for test graphs.

Conclusion: PASS