UNII Declaration Letter

We	have declared below	w featured for FCC ed	quipment authorizatio	on, device FCC ID: 24	AUYFRMX3910,
(1) [DFS Device		ent with Radar detect dar detection capabili		
(2)	Active / Passive Sca	inning , adhoc mode a	access point capabili	ty	
	Frequency Band (MHz)	Active Scanning (the device can transmit a probe (beacon))	passive scanning (where the device is can listen only with no probes)	Ad Hoc Mode capability	Access point capability
	2412 – 2462 MHz 5150 – 5250 MHz 5250 – 5350 MHz 5470 – 5725 MHz 5725 – 5850 MHz	⊠ Yes, □ No ⊠ Yes, □ No □ Yes, ⋈ No □ Yes, ⋈ No ⋈ Yes, □ No	☐ Yes, ☒ No ☐ Yes, ☒ No ☒ Yes, ☐ No ☒ Yes, ☐ No ☐ Yes, ☒ No	☐ Yes, ☒ No ☐ Yes, ☒ No ☐ Yes, ☒ No ☐ Yes, ☒ No ☐ Yes, ☒ No	⊠ Yes, □ No ⊠ Yes, □ No □ Yes, ⋈ No □ Yes, ⋈ No ⋈ Yes, □ No
(3) Country code selection ability - \square Yes , \boxtimes No If no, pls explain how was implemented : use Microsoft network utility					
 (4) Meet 15.202 requirement - ☑ Yes , ☐ No , pls check below : ☐ A master device is defined as a device operating in a mode in which it has the capability to transmit without receiving an enabling signal. In this mode it is able to select a channel and initiate a network by sending enabling signals to other devices ☑ A client device is defined as a device operating in a mode in which the transmissions of the device are under control of the master. A device in client mode is not able to initiate a network. (5) For client devices that have software configuration control to operate in different modes (active scanning in some and passive scanning in others) in different bands (devices with multiple equipment classes or those that operate on non-DFS frequencies) or modular devices which configure the modes of operations through software, the application must provide software and operations description on how the software and / or hardware is implemented to ensure that proper operations modes can not be modified by end user or an installer. ☑ Apply , ☐ No Apply , (If apply , pls help to provide explanation on how it was implement (By hardware or software , and how software was controlled) The active or passive mode was controlled by software. For non-DFS frequency used active scanning, for DFS frequency was switched to passive scanning by software Mechanism 					
If yo	ou have any question	ns, please feel free to	contact me at the ad	ddress shown below.	
You	rs sincerely,				
Sigr	natory				
			Megast.		
	tact Person: Mega l ail: mega@realme.c				