

TEST REPORT

Applicant: Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address: No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China
Equipment Type: Mobile Phone
Model Name: RMX3938
Brand Name: realme
FCC ID: 2AUYFRMX3938
Test Standard: 47 CFR Part 15 Subpart B
ANSI C63.4-2014
Sample Arrival Date: Sep. 24, 2024
Test Date: Sep. 25, 2024
Date of Issue: Sep. 30, 2024

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Li JunFeng

Checked by: Liu Zhenxiang

Approved by: Sunny Zou
(Technical Director)

Li JunFeng

Liu zhen xiang

Sunny Zou

Revision History		
<u>Version</u>	<u>Issue Date</u>	<u>Revisions</u>
<u>Rev. 01</u>	<u>Sep. 30, 2024</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	3
1.1	Test Laboratory	3
1.2	Test Location	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information	4
2.2	Manufacturer Information.....	4
2.3	General Description for Equipment under Test (EUT).....	4
2.4	Ancillary Equipment.....	4
2.5	Technical Information	5
3	SUMMARY OF TEST RESULTS	6
3.1	Test Standards	6
3.2	Verdict	6
3.3	Test Uncertainty	6
4	GENERAL TEST CONFIGURATIONS	7
4.1	Test Enclosure List.....	7
4.2	Test Configurations	7
4.3	Test Setups	9
5	TEST ITEMS	11
5.1	Emission Tests	11
ANNEX A	TEST RESULTS.....	16
A.1	Radiated Emission.....	16
ANNEX B	TEST SETUP PHOTOS	23
ANNEX C	EUT EXTERNAL PHOTOS.....	23
ANNEX D	EUT INTERNAL PHOTOS.....	23

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	<input checked="" type="checkbox"/> Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	<input type="checkbox"/> 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address	No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China

2.2 Manufacturer Information

Manufacturer	Realme Chongqing Mobile Telecommunications Corp., Ltd.
Address	No.178 Yulong Avenue, Yufengshan, Yubei District, Chongqing, China

2.3 General Description for Equipment under Test (EUT)

EUT Name	Mobile Phone
Model Name Under Test	RMX3938
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	11
Software Version	realme UI Android 14
Dimensions (Approx.)	167.26*76.67*7.84mm
Weight (Approx.)	187g
EUT ID	S03
IMEI Number	IMEI: 860996070019912/9904

2.4 Ancillary Equipment

Ancillary Equipment 1	Li-Polymer Battery 1	
	Brand Name	realme
	Model No.	BLPA75
	Capacitance	Rated: 4880mAh/19.09Wh Typical: 5000mAh/19.55Wh
	Rated Voltage	3.91V
	Limited Voltage	4.5 V
	Manufacturer	Dongguan NVT Technology Co., Ltd.
Ancillary Equipment 2	Power Supply Unit 1	
	Brand Name	SUPERVOOC
	Model No.	OP52JCUH (US Plug)
	Manufacturer	GOLDEN LAKE
	Rated Input	100-240VAC 50/60Hz 0.4A
	Rated Output	5.0VDC 2.0A 10.0W
Ancillary Equipment 3	Power Supply Unit 2	

	Brand Name	SUPERVOOC
	Model No.	OP52JCUH (US Plug)
	Manufacturer	Chenyang
	Rated Input	100-240VAC 50/60Hz 0.4A
	Rated Output	5.0VDC 2.0A 10.0W
Ancillary Equipment 4	USB Cable 1	
	Model No.	DL154
	Length (Approx.)	1.0 m
Ancillary Equipment 5	Li-Polymer Battery 2	
	Brand Name	realme
	Model No.	BLPB21
	Capacitance	Rated: 4880mAh/19.09Wh Typical: 5000mAh/19.55Wh
	Rated Voltage	3.91V
	Limited Voltage	4.48 V
	Manufacturer	Dongguan NVT Technology Co., Ltd.
Note 1: Letter in () means plug type.		
Note 2: All adapters are tested, only the worst data of OP52JCUH (US Plug) shown in this report.		
Note 3: All batteries are tested, only the worst data of BLPB21 shown in this report.		

2.5 Technical Information

Network and Wireless connectivity	2G Network GSM/GPRS/EDGE 850/1900 MHz 3G Network WCDMA/HSDPA/HSUPA Band 2/4/5 4G Network LTE FDD Band 2/4/5/7/13/66 LTE TDD Band 38/41 Bluetooth (BR+EDR+BLE) 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20/40) 5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80) U-NII-1/2A/2C/3, Galileo, GLONASS, GPS, BDS, SBAS
Classification of equipment	Class B
The highest internal frequency of EUT	5850 MHz

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Verdict

No.	Description	FCC Rule	Test Verdict	Remark
1	Radiated Emission	15.109	Pass	--
<p>Note: Compared with the EUT of test report BL-SZ2441131-401, the changes of the EUT of this report as below:</p> <ol style="list-style-type: none"> 1. The model name RMX3933 is updated to RMX3938. 2. Add a second supply battery. 3. Changed Rear Camera from 32M to 8M. 4. Changed Rear Camera from Flicker to AF. 5. Increase the shell color, the raw material yellow card unchanged. <p>Other hardware circuit and software are the same as EUT referred in test report BL-SZ2441131-401.</p> <p>Therefore, only The Rear Camera Test Mode of Radiated Emission was retested in this report.</p>				

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Radiated emissions (30 MHz-1 GHz)-966#2	4.4 dB
Radiated emissions (1 GHz-18 GHz)-966#2	5.0 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Enclosure List

Description	Manufacturer	Model	Serial No.	Length	Description	Use
Wireless Communications Test Set	R&S	CMW500	127801	N/A	Cal. Due 2024.12.04	<input checked="" type="checkbox"/>
Laptop	Lenovo	N/A	N/A	N/A	N/A	<input checked="" type="checkbox"/>
Data connector	N/A	N/A	N/A	N/A	N/A	<input checked="" type="checkbox"/>
USB disk	Sandisk	N/A	N/A	N/A	32G	<input checked="" type="checkbox"/>
TF Card	SAMSUNG	N/A	N/A	N/A	256G	<input checked="" type="checkbox"/>
Type-C Headset	OPPO	N/A	N/A	N/A	1.12m	<input checked="" type="checkbox"/>
Headset	OPPO	N/A	N/A	N/A	1.12m	<input checked="" type="checkbox"/>

4.2 Test Configurations

All test modes of EUT are listed in the table below.

Test Mode Configuration	Description
Mode 1	<u>The GSM850 RX Test Mode</u> GSM850 RX + EUT +Adapter + USB Cable + Battery + Headset + TF Card
Mode 2	<u>The WCDMA Band 5 RX Test Mode</u> WCDMA Band 5 RX + EUT +Adapter + USB Cable + Battery + Headset + TF Card
Mode 3	<u>The FDD LTE Band 5 RX Test Mode</u> LTE Band 5 RX + EUT +Adapter + USB Cable + Battery + Headset + TF Card
Mode 4	<u>The FDD LTE Band 13 RX Test Mode</u> LTE Band 13 RX + EUT +Adapter + USB Cable + Battery + Headset + TF Card
Mode 5	<u>The Standby Test Mode</u> EUT + Adapter + USB Cable + Battery + Headset + TF Card
Mode 6	<u>The Rear Camera Test Mode</u> EUT + Adapter + USB Cable + Battery + Headset + TF Card
Mode 7	<u>The Front Camera Test Mode</u> EUT + Adapter + USB Cable + Battery + Headset + TF Card
Mode 8	<u>The Video Play Test Mode</u> EUT + Adapter + USB Cable + Battery + Headset + TF Card
Mode 9	<u>The USB Test Mode</u> EUT + USB Cable + Battery + Laptop + Headset + TF Card
Mode 10	<u>The OTG Test Mode</u> EUT + Battery + Data connector + USB Disk + Headset + TF Card
Mode 11	<u>The Type-C Headset Test Mode</u>


	EUT + Type-C Headset + Battery
--	--------------------------------

Test Case	Test Worst Mode
Radiated Emission	6


Note: Only test data of the worst mode was presented in this report.

4.3 Test Setups

Test Setup 1




Radiated Emission (30 MHz-1 GHz)



Radiated Emission (above 1 GHz)

Test Setup 2



Conducted Emissions, AC Ports

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated Emission

5.1.1.1 Limit

Frequency range (MHz)	Class B (at 3 m)		Class A (at 3 m)
	Field Strength ($\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)
30 - 88	100	40	49.5
88 - 216	150	43.5	54
216 - 960	200	46	56.9
Above 960	500	54	60

NOTE:

- 1) Field Strength (dB $\mu\text{V/m}$) = 20*log [Field Strength ($\mu\text{V/m}$)].
- 2) In the emission tables above, the tighter limit applies at the band edges.
- 3) For 30 MHz to 1000 MHz, the CISPR quasi-peak is employed.

For above 1000 MHz, according to the requirements of FCC 15.35, unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Frequency range (GHz)	Class B (at 3 m)			Class A (at 3 m)	
	Field Strength ($\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)
1 - F _M	500	54	74	60	80

Note 1: The highest measurement frequency, F_M, in GHz, shall be determined as next Table.

Note 2: Average Class A limit at 3m L_{3m} is determined by the following conversion formula:

$$L_{3m} = L_{10m} + 20 \cdot \log(d_{10m}/d_{3m})$$
Where:
L_{3m} is Average Class A limit at 3m;
L_{10m} is Average Class A limit at 10m;
d_{10m} is Measurement distance in 10m;
d_{3m} is Measurement distance in 3m.
For this case: L_{3m} = 49.5 + 20*log(10/3)=60 (dB $\mu\text{V/m}$).

Highest internal frequency (F_X)	Highest measurement frequency (F_M)
$F_X \leq 108$ MHz	1 GHz
108 MHz $\leq F_X \leq 500$ MHz	2 GHz
500 MHz $\leq F_X \leq 1$ GHz	5 GHz
$F_X \geq 1$ GHz	$5 * F_X$ or 40 GHz, whichever is lower.
Note: F_X is Highest frequency generated or used in the device or on which the device operates or tunes.	

5.1.1.2 Test Setup

Refer to 4.3 section (test setup 1) for radiated emission test, the photo of test setup please refer to ANNEX B.

5.1.1.3 Test Procedure

All Radiated Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

The measurement frequency range is from 30 MHz to the 5th harmonic of the maximum frequency of the EUT internal source. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak for $f < 1$ GHz, peak & RMS Average for $f \geq 1$ GHz

Trace = max hold

5.1.1.4 Test Result and Test Equipment List

Please refer to ANNEX A.1.

NOTE:

1. Results (dB μ V/m) = Reading (dB μ V) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)

3. Margin = Limit - Results

5.1.2 Conducted Emission, AC Ports

5.1.2.1 Test Limit

Frequency range (MHz)	Class A	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	79	66
0.50 - 30	73	60

Frequency range (MHz)	Class B	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- 1) The lower limit shall apply at the band edges.
- 2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.

5.1.2.2 Test Setup

Refer to 4.3 section test (test setup 2) for conducted emission, the photo of test setup please refer to ANNEX B.

5.1.2.3 Test Procedure

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

Use the following spectrum analyzer settings:

RBW = 9 kHz

VBW \geq RBW

Sweep = 10ms

Detector function = peak & Average

Trace = max hold

5.1.2.4 Test Result and Test Equipment List

Please refer to ANNEX A.2.

NOTE:

1. Results (dB μ V) = Reading (dB μ V) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Margin = Limit - Results

ANNEX A TEST RESULTS

A.1 Radiated Emission

Note 1: The symbol of "--" in the table which means not application.


Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value

Note 3: The Radiated Emission is required to be investigated to the upper frequency of 5th harmonic of the highest internal frequency of EUT or 40 GHz, whichever is lower. The test results above 18GHz are only noise and are not recorded in the report.

Sample No.	S03	Temperature	25.6°C
Humidity	52%RH	Pressure	101kPa
Test Engineer	He shichang	Test Date	2024.09.25


Test Mode 6

1) Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	36.355	34.84	-27.97	40.0	5.16	Peak	170.00	101	Vertical	N/A
1*	36.355	31.15	-27.97	40.0	8.85	QP	170.00	101	Vertical	Pass
2	39.194	38.52	-26.92	40.0	1.48	Peak	92.00	100	Vertical	N/A
2*	39.194	34.78	-26.92	40.0	5.22	QP	92.00	100	Vertical	Pass
3	66.084	22.58	-27.80	40.0	17.42	Peak	88.00	100	Vertical	Pass
4	89.461	25.42	-28.71	43.5	18.08	Peak	294.00	100	Vertical	Pass
5	157.700	31.90	-29.72	43.5	11.60	Peak	231.00	100	Vertical	Pass
6	286.807	23.99	-23.90	46.0	22.01	Peak	353.00	200	Vertical	Pass


2) Test Antenna Horizontal, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	37.712	22.50	-27.33	40.0	17.50	Peak	310.00	200	Horizontal	Pass
2	132.820	26.21	-29.93	43.5	17.29	Peak	57.00	200	Horizontal	Pass
3	178.022	25.05	-28.66	43.5	18.45	Peak	55.00	200	Horizontal	Pass
4	287.293	26.74	-23.98	46.0	19.26	Peak	50.00	100	Horizontal	Pass
5	398.406	26.03	-21.02	46.0	19.97	Peak	100.00	100	Horizontal	Pass
6	676.699	24.99	-14.35	46.0	21.01	Peak	230.00	100	Horizontal	Pass


Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Below 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2024.08.01	2025.07.31	<input checked="" type="checkbox"/>
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B2017119081	2023.12.05	2024.12.04	<input checked="" type="checkbox"/>
Test Antenna- Bi-Log	SCHWARZB ECK	VULB 9168	9168-00867	2022.04.12	2025.04.11	<input checked="" type="checkbox"/>
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	<input checked="" type="checkbox"/>
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		<input checked="" type="checkbox"/>

3) Test Antenna Vertical, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1434.100	39.64	-15.80	74.0	34.36	Peak	74.00	100	Vertical	Pass
1**	1434.100	30.04	-15.80	54.0	23.96	AV	74.00	100	Vertical	Pass
2	2480.700	44.13	-10.04	74.0	29.87	Peak	159.00	100	Vertical	Pass
2**	2480.700	34.09	-10.04	54.0	19.91	AV	159.00	100	Vertical	Pass
3	3462.250	48.66	-4.35	74.0	25.34	Peak	120.00	100	Vertical	Pass
3**	3462.250	38.72	-4.35	54.0	15.28	AV	120.00	100	Vertical	Pass
4	5116.500	54.90	1.54	74.0	19.10	Peak	271.00	100	Vertical	Pass
4**	5116.500	46.08	1.54	54.0	7.92	AV	271.00	100	Vertical	Pass
5	7991.500	55.65	2.44	74.0	18.35	Peak	149.00	100	Vertical	Pass
5**	7991.500	45.43	2.44	54.0	8.57	AV	149.00	100	Vertical	Pass
6	13408.500	56.87	4.80	74.0	17.13	Peak	349.00	100	Vertical	Pass
6**	13408.500	47.04	4.80	54.0	6.96	AV	349.00	100	Vertical	Pass

4) Test Antenna Horizontal, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1076.500	38.69	-16.36	74.0	35.31	Peak	165.00	100	Horizontal	Pass
1**	1076.500	28.39	-16.36	54.0	25.61	AV	165.00	100	Horizontal	Pass
2	1922.300	40.66	-14.33	74.0	33.34	Peak	165.00	100	Horizontal	Pass
2**	1922.300	31.14	-14.33	54.0	22.86	AV	165.00	100	Horizontal	Pass
3	3183.250	48.72	-3.64	74.0	25.28	Peak	120.00	100	Horizontal	Pass
3**	3183.250	39.34	-3.64	54.0	14.66	AV	120.00	100	Horizontal	Pass
4	4545.750	52.13	-0.33	74.0	21.87	Peak	19.00	100	Horizontal	Pass
4**	4545.750	41.89	-0.33	54.0	12.11	AV	19.00	100	Horizontal	Pass
5	7999.750	56.30	2.90	74.0	17.70	Peak	360.00	100	Horizontal	Pass
5**	7999.750	46.23	2.90	54.0	7.77	AV	360.00	100	Horizontal	Pass
6	13795.000	56.54	5.59	74.0	17.46	Peak	292.00	100	Horizontal	Pass
6**	13795.000	47.53	5.59	54.0	6.47	AV	292.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Above 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2024.08.01	2025.07.31	<input checked="" type="checkbox"/>
Amplifier (1-12GHz)	Advanced Microwave	WLA652A	1740103	2023.12.05	2024.12.04	<input checked="" type="checkbox"/>
Amplifier (0.8-21GHz)	Mini-Circuits	ZVA-213-S+	225321316	2023.12.05	2024.12.04	<input checked="" type="checkbox"/>
Test Antenna-Horn	SCHWARZB ECK	BBHA 9120D	01917	2022.06.09	2025.06.08	<input checked="" type="checkbox"/>
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	<input checked="" type="checkbox"/>
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		<input checked="" type="checkbox"/>

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2490823-AE.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2490823-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2490823-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--