

Test Report

Applicant: Habitat Technologies LLC.
Address of Applicant: 330 East 38th Street, Suite 530, New York 10016, United States
Manufacturer/Factory: COMPUTIME ELECTRONICS (SHENZHEN) CO., LTD.
Address of Manufacturer/Factory: Computime Technology Pk, Dan Zhu Tou Cun Buji, Longgang Region Shenzhen China
Equipment Under Test (EUT)
Product Info: PTAC Coordinator
Model No.: HTZ-01, SAUPTZ1
FCC ID: 2AUYL-HTZ01
IC: 25666-HTZ01
Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247
RSS-Gen Issue 5
RSS-247 Issue 2
Date of sample receipt: March 02, 2020
Date of Test: March 04-24, 2020
Date of report issued: March 24, 2020
Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A circular blue stamp for GTS Global Testing Services Co., Ltd. is overlaid with a handwritten signature in black ink. The signature appears to read 'Robinson Lo' and is dated '2020 mar'. The stamp contains the text 'GTS GLOBAL TESTING SERVICES CO., LTD.' and '18019'.


Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	March 24, 2020	Original

Prepared By:



Date:

March 24, 2020

Project Engineer

Check By:



Date:

March 24, 2020

Reviewer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION.....	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS.....	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6 TEST FACILITY.....	7
5.7 TEST LOCATION	7
5.8 ADDITIONAL INSTRUCTIONS.....	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA.....	10
7.1 ANTENNA REQUIREMENT	10
7.2 CONDUCTED EMISSIONS	11
7.3 CONDUCTED PEAK OUTPUT POWER.....	14
7.4 CHANNEL BANDWIDTH & 99% OCCUPY BANDWIDTH.....	16
7.5 POWER SPECTRAL DENSITY	18
7.6 BAND EDGES.....	20
7.6.1 Conducted Emission Method.....	20
7.6.2 Radiated Emission Method.....	22
7.7 SPURIOUS EMISSION.....	29
7.7.1 Conducted Emission Method.....	29
7.7.2 Radiated Emission Method.....	31
7.8 FREQUENCY STABILITY	44
8 TEST SETUP PHOTO	46
9 EUT CONSTRUCTIONAL DETAILS	46

4 Test Summary

Test Item	Section	Result
Antenna requirement	FCC part 15.203/15.247 (c) RSS-Gen Section 6.8	Pass
AC Power Line Conducted Emission	FCC part 15.207 RSS-Gen Section 8.8	Pass
Conducted Peak Output Power	FCC part 15.247 (b)(3) RSS-247 Section 5.4(d)	Pass
Channel Bandwidth & 99% OCB	FCC part 15.247 (a)(2) RSS-247 Section 5.2(a) RSS-Gen Section 6.7	Pass
Power Spectral Density	FCC part 15.247 (e) RSS-247 Section 5.2(b)	Pass
Band Edge	FCC part 15.247(d) RSS-247 Section 5.5	Pass
Spurious Emission	FCC part 15.205/15.209 RSS-Gen Section 3.3 & 8.9 & 8.10	Pass
Frequency stability	RSS-Gen Section 6.11& Section 8.11	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark : Test according to ANSI C63.10:2013

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Info:	PTAC Coordinator
Model No.:	HTZ-01, SAUPTZ1
Test Model No:	HTZ-01
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The only difference is model name for commercial purpose.	
Serial No.:	001E5E0902238C65
Hardware version:	SBR1
Software version:	SAUPTZ1_Zigbee_20200108
Test sample(s) ID:	GTS202003000009-1
Sample(s) Status	Engineer sample
Operation Frequency:	2405MHz~2480MHz
Channel numbers:	16
Channel separation:	5MHz
Modulation type:	O-QPSK
Antenna Type:	PCB Antenna
Antenna gain:	0dBi (Declared by manufacturer)
Power supply:	DC 12V

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
11	2405MHz	15	2425MHz	19	2445MHz	23	2465MHz
12	2410MHz	16	2430MHz	20	2450MHz	24	2470MHz
13	2415MHz	17	2435MHz	21	2455MHz	25	2475MHz
14	2420MHz	18	2440MHz	22	2460MHz	26	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2405MHz
The middle channel	2440MHz
The Highest channel	2475/2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
<i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number
Supplied by client	AC adaptor AC input cable 90cm AC output cable 150cm	PPI76-24V05AC	N/A
Supplied by client	SAUPTR1	HTM-01	N/A

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

<p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> ● FCC —Registration No.: 381383 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383. ● IC —Registration No.: 9079A The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A ● NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

5.7 Test Location

All tests were performed at:
<p>Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960</p>

5.8 Additional instructions

Software (Used for test) from client

Built-in by manufacturer, power set default.
--

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 26 2019	June. 25 2020
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 26 2019	June. 25 2020
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 26 2019	June. 25 2020
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 26 2019	June. 25 2020
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 26 2019	June. 25 2020
9	Coaxial Cable	GTS	N/A	GTS211	June. 26 2019	June. 25 2020
10	Coaxial cable	GTS	N/A	GTS210	June. 26 2019	June. 25 2020
11	Coaxial Cable	GTS	N/A	GTS212	June. 26 2019	June. 25 2020
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 26 2019	June. 25 2020
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 26 2019	June. 25 2020
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 26 2019	June. 25 2020
15	Band filter	Amindeon	82346	GTS219	June. 26 2019	June. 25 2020
16	Power Meter	Anritsu	ML2495A	GTS540	June. 26 2019	June. 25 2020
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 26 2019	June. 25 2020
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 26 2019	June. 25 2020
19	Splitter	Agilent	11636B	GTS237	June. 26 2019	June. 25 2020
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 26 2019	June. 25 2020
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 19 2019	Oct. 18 2020
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 19 2019	Oct. 18 2020
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 19 2019	Oct. 18 2020
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 26 2019	June. 25 2020

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.15 2019	May.14 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 26 2019	June. 25 2020
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 26 2019	June. 25 2020
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June. 26 2019	June. 25 2020
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 26 2019	June. 25 2020
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 26 2019	June. 25 2020
9	ISN	SCHWARZBECK	NTFM 8158	GTD565	June. 26 2019	June. 25 2020

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 26 2019	June. 25 2020
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 26 2019	June. 25 2020
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 26 2019	June. 25 2020
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 26 2019	June. 25 2020
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 26 2019	June. 25 2020
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 26 2019	June. 25 2020
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 26 2019	June. 25 2020
8	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 26 2019	June. 25 2020
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 26 2019	June. 25 2020

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 26 2019	June. 25 2020
2	Barometer	ChangChun	DYM3	GTS255	June. 26 2019	June. 25 2020

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
<p>FCC Part 15.203 requirement:</p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(c) (1)(i) requirement:</p> <p>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p>	
<p>RSS-Gen 6.8</p> <p>The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.</p> <p>For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).</p>	
<p>EUT Antenna:</p> <p><i>The antenna is PCB antenna, the best case gain of the antenna is 0dBi, Reference to the appendix II for details.</i></p>	


7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207 RSS-Gen Section 8.8					
Test Method:	ANSI C63.10:2013 and RSS-Gen					
Test Frequency Range:	150KHz to 30MHz					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)	Limit (dBuV)				
		Quasi-peak		Average		
	0.15-0.5	66 to 56*		56 to 46*		
	0.5-5	56		46		
	5-30	60		50		
* Decreases with the logarithm of the frequency.						
Test setup:	<p>Reference Plane</p> <p>LISN</p> <p>40cm</p> <p>80cm</p> <p>LISN</p> <p>Filter</p> <p>AC power</p> <p>AUX Equipment</p> <p>E.U.T</p> <p>EMI Receiver</p> <p>Test table/Insulation plane</p> <p>Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>					
Test procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement. 					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V & AC 240V					
Test results:	Pass					

Remark: both AC 120V and 240V were test and compliance requirement, only AC 120V report.


Measurement data

Transmitting mode	Lowest	Polarization	Line
-------------------	--------	--------------	------



Freq MHz	Reading level dBuV	LISM/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.32	10.41	20.39	0.10	30.90	59.71	-28.81	QP
0.32	2.28	20.39	0.10	22.77	49.71	-26.94	Average
0.63	8.71	20.28	0.12	29.11	56.00	-26.89	QP
0.63	-0.36	20.28	0.12	20.04	46.00	-25.96	Average
0.84	5.00	20.23	0.14	25.37	56.00	-30.63	QP
0.84	-2.56	20.23	0.14	17.81	46.00	-28.19	Average
3.68	-5.74	20.20	0.18	14.64	56.00	-41.36	QP
3.68	-12.29	20.20	0.18	8.09	46.00	-37.91	Average
24.79	10.58	20.35	0.23	31.16	60.00	-28.84	QP
24.79	4.65	20.35	0.23	25.23	50.00	-24.77	Average
26.84	11.93	20.37	0.23	32.53	60.00	-27.47	QP
26.84	-1.84	20.37	0.23	18.76	50.00	-31.24	Average

Transmitting mode	Lowest	Polarization	Neutral
-------------------	--------	--------------	---------




Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.17	13.87	20.40	0.09	34.36	65.08	-30.72	QP
0.17	-3.84	20.40	0.09	16.65	55.08	-38.43	Average
0.24	7.96	20.40	0.11	28.47	62.22	-33.75	QP
0.24	0.46	20.40	0.11	20.97	52.22	-31.25	Average
0.32	12.08	20.39	0.10	32.57	59.71	-27.14	QP
0.32	3.94	20.39	0.10	24.43	49.71	-25.28	Average
0.50	7.22	20.31	0.11	27.64	56.00	-28.36	QP
0.50	-0.69	20.31	0.11	19.73	46.00	-26.27	Average
0.63	11.62	20.28	0.12	32.02	56.00	-23.98	QP
0.63	1.22	20.28	0.12	21.62	46.00	-24.38	Average
0.84	8.82	20.23	0.14	29.19	56.00	-26.81	QP
0.84	0.97	20.23	0.14	21.34	46.00	-24.66	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Conducted Peak Output Power


Test Requirement:	FCC Part15 C Section 15.247 (b)(3) RSS-247 Clause 5.4(d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance v05or02
Limit:	30dBm (36dBm e.i.r.p for IC requirement)
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data


Frequency (MHz)	Peak Output Power (dBm)	Limit(dBm)	Result
2405	19.05	30	PASS
2440	18.92		
2475	18.69		
2480	13.02		

Frequency (MHz)	E.I.R.P.(dBm)	Limit(dBm)	Result
2405	19.05	36	PASS
2440	18.92		
2475	18.69		
2480	13.02		


Test plot as follows:




2405MHz



2440MHz




2475MHz



2480MHz

7.4 Channel Bandwidth & 99% Occupy Bandwidth


Test Requirement:	FCC Part15 C Section 15.247 (a)(2) RSS-247 Clause 5.2(a)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance v05or02
Limit:	>500KHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data


Frequency (MHz)	Channel Bandwidth (MHz)	Limit(KHz)	Result
2405	1.681	>500	Pass
2440	1.677		
2475	1.656		
2480	1.689		

Frequency (MHz)	99% Occupy Bandwidth (MHz)	Result
2405	2.2702	Pass
2445	2.2694	
2475	2.2739	
2480	2.2847	


Test plot as follows:




2405MHz



2440MHz




2475MHz



2480MHz


7.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e) RSS-247 Clause 5.2(b)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance v05or02
Limit:	8dBm/3kHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Frequency (MHz)	Power Spectral Density (dBm)	Limit (dBm/3kHz)	Result
2405	4.06	8.00	Pass
2440	2.90		
2475	3.18		
2480	-2.49		


Test plot as follows:




2405MHz



2440MHz




2475MHz




2480MHz

7.6 Band edges


7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d) RSS-247 Clause 5.5 & RSS-Gen 8.9
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance v05or02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by two legs. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Test plot as follows:



Lowest channel




Highest channel/2475MHz



Highest channel/2480MHz

7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205 RSS-Gen Clause 8.9&8.10				
Test Method:	ANSI C63.10:2013 and RSS-Gen				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		RMS	1MHz	3MHz	Average
Limit:	Frequency	Limit (dBuV/m @3m)		Value	
	Above 1GHz	54.00		Average	
		74.00		Peak	
Test setup:					
Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report. 				
Test Instruments:	Refer to section 6.0 for details				


Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement data:

Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.


Test channel:	2405MHz
---------------	---------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	24.42	27.14	2.81	36.79	17.58	54.00	-36.42	Average
2310.000	39.73	27.14	2.81	36.79	32.89	74.00	-41.11	Peak
2390.000	33.98	27.37	2.91	36.85	27.41	54.00	-26.59	Average
2390.000	45.04	27.37	2.91	36.85	38.47	74.00	-35.53	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	29.86	27.14	2.81	36.79	23.02	54.00	-30.98	Average
2310.000	39.22	27.14	2.81	36.79	32.38	74.00	-41.62	Peak
2390.000	30.85	27.37	2.91	36.85	24.28	54.00	-29.72	Average
2390.000	40.05	27.37	2.91	36.85	33.48	74.00	-40.52	Peak


Test channel:	2475MHz
---------------	---------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.503	48.95	27.66	2.99	36.93	42.67	54.00	-11.33	Average
2483.503	58.05	27.66	2.99	36.93	51.77	74.00	-22.23	Peak
2500.000	47.65	27.70	3.01	36.94	41.42	54.00	-12.58	Average
2500.000	58.54	27.70	3.01	36.94	52.31	74.00	-21.69	Peak


Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.503	32.72	27.66	2.99	36.93	26.44	54.00	-27.56	Average
2483.503	43.06	27.66	2.99	36.93	36.78	74.00	-37.22	Peak
2500.000	28.79	27.70	3.01	36.94	22.56	54.00	-31.44	Average
2500.000	39.83	27.70	3.01	36.94	33.60	74.00	-40.40	Peak


Test channel:	2480MHz
---------------	---------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	57.58	27.66	2.99	36.93	51.30	54.00	-2.70	Average
2483.500	68.54	27.66	2.99	36.93	62.26	74.00	-11.74	Peak
2500.000	31.70	27.70	3.01	36.94	25.47	54.00	-28.53	Average
2500.000	43.01	27.70	3.01	36.94	36.78	74.00	-37.22	Peak

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	49.07	27.66	2.99	36.93	42.79	54.00	-11.21	Average
2483.500	60.12	27.66	2.99	36.93	53.84	74.00	-20.16	Peak
2500.000	29.83	27.70	3.01	36.94	23.60	54.00	-30.40	Average
2500.000	40.86	27.70	3.01	36.94	34.63	74.00	-39.37	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.


7.7 Spurious Emission

7.7.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d) RSS-247 Clause 5.5
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance v05or02
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:

Lowest channel




Middle channel




30MHz~25GHz

Highest channel/2475MHz






Highest channel/2480MHz



30MHz~25GHz

7.7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 RSS-Gen Clause 8.9&8.10				
Test Method:	ANSI C63.10:2013 and RSS-Gen				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit: (Spurious Emissions)	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	QP	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	300m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
		5000	Peak		
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				

<p>Test setup:</p>	<p>Below 30MHz</p>  <p>Below 1GHz</p>  <p>Above 1GHz</p> 
<p>Test Procedure:</p>	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

	<ol style="list-style-type: none"> 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test environment:	Temp.: 25 °C Humid.: 52% Press.: 1012mbar
Test voltage:	AC 120V, 60Hz
Test results:	Pass

Measurement data:

■ Below 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.


Remark:

Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

■ **Below 1GHz**


Remark: both AC 120V and 240V were test and compliance requirement, only AC 120V report.

Transmitting mode	Lowest	Polarization	Horizontal
-------------------	--------	--------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
35.499	38.90	11.42	0.61	35.39	15.54	40.00	-24.46	QP
40.845	38.24	12.21	0.67	35.71	15.41	40.00	-24.59	QP
98.487	34.65	12.00	1.18	36.71	11.12	43.50	-32.38	QP
319.937	36.53	13.98	2.47	37.44	15.54	46.00	-30.46	QP
696.857	42.65	19.60	4.08	37.63	28.70	46.00	-17.30	QP
768.748	39.69	20.84	4.35	37.62	27.26	46.00	-18.74	QP

Transmitting mode	Lowest	Polarization	Vertical
-------------------	--------	--------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
38.346	52.16	11.92	0.64	35.57	29.15	40.00	-10.85	QP
45.375	45.49	12.26	0.72	35.96	22.51	40.00	-17.49	QP
59.232	44.09	11.38	0.85	36.31	20.01	40.00	-19.99	QP
96.099	37.93	11.65	1.16	36.69	14.05	43.50	-29.45	QP
216.024	41.43	11.02	1.93	37.35	17.03	46.00	-28.97	QP
595.133	37.69	19.39	3.70	37.54	23.24	46.00	-22.76	QP

■ Above 1GHz


Test channel:	Lowest
---------------	--------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4810.000	25.55	31.20	4.61	37.73	23.63	54.00	-30.37	Average
4810.000	32.55	31.20	4.61	37.73	30.63	74.00	-43.37	Peak
7215.000	21.06	36.20	6.50	35.63	28.13	54.00	-25.87	Average
7215.000	29.55	36.20	6.50	35.63	36.62	74.00	-37.38	Peak
9620.000	22.20	37.93	7.98	34.94	33.17	54.00	-20.83	Average
9620.000	29.30	37.93	7.98	34.94	40.27	74.00	-33.73	Peak

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4810.000	25.59	31.20	4.61	37.73	23.67	54.00	-30.33	Average
4810.000	34.00	31.20	4.61	37.73	32.08	74.00	-41.92	Peak
7215.000	21.59	36.20	6.50	35.63	28.66	54.00	-25.34	Average
7215.000	30.24	36.20	6.50	35.63	37.31	74.00	-36.69	Peak
9620.000	21.17	37.93	7.98	34.94	32.14	54.00	-21.86	Average
9620.000	28.98	37.93	7.98	34.94	39.95	74.00	-34.05	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. No emission found in frequency above 18GHz.


Test channel:	Middle
---------------	--------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	35.55	31.31	4.69	37.75	33.80	54.00	-20.20	Average
4880.000	38.43	31.31	4.69	37.75	36.68	74.00	-37.32	Peak
7320.000	21.66	36.43	6.63	35.60	29.12	54.00	-24.88	Average
7320.000	31.08	36.43	6.63	35.60	38.54	74.00	-35.46	Peak
9760.000	21.80	38.10	8.03	35.03	32.90	54.00	-21.10	Average
9760.000	28.95	38.10	8.03	35.03	40.05	74.00	-33.95	Peak

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4880.000	25.54	31.31	4.69	37.75	23.79	54.00	-30.21	Average
4880.000	35.08	31.31	4.69	37.75	33.33	74.00	-40.67	Peak
7320.000	20.06	36.43	6.63	35.60	27.52	54.00	-26.48	Average
7320.000	29.77	36.43	6.63	35.60	37.23	74.00	-36.77	Peak
9760.000	21.51	38.10	8.03	35.03	32.61	54.00	-21.39	Average
9760.000	28.62	38.10	8.03	35.03	39.72	74.00	-34.28	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. No emission found in frequency above 18GHz.


Test channel:	Highest/2475MHz
---------------	-----------------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4950.000	26.05	31.41	4.77	37.78	24.45	54.00	-29.55	Average
4950.000	33.86	31.41	4.77	37.78	32.26	74.00	-41.74	Peak
7425.000	21.51	36.66	6.75	35.56	29.36	54.00	-24.64	Average
7425.000	30.89	36.66	6.75	35.56	38.74	74.00	-35.26	Peak
9900.000	23.80	38.27	8.09	35.12	35.04	54.00	-18.96	Average
9900.000	31.17	38.27	8.09	35.12	42.41	74.00	-31.59	Peak


Vertical::



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4950.000	25.85	31.41	4.77	37.78	24.25	54.00	-29.75	Average
4950.000	33.50	31.41	4.77	37.78	31.90	74.00	-42.10	Peak
7425.000	22.05	36.66	6.75	35.56	29.90	54.00	-24.10	Average
7425.000	28.56	36.66	6.75	35.56	36.41	74.00	-37.59	Peak
9900.000	21.24	38.27	8.09	35.12	32.48	54.00	-21.52	Average
9900.000	28.89	38.27	8.09	35.12	40.13	74.00	-33.87	Peak


Test channel:	Highest/2480MHz
---------------	-----------------

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	37.64	31.44	4.79	37.78	36.09	54.00	-17.91	Average
4960.000	38.84	31.44	4.79	37.78	37.29	74.00	-36.71	Peak
7440.000	28.03	36.66	6.77	35.56	35.90	54.00	-18.10	Average
7440.000	32.17	36.66	6.77	35.56	40.04	74.00	-33.96	Peak
9920.000	27.74	38.30	8.09	35.14	38.99	54.00	-15.01	Average
9920.000	32.17	38.30	8.09	35.14	43.42	74.00	-30.58	Peak

Vertical::




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4960.000	40.02	31.44	4.79	37.78	38.47	54.00	-15.53	Average
4960.000	40.95	31.44	4.79	37.78	39.40	74.00	-34.60	Peak
7440.000	28.54	36.66	6.77	35.56	36.41	54.00	-17.59	Average
7440.000	32.06	36.66	6.77	35.56	39.93	74.00	-34.07	Peak
9920.000	28.51	38.30	8.09	35.14	39.76	54.00	-14.24	Average
9920.000	32.07	38.30	8.09	35.14	43.32	74.00	-30.68	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. No emission found in frequency above 18GHz.

7.8 Frequency stability

Test Requirement:	RSS-Gen Section 6.11& Section 8.11
Test Method:	ANSI C63.10: 2013 & RSS-Gen
Limit:	Manufactures of devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified
Test Procedure:	The EUT was setup to ANSI C63.10, 2013; tested to 2.1055 for compliance to RSS-Gen requirements.
Test setup:	 <p style="text-align: center;">Note : Measurement setup for testing on Antenna connector</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Remark: Set the EUT transmits at un-modulation mode to test frequency stability.

Measurement data:

Frequency stability versus Temp.						
Power Supply: DC 12V						
Temp. (°C)	Operating Frequency (MHz)	0 minute Measured Frequency (MHz)	2 minute Measured Frequency (MHz)	5 minute Measured Frequency (MHz)	10 minute Measured Frequency (MHz)	Pass /Fail
-30	2405	2405.00	2405.01	2405.01	2405.01	Pass
	2440	2440.00	2440.01	2440.02	2440.02	Pass
	2475	2475.00	2475.00	2475.01	2475.01	Pass
	2480	2480.00	2480.00	2480.01	2480.01	Pass
20	2405	2405.00	2405.00	2405.00	2405.00	Pass
	2440	2440.00	2440.00	2440.00	2440.00	Pass
	2475	2475.00	2475.00	2475.00	2475.00	Pass
	2480	2480.00	2480.00	2480.00	2480.00	Pass
50	2405	2405.00	2405.00	2405.01	2405.01	Pass
	2440	2440.00	2440.00	2440.01	2440.01	Pass
	2475	2475.00	2475.00	2475.00	2475.00	Pass
	2480	2480.00	2480.00	2480.00	2480.00	Pass
Frequency stability versus Voltage						
Temperature: 20°C						
Power Supply (Vdc)	Operating Frequency (MHz)	0 minute Measured Frequency (MHz)	2 minute Measured Frequency (MHz)	5 minute Measured Frequency (MHz)	10 minute Measured Frequency (MHz)	Pass /Fail
12	2405	2405.00	2405.00	2405.00	2405.00	Pass
	2440	2440.00	2440.00	2440.00	2440.00	Pass
	2475	2475.00	2475.00	2475.00	2475.00	Pass
	2480	2480.00	2480.00	2480.00	2480.00	Pass
13.2	2405	2405.00	2405.00	2405.01	2405.01	Pass
	2440	2440.00	2440.00	2440.01	2440.01	Pass
	2475	2475.00	2475.00	2475.00	2475.00	Pass
	2480	2480.00	2480.00	2480.00	2480.00	Pass

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----