

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: **2AV29-B152BU**

EUT Specification

EUT	Wireless Video Baby Camera		
Frequency band (Operating)	<input type="checkbox"/>	WLAN: 2.412GHz ~ 2.462GHz	
	<input type="checkbox"/>	WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz	
	<input type="checkbox"/>	WLAN: 5.745GHz ~ 5825GHz	
	<input checked="" type="checkbox"/>	Others: SRD 2.4G	
Device category	<input type="checkbox"/>	Portable (<20cm separation)	
	<input checked="" type="checkbox"/>	Mobile (>20cm separation)	
	<input type="checkbox"/>	Others _____	
Exposure classification	<input type="checkbox"/>	Occupational/Controlled exposure	
	<input checked="" type="checkbox"/>	General Population/Uncontrolled exposure	
Antenna diversity	<input checked="" type="checkbox"/>	Single antenna	
	<input type="checkbox"/>	Multiple antennas	
	<input type="checkbox"/>	Tx diversity	
	<input type="checkbox"/>	Rx diversity	
	<input type="checkbox"/>	Tx/Rx diversity	
Max. output power	19.53 dBm (0.0897W)		
Antenna gain (Max)	2 dBi		
Evaluation applied	<input checked="" type="checkbox"/>	MPE Evaluation	
	<input type="checkbox"/>	SAR Evaluation	

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	30
1500-100000	--	--	1	30

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn



Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Operating Mode	Channel Frequency (MHz)	Maximum output power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
2.4G	2406	19.00	19.00 ±1	20.00	2	0.0315	1
	2442	19.53	19.53 ±1	20.53	2	0.0356	1
	2475	19.16	19.16 ±1	20.16	2	0.0327	1

Result: No Standalone SAR test is required.

