



Report No.: TBR-C-202204-0149-3  
Page: 1 of 50

# Radio Test Report

FCC ID: 2AV29-B255

**Report No.** : TBR-C-202204-0149-3

**Applicant** : Zhongshan Jesmay Electronics Co., Ltd

## Equipment Under Test (EUT)

**EUT Name** : Baby Monitor

**Model No.** : JM55875T

**Series Model No.** : B255

**Brand Name** : JouSecu, JouJou, JouLINK

**Sample ID** : 202204-0149-3-1# 202204-0149-3-2#

**Receipt Date** : 2022-05-16

**Test Date** : 2022-05-16 to 2022-06-01

**Issue Date** : 2022-06-06

**Standards** : FCC Part 15, Subpart C 15.247

**Test Method** : ANSI C63.10: 2013


**Conclusions** : **PASS**

In the configuration tested, the EUT complied with the standards specified above,

The EUT technically complies with the FCC requirements

**Test/Witness Engineer** : Seven Wu

**Engineer Supervisor** : Ivan Su

**Engineer Manager** :  Ray Lai

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

TB-RF-074-1.0

## Contents

<b>CONTENTS.....</b>	<b>2</b>
<b>1. GENERAL INFORMATION ABOUT EUT .....</b>	<b>5</b>
1.1 Client Information.....	5
1.2 General Description of EUT (Equipment Under Test) .....	5
1.3 Block Diagram Showing the Configuration of System Tested.....	6
1.4 Description of Support Units .....	7
1.5 Description of Test Mode.....	7
1.6 Description of Test Software Setting .....	8
1.7 Measurement Uncertainty .....	8
1.8 Test Facility.....	9
<b>2. TEST SUMMARY .....</b>	<b>10</b>
<b>3. TEST SOFTWARE.....</b>	<b>10</b>
<b>4. TEST EQUIPMENT.....</b>	<b>11</b>
<b>5. CONDUCTED EMISSION TEST.....</b>	<b>12</b>
5.1 Test Standard and Limit.....	12
5.2 Test Setup.....	12
5.3 Test Procedure.....	13
5.4 Deviation From Test Standard.....	13
5.5 EUT Operating Mode .....	13
5.6 Test Data.....	13
<b>5. RADIATED EMISSION TEST .....</b>	<b>14</b>
6.1 Test Standard and Limit.....	14
6.2 Test Setup.....	15
6.3 Test Procedure.....	16
6.4 Deviation From Test Standard.....	17
6.5 EUT Operating Condition .....	17
6.6 Test Data.....	17
<b>6. RESTRICTED BANDS AND BAND-EDGE TEST .....</b>	<b>18</b>
7.1 Test Standard and Limit.....	18
7.2 Test Setup.....	18
7.3 Test Procedure.....	19
7.4 Deviation From Test Standard.....	20
7.5 EUT Operating Condition .....	20
7.6 Test Data.....	20
<b>7. NUMBER OF HOPPING CHANNEL .....</b>	<b>21</b>
8.1 Test Standard and Limit.....	21
8.2 Test Setup.....	21
8.3 Test Procedure.....	21
8.4 Deviation From Test Standard.....	21
8.5 EUT Operating Condition .....	21

8.6 Test Data.....	21
<b>8. AVERAGE TIME OF OCCUPANCY.....</b>	<b>22</b>
9.1 Test Standard and Limit.....	22
9.2 Test Setup.....	22
9.3 Test Procedure.....	22
9.4 EUT Operating Condition .....	22
9.4 Deviation From Test Standard.....	22
9.5 Test Data.....	22
<b>9. CHANNEL SEPARATION AND BANDWIDTH TEST .....</b>	<b>23</b>
10.1 Test Standard and Limit .....	23
10.2 Test Setup.....	23
10.3 Test Procedure.....	23
10.4 Deviation From Test Standard.....	23
10.5 EUT Operating Condition .....	23
10.6 Test Data.....	23
<b>10. PEAK OUTPUT POWER TEST.....</b>	<b>24</b>
11.1 Test Standard and Limit .....	24
11.2 Test Setup.....	24
11.3 Test Procedure.....	24
11.4 Deviation From Test Standard.....	24
11.5 EUT Operating Condition .....	24
11.6 Test Data.....	24
<b>11. ANTENNA REQUIREMENT.....</b>	<b>25</b>
12.1 Standard Requirement.....	25
12.2 Deviation From Test Standard.....	25
12.3 Antenna Connected Construction .....	25
12.4 Result.....	25
<b>ATTACHMENT A-- CONDUCTED EMISSION TEST DATA .....</b>	<b>26</b>
<b>ATTACHMENT B-- RADIATED EMISSION TEST DATA .....</b>	<b>28</b>
<b>ATTACHMENT C-- RESTRICTED BANDS REQUIREMENT TEST DATA .....</b>	<b>36</b>
<b>ATTACHMENT D-- NUMBER OF HOPPING CHANNEL TEST DATA .....</b>	<b>43</b>
<b>ATTACHMENT E-- AVERAGE TIME OF OCCUPANCY TEST DATA.....</b>	<b>44</b>
<b>ATTACHMENT F-- CHANNEL SEPARATION AND BANDWIDTH TEST DATA.....</b>	<b>46</b>
<b>BANDWIDTH TEST DATA: .....</b>	<b>46</b>
<b>ATTACHMENT G-- PEAK OUTPUT POWER TEST DATA .....</b>	<b>49</b>

## Revision History

Report No.	Version	Description	Issued Date
TBR-C-202204-0149-3	Rev.01	Initial issue of report	2022-06-06

## 1. General Information about EUT

### 1.1 Client Information

<b>Applicant</b>	:	Zhongshan Jesmay Electronics Co., Ltd
<b>Address</b>	:	No.1 Industry District, Tan Zhou Town, Zhong Shan City, Guangdong, China
<b>Manufacturer</b>	:	Zhongshan Jesmay Electronics Co., Ltd
<b>Address</b>	:	No.1 Industry District, Tan Zhou Town, Zhong Shan City, Guangdong, China

### 1.2 General Description of EUT (Equipment Under Test)

<b>EUT Name</b>	:	Baby Monitor
<b>Models No.</b>	:	JM55875T, B255
<b>Model Difference</b>	:	All these models are the same PCB, layout and electrical circuit, The only difference is the Brand Name.
<b>Product Description</b>	Operation Frequency:	2410MHz~2477MHz
	Number of Channel:	23 Channels <small>See Note 2</small>
	Antenna Gain:	3dBi PIFA Antenna
	Modulation Type:	GFSK
<b>Power Rating</b>	:	Adapter (Model: ZD5C050100USW) Input: AC 100-240V~50/60Hz, 0.2A Output: DC 5.0V,1A
<b>Software Version</b>	:	N/A
<b>Hardware Version</b>	:	N/A
<b>Remark</b>	:	The adapter and antenna gain provided by the applicant, the verified for the RF conduction test provided by TOBY test lab.

**Note:**

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

**TOBY**


## (2) Channel List:

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2410	15	2456		
01	2414	16	2459		
02	2417	17	2462		
03	2420	18	<b>2465</b>		
04	2423	19	2468		
05	2426	20	2471		
06	2429	21	2474		
07	2432	22	<b>2477</b>		
08	2435				
09	2438				
10	2441				
11	2444				
12	2447				
13	2450				
14	2453				

**Note: Test frequencies are lowest channel: 2410MHz, middle channel: 2441MHz and highest channel: 2477MHz.**

## (3) The Antenna information about the equipment is provided by the applicant.

## 1.3 Block Diagram Showing the Configuration of System Tested

**Adapter & TX Mode**

## 1.4 Description of Support Units

The EUT has been tested as an independent unit.

## 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	Adapter+ TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	TX GFSK Mode
Mode 2	TX Mode(GFSK) Channel 00/10/22
Mode 3	Hopping TX Mode

### Note:

(1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate. We have pretested all the test modes above.

According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

TX Mode: GFSK (4Mbps)

(2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis, X-plane, Y-plane and Z-plane. The worst case was found positioned on X-plane as the normal use. Therefore only the test data of this X-plane was used for radiated emission measurement test.

## 1.6 Description of Test Software Setting

During testing channel power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth mode.

<b>Test Software Version</b>	Adjust and control the corresponding transmission frequency through the EUT entity key.		
Frequency	2410 MHz	2441 MHz	2477 MHz
GFSK	DEF	DEF	DEF

## 1.7 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty ( $U_{Lab}$ )
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	$\pm 3.50$ dB $\pm 3.10$ dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	$\pm 4.60$ dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	$\pm 4.20$ dB
Radiated Emission	Level Accuracy: Above 1000MHz	$\pm 4.20$ dB

## 1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1/F.,Building 6, Rundongsheng Industrial Zone, Longzhu, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

### **CNAS (L5813)**

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

### **A2LA Certificate No.: 4750.01**

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01. FCC Accredited Test Site Number: 854351. Designation Number:CN1223

### **IC Registration No.: (11950A-1)**

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

## 2. Test Summary

Standard Section	Test Item	Test Sample(s)	Judgment	Remark
FCC				
FCC 15.207(a)	Conducted Emission	202204-0149-3#-1#	PASS	N/A
FCC 15.209 & 15.247(d)	Radiated Unwanted Emissions	202204-0149-3#-1#	PASS	N/A
FCC 15.203	Antenna Requirement	202204-0149-3#-2#	PASS	N/A
FCC 15.247(a)	99% Occupied Bandwidth & 20dB Bandwidth	202204-0149-3#-2#	PASS	N/A
FCC 15.247(b)(1)	Peak Output Power	202204-0149-3#-2#	PASS	N/A
FCC 15.247(a)(1)	Carrier frequency separation	202204-0149-3#-2#	PASS	N/A
FCC 15.247(a)(1)	Time of occupancy	202204-0149-3#-2#	PASS	N/A
FCC 15.247(b)(1)	Number of Hopping Frequency	202204-0149-3#-2#	PASS	N/A
FCC 15.247(d)	Band Edge	202204-0149-3#-2#	PASS	N/A
FCC 15.207(a)	Conducted Unwanted Emissions	202204-0149-3#-2#	PASS	N/A
FCC 15.205	Emissions in Restricted Bands	202204-0149-3#-2#	PASS	N/A

**Note:** N/A is an abbreviation for Not Applicable.

## 3. Test Software

Test Item	Test Software	Manufacturer	Version No.
Conducted Emission	EZ-EMC	EZ	CDI-03A2
Radiation Emission	EZ-EMC	EZ	FA-03A2RE
Radiation Emission	TS+	Tonsced	3.0.0.4
RF Conducted Measurement	MTS-8310	MWRFtest	V2.0.0.0

## 4. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 02, 2021	Jul. 01, 2022
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 02, 2021	Jul. 01, 2022
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 02, 2021	Jul. 01, 2022
LISN	Rohde & Schwarz	ENV216	101131	Jul. 02, 2021	Jul. 01, 2022
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	Jul. 02, 2021	Jul. 01, 2022
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 02, 2021	Jul. 01, 2022
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Feb.27, 2022	Feb.26, 2023
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 02, 2022	Mar. 01, 2023
Horn Antenna	SCHWARZBECK	BBHA 9170	1118	Mar. 02, 2022	Mar. 01, 2023
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jul. 06, 2021	Jul. 05, 2022
Pre-amplifier	SONOMA	310N	185903	Feb. 26, 2022	Feb.25, 2023
Pre-amplifier	HP	8449B	3008A00849	Feb. 26, 2022	Feb.25, 2023
HF Amplifier	Tonscend	TAP0184050	AP21C806129	Sep. 03, 2021	Sep. 02, 2022
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 02, 2021	Jul. 01, 2022
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	Jul. 02, 2021	Jul. 01, 2022
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Sep. 03, 2021	Sep. 02, 2022
Vector Signal Generator	Agilent	N5182A	MY50141294	Sep. 03, 2021	Sep. 02, 2022
Analog Signal Generator	Agilent	N5181A	MY50141953	Sep. 03, 2021	Sep. 02, 2022
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Sep. 03, 2021	Sep. 02, 2022
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Sep. 03, 2021	Sep. 02, 2022
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Sep. 03, 2021	Sep. 02, 2022
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Sep. 03, 2021	Sep. 02, 2022

## 5. Conducted Emission Test

### 5.1 Test Standard and Limit

#### 5.1.1 Test Standard

FCC Part 15.207

RSS-Gen 8.8

#### 5.1.2 Test Limit


Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) \*Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 5.2 Test Setup



### 5.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

### 5.4 Deviation From Test Standard

No deviation

### 5.5 EUT Operating Mode

Please refer to the description of test mode.

### 5.6 Test Data

Please refer to the Attachment A.

## 5. Radiated Emission Test

### 6.1 Test Standard and Limit

#### 6.1.1 Test Standard

**FCC Part 15.209 & FCC Part 15.247(d)**

#### 6.1.2 Test Limit

Radiated Emission Limit (9 kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Distance Meters(at 3m)	
	Peak	Average
Above 1000	74	54


**Note:**

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m)


## 6.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

### 6.3 Test Procedure

- (1) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency Below 1GHz. The EUT was placed on a rotating 0.8m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

## 6.4 Deviation From Test Standard

No deviation

## 6.5 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

## 6.6 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Please refer to the Attachment B.

## 6. Restricted Bands and Band-edge test

### 7.1 Test Standard and Limit

#### 7.1.1 Test Standard

FCC Part 15.205 & FCC Part 15.247(d)


#### 7.1.2 Test Limit

Radiated measurement		
Restricted Frequency Band (MHz)	Distance Meters(at 3m)	
	Peak (dBuV/m)	Average (dBuV/m)
2310 ~2390	74	54
2483.5 ~2500	74	54
Conducted measurement		
	Peak (dBm) <sup>see 7.3 e)</sup>	Average (dBm) <sup>see 7.3 e)</sup>
2310 ~2390	-41.20	-21.20
2483.5 ~2500	-41.20	-21.20


Note: According the ANSI C63.10 11.12.2 antenna-port conducted measurements may also be used as an alternative to radiated measurements for determining compliance in the restricted frequency bands requirements. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case emissions is required.

### 7.2 Test Setup

#### Radiated measurement



#### Conducted measurement



## 7.3 Test Procedure

### ---Radiated measurement

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

### ---Conducted measurement

- a) Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 11.12.2.3 through 11.12.2.5 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP (see 11.12.2.6 for guidance on determining the applicable antenna gain).
- c) Add the appropriate maximum ground reflection factor to the EIRP (6 dB for frequencies  $\leq 30$  MHz; 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive; and 0 dB for frequencies  $> 1000$  MHz).
- d) For MIMO devices, measure the power of each chain and sum the EIRP of all chains in linear terms (i.e., watts and mW).
- e) Convert the resultant EIRP to an equivalent electric field strength using the following

relationship:

$$E = \text{EIRP} - 20 \log d + 104.8$$

where

$E$  is the electric field strength in dBuV/m

EIRP is the equivalent isotropically radiated power in dBm

$d$  is the specified measurement distance in m

f) Compare the resultant electric field strength level with the applicable regulatory limit.

g) Perform the radiated spurious emission test.

## 7.4 Deviation From Test Standard

No deviation

## 7.5 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

## 7.6 Test Data

Remark: The test uses antenna-port conducted measurements as an alternative to radiated measurements for determining compliance in the restricted frequency bands requirements.

Please refer to the Attachment C.

## 7. Number of Hopping Channel

### 8.1 Test Standard and Limit


#### 8.1.1 Test Standard

FCC Part 15.247 (a)(1)

#### 8.1.2 Test Limit

Section	Test Item	Limit
15.247	Number of Hopping Channel	>15

### 8.2 Test Setup



### 8.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as shown in the block diagram above.
- (2) Spectrum Setting: RBW=100 KHz, VBW=100 KHz, Sweep time= Auto.

### 8.4 Deviation From Test Standard

No deviation

### 8.5 EUT Operating Condition

The EUT was set to the Hopping Mode by the Customer.

### 8.6 Test Data

Please refer to the Attachment D.

## 8. Average Time of Occupancy

### 9.1 Test Standard and Limit


#### 9.1.1 Test Standard

FCC Part 15.247 (a)(1)

#### 9.1.2 Test Limit

Test Item	Limit
Average Time of Occupancy	0.4 sec

### 9.2 Test Setup



### 9.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=100KHz, VBW=300KHz.
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.

### 9.4 EUT Operating Condition

The average time of occupancy on any channel within the Period can be calculated with formulas:

The Dwell Time = Burst Width \* Total Hops. The detailed calculations are showed as follows:

The duration for dwell time calculation:  $0.4 \text{ [s]} * \text{hopping number} = 0.4 \text{ [s]} * 20 \text{ [ch]} = 8.0 \text{ [s*ch]}$ ;

The burst width, which is directly measured, refers to the duration on one channel hop.

The maximum number of hopping channels in 8.0s = $3*(8.0/0.24) = 100$

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

The EUT was set to the Hopping Mode by the Customer.

### 9.4 Deviation From Test Standard

No deviation

### 9.5 Test Data

Please refer to the Attachment E.

## 9. Channel Separation and Bandwidth Test

### 10.1 Test Standard and Limit


#### 10.1.1 Test Standard

FCC Part 15.247

#### 10.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Bandwidth	<=1 MHz (20dB bandwidth)	2400~2483.5
Channel Separation	>25KHz or >two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

### 10.2 Test Setup



### 10.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
Channel Separation: RBW=100 kHz, VBW=100 kHz.  
Bandwidth: RBW=30 kHz, VBW=100 kHz.
- (3) The bandwidth is measured at an amplitude level reduced 20dB from the reference level.  
The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.
- (4) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:30 kHz, and Video Bandwidth:100 kHz. Sweep Time set auto.

### 10.4 Deviation From Test Standard

No deviation

### 10.5 EUT Operating Condition

The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Bandwidth Test.

### 10.6 Test Data

Please refer to the Attachment F.

## 10. Peak Output Power Test

### 11.1 Test Standard and Limit


#### 11.1.1 Test Standard

FCC Part 15.247 (b) (1)

#### 11.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400~2483.5

### 11.2 Test Setup



### 11.3 Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.

(2) Spectrum Setting:

Peak Detector: RBW=1 MHz, VBW=3 MHz for bandwidth less than 1MHz.

RBW=3 MHz, VBW=3 MHz for bandwidth more than 1MHz.

### 11.4 Deviation From Test Standard

No deviation

### 11.5 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

### 11.6 Test Data

Please refer to the Attachment G.

## 11. Antenna Requirement

### 12.1 Standard Requirement

#### 12.1.1 Standard

##### FCC Part 15.203

#### 12.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 12.2 Deviation From Test Standard

No deviation

### 12.3 Antenna Connected Construction

The gains of the antenna used for transmitting is 3 dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

### 12.4 Result

The EUT antenna is a PIFA Antenna. It complies with the standard requirement.

Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna

## Attachment A-- Conducted Emission Test Data

Temperature:	24.8°C	Relative Humidity:	47%					
Test Voltage:	AC 120V/60Hz							
Terminal:	Line							
Test Mode:	TX GFSK Mode 2410MHz							
Remark:	All channels have been tested and Shows only the worst channels.							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1539	24.98	10.26	35.24	65.78	-30.54	QP
2		0.1539	6.90	10.26	17.16	55.78	-38.62	AVG
3		0.1914	22.05	10.24	32.29	63.97	-31.68	QP
4		0.1914	5.43	10.24	15.67	53.97	-38.30	AVG
5		0.5460	23.48	10.17	33.65	56.00	-22.35	QP
6	*	0.5460	16.49	10.17	26.66	46.00	-19.34	AVG
7		0.9820	15.42	10.13	25.55	56.00	-30.45	QP
8		0.9820	6.62	10.13	16.75	46.00	-29.25	AVG
9		1.2980	16.27	9.99	26.26	56.00	-29.74	QP
10		1.2980	7.42	9.99	17.41	46.00	-28.59	AVG
11		18.0900	16.16	9.71	25.87	60.00	-34.13	QP
12		18.0900	3.94	9.71	13.65	50.00	-36.35	AVG
Emission Level= Read Level+ Correct Factor								

<b>Temperature:</b>	24.8°C	<b>Relative Humidity:</b>	47%					
<b>Test Voltage:</b>	AC 120V/60Hz							
<b>Terminal:</b>	Neutral							
<b>Test Mode:</b>	TX GFSK Mode 2410MHz							
<b>Remark:</b>	All channels have been tested and Shows only the worst channels.							
No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1580	24.53	10.23	34.76	65.56	-30.80	QP
2		0.1580	4.56	10.23	14.79	55.56	-40.77	AVG
3		0.2180	19.52	10.25	29.77	62.89	-33.12	QP
4		0.2180	0.85	10.25	11.10	52.89	-41.79	AVG
5		0.2740	15.75	10.26	26.01	60.99	-34.98	QP
6		0.2740	-1.50	10.26	8.76	50.99	-42.23	AVG
7	*	0.5380	19.97	10.19	30.16	56.00	-25.84	QP
8		0.5380	9.08	10.19	19.27	46.00	-26.73	AVG
9		1.0900	10.69	10.09	20.78	56.00	-35.22	QP
10		1.0900	0.40	10.09	10.49	46.00	-35.51	AVG
11		16.4260	8.94	9.86	18.80	60.00	-41.20	QP
12		16.4260	-0.52	9.86	9.34	50.00	-40.66	AVG

Emission Level= Read Level+ Correct Factor

**TOBY**


## Attachment B-- Radiated Emission Test Data

### 9KHz~30MHz


From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

### 30MHz~1GHz



TOBY



**Above 1GHz (Only worse case is reported)**

Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60Hz						
Ant. Pol.	Horizontal						
Test Mode:	TX GFSK Mode 2410MHz						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4820.187	69.70	-25.17	44.53	54.00	-9.47	AVG
2	4820.354	81.81	-25.17	56.64	74.00	-17.36	peak

**Emission Level= Read Level+ Correct Factor**

Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60Hz						
Ant. Pol.	Vertical						
Test Mode:	TX GFSK Mode 2410MHz						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4820.367	-4737.52	4795.20	57.68	74.00	-16.32	peak
2 *	4820.367	-4749.86	4795.20	45.34	54.00	-8.66	AVG

**Emission Level= Read Level+ Correct Factor**

TOBY

<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	AC 120V/60Hz						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX GFSK Mode 2441MHz						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4882.280	69.08	-25.00	44.08	54.00	-9.92	AVG
2	4882.423	82.34	-25.00	57.34	74.00	-16.66	peak

**Emission Level= Read Level+ Correct Factor**

<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	AC 120V/60Hz						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX GFSK Mode 2441MHz						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4882.176	-4814.50	4857.18	42.68	54.00	-11.32	AVG
2	4882.327	-4799.89	4857.33	57.44	74.00	-16.56	peak

**Emission Level= Read Level+ Correct Factor**

Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60Hz						
Ant. Pol.	Horizontal						
Test Mode:	TX GFSK Mode 2477MHz						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	4954.167	67.48	-24.80	42.68	54.00	-11.32	AVG
2	4954.287	81.62	-24.80	56.82	74.00	-17.18	peak

**Emission Level= Read Level+ Correct Factor**

Temperature:	25°C	Relative Humidity:	55%				
Test Voltage:	AC 120V/60Hz						
Ant. Pol.	Vertical						
Test Mode:	TX GFSK Mode 2477MHz						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4954.290	-4872.55	4929.49	56.94	74.00	-17.06	peak
2 *	4954.354	-4886.59	4929.55	42.96	54.00	-11.04	AVG

**Emission Level= Read Level+ Correct Factor**


## Conducted Emission Test Data

Condition	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	2410	Ant1	-59.67	-20	Pass
NVNT	2441	Ant1	-52.38	-20	Pass
NVNT	2477	Ant1	-56.23	-20	Pass



TOBY






## Attachment C-- Restricted Bands Requirement Test Data


### (1) Radiation Test

Condition	Frequency (MHz)	Antenna	Hopping Mode	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
NVNT	2410	Ant1	No-Hopping	2310	-50.59	3	47.67	Peak	74	Pass
NVNT	2410	Ant1	No-Hopping	2310	-58.97	3	39.29	Average	54	Pass
NVNT	2410	Ant1	No-Hopping	2313.224	-45.44	3	52.82	Peak	74	Pass
NVNT	2410	Ant1	No-Hopping	2313.64	-55.67	3	42.59	Average	54	Pass
NVNT	2410	Ant1	No-Hopping	2390	-47.82	3	50.44	Peak	74	Pass
NVNT	2410	Ant1	No-Hopping	2390	-57.02	3	41.24	Average	54	Pass
NVNT	2477	Ant1	No-Hopping	2483.5	-37.38	3	60.88	Peak	74	Pass
NVNT	2477	Ant1	No-Hopping	2483.5	-44.55	3	53.71	Average	54	Pass
NVNT	2477	Ant1	No-Hopping	2483.638	-37.24	3	61.02	Peak	74	Pass
NVNT	2477	Ant1	No-Hopping	2483.503	-44.55	3	53.71	Average	54	Pass
NVNT	2477	Ant1	No-Hopping	2500	-61	3	37.26	Peak	74	Pass
NVNT	2477	Ant1	No-Hopping	2500	-70.12	3	28.14	Average	54	Pass

TOBY



TOBY



## (2) Conducted Band Edge Test

Condition	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	2410	Ant1	No-Hopping	-60.02	-20	Pass
NVNT	2477	Ant1	No-Hopping	-41.18	-20	Pass



TOBY



TOBY

Condition	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	2410	Ant1	Hopping	-56.35	-20	Pass
NVNT	2477	Ant1	Hopping	-42.08	-20	Pass




TOBY

## Band Edge(Hopping) NVNT 2477MHz Ant1 Hopping Ref




## Band Edge(Hopping) NVNT 2477MHz Ant1 Hopping Emission



TOBY

## Attachment D-- Number of Hopping Channel Test Data



## Attachment E-- Average Time of Occupancy Test Data

Temperature:	25°C	Relative Humidity:	55%			
Test Voltage:	AC 120V/60Hz					
Test Mode:	Hopping Mode (GFSK)					
Remark:	The number of total hopping frequencies up to 19.					
Test Mode	Channel (MHz)	Reading Time (ms)	Total hops	Test Result (ms)	Limit (ms)	Result
GFSK	2441	3.320	90	298.8	400	PASS

The Dwell Time = Burst Width \* Total Hops. The detailed calculations are showed as follows:

The duration for dwell time calculation:  $0.4 \text{ [s]} * \text{hopping number} = 0.4 \text{ [s]} * 23 \text{ [ch]} = 9200[\text{ms}*\text{ch}]$ ;


The burst width, which is directly measured, refers to the duration on one channel hop.

The maximum number of hopping channels in 9200ms is  $(9200/920*9)=90$ ;


Reading Time=3.320

### GFSK Hopping Mode

2441 MHz



TOBY





## Attachment F-- Channel Separation and Bandwidth Test Data

### Bandwidth Test Data:

Condition	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	2/3 *20dB BW (MHz)	Verdict
NVNT	2410	Ant1	4.47	2.98	Pass
NVNT	2441	Ant1	4.5	3.00	Pass
NVNT	2477	Ant1	4.6	3.06	Pass




**TOBY**



**Channel Separation Test data:**

Condition	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	Ant1	2437.97	2440.98	3.01	3.00	Pass




## Attachment G-- Peak Output Power Test Data

Condition	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	2410	Ant1	7.991	21	Pass
NVNT	2441	Ant1	7.913	21	Pass
NVNT	2477	Ant1	7.808	21	Pass



TOBY



-----END OF REPORT-----