

**CFR 47 FCC PART 15 SUBPART C  
ISED RSS-247 ISSUE 3**

**TEST REPORT**

*For*

**Smart Desktop Terminal**

**MODEL NUMBER: L1602, L1601, L1600**

**REPORT NUMBER: 4791017498-1-RF-3**

**ISSUE DATE: December 6, 2023**

**FCC ID: 2AV5BL160X**

**IC: 26043-L160X**

*Prepared for*

**Shenzhen Zolon Technology Co., Ltd.  
401, Building 3, Shenzhen Software Park, Maling Community, Yuehai Street,  
Nanshan District Shenzhen Guangdong 518057 China**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch**

**Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**

## Revision History

Rev.	Issue Date	Revisions	Revised By
V0	December 6, 2023	Initial Issue	

### Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c) RSS-GEN Clause 6.8	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.1.3	FCC Part 15.247 (b)(3) RSS-247 Clause 5.4 (d)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2) RSS-247 Clause 5.2 (a) ISED RSS-Gen Clause 6.7	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.2	FCC Part 15.247 (e) RSS-247 Clause 5.2 (b)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d) RSS-247 Clause 5.5	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.12 & Clause 11.13	FCC Part 15.247 (d) FCC Part 15.205/15.209 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

\*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

\*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C ISED RSS-247 ISSUE 3> when <Simple Acceptance> decision rule is applied.

## CONTENTS

<b>1. ATTESTATION OF TEST RESULTS</b> .....	<b>6</b>
<b>2. TEST METHODOLOGY</b> .....	<b>7</b>
<b>3. FACILITIES AND ACCREDITATION</b> .....	<b>7</b>
<b>4. CALIBRATION AND UNCERTAINTY</b> .....	<b>8</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i> .....	8
4.2. <i>MEASUREMENT UNCERTAINTY</i> .....	8
<b>5. EQUIPMENT UNDER TEST</b> .....	<b>9</b>
5.1. <i>DESCRIPTION OF EUT</i> .....	9
5.2. <i>CHANNEL LIST</i> .....	9
5.3. <i>MAXIMUM POWER</i> .....	10
5.4. <i>TEST CHANNEL CONFIGURATION</i> .....	10
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER</i> .....	10
5.6. <i>THE WORSE CASE CONFIGURATIONS</i> .....	11
5.7. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i> .....	12
5.8. <i>SUPPORT UNITS FOR SYSTEM TEST</i> .....	13
<b>6. MEASURING EQUIPMENT AND SOFTWARE USED</b> .....	<b>13</b>
<b>7. ANTENNA PORT TEST RESULTS</b> .....	<b>18</b>
7.1. <i>CONDUCTED OUTPUT POWER</i> .....	18
7.2. <i>6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH</i> .....	19
7.3. <i>POWER SPECTRAL DENSITY</i> .....	21
7.4. <i>CONDUCTED BAND EDGE AND SPURIOUS EMISSION</i> .....	23
7.5. <i>DUTY CYCLE</i> .....	25
<b>8. RADIATED TEST RESULTS</b> .....	<b>26</b>
8.1. <i>RESTRICTED BANDEDGE</i> .....	34
8.2. <i>SPURIOUS EMISSIONS(1 GHZ~3 GHZ)</i> .....	50
8.3. <i>SPURIOUS EMISSIONS(3 GHZ~18 GHZ)</i> .....	56
8.4. <i>SPURIOUS EMISSIONS(9 KHZ~30 MHZ)</i> .....	80
8.5. <i>SPURIOUS EMISSIONS(18 GHZ~26 GHZ)</i> .....	83
8.6. <i>SPURIOUS EMISSIONS(30 MHZ~1 GHZ)</i> .....	85
<b>9. ANTENNA REQUIREMENT</b> .....	<b>87</b>
<b>10. AC POWER LINE CONDUCTED EMISSION</b> .....	<b>88</b>
<b>11. TEST DATA</b> .....	<b>91</b>
11.1. <i>APPENDIX A: DTS BANDWIDTH</i> .....	91

11.1.1.	Test Result .....	91
11.1.2.	Test Graphs .....	92
11.2.	<i>APPENDIX B: OCCUPIED CHANNEL BANDWIDTH</i> .....	96
11.2.1.	Test Result .....	96
11.2.2.	Test Graphs .....	97
11.3.	<i>APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER</i> .....	101
11.3.1.	Test Result .....	101
11.4.	<i>APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY</i> .....	102
11.4.1.	Test Result .....	102
11.4.2.	Test Graphs .....	103
11.5.	<i>APPENDIX E: BAND EDGE MEASUREMENTS</i> .....	107
11.5.1.	Test Result .....	107
11.5.2.	Test Graphs .....	108
11.6.	<i>APPENDIX F: CONDUCTED SPURIOUS EMISSION</i> .....	111
11.6.1.	Test Result .....	111
11.6.2.	Test Graphs .....	112
11.7.	<i>APPENDIX G: DUTY CYCLE</i> .....	123
11.7.1.	Test Result .....	123
11.7.2.	Test Graphs .....	124

# 1. ATTESTATION OF TEST RESULTS

## Applicant Information

Company Name: Shenzhen Zolon Technology Co., Ltd.  
Address: 401, Building 3, Shenzhen Software Park, Maling Community, Yuehai Street, Nanshan District Shenzhen Guangdong 518057 China

## Manufacturer Information

Company Name: Shenzhen Zolon Technology Co., Ltd.  
Address: 401, Building 3, Shenzhen Software Park, Maling Community, Yuehai Street, Nanshan District Shenzhen Guangdong 518057 China

## EUT Information

EUT Name: Smart Desktop Terminal  
Model: L1602  
Series Model: L1601, L1600  
Brand: ZOLON  
Sample Received Date: September 26, 2023  
Sample Status: Normal  
Sample ID: 6488497  
Date of Tested: October 10, 2023 to December 6, 2023

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C ISED RSS-247 ISSUE 3	Pass

Prepared By:



Kebo Zhang  
Senior Project Engineer

Checked By:



Denny Huang  
Senior Project Engineer

Approved By:



Stephen Guo  
Operations Manager

## 2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C ISED RSS-247 ISSUE 3, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, KDB 662911 D01 Multiple Transmitter Output v02r01, CFR 47 FCC Part 2, ANSI C63.10-2013 and ISED RSS-GEN Issue 5

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 4102.01)</b>                  UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b>                  UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED (Company No.: 21320)</b>                  UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20192, R-20202, C-20153 and T-20155)</b>                  UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.                  Facility Name:                  Chamber D, the VCCI registration No. is G-20192 and R-20202                  Shielding Room B , the VCCI registration No. is C-20153 and T-20155</p>
---------------------------	--

**Note 1:**

All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China.

**Note 2:**

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

**Note 3:**

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	



## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	Smart Desktop Terminal
Model	L1602
Series Model	L1601, L1600
Model difference	For the detail refer to model declaration letter.
Note	All three models were considered, We have pre-tested for 3 models and the report only recorded data for the worst model L1602.

Radio Technology	IEEE802.11b/g/n HT20/HT40
Operation frequency	IEEE 802.11b: 2412MHz ~ 2462MHz IEEE 802.11g: 2412MHz ~ 2462MHz IEEE 802.11n HT20: 2412MHz ~ 2462MHz IEEE 802.11n HT40: 2422MHz ~ 2452MHz
Modulation	IEEE 802.11b: DSSS (CCK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK, BPSK)
Normal Test Voltage	AC 120 V, 60 Hz

### 5.2. CHANNEL LIST

Channel List For Bandwidth=20 MHz							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

Channel List For Bandwidth=40 MHz							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447	/	/

### 5.3. MAXIMUM POWER

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted AVG Output Power (dBm)
b	2412 ~ 2462	1-11[11]	13.33
g	2412 ~ 2462	1-11[11]	14.39
n HT20	2412 ~ 2462	1-11[11]	13.99
n HT40	2422 ~ 2452	3-9[7]	14.03

### 5.4. TEST CHANNEL CONFIGURATION

IEEE Std. 802.11	Test Channel Number	Frequency
b	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
g	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT40	CH 3(Low Channel), CH 6(MID Channel), CH 9(High Channel)	2422 MHz, 2437 MHz, 2452 MHz

### 5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		CMD					
Modulation Mode	Transmit Antenna Number	Test Channel					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	Default	Default	Default	/		
802.11g	1	Default	Default	Default			
802.11n HT20	1	Default	Default	Default			
802.11n HT40	1	/			Default	Default	Default

## 5.6. THE WORSE CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps

802.11g mode: 6 Mbps

802.11n HT20 mode: MCS0

802.11n HT40 mode: MCS0

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

## 5.7. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	FPC	1.69

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11g	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT40	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
Note: 1.BT&WLAN 2.4G, BT & WLAN 5G, WLAN 2.4G & WLAN 5G module can't transmit simultaneously. (declared by client)		

Note: The value of the antenna gain was declared by customer.

## 5.8. SUPPORT UNITS FOR SYSTEM TEST

### SUPPORT EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	Specification	Series No.
1	Laptop	Lenovo	E14	/	Laptop
2	Flash Disk*2	N/A	N/A	N/A	N/A
3	RS232 Load	N/A	N/A	N/A	N/A
4	Cash Drawer Load	N/A	N/A	N/A	N/A
5	RJ45 dummy load	N/A	N/A	N/A	N/A
6	Earphone	SENNHEISER	CX80S	N/A	N/A

### I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	Type C	/	1.0	/


### ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
1	AC Adapter	/	GLH048C-2400150AX	Input: 100-240V~ 50/60Hz 2A max Output: DC 24V, 1.5A 36W

**TEST SETUP**

The EUT can work in engineering mode with a software through a Laptop.

**SETUP DIAGRAM FOR TESTS**



## 6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System						
Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	/	Mar.31, 2023	Mar.30, 2024
Vector Signal Generator	R&S	SMBV100A	261637	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
Signal Generator	R&S	SMB100A	178553	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
Signal Analyzer	R&S	FSV40	101118	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
Software						
Description	Manufacturer	Name	Version			
For R&S TS 8997 Test System	Rohde & Schwarz	EMC 32	10.60.10			
Tonsend RF Test System						
Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Due. Date
Wideband Radio Communication Tester	R&S	CMW500	155523	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.28, 2022	Sep.27, 2023	Sep.26, 2024
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
DC power supply	Keysight	E3642A	MY55159130	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
Attenuator	Aglient	8495B	2814a12853	Oct.18, 2022	Oct.12, 2023	Oct.11, 2024
RF Control Unit	Tonscend	JS0806-2	23B80620666	/	April 18,2023	April 17,2024
Software						
Description	Manufacturer	Name	Version			
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System	V3.2.22			

Conducted Emissions						
Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Due. Date
EMI Test Receiver	R&S	ESR3	101961	Oct.17, 2022	Oct.13, 2023	Oct.12, 2024
Two-Line V-Network	R&S	ENV216	101983	Oct.17, 2022	Oct.13, 2023	Oct.12, 2024
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Oct.17, 2022	Oct.13, 2023	Oct.12, 2024
Software						
Description			Manufacturer	Name	Version	
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1	

Radiated Emissions						
Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Due. Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	/	Aug.02, 2021	Aug.01, 2024
Preamplifier	HP	8447D	2944A09099	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
EMI Measurement Receiver	R&S	ESR26	101377	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
Horn Antenna	TDK	HRN-0118	130940	/	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
Horn Antenna	Schwarzbeck	BBHA9170	697	/	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-2	TRS-307-00003	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
Preamplifier	TDK	PA-02-3	TRS-308-00002	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
Loop antenna	Schwarzbeck	1519B	00008	/	Dec.14, 2021	Dec.13, 2024
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01202035	Oct.17, 2022	Oct.12, 2023	Oct.11, 2024
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	/	Dec.01,2022	Nov.30,2023
Highpass Filter	Wainwright	WHKX10-5850-6500-1800-40SS	4	/	Dec.01,2022	Nov.30,2023



Band Reject Filter	Wainwright	WRCJV12-5695-5725-5850-5880-40SS	4	/	Dec.01,2022	Nov.30,2023
Band Reject Filter	Wainwright	WRCJV20-5120-5150-5350-5380-60SS	2	/	Dec.01,2022	Nov.30,2023
Band Reject Filter	Wainwright	WRCJV20-5440-5470-5725-5755-60SS	1	/	Dec.01,2022	Nov.30,2023
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	/	Dec.01,2022	Nov.30,2023
Band Reject Filter	Wainwright	WRCD5-1879-1879.85-1880.15-1881-40SS	1	/	Dec.01,2022	Nov.30,2023
Notch Filter	Wainwright	WHJ10-882-980-7000-40SS	1	/	Dec.01,2022	Nov.30,2023
<b>Software</b>						
Description			Manufacturer	Name	Version	
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1	

<b>Other Instrument</b>						
Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Due. Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Oct.22, 2022	Oct.19, 2023	Oct.18, 2024
Barometer	Yiyi	Baro	N/A	Oct.24, 2022	Oct.19, 2023	Oct.18, 2024
Attenuator	Agilent	8495B	2814a12853	Oct.18, 2022	Oct.12, 2023	Oct.11, 2024

## 7. ANTENNA PORT TEST RESULTS

### 7.1. CONDUCTED OUTPUT POWER

#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	AVG Output Power	1 watt or 30 dBm	2400-2483.5

#### TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.9.2.3.1.

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

The test result in dBm by adding  $[10 \log (1 / D)]$ , where D is the duty cycle.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	26.1°C	Relative Humidity	63%
Atmosphere Pressure	101.2kPa	Test Voltage	AC 120V 60Hz

#### TEST DATE / ENGINEER

Test Date	October 11, 2023	Test By	Walker Yuan
-----------	------------------	---------	-------------

#### TEST RESULTS

Please refer to section "Test Data" - Appendix C

## 7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: ≥3 × RBW For 99 % Occupied Bandwidth: ≥3 × RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### TEST SETUP



**TEST ENVIRONMENT**

Temperature	26.1°C	Relative Humidity	63%
Atmosphere Pressure	101.2kPa	Test Voltage	AC 120V 60Hz

**TEST DATE / ENGINEER**

Test Date	October 11, 2023	Test By	Walker Yuan
-----------	------------------	---------	-------------

**TEST RESULTS**

Please refer to section "Test Data" - Appendix A&B

### 7.3. POWER SPECTRAL DENSITY

#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 3			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

#### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.5.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	power averaging (rms)
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x OBW bandwidth
Trace	Employ trace averaging(rms)mode over a minimum of 100 traces
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	26.1°C	Relative Humidity	63%
Atmosphere Pressure	101.2kPa	Test Voltage	AC 120V 60Hz

#### TEST DATE / ENGINEER

Test Date	October 11, 2023	Test By	Walker Yuan
-----------	------------------	---------	-------------

**TEST RESULTS**

Please refer to section "Test Data" - Appendix D

## 7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.


Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	26.1°C	Relative Humidity	63%
Atmosphere Pressure	101.2kPa	Test Voltage	AC 120V 60Hz

### TEST DATE / ENGINEER

Test Date	October 11, 2023	Test By	Walker Yuan
-----------	------------------	---------	-------------

**TEST RESULTS**

Please refer to section "Test Data" - Appendix E&F



## 7.5. DUTY CYCLE


### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	26.1°C	Relative Humidity	63%
Atmosphere Pressure	101.2kPa	Test Voltage	AC 120V 60Hz

### TEST DATE / ENGINEER

Test Date	October 11, 2023	Test By	Walker Yuan
-----------	------------------	---------	-------------

### TEST RESULTS

Please refer to section "Test Data" - Appendix G

## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (uA/m)	Measurement distance (m)
9 - 490 kHz <sup>Note 1</sup>	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

**Note 1:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

**ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10**

Table 7 – Restricted frequency bands <sup>Note 1</sup>		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

**Note 1:** Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

**FCC Restricted bands of operation refer to FCC §15.205 (a):**

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note: <sup>1</sup>Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup>Above 38.6c

**TEST PROCEDURE**

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω. For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to  $Y-51.5 = Z$  dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: The manufacturer has recommended that the EUT only be used in the desktop (horizontal) orientation; therefore, all radiated testing was performed in desktop orientation.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5.  $\text{dBuA/m} = \text{dBuV/m} - 20\text{Log}_{10}[120\pi] = \text{dBuV/m} - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG:  $VBW=1/T_{on}$ , where:  $T_{on}$  is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):

Note:


1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.

**TEST SETUP**






Below 1 GHz and above 30 MHz



Above 1 GHz



**TEST ENVIRONMENT**

Temperature	25.3°C	Relative Humidity	62%
Atmosphere Pressure	101kPa	Test Voltage	


**TEST DATE / ENGINEER**

Test Date	November 17, 2023	Test By	Rex Huang
-----------	-------------------	---------	-----------

**TEST RESULTS**


## 8.1. RESTRICTED BANDEDGE

Test Mode:	802.11b PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.320	25.88	32.16	58.04	74.00	-15.96	peak
2	2390.000	23.01	32.16	55.17	74.00	-18.83	peak

Test Mode:	802.11b AV	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.320	6.42	32.16	38.58	54.00	-15.42	AVG
2	2390.000	5.23	32.16	37.39	54.00	-16.61	AVG

Test Mode:	802.11b PK	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	29.15	32.44	61.59	74.00	-12.41	peak
2	2485.040	29.71	32.44	62.15	74.00	-11.85	peak

Test Mode:	802.11b AV	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	7.82	32.44	40.26	54.00	-13.74	AVG
2	2485.040	9.65	32.44	42.09	54.00	-11.91	AVG

Test Mode:	802.11g PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	33.02	32.16	65.18	74.00	-8.82	peak

Test Mode:	802.11g AV	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	12.63	32.16	44.79	54.00	-9.21	AVG


Test Mode:	802.11g PK	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	39.98	32.44	72.42	74.00	-1.58	peak
2	2484.435	39.96	32.44	72.40	74.00	-1.60	peak




Test Mode:	802.11g AV	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	17.01	32.44	49.45	54.00	-4.55	AVG
2	2484.435	14.75	32.44	47.19	54.00	-6.81	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.200	39.94	32.16	72.10	74.00	-1.90	peak
2	2390.000	40.10	32.16	72.26	74.00	-1.74	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.200	14.43	32.16	46.59	54.00	-7.41	AVG
2	2390.000	15.19	32.16	47.35	54.00	-6.65	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	39.49	32.44	71.93	74.00	-2.07	peak
2	2484.050	40.23	32.44	72.67	74.00	-1.33	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	13.20	32.44	45.64	54.00	-8.36	AVG
2	2484.050	13.41	32.44	45.85	54.00	-8.15	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.220	40.43	32.15	72.58	74.00	-1.42	peak
2	2390.000	38.22	32.16	70.38	74.00	-3.62	peak

Test Mode:	802.11n HT40 AV	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.220	14.93	32.15	47.08	54.00	-6.92	AVG
2	2390.000	16.10	32.16	48.26	54.00	-5.74	AVG


Test Mode:	802.11n HT40 PK	Frequency(MHz):	2452
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	39.96	32.44	72.40	74.00	-1.60	peak
2	2484.530	40.05	32.44	72.49	74.00	-1.51	peak




Test Mode:	802.11n HT40 AV	Frequency(MHz):	2452
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	16.17	32.44	48.61	54.00	-5.39	AVG
2	2484.530	15.79	32.44	48.23	54.00	-5.77	AVG


## 8.2. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1038.000	49.39	-14.85	34.54	74.00	-39.46	peak
2	1634.000	46.86	-12.27	34.59	74.00	-39.41	peak
3	2340.000	48.68	-9.31	39.37	74.00	-34.63	peak
4	2412.000	53.74	-8.93	44.81	/	/	fundamental
5	2560.000	46.58	-8.31	38.27	74.00	-35.73	peak
6	2896.000	44.04	-7.29	36.75	74.00	-37.25	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1038.000	50.89	-14.85	36.04	74.00	-37.96	peak
2	1440.000	47.10	-12.98	34.12	74.00	-39.88	peak
3	2340.000	49.43	-9.31	40.12	74.00	-33.88	peak
4	2412.000	55.39	-8.93	46.46	/	/	fundamental
5	2558.000	47.09	-8.32	38.77	74.00	-35.23	peak
6	2868.000	44.73	-7.38	37.35	74.00	-36.65	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1038.000	49.49	-14.85	34.64	74.00	-39.36	peak
2	1438.000	46.96	-13.00	33.96	74.00	-40.04	peak
3	2340.000	48.33	-9.31	39.02	74.00	-34.98	peak
4	2437.000	54.10	-8.80	45.30	/	/	fundamental
5	2560.000	45.84	-8.31	37.53	74.00	-36.47	peak
6	2926.000	44.61	-7.20	37.41	74.00	-36.59	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1038.000	51.71	-14.85	36.86	74.00	-37.14	peak
2	1634.000	47.26	-12.27	34.99	74.00	-39.01	peak
3	2340.000	48.47	-9.31	39.16	74.00	-34.84	peak
4	2437.000	52.88	-8.80	44.08	/	/	fundamental
5	2584.000	46.52	-8.24	38.28	74.00	-35.72	peak
6	2824.000	43.86	-7.51	36.35	74.00	-37.65	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1038.000	49.46	-14.85	34.61	74.00	-39.39	peak
2	1634.000	46.75	-12.27	34.48	74.00	-39.52	peak
3	2340.000	47.87	-9.31	38.56	74.00	-35.44	peak
4	2462.000	55.72	-8.66	47.06	/	/	fundamental
5	2568.000	46.43	-8.28	38.15	74.00	-35.85	peak
6	2956.000	45.27	-7.11	38.16	74.00	-35.84	peak


Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1038.000	51.00	-14.85	36.15	74.00	-37.85	peak
2	1922.000	46.68	-11.32	35.36	74.00	-38.64	peak
3	2340.000	47.64	-9.31	38.33	74.00	-35.67	peak
4	2462.000	54.42	-8.66	45.76	/	/	fundamental
5	2570.000	46.55	-8.27	38.28	74.00	-35.72	peak
6	2956.000	44.67	-7.11	37.56	74.00	-36.44	peak

### 8.3. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	49.60	-0.26	49.34	74.00	-24.66	peak
2	8010.000	39.30	6.32	45.62	74.00	-28.38	peak
3	8895.000	38.18	9.71	47.89	74.00	-26.11	peak
4	10245.000	36.30	12.48	48.78	74.00	-25.22	peak
5	12705.000	31.97	18.06	50.03	74.00	-23.97	peak
6	17940.000	24.80	25.34	50.14	74.00	-23.86	peak




Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	46.10	-0.26	45.84	74.00	-28.16	peak
2	9180.000	37.34	10.56	47.90	74.00	-26.10	peak
3	10890.000	34.63	14.39	49.02	74.00	-24.98	peak
4	13110.000	30.88	19.20	50.08	74.00	-23.92	peak
5	13620.000	28.82	21.15	49.97	74.00	-24.03	peak
6	17985.000	24.51	25.60	50.11	74.00	-23.89	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	46.39	-0.03	46.36	74.00	-27.64	peak
2	7305.000	39.00	6.47	45.47	74.00	-28.53	peak
3	9240.000	37.01	10.58	47.59	74.00	-26.41	peak
4	11910.000	32.34	17.72	50.06	74.00	-23.94	peak
5	13920.000	28.83	21.79	50.62	74.00	-23.38	peak
6	17970.000	24.84	25.51	50.35	74.00	-23.65	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	44.68	-0.03	44.65	74.00	-29.35	peak
2	8115.000	37.80	6.43	44.23	74.00	-29.77	peak
3	8910.000	37.53	9.82	47.35	74.00	-26.65	peak
4	11055.000	34.26	14.96	49.22	74.00	-24.78	peak
5	12690.000	32.84	18.02	50.86	74.00	-23.14	peak
6	17760.000	25.18	24.27	49.45	74.00	-24.55	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	42.25	0.14	42.39	74.00	-31.61	peak
2	7380.000	41.68	6.42	48.10	74.00	-25.90	peak
3	9105.000	36.74	10.53	47.27	74.00	-26.73	peak
4	12180.000	32.76	17.83	50.59	74.00	-23.41	peak
5	13590.000	29.17	21.09	50.26	74.00	-23.74	peak
6	17985.000	23.63	25.60	49.23	74.00	-24.77	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	44.76	0.14	44.90	74.00	-29.10	peak
2	7380.000	43.69	6.42	50.11	74.00	-23.89	peak
3	10200.000	36.23	12.40	48.63	74.00	-25.37	peak
4	11895.000	32.83	17.68	50.51	74.00	-23.49	peak
5	13065.000	31.33	19.00	50.33	74.00	-23.67	peak
6	17925.000	24.57	25.25	49.82	74.00	-24.18	peak

Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	49.01	-0.26	48.75	74.00	-25.25	peak
2	7245.000	39.99	6.51	46.50	74.00	-27.50	peak
3	9210.000	37.67	10.57	48.24	74.00	-25.76	peak
4	12675.000	32.75	17.99	50.74	74.00	-23.26	peak
5	13020.000	31.20	18.80	50.00	74.00	-24.00	peak
6	17940.000	24.54	25.34	49.88	74.00	-24.12	peak

Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	48.91	-0.26	48.65	74.00	-25.35	peak
2	7230.000	41.54	6.53	48.07	74.00	-25.93	peak
3	9255.000	37.11	10.59	47.70	74.00	-26.30	peak
4	11070.000	34.19	15.03	49.22	74.00	-24.78	peak
5	13650.000	28.40	21.21	49.61	74.00	-24.39	peak
6	17985.000	23.95	25.60	49.55	74.00	-24.45	peak


Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	44.77	-0.03	44.74	74.00	-29.26	peak
2	7305.000	42.46	6.47	48.93	74.00	-25.07	peak
3	9105.000	37.84	10.53	48.37	74.00	-25.63	peak
4	11070.000	34.45	15.03	49.48	74.00	-24.52	peak
5	13665.000	29.18	21.25	50.43	74.00	-23.57	peak
6	17925.000	24.17	25.25	49.42	74.00	-24.58	peak




Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	44.04	-0.03	44.01	74.00	-29.99	peak
2	7320.000	42.61	6.46	49.07	74.00	-24.93	peak
3	11055.000	34.05	14.96	49.01	74.00	-24.99	peak
4	12690.000	32.25	18.02	50.27	74.00	-23.73	peak
5	13875.000	29.26	21.70	50.96	74.00	-23.04	peak
6	17955.000	24.32	25.42	49.74	74.00	-24.26	peak

Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	42.49	0.14	42.63	74.00	-31.37	peak
2	7380.000	43.40	6.42	49.82	74.00	-24.18	peak
3	9315.000	37.01	10.61	47.62	74.00	-26.38	peak
4	11025.000	35.62	14.85	50.47	74.00	-23.53	peak
5	12675.000	32.11	17.99	50.10	74.00	-23.90	peak
6	18000.000	23.71	25.69	49.40	74.00	-24.60	peak

Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	41.31	0.14	41.45	74.00	-32.55	peak
2	7380.000	42.59	6.42	49.01	74.00	-24.99	peak
3	9150.000	37.27	10.54	47.81	74.00	-26.19	peak
4	11025.000	34.56	14.85	49.41	74.00	-24.59	peak
5	13875.000	28.77	21.70	50.47	74.00	-23.53	peak
6	18000.000	24.15	25.69	49.84	74.00	-24.16	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	46.91	-0.26	46.65	74.00	-27.35	peak
2	7230.000	38.66	6.53	45.19	74.00	-28.81	peak
3	9240.000	37.07	10.58	47.65	74.00	-26.35	peak
4	10200.000	36.01	12.40	48.41	74.00	-25.59	peak
5	13560.000	29.04	21.04	50.08	74.00	-23.92	peak
6	17985.000	23.92	25.60	49.52	74.00	-24.48	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	44.47	-0.26	44.21	74.00	-29.79	peak
2	7230.000	39.79	6.53	46.32	74.00	-27.68	peak
3	11055.000	34.69	14.96	49.65	74.00	-24.35	peak
4	12675.000	32.79	17.99	50.78	74.00	-23.22	peak
5	13980.000	28.55	21.92	50.47	74.00	-23.53	peak
6	17985.000	24.55	25.60	50.15	74.00	-23.85	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	44.51	-0.09	44.42	74.00	-29.58	peak
2	7305.000	41.52	6.47	47.99	74.00	-26.01	peak
3	10215.000	36.33	12.43	48.76	74.00	-25.24	peak
4	12555.000	33.15	17.72	50.87	74.00	-23.13	peak
5	13875.000	29.18	21.70	50.88	74.00	-23.12	peak
6	17940.000	24.69	25.34	50.03	74.00	-23.97	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	44.18	-0.09	44.09	74.00	-29.91	peak
2	7305.000	43.20	6.47	49.67	74.00	-24.33	peak
3	10305.000	36.24	12.61	48.85	74.00	-25.15	peak
4	12675.000	31.24	17.99	49.23	74.00	-24.77	peak
5	13920.000	29.18	21.79	50.97	74.00	-23.03	peak
6	18000.000	24.67	25.69	50.36	74.00	-23.64	peak


Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	42.67	0.14	42.81	74.00	-31.19	peak
2	7380.000	42.37	6.42	48.79	74.00	-25.21	peak
3	10080.000	36.18	12.16	48.34	74.00	-25.66	peak
4	11055.000	35.06	14.96	50.02	74.00	-23.98	peak
5	12645.000	33.04	17.92	50.96	74.00	-23.04	peak
6	17670.000	26.03	23.73	49.76	74.00	-24.24	peak




Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	42.67	0.14	42.81	74.00	-31.19	peak
2	7380.000	43.39	6.42	49.81	74.00	-24.19	peak
3	8910.000	38.21	9.82	48.03	74.00	-25.97	peak
4	10920.000	35.56	14.49	50.05	74.00	-23.95	peak
5	12690.000	32.66	18.02	50.68	74.00	-23.32	peak
6	17670.000	26.18	23.73	49.91	74.00	-24.09	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	44.44	-0.20	44.24	74.00	-29.76	peak
2	9060.000	37.96	10.51	48.47	74.00	-25.53	peak
3	10875.000	35.50	14.32	49.82	74.00	-24.18	peak
4	12690.000	32.64	18.02	50.66	74.00	-23.34	peak
5	13920.000	29.15	21.79	50.94	74.00	-23.06	peak
6	18000.000	24.42	25.69	50.11	74.00	-23.89	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	42.78	-0.26	42.52	74.00	-31.48	peak
2	9135.000	37.49	10.55	48.04	74.00	-25.96	peak
3	10305.000	36.51	12.61	49.12	74.00	-24.88	peak
4	11940.000	32.02	17.80	49.82	74.00	-24.18	peak
5	13920.000	28.89	21.79	50.68	74.00	-23.32	peak
6	17850.000	25.52	24.81	50.33	74.00	-23.67	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	42.48	-0.09	42.39	74.00	-31.61	peak
2	7290.000	39.29	6.48	45.77	74.00	-28.23	peak
3	9195.000	37.76	10.56	48.32	74.00	-25.68	peak
4	11055.000	34.44	14.96	49.40	74.00	-24.60	peak
5	13635.000	29.44	21.19	50.63	74.00	-23.37	peak
6	17985.000	24.59	25.60	50.19	74.00	-23.81	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4515.000	43.03	-1.40	41.63	74.00	-32.37	peak
2	7320.000	39.26	6.46	45.72	74.00	-28.28	peak
3	9120.000	37.08	10.53	47.61	74.00	-26.39	peak
4	11805.000	31.62	17.43	49.05	74.00	-24.95	peak
5	13650.000	28.67	21.21	49.88	74.00	-24.12	peak
6	17940.000	23.67	25.34	49.01	74.00	-24.99	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2452
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	41.62	-0.03	41.59	74.00	-32.41	peak
2	7350.000	40.10	6.44	46.54	74.00	-27.46	peak
3	9255.000	38.01	10.59	48.60	74.00	-25.40	peak
4	11295.000	33.87	15.85	49.72	74.00	-24.28	peak
5	13920.000	28.95	21.79	50.74	74.00	-23.26	peak
6	17940.000	24.57	25.34	49.91	74.00	-24.09	peak


Test Mode:	802.11n HT40	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4890.000	42.44	0.03	42.47	74.00	-31.53	peak
2	7335.000	43.42	6.45	49.87	74.00	-24.13	peak
3	9210.000	37.97	10.57	48.54	74.00	-25.46	peak
4	10215.000	36.14	12.43	48.57	74.00	-25.43	peak
5	12240.000	32.15	17.79	49.94	74.00	-24.06	peak
6	18000.000	24.76	25.69	50.45	74.00	-23.55	peak

### 8.4. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0102	77.05	-101.40	-24.35	47.43	-75.85	-4.07	-71.78	peak
2	0.0131	74.47	-101.38	-26.91	45.25	-78.41	-6.25	-72.16	peak
3	0.0212	71.54	-101.35	-29.81	41.07	-81.31	-10.43	-70.88	peak
4	0.0279	69.17	-101.38	-32.21	38.69	-83.71	-12.81	-70.90	peak
5	0.0656	61.86	-101.55	-39.69	31.26	-91.19	-20.24	-70.95	peak
6	0.0819	60.02	-101.65	-41.63	29.34	-93.13	-22.16	-70.97	peak




Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1595	76.86	-101.65	-24.79	23.55	-76.29	-27.95	-48.34	peak
2	0.1794	73.27	-101.68	-28.41	22.53	-79.91	-28.97	-50.94	peak
3	0.2190	70.77	-101.75	-30.98	20.79	-82.48	-30.71	-51.77	peak
4	0.2620	67.31	-101.81	-34.50	19.24	-86.00	-32.26	-53.74	peak
5	0.2988	64.27	-101.85	-37.58	18.09	-89.08	-33.41	-55.67	peak
6	0.3392	63.40	-101.90	-38.50	16.99	-90.00	-34.51	-55.49	peak


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.4900	64.72	-62.06	2.66	13.80	-48.84	-37.70	-11.14	peak
2	0.5917	64.74	-62.08	2.66	32.16	-48.84	-19.34	-29.50	peak
3	0.7641	63.42	-62.12	1.30	29.94	-50.20	-21.56	-28.64	peak
4	1.4818	59.11	-62.05	-2.94	24.19	-54.44	-27.31	-27.13	peak
5	3.4704	56.35	-61.46	-5.11	29.54	-56.61	-21.96	-34.65	peak
6	6.2445	55.63	-61.32	-5.69	29.54	-57.19	-21.96	-35.23	peak


### 8.5. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	19392.000	50.12	-5.57	44.55	74.00	-29.45	peak
2	20200.000	49.54	-5.58	43.96	74.00	-30.04	peak
3	21600.000	49.02	-4.54	44.48	74.00	-29.52	peak
4	22160.000	49.08	-4.31	44.77	74.00	-29.23	peak
5	23480.000	48.04	-3.16	44.88	74.00	-29.12	peak
6	25032.000	46.84	-2.04	44.80	74.00	-29.20	peak


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18616.000	49.89	-5.34	44.55	74.00	-29.45	peak
2	20240.000	49.82	-5.61	44.21	74.00	-29.79	peak
3	21928.000	49.05	-4.43	44.62	74.00	-29.38	peak
4	23216.000	47.51	-3.38	44.13	74.00	-29.87	peak
5	24568.000	46.60	-2.33	44.27	74.00	-29.73	peak
6	24968.000	46.26	-2.14	44.12	74.00	-29.88	peak


## 8.6. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	68.8000	56.02	-20.71	35.31	40.00	-4.69	QP
2	148.3400	50.22	-18.45	31.77	43.50	-11.73	QP
3	193.9299	46.13	-16.65	29.48	43.50	-14.02	QP
4	313.2400	40.14	-14.63	25.51	46.00	-20.49	QP
5	480.0800	38.06	-11.05	27.01	46.00	-18.99	QP
6	742.9500	49.18	-7.17	42.01	46.00	-3.99	QP

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	AC 120V_60Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	40.6699	52.77	-19.94	32.83	40.00	-7.17	QP
2	66.8600	54.01	-20.63	33.38	40.00	-6.62	QP
3	227.8800	49.42	-17.84	31.58	46.00	-14.42	QP
4	480.0800	43.70	-11.05	32.65	46.00	-13.35	QP
5	614.9099	40.80	-9.37	31.43	46.00	-14.57	QP
6	742.9500	42.50	-7.17	35.33	46.00	-10.67	QP

## 9. ANTENNA REQUIREMENT

### REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### DESCRIPTION

Pass

## 10. AC POWER LINE CONDUCTED EMISSION

### LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8


FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

### TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	23.5°C	Relative Humidity	56.8%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz


### TEST DATE / ENGINEER

Test Date	November 20, 2023	Test By	Eason He
-----------	-------------------	---------	----------



**TEST RESULTS**

Test Mode:	WIFI2.4G	Frequency(MHz):	2412
Line:	Line		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1510	40.74	9.59	50.33	65.94	-15.61	QP
2	0.1510	20.80	9.59	30.39	55.94	-25.55	AVG
3	0.1618	39.53	9.59	49.12	65.37	-16.25	QP
4	0.1618	21.76	9.59	31.35	55.37	-24.02	AVG
5	0.1899	35.70	9.59	45.29	64.04	-18.75	QP
6	0.1899	19.37	9.59	28.96	54.04	-25.08	AVG
7	0.4227	26.69	9.60	36.29	57.39	-21.10	QP
8	0.4227	19.70	9.60	29.30	47.39	-18.09	AVG
9	6.3878	17.51	9.74	27.25	60.00	-32.75	QP
10	6.3878	11.24	9.74	20.98	50.00	-29.02	AVG
11	12.3753	16.21	9.76	25.97	60.00	-34.03	QP
12	12.3753	8.26	9.76	18.02	50.00	-31.98	AVG

**Note:**

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

Test Mode:	WIFI2.4G	Frequency(MHz):	2412
Line:	Neutral		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1501	41.13	9.49	50.62	65.99	-15.37	QP
2	0.1501	20.59	9.49	30.08	55.99	-25.91	AVG
3	0.1615	40.11	9.51	49.62	65.39	-15.77	QP
4	0.1615	21.72	9.51	31.23	55.39	-24.16	AVG
5	0.1756	37.32	9.54	46.86	64.69	-17.83	QP
6	0.1756	18.31	9.54	27.85	54.69	-26.84	AVG
7	0.4238	34.05	9.53	43.58	57.37	-13.79	QP
8	0.4238	27.28	9.53	36.81	47.37	-10.56	AVG
9	0.7044	18.44	9.50	27.94	56.00	-28.06	QP
10	0.7044	14.02	9.50	23.52	46.00	-22.48	AVG
11	12.3260	19.04	9.66	28.70	60.00	-31.30	QP
12	12.3260	12.81	9.66	22.47	50.00	-27.53	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.


## 11. TEST DATA


### 11.1. APPENDIX A: DTS BANDWIDTH

#### 11.1.1. Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.56	2407.48	2417.04	≤0.5	PASS
		2437	8.08	2432.96	2441.04	≤0.5	PASS
		2462	7.12	2458.44	2465.56	≤0.5	PASS
11G	Ant1	2412	16.32	2403.84	2420.16	≤0.5	PASS
		2437	16.28	2428.88	2445.16	≤0.5	PASS
		2462	16.32	2453.84	2470.16	≤0.5	PASS
11N20SISO	Ant1	2412	17.28	2403.24	2420.52	≤0.5	PASS
		2437	16.56	2428.84	2445.40	≤0.5	PASS
		2462	16.80	2453.60	2470.40	≤0.5	PASS
11N40SISO	Ant1	2422	35.60	2404.16	2439.76	≤0.5	PASS
		2437	35.76	2419.24	2455.00	≤0.5	PASS
		2452	35.68	2434.24	2469.92	≤0.5	PASS


### 11.1.2. Test Graphs






Date: 11.OCT.2023 12:59:26

11G\_Ant1\_2412




Date: 11.OCT.2023 13:04:08

11G\_Ant1\_2437





Date: 11.OCT.2023 13:09:48

11G\_Ant1\_2462




Date: 11.OCT.2023 13:33:50





11N40SISO\_Ant1\_2437



11N40SISO\_Ant1\_2452


## 11.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH


### 11.2.1. Test Result

Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
11B	Ant1	2412	11.828	2406.1658	2417.9940	PASS
		2437	11.828	2431.1259	2442.9540	PASS
		2462	11.788	2456.1658	2467.9540	PASS
11G	Ant1	2412	17.143	2403.4086	2420.5514	PASS
		2437	17.103	2428.4885	2445.5914	PASS
		2462	17.143	2453.4486	2470.5914	PASS
11N20SISO	Ant1	2412	17.982	2403.0090	2420.9910	PASS
		2437	17.902	2428.0889	2445.9910	PASS
		2462	17.902	2453.0889	2470.9910	PASS
11N40SISO	Ant1	2422	36.523	2403.7782	2440.3017	PASS
		2437	36.444	2418.8581	2455.3017	PASS
		2452	36.364	2433.9381	2470.3017	PASS




### 11.2.2. Test Graphs






Date: 11.OCT.2023 12:59:33




Date: 11.OCT.2023 13:04:14




Date: 11.OCT.2023 13:09:55




Date: 11.OCT.2023 13:33:57





11N40SISO\_Ant1\_2437



11N40SISO\_Ant1\_2452

### 11.3. APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER

#### 11.3.1. Test Result

Test Mode	Antenna	Frequency[MHz]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	13.33	≤30.00	PASS
		2437	12.95	≤30.00	PASS
		2462	13.16	≤30.00	PASS
11G	Ant1	2412	14.39	≤30.00	PASS
		2437	14.03	≤30.00	PASS
		2462	14.50	≤30.00	PASS
11N20SISO	Ant1	2412	13.68	≤30.00	PASS
		2437	13.36	≤30.00	PASS
		2462	13.99	≤30.00	PASS
11N40SISO	Ant1	2422	13.57	≤30.00	PASS
		2437	13.53	≤30.00	PASS
		2452	14.03	≤30.00	PASS

Note: 1. Conducted Power=Meas. Level+ Correction Factor

2. The Duty Cycle Factor (refer to section 7.5) had already compensated to the test data.


## 11.4. APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY

### 11.4.1. Test Result


Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-19.41	≤8.00	PASS
		2437	-19.35	≤8.00	PASS
		2462	-19.24	≤8.00	PASS
11G	Ant1	2412	-20.71	≤8.00	PASS
		2437	-21.09	≤8.00	PASS
		2462	-20.72	≤8.00	PASS
11N20SISO	Ant1	2412	-21.78	≤8.00	PASS
		2437	-21.71	≤8.00	PASS
		2462	-21.37	≤8.00	PASS
11N40SISO	Ant1	2422	-21.56	≤8.00	PASS
		2437	-21.96	≤8.00	PASS
		2452	-21.19	≤8.00	PASS

Note: 1. The Duty Cycle Factor (refer to section 7.5) had already compensated to the test data.


### 11.4.2. Test Graphs




11B\_Ant1\_2412




11B\_Ant1\_2437




11B\_Ant1\_2462




11G\_Ant1\_2412






11G\_Ant1\_2437




11G\_Ant1\_2462








11N40SISO\_Ant1\_2422



11N40SISO\_Ant1\_2437





11N40SISO\_Ant1\_2452


## 11.5. APPENDIX E: BAND EDGE MEASUREMENTS

### 11.5.1. Test Result


Test Mode	Antenna	ChName	Frequency [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	3.54	-45.82	≤-26.46	PASS
		High	2462	3.51	-45.68	≤-26.49	PASS
11G	Ant1	Low	2412	1.57	-29.29	≤-28.43	PASS
		High	2462	1.68	-42.62	≤-28.32	PASS
11N20SISO	Ant1	Low	2412	0.75	-29.83	≤-29.25	PASS
		High	2462	0.97	-39.64	≤-29.03	PASS
11N40SISO	Ant1	Low	2422	-2.20	-33.2	≤-32.2	PASS
		High	2452	-1.65	-40.01	≤-31.65	PASS

### 11.5.2. Test Graphs






Date: 11.OCT.2023 13:10:27



Date: 11.OCT.2023 13:44:32



Date: 11.OCT.2023 13:50:03



Date: 11.OCT.2023 14:01:34

