Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Report No: CCISE200900404

RF Exposure Evaluation Report

Applicant: Shenzhen Peicheng Technology Co., Ltd

Address of Applicant: 5th Floor, B Building, Baotian Industrial Zone, Qianjin 2nd road,

Xixiang, Bao'an District, Shenzhen, Guangdong, China 518102

Equipment Under Test (EUT)

Product Name: Tablet pc

Model No.: K75, K76, K77, K78, K79, K80

Trade mark: SMART TEK

FCC ID: 2AV6Y-K75

Applicable standards: FCC CFR Title 47 Part 2 Subpart J Section 2.1093

Date of sample receipt: 02 Sep., 2020

Date of Test: 02 Sep., to 20 Oct., 2020

Date of report issue: 20 Oct., 2020

Test Result: PASS*

Authorized Signature:



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.





Version

Version No.	Date	Description
00	20 Oct., 2020	Original

Tested by:

Test Engineer

Reviewed by:

Project Engineer **Date:** 20 Oct., 2020

Date: 20 Oct., 2020





3 Contents

			Page
1	COV	/ER PAGE	1
2	VER	SION	2
3	CON	ITENTS	3
4	GEN	IERAL INFORMATION	4
4	1.1	CLIENT INFORMATION	4
	1.2	GENERAL DESCRIPTION OF E.U.T.	4
4	1.3	OPERATING MODES	4
4	1.4	ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD	
4	4.5	LABORATORY FACILITY	4
4	4.6	LABORATORY LOCATION	4
5	TEC	HNICAL REQUIREMENTS SPECIFICATION IN FCC CFR TITLE 47 PART 2.1093	5
5	5.1	LIMITS	5
5	5.2	RESULT	5
5	5.3	CONCLUSION	5



4 General Information

4.1 Client Information

Applicant:	Shenzhen Peicheng Technology Co., Ltd	
Address:	5th Floor, B Building, Baotian Industrial Zone, Qianjin 2nd road, Xixiang, Bao'an District, Shenzhen, Guangdong, China 518102	
Manufacturer/Factory:	Shenzhen Peicheng Technology Co., Ltd	
Address:	5th Floor, B Building, Baotian Industrial Zone, Qianjin 2nd road, Xixiang, Bao'an District, Shenzhen, Guangdong, China 518102	

4.2 General Description of E.U.T.

Product Name:	Tablet pc	
Model No.:	No.: K75, K76, K77, K78, K79, K80	
Operation Frequency	2.4G Wi-Fi: 2412MHz~2462MHz; 2422MHz~2452MHz	
Operation Frequency:	Bluetooth/ BLE: 2402MHz~2480MHz	
Madulation to shool and	802.11b: DSSS, 802.11g/n: OFDM	
Modulation technology:	Bluetooth BDR /BLE: GFSK, Bluetooth EDR: л/4-DQPSK, 8DPSK	
Antenna Type:	Internal Antenna	
Antenna gain:	BT/ BLE: 0.8 dBi; Wi-Fi: 0.8 dBi	
Test Sample Condition:	Test Sample Condition: The test samples were provided in good working order with no visible defe	

4.3 Operating Modes

Operating mode	Detail description
BLE mode	Keep the EUT in continuously transmitting in BLE mode
BT mode	Keep the EUT in continuously transmitting in BT mode
2.4G WIFI mode	Keep the EUT in continuously transmitting in 2.4G WIFI mode

4.4 Additions to, deviations, or exclusions from the method

No

4.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Designation No.: CN1211

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● ISED - CAB identifier.: CN0021

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

• A2LA - Registration No.: 4346.01

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf

4.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No.110~116, Building B, Jinyuan Business Building, Xixiang Road,

Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

Shenzhen Zhongjian Nanfang Testing Co., Ltd. No.110~116, Building B, Jinyuan Business Building, Xixiang Road, Bao'an District, Shenzhen, Guangdong, China Telephone: +86 (0) 755 23118282 Fax: +86 (0) 755 23116366



Report No: CCISE200900404

5 Technical Requirements Specification in FCC CFR Title 47 Part 2.1093

5.1 Limits

According to 447498 D01 General RF Exposure Guidance v06 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/ (min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

5.2 Result

Worse case for BT(π /4-DQPSK) as below:

[2402MHz: max. power 6.994dBm, tune-up (7.0dBm, 5.012 mW) output power] (5.012 mW /5mm) $\cdot [\sqrt{2.402(GHz)}]=1.55 < 3.0$ for 1-g SAR

Worse case for Wi-Fi(802.11b) as below: [2412MHz: max. power 7.44dBm, tune-up (7.5dBm, 5.623 mW) output power] $(5.623\text{mW}/5\text{mm}) \cdot [\sqrt{2.412}(\text{GHz})] = 1.74 < 3.0 \text{ for } 1-\text{g SAR}$

5.3 Conclusion

The device is exempt from the RF exposure evaluation.

-----End of report-----