

Test Model

Band-edge Conducted Emissions

Channel 0: 2402MHz

GFSK



Test Model

Maximum Conducted Level RBW=100kHz

Channel 39: 2441MHz

GFSK



Test Model

Conducted Spurious RF Conducted Emission

Channel 39: 2441MHz

GFSK



Test Model

Maximum Conducted Level RBW=100kHz

Channel 78: 2480MHz

GFSK



Test Model

Conducted Spurious RF Conducted Emission

Channel 78: 2480MHz

GFSK



Test Model

Band-edge Conducted Emissions

Channel 78: 2480MHz

GFSK



Test Model Maximum Conducted Level RBW=100kHz
Hopping GFSK




Test Model Conducted Spurious RF Conducted Emission
Hopping GFSK



Test Model

Band-edge Conducted Emissions


Hopping



Test Model

Band-edge Conducted Emissions

Hopping



9.7 RADIATED SPURIOUS EMISSION

9.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 D01 15.247 MEAS GUIDANCE v05r02

9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μ V/m)	Field Strength ($\text{dB}\mu\text{V/m}$)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (μ V/m)	300
0.490-1.705	24000/F(KHz)	20 log (μ V/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

9.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

9.7.5 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature:	29.5°C
Relative Humidity:	52%
ATM Pressure:	1017 mbar

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


Distance extrapolation factor = $40\log(\text{Specific distance}/ \text{test distance})(\text{dB})$;

Limit line=Specific limits(dBuV) + distance extrapolation factor



■ Spurious Emission below 1GHz (30MHz to 1GHz)

Bluetooth (GFSK, $\pi/4$ DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:



Site 3m Chamber #3

Polarization: **Vertical**

Temperature: 22.5 C

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 45 %


Mode:TX 2402MHz

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		38.9732	31.90	-15.19	16.71	40.00	-23.29	QP		
2		46.2793	30.43	-14.50	15.93	40.00	-24.07	QP		
3		55.8047	31.27	-13.91	17.36	40.00	-22.64	QP		
4		104.3071	35.23	-16.45	18.78	43.50	-24.72	QP		
5		249.9722	32.44	-13.77	18.67	46.00	-27.33	QP		
6	*	852.1551	29.18	2.71	31.89	46.00	-14.11	QP		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		40.4170	31.18	-14.96	16.22	40.00	-23.78	QP		
2		47.1392	30.92	-14.54	16.38	40.00	-23.62	QP		
3		54.5471	30.96	-13.98	16.98	40.00	-23.02	QP		
4		64.0388	30.34	-14.01	16.33	40.00	-23.67	QP		
5		287.9904	31.52	-12.29	19.23	46.00	-26.77	QP		
6	*	853.2764	28.80	2.63	31.43	46.00	-14.57	QP		



Site 3m Chamber #3

 Polarization: *Vertical*

Temperature: 22.5 C

Limit: (RE)FCC PART 15 CLASS B


Power: AC 120V/60Hz

Humidity: 45 %

Mode: TX 2441MHz

Note:

No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Height	Table Degree	Comment
		dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	
1	40.2580	30.53	-14.97	15.56	40.00	-24.44	QP		
2	46.6050	32.10	-14.51	17.59	40.00	-22.41	QP		
3	54.8107	31.69	-13.97	17.72	40.00	-22.28	QP		
4	63.8986	30.74	-14.01	16.73	40.00	-23.27	QP		
5	104.3071	34.62	-16.45	18.17	43.50	-25.33	QP		
6 *	851.7816	28.55	2.74	31.29	46.00	-14.71	QP		



Site 3m Chamber #3

 Polarization: **Horizontal**

Temperature: 22.5 C

Limit: (RE)FCC PART 15 CLASS B


Power: AC 120V/60Hz

Humidity: 45 %

Mode: TX 2441MHz

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table			
			Level	Factor	ment							
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		32.5197	31.77	-16.49	15.28	40.00	-24.72	QP				
2		38.8027	30.63	-15.23	15.40	40.00	-24.60	QP				
3		45.7148	30.98	-14.53	16.45	40.00	-23.55	QP				
4		55.6581	30.85	-13.92	16.93	40.00	-23.07	QP				
5		64.7444	30.81	-14.03	16.78	40.00	-23.22	QP				
6	*	849.5445	29.02	2.88	31.90	46.00	-14.10	QP				



Site 3m Chamber #3

 Polarization: *Vertical*

Temperature: 22.5 C

Limit: (RE)FCC PART 15 CLASS B


Power: AC 120V/60Hz

Humidity: 45 %

Mode: TX 2480MHz

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		38.9220	30.79	-15.20	15.59	40.00	-24.41	QP		
2		46.6254	30.58	-14.51	16.07	40.00	-23.93	QP		
3		55.7558	31.79	-13.91	17.88	40.00	-22.12	QP		
4		63.7867	30.25	-14.00	16.25	40.00	-23.75	QP		
5		104.3071	35.37	-16.45	18.92	43.50	-24.58	QP		
6	*	843.2377	28.34	2.86	31.20	46.00	-14.80	QP		



Site 3m Chamber #3

 Polarization: *Horizontal*

Temperature: 22.5 C

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 45 %

Mode: TX 2480MHz

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment				Height	Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		32.4342	30.84	-16.50	14.34	40.00	-25.66	QP			
2		39.2130	31.42	-15.14	16.28	40.00	-23.72	QP			
3		46.7687	31.46	-14.52	16.94	40.00	-23.06	QP			
4		54.9551	30.64	-13.96	16.68	40.00	-23.32	QP			
5		63.5913	30.53	-13.99	16.54	40.00	-23.46	QP			
6	*	854.3991	29.37	2.54	31.91	46.00	-14.09	QP			

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

Bluetooth (GFSK, π/4DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:

Test mode: GFSK Frequency: Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
7162.50	V	52.09	33.70	74	54	-21.91	-20.30
12096.75	V	56.52	37.40	74	54	-17.48	-16.60
15386.25	V	57.27	38.40	74	54	-16.73	-15.60
7389.45	H	52.20	34.10	74	54	-21.80	-19.90
10947.55	H	55.77	36.40	74	54	-18.23	-17.60
14677.35	H	57.77	38.90	74	54	-16.23	-15.10

Test mode: GFSK Frequency: Channel 39: 2441MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
7724.35	V	51.77	33.60	74	54	-22.23	-20.40
12137.55	V	56.62	36.40	74	54	-17.38	-17.60
14959.55	V	58.20	38.50	74	54	-15.80	-15.50
7384.35	H	51.22	33.50	74	54	-22.78	-20.50
10353.40	H	55.53	37.10	74	54	-18.47	-16.90
15022.45	H	57.84	37.80	74	54	-16.16	-16.20

Test mode: GFSK Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
7827.20	V	51.37	33.80	74	54	-22.63	-20.20
10695.10	V	54.55	36.20	74	54	-19.45	-17.80
14668.85	V	58.25	37.60	74	54	-15.75	-16.40
7384.35	H	51.22	33.50	74	54	-22.78	-20.50
10353.40	H	55.53	37.10	74	54	-18.47	-16.90
15022.45	H	57.84	37.80	74	54	-16.16	-16.20

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) The reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Bluetooth (GFSK, $\pi/4$ DQPSK, 8DPSK, Hopping) mode have been tested, and the worst result(GFSK, Hopping) was report as below:

Test mode: GFSK Frequency: Channel 0: 2402MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2389.028	H	52.58	74	34.90	54
2388.364	V	52.13	74	35.20	54

Test mode: GFSK Frequency: Channel 78: 2480MHz



Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2483.511	H	54.70	74	36.70	54
2483.506	V	56.21	74	37.80	54



Test mode: GFSK Frequency: Hopping

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2400.0	H	61.01	74	44.60	54
2483.5	H	52.44	74	34.90	54
2400.0	V	68.75	74	47.40	54
2483.5	V	51.78	74	35.60	54

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).


(2) Emission Level= Reading Level+Probe Factor +Cable Loss.






Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz

Test Model	Hopping	GFSK	H
------------	---------	------	---



Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz

Test Model	Hopping	GFSK	V
------------	---------	------	---



9.8 CONDUCTED EMISSION TEST

9.8.1 Applicable Standard

According to FCC Part 15.207(a)

9.8.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

9.8.3 Test Configuration

Test according to clause 7.3 conducted emission test setup

9.8.4 Test Procedure


The EUT was placed on a table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

9.8.5 Test Results

The 120V voltage have been tested, and the worst result recorded was report as below:



Site Conduction #1

 Phase: *L1*

Temperature: 24.1

Limit: (CE)FCC PART 15 class B_QP


Power: AC 120V/60Hz

Humidity: 53 %

Mode: BT

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		0.1700	34.11	9.62	43.73	64.96	-21.23	QP	
2		0.1700	17.07	9.62	26.69	54.96	-28.27	AVG	
3		0.2260	31.58	9.67	41.25	62.60	-21.35	QP	
4		0.2260	14.15	9.67	23.82	52.60	-28.78	AVG	
5		0.2980	32.55	9.73	42.28	60.30	-18.02	QP	
6		0.2980	13.08	9.73	22.81	50.30	-27.49	AVG	
7		0.4900	34.17	9.64	43.81	56.17	-12.36	QP	
8		0.4900	14.62	9.64	24.26	46.17	-21.91	AVG	
9		0.6180	35.00	9.63	44.63	56.00	-11.37	QP	
10		0.6180	20.04	9.63	29.67	46.00	-16.33	AVG	
11	*	1.6460	35.64	9.63	45.27	56.00	-10.73	QP	
12		1.6460	19.10	9.63	28.73	46.00	-17.27	AVG	



Site Conduction #1

 Phase: **N**

Temperature: 24.1

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 53 %

Mode: BT

Note:

No. Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
		dBuV	dB	dBuV	dB			
1	0.1740	36.91	9.62	46.53	64.77	-18.24	QP	
2	0.1740	21.22	9.62	30.84	54.77	-23.93	AVG	
3	0.2260	36.50	9.67	46.17	62.60	-16.43	QP	
4	0.2260	20.52	9.67	30.19	52.60	-22.41	AVG	
5	0.2980	34.82	9.73	44.55	60.30	-15.75	QP	
6	0.2980	13.75	9.73	23.48	50.30	-26.82	AVG	
7	0.3940	37.37	9.68	47.05	57.98	-10.93	QP	
8	0.3940	20.74	9.68	30.42	47.98	-17.56	AVG	
9 *	0.5420	40.25	9.63	49.88	56.00	-6.12	QP	
10	0.5420	24.32	9.63	33.95	46.00	-12.05	AVG	
11	0.6260	38.21	9.63	47.84	56.00	-8.16	QP	
12	0.6260	25.04	9.63	34.67	46.00	-11.33	AVG	

ANTENNA APPLICATION

9.8.6 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

9.8.7 Result

PASS.

The EUT is PCB antenna, the gain is 1.5 dBi.

Note: Antenna use a permanently attached antenna which is not replaceable.
 Not using a standard antenna jack or electrical connector for antenna replacement
 The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.

Detail of factor for radiated emission

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

----- End of Report -----