

FCC RF EXPOSURE REPORT

For

Smart Cordless Floor Washer

FCC MODEL NUMBER: FW221500US

FCC ADDITIONAL MODEL NUMBER: FW221100US, FW22***** ("*" = 0-9, A-Z or blank used to denote different countries, customers, colors or minor cosmetic changes, or for indicate factory identification)

PROJECT NUMBER: 4791094392

REPORT NUMBER: 4791094392-3

FCC ID: 2AV7A-FS22

ISSUE DATE: Jan. 06, 2024

Prepared for

Tineco Intelligent Technology Co., Ltd.

Prepared by

UL-CCIC COMPANY LIMITED No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, China Tel: +86 512-6808 6400 Fax: +86 512-6808 4099 Website: www.ul.com



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	01/06/2024	Initial Issue	

Form-ULID-008536-13 V3.0



TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	.4
2.	TEST METHODOLOGY	.5
3.	FACILITIES AND ACCREDITATION	.5
4.	MEASUREMENT UNCERTAINTY	.6
5.	REQUIREMENT	.7



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name:	Tineco Intelligent Technology Co., Ltd.
Address:	No. 108 Shihu Road West, Wuzhong Zone Suzhou, Jiangsu, China 215128
Manufacturer Information	
Company Name:	Tineco Intelligent Technology Co., Ltd.
Address:	No. 108 Shihu Road West, Wuzhong Zone Suzhou, Jiangsu, China 215128
EUT Description	
Product Name:	Smart Cordless Floor Washer
FCC Model Number:	FW221500US
FCC Additional No.:	FW221100US, FW22*****
	("*" = 0-9, A-Z or blank used to denote different countries,
	customers, colors or minor cosmetic changes, or for indicate
	factory identification)
Model Difference:	Their electrical circuit design, layout, components used and
	internal wiring are identical, only the model names are different.
	The model FW221500US was selected as the representative
	model for compliance test.
Sample Number:	6686647
Data of Receipt Sample:	Nov. 24, 2023
Test Date:	Nov. 24, 2023~ Dec. 30, 2023

APPLICABLE STANDARDS

STANDARD

TEST RESULTS

FCC Guidelines for Human Exposure IEEE

C95.1

Complies

Prepared By:

Tom Tang

Tom Tang

Authorized By:

Leon Wu

Leon Wu

Reviewed By:

Kenn. Shen

Kevin Shen



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06 and FCC Guidelines for Human Exposure IEEE C95.1.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4829.01) UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1247) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. IC (IC Designation No.: 25056; CAB No.: CN0073) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.
------------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, China.

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.



4. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty				
Output Power to Antenna	1.3 dB				
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.					



5. REQUIREMENT

<u>LIMIT</u>

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure							
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time E ² , H ² or S (minutes)			
0.3-1.34	614	1.63	(100) *	30			
1.34-30	824/f	2.19/f	(180/f²) *	30			
30-300	27.5	0.073	0.2	30			
300-1500			f/1500	30			
1500-100,000			1.0	30			
Note 1: f = frequency in MHz, * means Plane-wave equivalent power density							

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Note 3: The limit value 1.0mW/cm² is available for this EUT.

MPE CALCULATION METHOD

$S = PG/(4\pi R2)$

where: S = power density (in appropriate units, e.g. mW/ cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



CALCULATED RESULTS

BLE (Worst case)									
Mode	Frequency	Output Power to Antenna		Antenna Gain		Power Density	Limit	Verdict	
	(MHz)	(dBm)	(mW)	(dBi)	(Numeric)	(mW/cm2)	(mW/cm2)	Vordiot	
BLE	2402MHz- 2480MHz	7.5	5.62	3.75	2.37	0.0027	1	Complies	

2.4GHz WiFi (Worst case)									
Mode	Frequency	Output Power to Antenna		Antenna Gain		Power Density	Limit Verdict		
	(MHz)	(dBm)	(mW)	(dBi)	(Numeric)	(mW/cm2)	(mW/cm2)	Voralot	
11B	2412MHz- 2462MHz	18.5	70.79	3.75	2.37	0.0333	1	Complies	

Note:

- 1. The output power is from operation description.
- 2. The minimum separation distance of the device is greater than 20 cm.
- 3. All the channels had been tested, but only the worst data was recorded in the report.
- 4. The calculated result for the sample received is <Pass> according to < 47 CFR FCC Part 2 Subpart J, section 2.1091> when <Accuracy Method> decision rule is applied.

END OF REPORT

Form-ULID-008536-13 V3.0