

FCC RF EXPOSURE REPORT

For

Carpet One Spot

MODEL NUMBER: SC100100US

PROJECT NUMBER: 4790446015

REPORT NUMBER: 4790446015-4

FCC ID: 2AV7A-SC10

IC: 26039-SC10

ISSUE DATE: Jul. 23, 2022

Prepared for

Tineco Intelligent Technology Co., Ltd.

Prepared by

UL-CCIC COMPANY LIMITED

No. 2, Chengwan Road, Suzhou Industrial Park, People's Republic of China

Tel: + 86-512-6808 6400 Fax: + 86-512-6808 4099 Website: www.ul.com



REPORT NO: 4790446015-4

Page 2 of 8


Revision History

Rev.	Issue Date	Revisions	Revised By
V0	07/23/2022	Initial Issue	



TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	4
2.	TEST METHODOLOGY	5
3.	FACILITIES AND ACCREDITATION	5
4.	MEASUREMENT UNCERTAINTY	6
5.	REQUIREMENT	7





1. ATTESTATION OF TEST RESULTS

Company Name:	Tineco Intelligent Technology Co., Ltd.
Address:	NO 108 SHI HU RD (W) WU ZHONG ZONE SUZHOU

JIANGSU 215128, CHINA.

Factory Information

Company Name: Tineco Intelligent Technology Co., Ltd.

Address: NO 108 SHI HU RD (W) WU ZHONG ZONE SUZHOU

JIANGSU 215128, CHINA.

EUT Description

Product Name: Carpet One Spot Model Number: SC100100US Sample Number: 5055687

Data of Receipt Sample: Jun.15, 2022

Date Tested: Jun.15, 2022 – Jul. 22, 2022

APPLICABLE STANDARDS

STANDARD TEST RESULTS

FCC 47CFR§2.1091 KDB-447498 D01 V06

Complies

Prepared By:	Reviewed By:
Tom Tang	Leon Wu
Tom Tang	Leon Wu
Authorized By:	
Chris Zhong	

Chris Zhong Laboratory Leader



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.


3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4829.01) UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1247) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. IC (IC Designation No.: 25056; CAB No.: CN0073) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.
------------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, People's Republic of China

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.





4. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty			
Output Power to Antenna	0.69 dB			
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.				



5. REQUIREMENT

LIMIT

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure						
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	PowerDensity (S) (mW/cm²)	Averaging Time E ² , H ² or S (minutes)		
0.3-1.34	614	1.63	(100) *	30		
1.34-30	824/f	2.19/f	(180/f2) *	30		
30-300	27.5	0.073	0.2	30		
300-1500			f/150	30		
1500-100,000		-	1.0	30		

Note 1: f = frequency in MHz, * means Plane-wave equivalent power density

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Note 3: The limit value 1.0mW/cm² is available for this EUT.

MPE CALCULATION METHOD

 $S = PG/(4\pi R2)$

where: S = power density (in appropriate units, e.g. mW/ cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



REPORT NO: 4790446015-4 Page 8 of 8

CALCULATED RESULTS

WIFI (Worst case)									
Mode	Frequency	•	Power to enna	to Antenna Gain		Power Density	Limit	Verdict	
	(MHz)	(dBm)	(mW)	(dBi)	(Numeric)	(mW/cm2)	(mW/cm2)	Vordiot	
11b	2412	17.50	56.23	2.87	1.94	0.0217	1	Complies	

Note:

- 1. The output power to antenna and antenna gain are referred to the OD document(For the antenna gain can even refer the report 4790446015-3).
- 2. The minimum separation distance of the device is greater than 20 cm.
- 3. All the modes and channels had been tested, but only the worst data was recorded in the report.
- 4. The calculated result for the sample received is <Pass> according to < 47 CFR FCC Part 2 Subpart J, section 2.1091> when <Accuracy Method> decision rule is applied.

END OF REPORT