

# **RF Exposure Evaluation**

## Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
	(A) Limits	for Occupational/Controlled	Exposures	•
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
·	(B) Limits for	General Population/Uncontro	olled Exposure	
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

Friis transmission formula: Pd = (Pout\*G)/(4\*pi\*r<sup>2</sup>)

#### Where

Pd = power density in mW/cm<sup>2</sup>, Pout = output power to antenna in mW;


**G** = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## **Test Procedure**

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.





### Test Result of RF Exposure Evaluation

BT Mode					
Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
GFSK	-1.634	0.69	0.000297	1.0	PASS
π /4-DQPSK	-1.275	0.75	0.000321	1.0	PASS
8-DPSK	-0.994	0.80	0.000342	1.0	PASS

		2.4G WIFI Mode			
Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
802.11b	13.549	22.64	0.009741	1.0	PASS
802.11g	12.896	19.48	0.008382	1.0	PASS
802.11n20	11.992	15.82	0.006807	1.0	PASS

5.2G WIFI Mode					
Channel (MHz)	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
5180	11.632	14.56	0.005139	1.0	PASS

FM Mode					
Channel (MHz)	Electric Field (dBuV/m)	Electric Field (V/m)	Limit of Electric field strength (V/m)	Result	
107.9	46.37	0.0002	61.4	PASS	

Remark: dBuV/m to V/m , V/m = 10<sup>(((dBmV / m) - 120)/ 20);</sup>

2.4G / 5.2G Band antenna gain: 3.35dBi / 2.49dBi ;

The device can not transmit with BT and 2.4G WI-FI and 5G WI-FI simultaneously;

But FM can be transmitted simultaneously with one of the (BT / 2.4G WI-FI / 5G WI-FI), since the FM transmission power is too low, the simultaneous transmission passes by default.

Shenzhen ZKT Technology Co., Ltd. 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

