

承 認 書

SPECIFICATION FOR APPROVAL

客 戶: CUSTOMER:	J026
客 戶 料 號: CUST P/N:	Y.45.TK00004
泛 亞 料 號: FINE P/N:	FYJ026002
産 品 型 號: DESC:	FYJ02612024070902L
日 期: DATE:	2024/07/09
版 本: Version:	A.0

CUSTOMER AUTHORIZED SIGNATURE/客户永认签核					

擬制	審核 和亚电子家 批准
PREPARED BY	CHECKED BY
尹 艺	蔡纪雨
	▲任部

东莞市泛亚电子有限公司

Dongguan FANYA Electronics Co., LTD

地址: 东莞市石碣镇刘屋科技东路 194 号

TEL: 0769-22490287 / 22452492

FAX: 0769-22499451

E-mail: fineelec@163.com



版本變更	巨履歷
------	-----

Version Change History

版本 Rev.	變 更前 Before Change	變 更 後 After Change	更改日期 Change Date	批 准 Approved By
A.0	新发行		2024/07/09	蔡纪雨



SPECIFICATION

-、尺寸 DIMENSION:(mm) A 21.8±0.5 F B 39±1 C 0.9±0.1 D D 7±1 E E 2-4 F F 43.5±0.5 G G 2.5 MX G G 2.5 MX (************************************									
ECCOFYJ026012024070902LRev: A.0 $\underbrace{\mathbb{E} v: \mathbb{A} \cup \mathbb{B}}{\mathbb{B} \cap \mathbb{A} \cap \mathbb{C}}$ FYJ026012 \mathbb{R} v: A.0 $\underbrace{\mathbb{E} v: \mathbb{A} \cup \mathbb{B}}{\mathbb{C} \cup \mathbb{S} \cap \mathbb{N} : \mathbb{C} \vee \mathbb{A} \cup \mathbb{S} \cup \mathbb{K} \cup \mathbb{C} \cup \mathbb{S} \cup \mathbb{S}$					版本 客戶 CU		ST:	J026	
字科号 CUST P/N: Y.45.TK00004 マ、尺寸 DIMENSION:(mm) A 21.8±0.5 第 3.9±1 C 0.9±0.1 ロー・「アー」 ロー・「アー」 ロー・「アー」 ロー・「アー」 ロー・ロー・ロー・ロー・ロー・ロー・ロー・ロー・ロー・ロー・ロー・ロー・ロー・ロ		DESC		12024070902L		泛亚料号	Fine P/N:	FYJ026002	
FB 39 ± 1 Image: Schematric DiagramImage: Schematric Diagram <t< th=""><th></th><th></th><th></th><th></th><th></th><th></th><th>CUST P/N</th><th>: Y.45.TK00004</th></t<>							CUST P/N	: Y.45.TK00004	
I I <	一、尺寸	寸 DIME	NSION:(mm)			-1	А	21.8 ± 0.5	
C 0.9 ± 0.1 D 7 ± 1 E $2-4$ F $3M$ G $2.5 MX$ G $2.5 MX$ G $2.5 MX$ G $C.7 A Z Z S L D B S S L 0.5$ G $2.5 MX$ G $C.7 A Z Z S L D B S S L 0.5$ G $2.5 MX$ G $C.7 A Z Z S L D B S S L 0.5$ G $C.7 A Z Z S L D B S S L 0.5$ G $C.7 A Z Z S L D B S S L 0.5$ G $C.7 A Z Z S L D B S S L 0.5$ C $C.7 A Z Z S L D B S S L 0.5$ C $C.7 A Z Z S L D B S S L 0.5$ C $C.7 A Z Z S L D B S S L 0.5$ C $C.7 A Z Z S L D B S S L 0.5$ C $C.7 A Z Z S L D B S S L 0.5$ C $C.7 A Z Z S L D B S S L 0.5$ C $C.7 A Z Z S L D B S L 0.5$ C $C.7 A Z Z S L D B S L 0.5$ C $C.7 B Z Z S L D B S L 0.5$ C $C.7 B Z Z S L D B S L 0.5$ C $C.7 B Z Z S L D B S L 0.5$ C $C.7 B Z Z S L D B S L 0.5$ C $C.7 B Z Z S L D B S L 0.5$ C $C.7 B Z Z S L D B S L 0.5$ C $C.7 B Z Z S L D B S L 0.5$ C $C.7 B Z Z S L D B S L 0.5$ C $C.7 B Z Z S L 0.5$ C $C.7 B Z Z S L 0.5$ C $C.7 B Z Z S Z S L 0.5$ C $C.7 B Z Z S Z S L 0.5$ C $C.7 B Z Z S Z S Z S Z S Z S Z S Z S Z S Z S$	-						В	39 ± 1	
		<u>B</u>					С	0.9 ± 0.1	
Image: Stripped in the second stripp							D	7±1	
$F = 43, 5\pm 0.5$ $G = 1.5$ MA $G = 0.5$ MA							Е	2-4	
3M 3M9448A State State 3M 3M9448A 3M 3M9448A 3M State 3M 3M9448A 3M State State State State State State State							F	43.5±0.5	
3M 3M9448A State State 3M 3M9448A 3M 3M9448A 3M State 3M 3M9448A 3M State State State State State State State					3M			2.5 MAX	
Note 1.add does not need to be bent: Starting wire package form wire package form wire have package form wire package form wire have package form wire have package form wire have package for the colle address magnetic disc,				3M 3Mouto			G	(不含离型纸及引线部分)	
1Lad does not need to be bent: Starting site package mm wide high-starting site site site site package site site site site site package site site site site package site site site site package site site site site package site site package site site package site site package site package site site package site site package site site package site site package site package site site package sit				JM JM9448	A				
○peration frequency: 113kHz-205kHz,360kHz Antenna Type: Loop coil Antenna Antenna gain: 0dBi 三、绕线参数 Winding Specification: 0dBi ○Peration frequency: 113kHz-205kHz,360kHz Antenna gain: 0dBi ○Deration frequency: 113kHz-205kHz,360kHz Antenna gain: 0dBi ○Deration frequency: 113kHz-205kHz,360kHz Antenna gain: 0dBi ○Deration frequency: 113kHz-205kHz,360kHz NO. TERMINAL WIRE □ S F Litz0.08*65p 11Ts □ NO. TEMPERATURE:25±10°C, 湿度 RELATIVE HUMIDITY:65±20% □ □ □ Kaft 測试条件 測试仪器 NO. ITEM TERMINAL SPECIFICATION TEST FREQUENCY TEST EQUIPMENT 1 IND. S-F 8.5uH ±5% 100KHz/1.0V TH2829LX 2 DCR S-F 70m Ω Max 25°C TH2829LX □ □ □ □ □ □ □ □ □ □ </th <th colspan="7">2. Coil backstick magnetic disc, magnetic disc size: ÿ43.5*5.3*1.0 Open hole open double slot. On the back, ÿ42*6*0.15mm 3m double-sided back tape is hand-tornÿ3. The middle of the coil is affixed with a small magnetic disc, the size of the small magnetic disc is 20*0.75mm, and the small magnetic side is affixed with ÿ15*0.08 ordinary double-sided adhesive. 4. The coil fitting should be located in the center of ferrite, and the concentric circle deviation should not exceed 0.5mm</th>	2. Coil backstick magnetic disc, magnetic disc size: ÿ43.5*5.3*1.0 Open hole open double slot. On the back, ÿ42*6*0.15mm 3m double-sided back tape is hand-tornÿ3. The middle of the coil is affixed with a small magnetic disc, the size of the small magnetic disc is 20*0.75mm, and the small magnetic side is affixed with ÿ15*0.08 ordinary double-sided adhesive. 4. The coil fitting should be located in the center of ferrite, and the concentric circle deviation should not exceed 0.5mm								
Antenna Type: Loop coil Antenna Antenna gain: 0dBi 三、绕线参数 Winding Specification: 0dBi 「序号」端子 銭径 圏数 绕线方向 NO. TERMINAL WIRE Turns Winding Direction 1 S F Litz0.08*65p 11Ts CCW 四、电气特性 ELECTRICAL CHARACTERISTICS: 温度 TEMPERATURE:25±10°C, 湿度 RELATIVE HUMIDITY:65±20% 「序号 项目 端子 标准 测试条件 测试仪器 NO. ITEM TERMINAL SPECIFICATION TEST FREQUENCY TEST EQUIPMENT 1 IND. S-F 8.5uH ±5% 100KHz/1.0V TH2829LX 2 DCR S-F 70m \Omega Max 25 °C TH2829LX 2 DCR S-F 70m \Omega Max 25 °C TH2829LX E ### /日期 審核/日期 APPROVED BY/DATE				-			-		
Antenna gain: OdBi				Antenna Ty					
三、绕线参数 Winding Specification: 							-		
NO.TERMINALWIRETurnsWinding Direction1SFLitz0.08*65p11TsCCW四、电气特性 ELECTRICAL CHARACTERISTICS: 温度 TEMPERATURE:25±10°C, 湿度 RELATIVE HUMIDITY:65±20%测试条件测试仪器序号项目端子标准测试条件测试仪器NO.ITEMTERMINALSPECIFICATIONTEST FREQUENCYTEST EQUIPMENT1IND.S-F 8.5 uH ±5%100KHz/1.0VTH2829LX2DCRS-F $70m \Omega$ Max 25° TH2829LX2DCRS-F $70m \Omega$ Max 25° TH2829LX擬制/日期審核/日期批准/日期PREPARED BY/DATECHECKED BY/DATEAPPROVED BY/DATE				cation:			i		
1 S F Litz0.08*65p 11Ts CCW 四、电气特性 ELECTRICAL CHARACTERISTICS: CCW 温度 TEMPERATURE:25±10°C, 湿度 RELATIVE HUMIDITY:65±20% 序号 项目 端子 标准 NO. ITEM TERMINAL SPECIFICATION TEST FREQUENCY TEST EQUIPMENT 1 IND. S-F 8.5uH ±5% 100KHz/1.0V TH2829LX 2 DCR S-F 70m					圈数				
四、电气特性 ELECTRICAL CHARACTERISTICS: 温度 TEMPERATURE:25±10°C, 湿度 RELATIVE HUMIDITY:65±20% 序号 项目 端子 标准 测试条件 测试仪器 NO. ITEM TERMINAL SPECIFICATION TEST FREQUENCY TEST EQUIPMENT 1 IND. S-F 8.5uH±5% 100KHz/1.0V TH2829LX 2 DCR S-F 70m Ω Max 25°C TH2829LX 2 DCR S-F 70m Ω Max 25°C TH2829LX								-	
温度 TEMPERATURE:25±10°C, 湿度 RELATIVE HUMIDITY:65±20% 序号 项目 端子 标准 测试条件 测试仪器 NO. ITEM TERMINAL SPECIFICATION TEST FREQUENCY TEST EQUIPMENT 1 IND. S-F 8.5uH±5% 100KHz/1.0V TH2829LX 2 DCR S-F 70m Ω Max 25 °C TH2829LX Image: Set the set th	· ·				p		1115	CCW	
序号项目端子标准测试条件测试仪器NO.ITEMTERMINALSPECIFICATIONTEST FREQUENCYTEST EQUIPMENT1IND.S-F8.5uH±5%100KHz/1.0VTH2829LX2DCRS-F70m Ω Max25 °CTH2829LX4IIIIIII4IIIIIIIIIIIII5F70m Ω Max25 °CTH2829LX6IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII						5+20%			
NO. ITEM TERMINAL SPECIFICATION TEST FREQUENCY TEST EQUIPMENT 1 IND. S-F 8.5uH±5% 100KHz/1.0V TH2829LX 2 DCR S-F 70m Ω Max 25°C TH2829LX			1					测试仪器	
1 IND. S-F 8.5uH±5% 100KHz/1.0V TH2829LX 2 DCR S-F 70m Ω Max 25°C TH2829LX 4 - - - - - 4 - - - - - 5 - - - - - 6 - - - - - 7 - - - - - 7 - - - - - - 7 - - - - - - - 7 - - - - - - - - 7 - - - - - - - - - 7 -								TEST EQUIPMENTS	
2 DCR S-F 70m Ω Max 25℃ TH2829LX μ μ μ μ μ μ μ μ μ μ μ μ μ μ								-	
PREPARED BY/DATE CHECKED BY/DATE APPROVED BY/DATE									
PREPARED BY/DATE CHECKED BY/DATE APPROVED BY/DATE									
PREPARED BY/DATE CHECKED BY/DATE APPROVED BY/DATE					I				
PREPARED BY/DATE CHECKED BY/DATE APPROVED BY/DATE		擬制/日期 案柄			/日期			批准/日期	
3 . 0									
	尹艺 2024/07/09				蔡纪雨 2024/07/09		د	13mg	