




802.11b




802.11g



CH11



CH01



30MHz-3GHz



30MHz-3GHz




3GHz -25GHz

3GHz -25GHz


802.11g



CH06



CH11



30MHz-3GHz



30MHz-3GHz





3GHz -25GHz

3GHz -25GHz

802.11n(HT20)



CH01



30MHz-3GHz


30MHz-3GHz




3GHz -25GHz

3GHz -25GHz


802.11n(HT20)




802.11n(HT40)



CH11



CH03



30MHz-3GHz



30MHz-3GHz




3GHz -25GHz

3GHz -25GHz


802.11n(HT40)



CH06



CH09



30MHz-3GHz




30MHz-3GHz



3GHz -25GHz


3GHz -25GHz

Band-edge Measurements for RF Conducted Emissions:**802.11b**


Left bandedge




Right bandedge

802.11g


Left bandedge



Right bandedge


802.11n(HT20)

Left bandedge



Right bandedge

802.11n(HT40)



Left bandedge



Right bandedge

4.7 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):



(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result:


The maximum gain of antenna was 5.19 dBi for 2.4GHz WIFI.

Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Shenzhen GUOREN Certification Technology Service Co., Ltd. does not assume any responsibility.

5 Test Setup Photos of the EUT







6 Photos of the EUT







WIFI
Antenna







***** End of Report *****