


Common Information

Project No.: RKSA231222003
 EUT Model: MWC-708
 Test Mode: 802.11n40 Mode High Channel of Chain 0&1
 Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
 Test Equipment: ESU40, 3115, 2641-1
 Temperature: 21.7°C
 Humidity: 42%
 Atmospheric pressure: 102.2KPa
 Test Engineer: James Ji
 Test Date: 2024/1/17

Full Spectrum



Critical Freqs


| Frequency (MHz) | Corrected Amplitude | | Limit (dB µ V/m) | Margin (dB) | Pol | Corr. (dB/m) |
|-----------------|---------------------|--------------------|------------------|-------------|-----|--------------|
| | MaxPeak (dB µ V/m) | Average (dB µ V/m) | | | | |
| 2458.576000 | --- | 93.44 | --- | --- | H | 0.2 |
| 2458.576000 | 101.35 | --- | --- | --- | H | 0.2 |
| 2485.426000 | 54.25 | --- | 74.00 | 19.75 | H | 0.2 |
| 2485.426000 | --- | 51.03 | 54.00 | 2.97 | H | 0.2 |
| 2495.920000 | 58.21 | --- | 74.00 | 15.79 | H | 0.2 |
| 2495.920000 | --- | 44.03 | 54.00 | 9.97 | H | 0.2 |

802.11ax-HE40 Mode:

Common Information

| | |
|-----------------------|---|
| Project No.: | RKSA231222003 |
| EUT Model: | MWC-708 |
| Test Mode: | 802.11ax40 Mode Low Channel of Chain 0&1 |
| Standard: | FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209 |
| Test Equipment: | ESU40、3115、2641-1 |
| Temperature: | 21.7°C |
| Humidity: | 42% |
| Atmospheric pressure: | 102.2KPa |
| Test Engineer: | James Ji |
| Test Date: | 2024/1/17 |

Full Spectrum




Critical Freqs

| Frequency (MHz) | Corrected Amplitude | | Limit (dB μ V/m) | Margin (dB) | Pol | Corr. (dB/m) |
|-----------------|---------------------|--------------------|------------------|-------------|-----|--------------|
| | MaxPeak (dB μ V/m) | Average (dB μ V/m) | | | | |
| 2388.022000 | --- | 52.92 | 54.00 | 1.08 | H | 0.1 |
| 2388.022000 | 57.20 | --- | 74.00 | 16.80 | H | 0.1 |
| 2389.296000 | --- | 46.98 | 54.00 | 7.02 | H | 0.1 |
| 2389.296000 | 59.75 | --- | 74.00 | 14.25 | H | 0.1 |
| 2426.858000 | --- | 94.43 | --- | --- | H | 0.1 |
| 2426.858000 | 105.76 | --- | --- | --- | H | 0.1 |

Common Information

Project No.: RKSA231222003
 EUT Model: MWC-708
 Test Mode: 802.11ax40 Mode High Channel of Chain 0&1
 Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
 Test Equipment: ESU40, 3115, 2641-1
 Temperature: 21.7°C
 Humidity: 42%
 Atmospheric pressure: 102.2KPa
 Test Engineer: James Ji
 Test Date: 2024/1/17

Full Spectrum



Critical Freqs

| Frequency (MHz) | Corrected Amplitude | | Limit (dB μ V/m) | Margin (dB) | Pol | Corr. (dB/m) |
|-----------------|---------------------|--------------------|------------------|-------------|-----|--------------|
| | MaxPeak (dB μ V/m) | Average (dB μ V/m) | | | | |
| 2458.426000 | --- | 92.65 | --- | --- | H | 0.2 |
| 2458.426000 | 103.18 | --- | --- | --- | H | 0.2 |
| 2483.512000 | 61.47 | --- | 74.00 | 12.53 | H | 0.2 |
| 2483.512000 | --- | 49.21 | 54.00 | 4.79 | H | 0.2 |
| 2489.212000 | 55.93 | --- | 74.00 | 18.07 | H | 0.2 |
| 2489.212000 | --- | 52.46 | 54.00 | 1.54 | H | 0.2 |

FCC §15.247(A) (2) - 6 DB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 * RBW$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions & Test Information

| | |
|---------------------------|--------------------------|
| Temperature: | 16.8-17.2 °C |
| Relative Humidity: | 41-45 % |
| ATM Pressure: | 102.5-102.7 kPa |
| Test Date: | 2024-01-22 to 2024-01-31 |
| Test Engineer: | Jay Liu |


EUT operation mode: Transmitting

Test Result: Pass


| Test Mode | Channel (MHz) | DTS Bandwidth (MHz) | | Limit (MHz) | Verdict |
|---------------|---------------|---------------------|---------|-------------|---------|
| | | Chain 0 | Chain 1 | | |
| 802.11b | 2412 | 8.02 | 7.54 | 0.5 | PASS |
| | 2437 | 7.37 | 7.45 | 0.5 | PASS |
| | 2462 | 7.94 | 7.62 | 0.5 | PASS |
| 802.11g | 2412 | 15.87 | 15.87 | 0.5 | PASS |
| | 2437 | 15.79 | 16.27 | 0.5 | PASS |
| | 2462 | 16.27 | 16.03 | 0.5 | PASS |
| 802.11n-HT20 | 2412 | 17.23 | 16.67 | 0.5 | PASS |
| | 2437 | 17.07 | 17.56 | 0.5 | PASS |
| | 2462 | 16.51 | 17.15 | 0.5 | PASS |
| 802.11n-HT40 | 2422 | 35.92 | 35.91 | 0.5 | PASS |
| | 2437 | 35.91 | 36.23 | 0.5 | PASS |
| | 2452 | 36.23 | 35.91 | 0.5 | PASS |
| 802.11ax-HE20 | 2412 | 18.44 | 18.84 | 0.5 | PASS |
| | 2437 | 18.44 | 18.36 | 0.5 | PASS |
| | 2462 | 18.76 | 18.68 | 0.5 | PASS |
| 802.11ax-HE40 | 2422 | 37.68 | 38.16 | 0.5 | PASS |
| | 2437 | 38 | 37.68 | 0.5 | PASS |
| | 2452 | 37.52 | 37.84 | 0.5 | PASS |

Chain 0:


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




802.11n-HT40 Mode Low Channel




802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel




802.11ax-HE20 Mode Low Channel




802.11ax-HE20 Mode Middle Channel




802.11ax-HE20 Mode High Channel




802.11ax-HE40 Mode Low Channel



802.11ax-HE40 Mode Middle Channel




802.11ax-HE40 Mode High Channel




Chain 1:


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode High Channel




802.11n-HT40 Mode Low Channel




802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel




802.11ax-HE20 Mode Low Channel




802.11ax-HE20 Mode Middle Channel




802.11ax-HE20 Mode High Channel




802.11ax-HE40 Mode Low Channel



802.11ax-HE40 Mode Middle Channel



802.11ax-HE40 Mode High Channel



FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliant with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions & Test Information

| | |
|---------------------------|------------|
| Temperature: | 16.8 °C |
| Relative Humidity: | 41 % |
| ATM Pressure: | 102.5 kPa |
| Test Date: | 2024-01-17 |
| Test Engineer: | Jay Liu |

EUT operation mode: Transmitting

| Test Mode | Channel (MHz) | Maximum Conducted Peak Output Power (dBm) | | | Limit (dBm) | Verdict |
|---------------|---------------|---|---------|-------|-------------|---------|
| | | Chain 0 | Chain 1 | Total | | |
| 802.11b | 2412 | 22.92 | 22.60 | / | ≤30.00 | PASS |
| | 2437 | 22.85 | 22.85 | / | ≤30.00 | PASS |
| | 2462 | 21.03 | 21.15 | / | ≤30.00 | PASS |
| 802.11g | 2412 | 21.33 | 20.57 | / | ≤30.00 | PASS |
| | 2437 | 21.42 | 20.71 | / | ≤30.00 | PASS |
| | 2462 | 19.43 | 20.91 | / | ≤30.00 | PASS |
| 802.11n-HT20 | 2412 | 19.44 | 19.13 | 22.30 | ≤30.00 | PASS |
| | 2437 | 19.27 | 19.39 | 22.34 | ≤30.00 | PASS |
| | 2462 | 18.51 | 18.42 | 21.48 | ≤30.00 | PASS |
| 802.11n-HT40 | 2422 | 15.75 | 15.66 | 18.72 | ≤30.00 | PASS |
| | 2437 | 15.67 | 15.72 | 18.71 | ≤30.00 | PASS |
| | 2452 | 14.08 | 13.63 | 16.87 | ≤30.00 | PASS |
| 802.11ax-HE20 | 2412 | 19.54 | 19.20 | 22.38 | ≤30.00 | PASS |
| | 2437 | 19.58 | 19.70 | 22.65 | ≤30.00 | PASS |
| | 2462 | 17.94 | 17.81 | 20.89 | ≤30.00 | PASS |
| 802.11ax-HE40 | 2422 | 15.19 | 15.15 | 18.18 | ≤30.00 | PASS |
| | 2437 | 15.36 | 15.32 | 18.35 | ≤30.00 | PASS |
| | 2452 | 14.11 | 13.73 | 16.93 | ≤30.00 | PASS |

Note:

The maximum antenna gain is 4.9dBi, the device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:

Array Gain = 0 dB (i.e., no array gain) for NANT ≤ 4;

So: Directional gain = GANT + Array Gain = 4.9dBi < 6dBi, no RF outpower limit was reduced.

FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliant with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions & Test Information


| | |
|---------------------------|--------------------------|
| Temperature: | 16.8-17.2 °C |
| Relative Humidity: | 41-45 % |
| ATM Pressure: | 102.5-102.7 kPa |
| Test Date: | 2024-01-22 to 2024-01-31 |
| Test Engineer: | Jay Liu |

EUT operation mode: Transmitting


Test Result: Compliant

Chain 0:


802.11b Mode Left Side




802.11b Mode Right Side




802.11g Mode Left Side




802.11g Mode Right Side




802.11n-HT20 Mode Left Side




802.11n-HT20 Mode Right Side




802.11n-HT40 Mode Left Side




802.11n-HT40 Mode Right Side




802.11ax-HE20 Mode Left Side




802.11ax-HE20 Mode Right Side



802.11ax-HE40 Mode Left Side




802.11ax-HE40 Mode Right Side




Chain 1:


802.11b Mode Left Side




802.11b Mode Right Side




802.11g Mode Left Side




802.11g Mode Right Side




802.11n-HT20 Mode Left Side




802.11n-HT20 Mode Right Side




802.11n-HT40 Mode Left Side




802.11n-HT40 Mode Right Side




802.11ax-HE20 Mode Left Side




802.11ax-HE20 Mode Right Side



802.11ax-HE40 Mode Left Side



802.11ax-HE40 Mode Right Side



FCC §15.247(E) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine Compliant, and it is optional if the maximum conducted (average) output power was used to determine Compliant:

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 * \text{RBW}$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions & Test Information

| | |
|---------------------------|--------------------------|
| Temperature: | 16.8-17.2 °C |
| Relative Humidity: | 41-45 % |
| ATM Pressure: | 102.5-102.7 kPa |
| Test Date: | 2024-01-22 to 2024-01-31 |
| Test Engineer: | Jay Liu |

EUT operation mode: Transmitting

Test Result: Pass

| Test Mode | Channel (MHz) | Power Spectral Density (dBm/3kHz) | | | Limit (dBm/3kHz) | Verdict |
|---------------|---------------|-----------------------------------|---------|--------|------------------|---------|
| | | Chain 0 | Chain 1 | Total | | |
| 802.11b | 2412 | -0.19 | -1.68 | / | ≤8.00 | PASS |
| | 2437 | 0.3 | 0.48 | / | ≤8.00 | PASS |
| | 2462 | 0.57 | -0.96 | / | ≤8.00 | PASS |
| 802.11g | 2412 | -11.98 | -12.11 | / | ≤8.00 | PASS |
| | 2437 | -10.48 | -11.96 | / | ≤8.00 | PASS |
| | 2462 | -12.98 | -11.79 | / | ≤8.00 | PASS |
| 802.11n-HT20 | 2412 | -12.5 | -12.91 | -9.69 | ≤6.10 | PASS |
| | 2437 | -12.43 | -12.87 | -9.63 | ≤6.10 | PASS |
| | 2462 | -12.77 | -13.24 | -9.99 | ≤6.10 | PASS |
| 802.11n-HT40 | 2422 | -19.13 | -18.81 | -15.96 | ≤6.10 | PASS |
| | 2437 | -18.02 | -19.38 | -15.64 | ≤6.10 | PASS |
| | 2452 | -20.57 | -20.17 | -17.36 | ≤6.10 | PASS |
| 802.11ax-HE20 | 2412 | -12.4 | -13.99 | -10.11 | ≤6.10 | PASS |
| | 2437 | -13.86 | -14.01 | -10.92 | ≤6.10 | PASS |
| | 2462 | -15.55 | -15.4 | -12.46 | ≤6.10 | PASS |
| 802.11ax-HE40 | 2422 | -21.79 | -22.07 | -18.92 | ≤6.10 | PASS |
| | 2437 | -21.27 | -21.06 | -18.15 | ≤6.10 | PASS |
| | 2452 | -20.97 | -21.57 | -18.25 | ≤6.10 | PASS |


The maximum antenna gain is 4.9 dBi. The device employed Cyclic Delay Diversity (CDD) for 802.11MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:

Array Gain = $10 * \log(NANT/NSS)$ dB.


So: Directional gain = GANT + Array Gain = 4.9 + $10 * \log(2/1)$ = 7.9dBi > 6dBi, power spectral density limit was reduced 1.9dB

For Chain 0:


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




802.11n-HT40 Mode Low Channel




802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel




802.11ax-HE20 Mode Low Channel




802.11ax-HE20 Mode Middle Channel




802.11ax-HE20 Mode High Channel




802.11ax-HE40 Mode Low Channel



802.11ax-HE40 Mode Middle Channel




802.11ax-HE40 Mode High Channel




For Chain 1:


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




802.11n-HT40 Mode Low Channel




802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel




802.11ax-HE20 Mode Low Channel




802.11ax-HE20 Mode Middle Channel




802.11ax-HE20 Mode High Channel




802.11ax-HE40 Mode Low Channel



802.11ax-HE40 Mode Middle Channel



802.11ax-HE40 Mode High Channel



EUT PHOTOGRAPHS

Please refer to the attachment EXHIBIT A_EUT EXTERNAL PHOTOGRAPHS and EXHIBIT B_EUT INTERNAL PHOTOGRAPHS.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment EXHIBIT C_TEST SETUP PHOTOGRAPHS.

Declarations

1. Bay Area Compliance Laboratories Corp. (Kunshan) is not responsible for authenticity of any test data provided by the applicant. Test data from the applicant that may affect test results are marked with an asterisk “★”. The model number, product name, address, trademark, etc. from the applicant are not considered as test data.
2. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
3. Unless required by the rule provided by the applicant or product regulations, then decision rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95.45% confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of Bay Area Compliance Laboratories Corp. (Kunshan).
6. This report is valid only with a valid digital signature. The digital signature may be available only under the adobe software above version 7.0.
7. This report may contain standards and test items that are not covered by the accreditation scope and shall be marked with an asterisk “▲”.

******* END OF REPORT *******