

4R=1mm



INSTALLATION ONLY BY A TRAINED INSTALLER Font height ≥ 2.8mm

Date : 202302

产品生产日期 / 2023: 年 / 02: 月
 *由市场部提供机器生产年月

Refers to the year and month of machine production.
 2023→Y
 02→M
 *The marketing department provides the machine production time

材料特性要求

- ★ 1.成品标签材料需要过UL969
 纸材不干胶 (面料, 胶水, 底纸), PE膜, 油墨
- ★ 2.背胶粘贴牢固, 不易脱落耐高低温
 测试条件: 60°C 80%RH -20°C

Material characteristic requirements:

- ★ 1. Finished product label materials shall comply with UL969 certification.
 Including: PET adhesive (fabric, glue, backing paper), PE film, ink
- ★ 2. The glue is firmly adhered, not easy to fall off, and resistant to high and low temperature environment.
 Test conditions:60°C 80%RH -20°C

要求 Requirement	1. 符合RoHS/Reach标准; 2. 制品中不可含有六价铬、镉、铅、水银、PBB (多溴化联苯)、PBDE等物质; 3. 制品中氯系和溴系化合物含量900PPM以下,且两者总和1500PPM以下,红磷100PPM以下。 1. Comply with RoHS / Reachstandard; 2. Products should not contain hexavalent chromium, cadmium, lead, mercury, PBB (polybrominated biphenyl), PBDE and other substances; 3. The content of chlorine and bromine compounds in the product is below 900PPM, and the sum of the two is below 1500PPM, and the red phosphorus is below 100PPM.	规格 specification	1. 尺寸:见上模切图 2. 材料:50u PET不干胶贴纸/过光膜(MZ0333+光膜) 3.单色印刷 C:0 M:0 Y:0 K:100; 4. 注意:印刷清楚,无脏污等不良。 1. Size: See the die-cut above 2. Material: 50u PET/Gloss lamination; 3.single-color printing C:0 M:0 Y:0 K:100; 4.Note: The printing is clear, no dirt and other defects.	名称 Name	XP02-433 FCC标签 XP02-433 Label	设计 DRN	Ivy
				料号 P/N	D.LB.2116-01C-1	更新日期 Revise date	20230909
				单位 Unit	mm	审核 CHK	
				版本 Ver	A3	批准 APR	