

Annex 1: Measurement diagrams to
TEST REPORT
No.: 19-1-0117401T02a-C2

According to:
FCC Regulations Title 47, Part 15
Subpart B (Unintentional radiators)
§15.107, §15.109

ISED-Regulations

ICES-003, Issue 6

for

R&M USA Inc.

**R&MinteliPhy SensorBar for 48 port panel ELISO RFID based network
infrastructure monitoring system**
FCC ID: 2AVF4R837017



Laboratory Accreditation and Listings
<div style="text-align: center;"><p>Deutsche Akkreditierungsstelle D-PL-12047-01-01 D-PL-12047-01-03 D-PL-12047-01-04</p></div> <p>Accredited EMC-Test Laboratory</p>
accredited according to DIN EN ISO/IEC 17025:2018
<p>CETECOM GmbH Laboratory Radio Communications & Electromagnetic Compatibility Im Teelbruch 116 • 45219 Essen • Germany Registered in Essen, Germany, Reg. No.: HRB Essen 8984 Tel.: + 49 (0) 20 54 / 95 19-0 • Fax: + 49 (0) 20 54 / 95 19-150 E-mail: contact@cetecom.com • Internet: www.cetecom.com</p>

Table of contents

1. MEASUREMENT DIAGRAMS OF EMISSION TEST	3
1.1. Diagrams of conducted emissions on AC-Power lines (Diagram group 01)	3
1.2. Diagrams of radiated field strength emissions, 30 MHz - 1 GHz (Diagram group 03)	4

1. Measurement diagrams of emission test

1.1. Diagrams of conducted emissions on AC-Power lines (Diagram group 01)

1.01


Common Information

Test Description: Conducted Voltage Measurement Class B
 Test Site Location: Conducted Emission, CETECOM GmbH Essen
 Test Software: R&S EMC32 v9.15
 Test Standard: FCC 15.107, FCC 15.207
 Operating Mode: Transceiver disabled. internal communication
 Measured on line: N/L1
 Diagram details: Shows the peak values as a sum of measured ports in maxhold mode
 Environmental Conditions: Humidity : 59% rH; Temperature: 22° C
 Operator: Mah
 EUT Setup: 1
 Verdict: Passed

EUT Information

Manufacturer: R&M USA Inc.
 Product: R&MinteliPhy SensorBar for 48 port panel ELISO
 Model: RFID based network infrastructure monitoring system
 HW version: Rev. B
 SW version: N/A
 SerialNo.: 1002011000006346
 Power Supply: 120 AC 60 Hz

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	PE	Corr. (dB)
0.523125	38.92	---	56.00	17.08	1000.0	9.000	N	GN	0.1
0.523125	---	38.60	46.00	7.40	1000.0	9.000	N	GN	0.1
1.183750	23.21	---	56.00	32.79	1000.0	9.000	N	GN	0.3
1.183750	---	22.46	46.00	23.54	1000.0	9.000	N	GN	0.3
20.080625	---	22.41	50.00	27.59	1000.0	9.000	L1	GN	0.8
20.080625	26.12	---	60.00	33.88	1000.0	9.000	L1	GN	0.8

1.2. Diagrams of radiated field strength emissions, 30 MHz - 1 GHz (Diagram group 03)

3.01


Common Information

Test description:	Electric Field Strength Measurement
Test Site Location:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	not used
Used filter:	not used
Test Standard.:	FCC 15.109 Class B; RSS-Gen. Issue 5
Operator:	MSouissi
Operating Mode:	TX
Environmental Conditions:	Humidity : 45.3% rH; Temperature: 22.6° C
EUT Setup:	1
Verdict:	Passed

EUT Information

Manufacturer:	R&M USA Inc.
Product:	R&MinteliPhy SensorBar for 48 port panel ELISO
Model:	RFID based network infrastructure monitoring system
HW version:	Rev. B
SW version:	N/A
Serial number:	1002011000006346
Power Supply:	110 V AC

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
64.780000	29.18	40.00	10.82	120.000	109.0	V	0.0	7.3
862.640000	32.14	46.00	13.86	120.000	368.0	H	243.0	26.6

3.02


Common Information

Test Description: Electric Field Strength Measurement
 Test Site Location: Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
 Version of Testsoftware: EMC32 V9.25.0
 Distance correction: not used
 Used Filter: not used
 Test Standard.: FCC 15.109 Class B; RSS-Gen. Issue 5
 Operator: GHu
 Operating Mode: Data communication
 Power during tests:
 Environmental Conditions: Humidity : 45% rH; Temperature: 21° C
 EUT Setup: 1
 Verdict: Passed
 Comment:

EUT Information

Manufacturer: R&M USA Inc.
 Product: R&MinteliPhy SensorBar for 48 port panel ELISO
 Model: RFID based network infrastructure monitoring system
 HW version: Rev. B
 SW version: N/A
 Serial number: 1002011000006346
 Power Supply: 110 V AC

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
59.870000	27.99	40.00	12.01	120.000	126.0	V	21.0	8.9