

## RF Exposure Requirements

---

Product Description: HTC True Wireless Earbuds 9

Model No.: HTC TWS9

FCC ID: 2AVFE-HTCTWS9

According to the KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\left[ \frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

-  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation

- The result is rounded to one decimal place for comparison

### Calculation Result:

Tx frequency range: 2402-2480MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power: 4.98dBm

Tune-Up output power: 5.0dBm

RF channel transmit frequency: 2480MHz

Result: 1.0

Limit: 3.0

The exclusion thresholds is  $1.0 < 3.0$ , so the transmitter complies with the RF exposure requirements and the SAR is not required.