

# TEST REPORT

**Reference No.**..... : WTX22X03048724W-2  
**FCC ID** ..... : 2AVFE-HTCUW01  
**Applicant** ..... : Water World International Industrial Limited  
**Address**..... : UNIT C 24/F, GOLDEN BEAR INDUSTRIAL CENTRE, 66-82 CHAI WAN  
KOK STREET TSUEN WAN NT, HONG KONG  
**Manufacturer** ..... : The same as Applicant  
**Address**..... : The same as Applicant  
**Product Name** ..... : HTC Wireless Charger  
**Model No.**..... : HTC UW01  
**Standards** ..... : KDB 680106 D01 V03  
**Date of Receipt sample** .... : 2022-03-21  
**Date of Test**..... : 2022-03-26 to 2022-04-11  
**Date of Issue** ..... : 2022-04-11  
**Test Report Form No.** ..... : WTX\_KDB 680106 D01 V03W  
**Test Result**..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.


**Prepared By:**

**Waltek Testing Group (Shenzhen) Co., Ltd.**

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,  
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Mike Shi

Approved by:



Silin Chen

**TABLE OF CONTENTS**

**1. GENERAL INFORMATION.....4**  
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4  
1.2 AUXILIARY EQUIPMENT LIST AND DETAILS .....5  
1.3 TEST EQUIPMENT LIST AND DETAILS .....6

**2. RF EXPOSURE TEST REPORT.....7**  
2.1 STANDARD APPLICABLE.....7  
2.2 TEST CONDITIONS .....7  
2.3 TEST PROCEDURE.....8  
2.4 TEST RESULT.....9  
2.5 MEASUREMENT UNCERTAINTY .....11  
2.6 TEST PHOTOS .....12

**APPENDIX PHOTOGRAPHS.....13**

**Report version**

Version No.	Date of issue	Description
Rev.00	2022-04-11	Original
/	/	/

## 1. GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	HTC Wireless Charger
Trade Name:	HTC
Model No.:	HTC UW01
Adding Model(s):	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	112~205KHz
Modulation Type:	ASK
Antenna Type:	Coil Antenna
Antenna Gain:	0dBi
Input:	DC5V 2A, DC9V 2A,DC12V1.67A
Wireless output:	5W,7.5W,10W,15W
Power adapter:	/

## 1.2 Auxiliary Equipment List and Details

### EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
Type-C Cable	1.0	Unshielded	Without Ferrite

### Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Adapter	/	PN453C	/
Wireless Charging Load	YBZ	YBZ wireless charging tester	/

### Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

**1.3 Test Equipment List and Details**

<b>Description</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial No.</b>	<b>Cal Date</b>	<b>Due Date</b>
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200AC	180ZX10226	2021-05-20	2024-05-19

## 2. RF Exposure Test Report

### 2.1 Standard Applicable

According to § 1.1310 system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)



Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

### 2.2 Test Conditions

Test Mode	Description	Remark
TM1	Wireless charging	5W output
TM2	Wireless charging	7.5W output
TM3	Wireless charging	10W output
TM4	Wireless charging	15W output
<b>Measurement Distance:</b>		
15 cm and 20 cm		

### 2.3 Test Procedure



- a. The measurement probe was placed at test distance(15 cm for A,B,C,D,F and 20 cm for E) which is between the edge of the charger and the geometric center of probe.
- b. The highest emission level was recorded at the measurement points(A, B, C, D, E, F).
- c. The EUT was measured according to the distance of KDB 680106 D01 V03.



## 2.4 Test Result

The EUT complies with item 5.2 of KDB 680106 D01V03

1. Power transfer frequency is less than 1 MHz  
Yes, the device operates in the frequency range from 112kHz to 205kHz.
2. Output power from each primary coil is less than or equal to 15 watts  
Yes, the maximum output power of the primary coil is less than 15W.
3. The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils  
Yes, the client device includes only single primary coils.
4. Client device is inserted in or placed directly in contact with the transmitter  
Yes, Client device is placed directly in contact with the transmitter.
5. Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).  
Yes, It is mobile exposure conditions only.
6. The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.  
Yes, The EUT field strength levels are less than 50% of the MPE limit, refer to test TM1, TM2, TM3, TM4 list, and the coils can't be transmitted simultaneously.


*Test Mode: TM4 (worst case)*

<b>Electric Field Emissions</b>			
<b>Test Position</b>	<b>Measure Value (V/m)</b>	<b>Limit(V/m)</b>	<b>50% Limit (V/m)</b>
Point E	7.02	614	307
Point F	6.18	614	307
Point A	3.84	614	307
Point B	4.02	614	307
Point C	3.08	614	307
Point D	2.97	614	307
<b>Magnetic Field Emissions</b>			
<b>Test Position</b>	<b>Measure Value (A/m)</b>	<b>Limit(A/m)</b>	<b>50% Limit (A/m)</b>
Point E	0.46	1.63	0.815
Point F	0.34	1.63	0.815
Point A	0.26	1.63	0.815
Point B	0.24	1.63	0.815
Point C	0.31	1.63	0.815
Point D	0.19	1.63	0.815

**2.5 Measurement Uncertainty**

<b>Measurement uncertainty</b>		
<b>Parameter</b>	<b>Conditions</b>	<b>Uncertainty</b>
Electric Field Emissions	Radiated	$\pm 1.56$ (V/m)
Magnetic Field Emissions	Radiated	$\pm 0.08$ (A/m)

**2.6 Test Photos**



## **APPENDIX PHOTOGRAPHS**

---

**Please refer to “ANNEX”**

**\*\*\*\*\* END OF REPORT \*\*\*\*\***