

RF Exposure evaluation

FCC ID: 2AVFN-FT205L

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Antenna Information

FT205L can only use antennas certificated as follows provided by manufacturer;

Antenna No.	Model No. of antenna:	Type of antenna:	Gain of the antenna (Max.)	Frequency range:
LTE	/	External antenna	Band 2: 8.000dBi Band 4: 5.000dBi Band 5: 9.416dBi Band 12: 8.734dBi Band 13: 9.173dBi Band 14: 9.255dBi Band 66: 5.000dBi Band 71: 8.545dBi	
WCDMA	/	External antenna	FDD Band II: 8.000dBi FDD Band IV: 5.000dBi FDD Band V: 9.416dBi	

5. Standalone MPE Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna is refer to section 4, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
WCDMA B2	25.0	316.2278	8.0	6.3096	0.397	1.0000
WCDMA B4	25.0	316.2278	5.0	3.1623	0.199	1.0000
WCDMA B5	25.0	316.2278	9.416	8.7418	0.550	0.550
LTE Band 2	25.0	316.2278	8.0	6.3096	0.397	1.0000
LTE Band 4	25.0	316.2278	5.0	3.1623	0.199	1.0000
LTE Band 5	25.0	316.2278	9.416	8.7418	0.550	0.550

LTE Band 12	25.0	316.2278	8.734	7.4714	0.470	0.470
LTE Band 13	25.0	316.2278	9.173	8.2661	0.520	0.520
LTE Band 14	25.0	316.2278	9.255	8.4236	0.530	0.530
LTE Band 66	25.0	316.2278	5.0	3.1623	0.199	1.0000
LTE Band 71	25.0	316.2278	8.545	7.1532	0.450	0.450

Remark:

1. *Output power (Peak) including turn-up tolerance;*
2. *MPE evaluate distance is 20cm from user manual provide by manufacturer.*

6. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----THE END OF REPORT-----