


RF EXPOSURE EVALUATION REPORT

Application No.: SZCR2303000836AT
Applicant: Leax Arkivator Telecom USA Inc.
Address of Applicant: 833 E Arapaho Rd Suite 203, Richardson, Texas 75081 United States
Manufacturer: Leax Arkivator Telecom USA Inc.
Address of Manufacturer: 833 E Arapaho Rd Suite 203, Richardson, Texas 75081 United States
Factory: Leax Arkivator Telecom USA Inc.
Address of Factory: 833 E Arapaho Rd Suite 203, Richardson, Texas 75081 United States
Equipment Under Test (EUT):
EUT Name: TD LTE Base Station
Model No.: LBS8529
FCC ID: 2AVFNLBS8529
Standard(s) : FCC Rules 47 CFR §2.1091
KDB 447498 D04 interim General RF Exposure Guidance v01
Date of Receipt: 2023-03-28
Date of Evaluation: 2023-03-29 to 2023-05-04
Date of Issue: 2023-05-18

Evaluation Result:

Pass*

* In the configuration evaluated, the EUT complied with the standards specified above.



Keny Xu
EMC Laboratory Manager



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2023-05-18		Original

Authorized for issue by:			
		<i>Benson Wang</i>	
		Benson Wang/Project Engineer	
		<i>Eric Fu</i>	
		Eric Fu/Reviewer	



2 Contents

	Page
1 Cover Page	1
2 Contents	3
3 General Information.....	4
3.1 General Description of E.U.T.....	4
3.2 Details of E.U.T.....	4
3.3 Separation Distance	4
3.4 Test Location	5
3.5 Test Facility.....	5
3.6 Deviation from Standards.....	5
3.7 Abnormalities from Standard Conditions.....	5
4 FCC Radiofrequency radiation exposure limits	6
5 Measurement and Calculation	7
5.1 Maximum transmit power	7



3 General Information

3.1 General Description of E.U.T.

Product Type:	<input type="checkbox"/> Portable device
	<input type="checkbox"/> Mobile device
	<input checked="" type="checkbox"/> Fixed device

3.2 Details of E.U.T.

Power supply:	Adapter Model: HEP-480-54 INPUT: 100-240V 5.5A-2.2A 50/60Hz OUTPUT: DC54V 8.9A DC adapter: INPUT: DC48V OUTPUT: DC13V 4A
Cable:	GND Cable: 480cm unshielded Adapter Cable: 190cm unshielded DC Adapter cable: 87cm unshielded + 20cm unshielded
EUT Type:	CBSD
Category of EUT:	Category B
LTE Operation Frequency Band:	Band 48 (3550-3700MHz)
Test Mode:	E-TM1.1; E-TM3.2; E-TM3.1;
Modulation Type:	QPSK, 16QAM, 64QAM
Bandwidth:	5MHz; 10MHz; 15MHz; 20MHz
Transmission (TX) and Receiving (RX) Antenna Ports:	TX port: 2
MIMO supported	2*2 UL
Antenna Type:	N-Type connector for external high gain antenna
Antenna Gain:	16.5dBi

Note:

(1)The antenna gain value is provided by the customer. The test lab will not be responsible for wrong test result due to incorrect information about antenna gain values.

3.3 Separation Distance

Minimum test separation distance:	90cm
Remark: This minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

3.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• **VCCI (Member No. 1937)**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• **FCC –Designation Number: CN1336**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

3.6 Deviation from Standards

None

3.7 Abnormalities from Standard Conditions

None



4 FCC Radiofrequency radiation exposure limits

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30



5 Measurement and Calculation

5.1 Maximum transmit power

LTE:

The Power Data is based on the RF Test Report SZCR230300083602 and Tune up procedure.

Antenna Gain: 16.5dBi

MPE Calculation

According to the formula $S=P/4\pi R^2$, we can calculate S which is MPE.

Note:

- 1) P (mW)
- 2) R = distance to the center of radiation of antenna (in centimeter)
- 3) MPE limit = 1mW/cm²

Test Mode	Frequency Band (MHz)	Max Conducted power (dBm)	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit of Power Density S(mW/cm ²)	Result
LTE Band 48	3625	33	90	0.88	1.00	Pass

--End of the Report--

