Request for Modular/Limited Modular Approval

Date	e: Jan 6, 2020				
Sub	ject: Manufacturer's Declaration for	☑ - Modular Approval☐ - Limited Modular Approval	□ - Split Modula□ - Limited Spli		approval
Con	fidentiality Request for: 2AVFQ-MCI	<u>UDISP</u>			
		sic Requirements – FCC Part 15.212(
		Limited Module Description Must be pproval Requirement	Filled Out on the Fo		ment Met
	1. The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with FCC limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation. The physical crystal and tuning capacitors may be located external to the shielded radio elements. 15.212(a)(1)(i)			⊠ - YES	□ - NO(*)
	Details:The module has a metal shield.Ref	er to the external photo of EUT.			
	The modular transmitter must have buffered ensure that the module will comply with FC over-modulation. 15.212(a)(1)(ii)			⊠ - YES	□ - NO(*)
	Details: Data to the modulation circuit is buffered as described in the clause 4 of user manual provided with the application.				
	The modular transmitter must have its own pensure that the module will comply with FC supplying circuitry in the device into which	C requirements regardless of the design	of the power	⊠ - YES	□ - NO(*)
	Details: The module contains its own pow manual with this application.	er supply regulation integrated in the o	chip. Please refer to	the clause 4 o	f user
	The modular transmitter must comply with t 15.203, 15.204(b), 15.204(c), 15.212(a), and attached or employ a "unique" antenna cou antenna, including the cable). The "professi to modules but can apply to limited modular	1 2.929(b). The antenna must either be pupler (at all connections between the motional installation' provision of § 15.203	bermanently dule and the B is not applicable	⊠ - YES	□ - NO(*)
	Details: The module uses PCB antenna. provided with the application.	The antenna information can be found	l in user manual and	operation des	scription
	The modular transmitter must be tested in a inside another device during testing. This is complying with Part 15 emission limits regar Unless the transmitter module will be batter requirements found in Section 15.207. AC of the module must not contain ferrites, unless 15.27(a)). The length of these lines shall be least 10 centimeters to insure that there is no equipment. Any accessories, peripherals, or shall be unmodified or commercially available.	intended to demonstrate that the module ardless of the device into which it is every powered, it must comply with the AC or DC power lines and data input/output they will be marketed with the module length typical of actual use or, if that less coupling between the case of the modus support equipment connected to the module.	e is capable of ntually installed. line conducted lines connected to (see Section ngth is unknown, at alle and supporting dule during testing	⊠ - YES	□ - NO(*)
	Details: The module was tested stand-alor	ne as shown in test setup photographs j	filed with this applica	tion.	

	Modular Approval Requirement	Require	Requirement Met	
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748). If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for	⊠ - YES	□ - NO(*)	
	equipment authorization. 15.212(a)(1)(vi) Details: The FCC ID is printed on the label of the module.Refer to the label of EUT.			
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)	
	Details: The module comply with all specific rules.Refer to the datasheet.			
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)	
	Details: The module meets Portable exclusion levels as shown in the RF exposure information filed with this application.			

Limited Module Description – When Applicable

* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA). This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of the end product is always ensured should be provided here.

Details: <example - N/A>

Software Considerations – KDB 594280 / KDB 442812 (One of the following 2 items must be applied)				
	Requirement	Requirement Met		
1.	For <u>non-Software Defined Radio</u> transmitter modules where software is used to ensure compliance of the device, technical description must be provided about how such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280.	☐ - Provided in Separate Cover Letter	⊠ - N/A	
	Details: <example adjusted="" application.="" be="" by="" can="" device="" filed="" firmware="" letter="" modified="" not="" of="" or="" the="" this="" with="" –=""></example>	e end user as described in a se	parate cover	
2.	For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812.	☐ - Provided in Separate Cover Letter	⊠ - N/A	
	Details: <example -n="" a=""></example>			

Split Modular Requirements				
Requirement	Provided in Manual			
 For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained. 	☐ - Provided in Separate Cover Letter	⊠ - N/A		
Details: <example a="" n="" –=""></example>				

OEM Integration Manual Guidance – KDB 996369 D03 Section 2					
			scribing the Conditions, Limitation		ures
	ior un	ira-parties to use an	d/or integrate the module into a ho	ost device.	
Require	ement				
11000111				□ - No,	
			If No, and LMA applies, t		n ontionally choose to not
			make the following detail		
T. 41.: d1.	:		to be basic integration		
Is this module sale to third pa		🛛 - YES	information below mu		
sale to till pa	nties:		description. If the applic		
			this will require a separa		
			module is not for sal		
	T4		instructions are		ntial documents.
As of Mov. 1. 2			e manual – See KDB 996369 D03, ing information to be in the install		Madular transmittar
			ns for all these items indicating cl		
			cate "Not Applicable". Also if a n		
			user instructions may not need to		
			on, but this should include a cover	r letter as cited	above.
		DB 996369 D03, Sect			
	<u> </u>	ated to the transmitter			
2. Summarize the			DB 996369 D03, Section 2.3		
a.			eable loss, reduction of power for po	oint to point	
2 1 4 1 1 1	7 / 1	onal installation info	2.4		
3. Limited Modu a.		B 996369 D03, Section	on 2.4 tee uses to verify the host meets the	nacassary	
a.	limiting condition		tiee uses to verify the flost meets the	; necessary	N
b.	h When RF exposure evaluation is necessary state how control will be maintained such				
			ss II for new hosts, etc.		the left are provided in
4 Trace entenne designs VDR 006360 D03 Section 2.5				Guide (or UM) for Full	
a.			a, connectors, isolation requirement		Modular Approval (MA)
			procedures for ensuring compliance		or LMA.
			onfidential must be identified and in	formation	
5 DE		perational description. B 996369 D03, Section	- 2.6		- An LMA applies
a.			n 2.0 nat allow host manufacturers to use t	the module	and is approved ONLY
a.			first to the host manufacturer to de		for use by the grantee in
			om body) and second additional text		their own products, and
	provided to the en	nd user in the host pro	luct manuals.		not intended for sale to
	B 996369 D03, Se				3 rd parties as provided in
a.			ion and all applicable professional i		a separate cover letter. Therefore the
			na list shall also identify the antenna		information shown to the
(monopole, PIFA, dipole, etc – note that "omni-directional" is not considered a type) 7. Label and compliance information. KDB 996369 D03, Section 2.8					
a.	theory of operation				
"Contains FCC ID: " with their finished product					
8. Information on test modes and additional testing requirements. KDB 996369 D03, Section 2.9					
a. Test modes that should be taken into consideration by host integrators including					
clarifications necessary for stand-alone and simultaneous configurations.					
b. Provide information on how to configure test modes for evaluation					
9. Additional test	9. Additional testing, Part 15 Subpart B disclaimer. KDB 996369 D03, Section 2.10				
<u> </u>					
Cincomaly,	-				
Sincerely,		_{-			
Dyn	1	200	I a 71		
By:	/C!- /	numa /Ti41a1\	Joy Zhu		
	(Signat	cure/Title ¹)	(Print name)		

¹ - Must be signed by applicant contact given for applicant on the FCC site, or by the authorized agent if an appropriate authorized agent letter has been provided. Letters should be placed on appropriate letterhead.