

# Honeywell Integrated Technology (China) Co., Ltd SAR COMPLIANCE REPORT

**Report Type:** FCC SAR assessment report

Model: MCUDISP

**REPORT NUMBER:** 191200197SHA-002

**ISSUE DATE:** Jan 16, 2020

**DOCUMENT CONTROL NUMBER:** TTRFFCCSAR-01\_V1 © 2018 Intertek



Total Quality. Assured. TEST REPORT	Intertek Testing Services Shanghai Building No.86, 1198 Qinzhou Road (North) Caohejing Development Zone Shanghai 200233, China Telephone: 86 21 6127 8200 www.intertek.com Report no.: 191200197SHA-002
Applicant	<ul> <li>Honeywell Integrated Technology (China) Co., Ltd No.430, Libing Rd., Zhangjiang Hi-tech Park, Pudong New area, Shanghai, P.R.C</li> </ul>
Manufacturer	: Honeywell Integrated Technology (China) Co., Ltd No.430, Libing Rd., Zhangjiang Hi-tech Park, Pudong New area,Shanghai,P.R.C
FCC ID	: 2AVFQ-MCUDISP

#### **SUMMARY:**

The equipment complies with the requirements according to the following standard(s) or Specification:
KDB447498 D01 General RF Exposure Guidance v06
FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

PREPARED BY:

Teddy yin

Project Engineer Teddy Yin **REVIEWED BY:** 

Damiel 2hao

Reviewer Daniel Zhao

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.



# **Revision History**

Report No.	Version	Version Description							
191200197SHA-002	Rev. 01	Initial issue of report	Jan 16, 2020						

Intertek Total Quality. Assured. TEST REPORT

### **1 GENERAL INFORMATION**

### 1.1 Description of Equipment Under Test (EUT)

Product name:	BLE Module
Type/Model:	MCUDISP
Description of EUT:	The EUT is a BLE Module.
Rating:	DC 3.3V
Category of EUT:	Class B
EUT type:	🔀 Table top 🔲 Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	Dec 8, 2019
Date of test:	Dec 8~20, 2019

# **1.2 Technical Specification**

Frequency Range:	2402-2480MHz
Support Standards:	Bluetooth LE 4.2
Type of Modulation:	GFSK
Channel Number:	40
Data Rate:	1Mbps
Channel Separation:	2MHz
Antenna Information:	-0.6dBi, PCB antenna



### **1.3 Description of Test Facility**

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telephone.	00 21 012/0200
Telefax:	86 21 54262353

The test facility is recognized,	CNAS Accreditation Lab Registration No. CNAS L0139
certified, or accredited by these organizations:	FCC Accredited Lab Designation Number: CN1175
organizations.	IC Registration Lab CAB identifier.: CN0051
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

# Total Quality. Assured.

TEST REPORT

# 2 SAR Assessment

Test result: Pass

### 2.1 SAR Test Exclusion Limit

100 MHz – 6 GHz and  $\leq$  50 mm

$100 \text{ MHz} - 6 \text{ GHz} and \leq 50 \text{ mm}$											
MHz	5	10	15	20	25	mm					
150	39	77	116	155	194						
300	27	55	82	110	137						
450	22	45	67	89	112						
835	16	33	49	66	82						
900	16	32	47	63	79						
1500	12	24	37	49	61	SAR Test Exclusion					
1900	11	22	33	44	54	Threshold (mW)					
2450	10	19	29	38	48						
3600	8	16	24	32	40						
5200	7	13	20	26	33						
5400	6	13	19	26	32						
5800	6	12	19	25	31						
MHz	30	35	40	45	50	mm					
150	232	271	310	349	387						
300											
300	164	192	219	246	274						
450	164 134		219 179								
		192		246	274						
450	134	192 157	179	246 201	274 224						
450 835	134 98	192 157 115	179 131	246 201 148	274 224 164	SAR Test Fxclusion					
450 835 900	134 98 95	192 157 115 111	179 131 126	246 201 148 142	274 224 164 158	Exclusion					
450 835 900 1500	134 98 95 73	192 157 115 111 86	179 131 126 98	246 201 148 142 110	274 224 164 158 122						
450 835 900 1500 1900	134 98 95 73 65	192 157 115 111 86 76	179 131 126 98 87	246 201 148 142 110 98	274 224 164 158 122 109	Exclusion					
450 835 900 1500 1900 2450	134 98 95 73 65 57	192 157 115 111 86 76 67	179 131 126 98 87 77	246 201 148 142 110 98 86	274 224 164 158 122 109 96	Exclusion					
450 835 900 1500 1900 2450 3600	134 98 95 73 65 57 47	192           157           115           111           86           76           67           55	179 131 126 98 87 77 63	246 201 148 142 110 98 86 71	274 224 164 158 122 109 96 79	Exclusion					

# intertek Total Quality. Assured.

**TEST REPORT** 

### 100 MHz – 6 GHz and > 50 mm

MHz	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	mm
100	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567	
150	387	397	407	417	427	437	447	457	467	477	487	497	507	517	527	
300	274	294	314	334	354	374	394	414	434	454	474	494	514	534	554	
450	224	254	284	314	344	374	404	434	464	494	524	554	584	614	644	
835	164	220	275	331	387	442	498	554	609	665	721	776	832	888	943	
900	158	218	278	338	398	458	518	578	638	698	758	818	878	938	998	
1500	122	222	322	422	522	622	722	822	922	1022	1122	1222	1322	1422	1522	mW
1900	109	209	309	409	509	609	709	809	909	1009	1109	1209	1309	1409	1509	
2450	96	196	296	396	496	596	696	796	896	996	1096	1196	1296	1396	1496	
3600	79	179	279	379	479	579	679	779	879	979	1079	1179	1279	1379	1479	
5200	66	166	266	366	466	566	666	766	866	966	1066	1166	1266	1366	1466	
5400	65	165	265	365	465	565	665	765	865	965	1065	1165	1265	1365	1465	
5800	62	162	262	362	462	562	662	762	862	962	1062	1162	1262	1362	1462	

### < 100 MHz and < 200 mm

MHz	< 50	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	mm
100	237	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567	
50	308	617	625	634	643	651	660	669	677	686	695	703	712	721	729	738	
10	474	948	961	975	988	1001	1015	1028	1041	1055	1068	1081	1095	1108	1121	1135	
1	711	1422	1442	1462	1482	1502	1522	1542	1562	1582	1602	1622	1642	1662	1682	1702	тW
0.1	948	1896	1923	1949	1976	2003	2029	2056	2083	2109	2136	2163	2189	2216	2243	2269	
0.05	1019	2039	2067	2096	2125	2153	2182	2211	2239	2268	2297	2325	2354	2383	2411	2440	
0.01	1185	2370	2403	2437	2470	2503	2537	2570	2603	2637	2670	2703	2737	2770	2803	2837	



### 2.2 Assessment Results

The highest AV EIRP adjusted with tune-up tolerance is 81.0-95.3 = -14.3 dBm = 0.037 mW < <u>10mW (Test Exclusion Thresholds of 2450MHz at 5mm)</u>. Therefore, the SAR requirement is deemed to be satisfied without test.