


**Performance**

Product Name	Air Purifier
Rated Voltage	110V/120V~
Rated Frequency	50/60Hz
Product Usage	Removes odors, such as particulate matter, gas pollutants, and microorganisms in the air.
Method of Cleaning	1. Washable pre-filter 2. Washable pre-filter (HEPA-Activated carbon)
Rated Power	43W
Particulate CADR	200m <sup>3</sup> /h
Particulate CCM	P1
Energy Efficiency Index	Qualified PlusGrade
Noise	57dB(A)
Applicable area	14-26 m <sup>2</sup>
Product Size	326x172x511mm
Weight	5kg

**Product Structure**



**Features**

- Pre-filter**  
The primary filter in the air purifier. It is mainly used to filter dust particles above 5 microns, including large particles of dust, dander, pollen, feeding matter and other pollutants. Can be cleaned and reused multiple times.
- HEPA-activated carbon composite filter**  
The activated carbon filter is based on the standard of filter material for household purifier filtration. The resin polymer material is used as the carrier, and the high-adsorption capacity activated carbon is used as the adsorbent material. It has good adsorption and dust collecting effect; good formability, high strength and low adsorption capacity. It can adsorb and decompose harmful gas with good adsorption function.
- The HEPA filter filters 0.3 micron particles of bacteria, smoke and dust in the air, and the filtration efficiency is over 99%. Combined with multi-purpose filter, the HEPA filter filters out tiny particles larger than 20 nanometers in diameter, including bacterial mold, dust, allergens and some viruses, while also filtering out human flu virus, and Legionella bacteria are all larger than 20 nanometers, so this product can be filtered out.

**Filter/ dust sensor maintenance**

1. Pre-filter (about half a month)  
Use a vacuum cleaner to remove dust from the surface of the filter, or wash it with water and dry it thoroughly.
2. HEPA-activated carbon composite filter (about once every two months)  
When the 1500-hour filter replacement prompt appears, press and hold the reset button to clear. After the filter indicator light turns off, the timing function.

Place the filter in a ventilated place so that the harmful gases and bacteria on the filter can be removed. Do not touch the filter with your hands.

Do not touch the filter with your hands. Do not touch the filter with your hands. Do not touch the filter with your hands.

Do not touch the filter with your hands. Do not touch the filter with your hands. Do not touch the filter with your hands.

Do not touch the filter with your hands. Do not touch the filter with your hands. Do not touch the filter with your hands.

Do not touch the filter with your hands. Do not touch the filter with your hands. Do not touch the filter with your hands.

Do not touch the filter with your hands. Do not touch the filter with your hands. Do not touch the filter with your hands.

**How to use**

1. After plugging in the power, you will hear a sound "D", the machine enters standby mode, and the air quality indicator will show red color.
2. Boot
3. Timer  
1 2 3 4 h
4. Speed  
1 2 3 4


The machine's working time can be set by the timer button. When the machine enters standby mode, press the timer button to set the time. The time will be displayed on the LCD screen. Press the timer button again to turn off the corresponding indicator light for the selected time.

Press the speed button to change the speed of the motor. It is divided into first gear, second gear, third gear, etc. AUTO. When pressed, the motor increases one gear from the current gear position, and then returns to the AUTO mode. PAZ.5 corresponds to the corresponding table of air quality and gear position. The red indicator light is good air quality, second gear 101-200, yellow light = good air quality = second gear 201-300, red light = poor air quality = third gear.

When the child lock button is pressed, the button function of the machine enters the locked state, and all the buttons cannot be operated. Long Press the button for 3 seconds to unlock.


This unit is equipped with a timing change filter function, which will flash until the 1500-hour filter replacement prompt. Press and hold the reset button for 3 seconds to clear the filter indicator and reset the timing function.

When the power is on, touch the "Power" button on the operation, and the machine enters the standby state. (The spotlight is on when the machine enters the standby state.)



**Installation**

- Install filter**  
First, remove the filter from the plastic bag. 1. Remove the air inlet. 2. Remove the filter. 3. Remove the filter from the plastic bag.



Note: There are internal and external points, the one with the pull tab being out, be sure to install the front panel before use.