



Report No.: TW2107059-01E File Reference No.: 2021-07-28

Applicant: SHENZHEN JINGWEIXIAN TECHNOLOGY CO., LTD

Product: Screen Protector Film Cutter

Model No.: Mini 8, Mini 9, Mini 10, Mini 11, Mini 12, Mini 13, Mini 14,

Mini 15, Mini 16, Mini 17, Mini 18, Mini 19, Mini 20

Trademark: SKYCUT

Test Standards: FCC Part 15.247

Test Result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10, FCC Part 15.247 for the

evaluation of electromagnetic compatibility

Approved By

Jack Chung

Manager

Dated: July 28, 2021

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

Report No.: TW2107059-01E

Date: 2021-07-28



Page 2 of 98

Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

Industry Canada (IC) —Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

A2LA (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

Page 3 of 98

Report No.: TW2107059-01E

Date: 2021-07-28



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	5
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment	6
3.0	Technical Details	8
3.1	Summary of Test Results	8
3.2	Test Standards.	8
4.0	EUT Modification.	8
5.0	Power Line Conducted Emission Test.	9
5.1	Schematics of the Test.	9
5.2	Test Method and Test Procedure.	9
5.3	Configuration of the EUT	9
5.4	EUT Operating Condition.	10
5.5	Conducted Emission Limit.	10
5.6	Test Result.	10
6.0	Radiated Emission test	13
5.1	Test Method and Test Procedure.	13
6.2	Configuration of the EUT	14
5.3	EUT Operation Condition.	14
5.4	Radiated Emission Limit	14
7.0	6dB Bandwidth Measurement	24
8.0	Maximum Output Power	44
9.0	Power Spectral Density Measurement.	47
10.0	Out of Band Measurement	65
11.0	Antenna Requirement.	83
12.0	FCC ID Label.	84
13.0	Photo of Test Setup and EUT View	85

Report No.: TW2107059-01E

Date: 2021-07-28



Page 4 of 98

1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le

Village, Nanshan District, Shenzhen, China

Telephone: (755) 83448688 Fax: (755) 83442996

Site Listed with Federal Communications commission (FCC)

Registration Number:744189 For 3m Anechoic Chamber

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A

For 3m Anechoic Chamber

1.2 Applicant Details

Applicant: SHENZHEN JINGWEIXIAN TECHNOLOGY CO.,LTD

Address: Building C, XinHang Technology Park, No. 229 Qingshui Road, Longgang District,

Shenzhen, 518116, China

Telephone: 13823176591 Fax: 0755-84565855

1.3 Description of EUT

Product: Screen Protector Film Cutter

Manufacturer: SHENZHEN JINGWEIXIAN TECHNOLOGY CO.,LTD

Address: Building C, XinHang Technology Park, No. 229 Qingshui Road, Longgang

District, Shenzhen, 518116, China

Brand Name: SKYCUT
Model Number: Mini 8

Additional Model Number: Mini 9, Mini 10, Mini 11, Mini 12, Mini 13, Mini 14, Mini 15, Mini 16, Mini 17,

Mini 18, Mini 19, Mini 20

Hardware Version: V9.0810 Software Version: V21.0710

Type of Modulation IEEE 802.11b: DSSS (CCK, QPSK, DBPSK)

IEEE 802.11g/n (HT20, HT40): OFDM (64QAM, 16QAM, QPSK, BPSK)

Frequency range IEEE 802.11b/g/n (HT20): 2412-2462MHz; 802.11n HT40: 2422-2452MHz

Channel Spacing 5MHz for IEEE 802.11b/g/n HT20, HT40

Air Data Rate IEEE 802.11b: 11, 5.5, 2, 1 Mbps

IEEE 802.11g: 54, 48,36, 24, 18, 12, 9, 6 Mbps

IEEE 802.11n HT20/HT40: mcs0-mcs7

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2107059-01E

Date: 2021-07-28



Page 5 of 98

Frequency Selection By software

Channel Number IEEE 802.11b/g/n (HT20): 11 Channels; EEE 802.11n (HT40): 7 Channels;

Antenna: PCB antenna used. The gain of the antennas is 2.5dBi (get from the antenna

specification provided the applicant)

Input Voltage: DC24V, 2.75A

Power Supply: Model: GM60-240275-F; Input: 100-240V, 50/60Hz, 2.0A;

Output: DC24V, 2.75A, 66W

1.4 Submitted Sample: 4 Samples

1.5 Test Duration

2021-07-05 to 2021-07-28

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB

Radiated Emissions below 1GHz Uncertainty =4.7dB

Radiated Emissions above 1GHz Uncertainty =6.0dB

Conducted Power Uncertainty = 6.0dB

Occupied Channel Bandwidth Uncertainty = 5%

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

Report No.: TW2107059-01E Page 6 of 98

Date: 2021-07-28



2.0 Test Equipment						
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date	
ESPI Test Receiver	R&S	ESPI 3	100379	2021-06-18	2022-06-17	
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2021-06-18	2022-06-17	
Loop Antenna	EMCO	6507	00078608	2021-06-18	2024-06-17	
Spectrum	R&S	FSIQ26	100292	2021-06-18	2022-06-17	
Horn Antenna	A-INFO	LB-180400-KF	J211060660	2021-07-02	2024-07-01	
Horn Antenna	R&S	BBHA 9120D	9120D-631	2021-07-02	2024-07-01	
Power meter	Anritsu	ML2487A	6K00003613	2021-06-18	2022-06-17	
Power sensor	Anritsu	MA2491A	32263	2021-06-18	2022-06-17	
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2018-07-04	2021-07-03	
9*6*6 Anechoic			N/A	2021-07-02	2022-07-01	
EMI Test Receiver	RS	ESVB	826156/011	2021-06-18	2022-06-17	
EMI Test Receiver	RS	ESH3	860904/006	2021-06-18	2022-06-17	
Spectrum	HP/Agilent	ESA-L1500A	US37451154	2021-06-18	2022-06-17	
Spectrum	HP/Agilent	E4407B	MY50441392	2021-06-18	2022-06-17	
Spectrum	RS	FSP	1164.4391.38	2020-01-16	2021-01-15	
RF Cable	Zhengdi	ZT26-NJ-NJ-8 M/FA		2021-06-18	2022-06-17	
RF Cable	Zhengdi	7m		2021-06-18	2022-06-17	
RF Switch	EM	EMSW18	060391	2021-06-18	2022-06-17	
Pre-Amplifier	Schwarebeck	BBV9743	#218	2021-06-18	2022-06-17	
Pre-Amplifier	HP/Agilent	8449B	3008A00160	2021-06-18	2022-06-17	
LISN	SCHAFFNER	NNB42	00012	2021-01-06	2022-01-05	

2.2 Automation Test Software

For Conducted Emission Test

Name	Version
EZ-EMC	Ver.EMC-CON 3A1.1

For Radiated Emissions

Name	Version
EMI Test Software BL410-EV18.91	V18.905
EMI Test Software BL410-EV18.806 High Frequency	V18.06

The report refers only to the sample tested and does not apply to the bulk.

This report released in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Report No.: TW2107059-01E

Date: 2021-07-28



Page 7 of 98

3. DESCRIPTION OF TEST MODES

IEEE 802.11b, 802.11g, 802.11n (HT20) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode: 1Mbps data rate (worst case) was chosen for full testing. IEEE 802.11g mode: 6Mbps data rate (worst case) was chosen for full testing. IEEE 802.11n (HT20) mode: mcs0 (worst case) were chosen for full testing

IEEE 802.11n (HT40) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2422
Middle	2437
High	2452

IEEE 802.11n (HT40) mode: msc0 data rate (worst case) were chosen for full testing

Note: during the test, the duty cycle was set up to 100%.

Page 8 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



3.0 **Technical Details**

3.1 **Summary of test results**

The EUT has been tested ac	cording to the following speci	tications:	
Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.247(a)(2) Limit	Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System Limit: 6dB bandwidth>500kHz	PASS	Complies
FCC Part 15, Paragraph 15.247(b)	Maximum peak output power Limit: max. 30dBm	PASS	Complies
FCC Part 15, Paragraph 15.205 & 15.209	Transmitter Radiated Emission Limit: Table 15.209	PASS	Complies
FCC Part 15, Paragraph 15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Complies
FCC Part 15, Paragraph 15.247(d)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band limit: Table 15.209	PASS	Complies

3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

4.0 **EUT Modification**

No modification by SHENZHEN TIMEWAY TESTING LABORATORIES.

Page 9 of 98


Report No.: TW2107059-01E

Date: 2021-07-28



5.0 Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10-2013.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device	Manufacturer	Model	FCC ID
Screen Protector Film Cutter	SHENZHEN JINGWEIXIAN TECHNOLOGY CO., LTD	Mini 8, Mini 9, Mini 10, Mini 11, Mini 12, Mini 13, Mini 14, Mini 15, Mini 16, Mini 17, Mini 18, Mini 19, Mini 20	2AVGR-MINI8MINI9

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2107059-01E

Date: 2021-07-28



Page 10 of 98

C. Peripherals

Device	Manufacturer	Model	Rating

5.4 **EUT Operating Condition**

Operating condition is according to ANSI C63.10-2013.

- A Setup the EUT and simulators as shown on follow
- В Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207

Frequency	Limits (c	lB μ V)
(MHz)	Quasi-peak Level	Average Level
$0.15 \sim 0.50$	66.0~56.0*	56.0~46.0*
$0.50 \sim 5 00$	56.0	46.0
$5.00 \sim 30 \ 00$	60.0	50.

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Report No.: TW2107059-01E Page 11 of 98

Date: 2021-07-28



A: Conducted Emission on Live Terminal (150kHz to 30MHz)


EUT Operating Environment

Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

EUT set Condition: Keep WIFI Transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1659	35.99	9.77	45.76	65.16	-19.40	QP	Р
2	0.1659	25.04	9.77	34.81	55.16	-20.35	AVG	Р
3	0.6102	27.14	9.78	36.92	56.00	-19.08	QP	Р
4	0.6102	9.63	9.78	19.41	46.00	-26.59	AVG	Р
5	2.0181	20.43	9.80	30.23	56.00	-25.77	QP	Р
6	2.0181	13.38	9.80	23.18	46.00	-22.82	AVG	Р
7	9.5403	15.81	10.14	25.95	60.00	-34.05	QP	Р
8	9.5403	6.61	10.14	16.75	50.00	-33.25	AVG	Р
9	16.7007	20.76	10.48	31.24	60.00	-28.76	QP	Р
10	16.7007	16.29	10.48	26.77	50.00	-23.23	AVG	Р

Page 12 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)


EUT Operating Environment

Humidity: 65%RH Atmospheric Pressure: 101 kPa Temperature: 26°C

EUT set Condition: Keep WIFI Transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1812	36.30	9.76	46.06	64.43	-18.37	QP	Р
2	0.1812	15.27	9.76	25.03	54.43	-29.40	AVG	Р
3	0.2631	34.26	9.75	44.01	61.33	-17.32	QP	Р
4	0.2631	20.14	9.75	29.89	51.33	-21.44	AVG	Р
5	1.4565	19.62	9.79	29.41	56.00	-26.59	QP	Р
6	1.4565	11.21	9.79	21.00	46.00	-25.00	AVG	Р
7	3.8399	23.67	9.88	33.55	56.00	-22.45	QP	Р
8	3.8399	18.67	9.88	28.55	46.00	-17.45	AVG	Р
9	9.3414	25.37	10.13	35.50	60.00	-24.50	QP	Р
10	9.3414	18.26	10.13	28.39	50.00	-21.61	AVG	Р

Report No.: TW2107059-01E

Date: 2021-07-28




Page 13 of 98

6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. F For measurement above 1GHz, peak values with RBW=1MHz VBW=3MHz and PK detector. AV value with RBW=1MHz, VBW=3MHz and RMS detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup

For radiated emissions from 9kHz to 30MHz




Report No.: TW2107059-01E


Date: 2021-07-28



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



- 6.2 Configuration of The EUT

 Same as section 5.3 of this report
- 6.3 EUT Operating Condition

 Same as section 5.4 of this report.
- 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Page 15 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



Frequencies in restricted band are complied to limit on Paragraph 15.209

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. Worse case were recorded in the test report. 802.11b was the worst case.

Page 16 of 98

Report No.: TW2107059-01E

Date: 2021-07-28




Test result General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Transmitting

Results: Pass



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	55.941	33.55	-12.00	40.0	-6.45	Peak	357.00	100	Horizontal	Pass
2	138.128	34.54	-17.29	43.5	-8.96	Peak	300.00	100	Horizontal	Pass
3	291.835	41.77	-11.25	46.0	-4.23	Peak	302.00	100	Horizontal	Pass
4	415.236	42.00	-8.27	46.0	-4.00	Peak	359.00	100	Horizontal	Pass
5	791.987	40.52	-3.10	46.0	-5.48	Peak	307.00	100	Horizontal	Pass
6	970.907	36.99	-1.52	54.0	-17.01	Peak	300.00	100	Horizontal	Pass

Page 17 of 98

Report No.: TW2107059-01E

Date: 2021-07-28




Test result General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Vertical (30MHz----1000MHz)

EUT set Condition: Keep Transmitting

Results: Pass



No.	Frequency	Results	Factor	Limit	Over	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	Limit			(cm)		
					(dB)					
1	55.456	38.71	-11.89	40.0	-1.29	Peak	68.00	100	Vertical	Pass
1*	55.456	34.45	-11.89	40.0	-5.55	QP	68.00	100	Vertical	Pass
2	120.187	34.41	-15.39	43.5	-9.09	Peak	5.00	100	Vertical	Pass
3	144.189	38.91	-17.09	43.5	-4.59	Peak	5.00	100	Vertical	Pass
4	301.290	34.23	-11.00	46.0	-11.77	Peak	90.00	100	Vertical	Pass
5	500.090	39.21	-6.91	46.0	-6.79	Peak	11.00	100	Vertical	Pass
6	911.995	36.46	-1.80	46.0	-9.54	Peak	72.00	100	Vertical	Pass


Report No.: TW2107059-01E Page 18 of 98

Date: 2021-07-28



Please refer to the following test plots for details:

CH01 for 11b at 1Mbps: Horizontal




Ī	No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
		(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
ſ	2	4824.044	49.78	3.14	74.0	-24.22	Peak	308.00	100	Horizontal	Pass

Report No.: TW2107059-01E Page 19 of 98

Date: 2021-07-28



CH01 for 11b at 1Mbps: Vertical




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
2	4824.044	50.25	3.14	74.0	-23.75	Peak	323.00	100	Vertical	Pass

Report No.: TW2107059-01E Page 20 of 98

Date: 2021-07-28



CH06 for 11b at 1Mbps: Vertical




1	No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
		(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
2	2	4875.031	49.56	3.19	74.0	-24.44	Peak	351.00	100	Vertical	Pass

Report No.: TW2107059-01E Page 21 of 98

Date: 2021-07-28



CH06 for 11b at 1Mbps: Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
2	4875.031	50.12	3.19	74.0	-23.88	Peak	291.00	100	Horizontal	Pass

Report No.: TW2107059-01E Page 22 of 98

Date: 2021-07-28



CH11 for 11b at 1Mbps: Vertical




Ī	No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
		(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
	2	4921.770	50.61	3.27	74.0	-23.39	Peak	353.00	100	Vertical	Pass

Page 23 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



CH11 for 11g at 6Mbps: Horizontal



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
2	4921.770	49.85	3.27	74.0	-24.15	Peak	293.00	100	Horizontal	Pass

Note: 1. Result Level = Reading + Factor

2. Factor= AF + Cable Loss- Preamp

3. Margin = Result– Limit

4. For radiated Emissions from 18-25GHz, it is only the floor noise.

5. The peak value less than the AV limit, no necessary to take down the AV measurement result.


Report No.: TW2107059-01E Page 24 of 98

Date: 2021-07-28



7.0 6dB Bandwidth Measurement

7.1 Test Setup



7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500 kHz

7.3 Test Procedure

- 1. Set resolution bandwidth (RBW) = 100 kHz
- 2. Set the video bandwidth $(VBW) \ge 3 \times RBW$.
- 3. Detector = Peak.
- 4. Trace mode = \max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 Test Result

Page 25 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



6dB Occupied Bandwidth


EUT		Screen Pro	tector Film	Cutter	Mod	lel	Mi	ni 8
Mode		8	302.11b		Input Vol	tage	12	0V~
Temperat	ure	24	4 deg. C,		Humidity	,	56%	6 RH
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)			mum Limit MHz)	Pass/ Fail
1		2412	1	10	.04		0.5	Pass
6		2437	1	10	.04		0.5	Pass
11		2462	1	10	.04		0.5	Pass
1		2412	11	9.	92	0.5		Pass
6		2437	11	9.	86		0.5	Pass
11		2462	11	10	.64		0.5	Pass

Page 26 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



1. 802.11b at 1Mbps of CH01




27.JUL.2021 17:04:34 Date:

Page 27 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



2. 802.11b at 1Mbps of CH06




27.JUL.2021 17:15:49 Date:

Page 28 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



3. 802.11b at 1Mbps of CH11




27.JUL.2021 17:24:34 Date:

Page 29 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



4. 802.11b at 11Mbps of CH01




27.JUL.2021 17:07:37 Date:

Page 30 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



5. 802.11b at 11Mbps of CH06




27.JUL.2021 17:13:39 Date:

Page 31 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



6. 802.11b at 11Mbps of CH11



27.JUL.2021 17:39:20 Date:

Report No.: TW2107059-01E Page 32 of 98

Date: 2021-07-28



6dB Occupied Bandwidth

EUT		Screen Pro	tector Film	Cutter	Mod	lel	-	Mini 8
Mode		8	302.11g		Input Vol	tage		120V~
Temperat	ure	24	4 deg. C,		Humidity	,	5	6% RH
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)		andwidth Hz)		num Limit MHz)	Pass/ Fail
1		2412	6	16	5.41		0.5	Pass
6		2437	6	16	5.41	0.5		Pass
11		2462	6	16	5.41	0.5		Pass


Page 33 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



Test Plots:

1. 802.11g at 6Mbps of CH01




Date: 27.JUL.2021 17:09:26

Page 34 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



2. 802.11g at 6Mbps of CH06




Date: 27.JUL.2021 17:11:03

Page 35 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



3. 802.11g at 6Mbps of CH11



Date: 27.JUL.2021 17:42:25 Report No.: TW2107059-01E Page 36 of 98

Date: 2021-07-28



6dB Occupied Bandwidth

EUT		Screen Protector Film Cutter			Model		Mini 8	
Mode		802.11n HT20			Input Voltage		120V~	
Temperature		24 deg. C,			Humidity		56% RH	
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)		Minimum Limit (MHz)		Pass/ Fail
1	2412		mcs0	17.56		0.5		Pass
6		2437	mcs0	17.56		0.5		Pass
11		2462	mcs0	17.68		0.5		Pass


Report No.: TW2107059-01E Page 37 of 98

Date: 2021-07-28



Test Plots:

1. 802.11n at HT20 of CH01




Date: 27.JUL.2021 17:53:31

Page 38 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



2. 802.11n at HT20 of CH06




Date: 27.JUL.2021 17:50:03

Page 39 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



3. 802.11n at HT20 of CH11



Date: 27.JUL.2021 17:45:46 Report No.: TW2107059-01E Page 40 of 98

Date: 2021-07-28



6dB Occupied Bandwidth

EUT		Screen Pro	tector Film Cutter		Model		Mini 8	
Mode	Mode 802		.11n HT40		Input Voltage		120V~	
Temperat	ure	24	4 deg. C,		Humidity		56% RH	
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)		ndwidth Hz)		mum Limit MHz)	Pass/ Fail
3		2422	mcs0	36	.19		0.5	Pass
6		2437		36	.20		0.5	Pass
9		2452	mcs0	36	.03		0.5	Pass


Report No.: TW2107059-01E Page 41 of 98

Date: 2021-07-28



Test Plots:

1. 802.11n at HT40 of CH03




Date: 27.JUL.2021 17:59:24

Page 42 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



2. 802.11n at HT40 of CH06




18:00:50 Date: 27.JUL.2021

Page 43 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



3. 802.11n at HT40 of CH09



27.JUL.2021 18:02:45 Date:

Report No.: TW2107059-01E


Date: 2021-07-28



Page 44 of 98

8. Maximum Output Power

8.1 Test Setup



8.2 Limits of Maximum Output Power

The Maximum Output Power Measurement is 30dBm.

8.3 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the Peak power was measured

Report No.: TW2107059-01E Page 45 of 98

Date: 2021-07-28



8.4Test Results

EUT		Screen Protector Film Cutter		Model	Mini 8	
Mode			802.11b	Input Voltage	120V~	
Temperat	ure	24 deg. C,		Humidity	56% RH	
Channel	Frequency (MH	uency z)	Max. Powe	er Output (dBm)	Power Limit (dBm)	Pass/ Fail
1	2412			19.77	30	Pass
6	2437		2	20.18	30	Pass
11	2462			20.48	30	Pass

Note: 1. At finial test to get the worst-case emission at 1Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Power Output = Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT		Screen Protector Film Cutter		Model	Min	i 8
Mode			802.11g	Input Voltage	120V~	
Temperat	ure	24 deg. C,		Humidity	56% RH	
Channel	Frequency (MH	uency z)	Max. Power	r Output (dBm)	Power Limit (dBm)	Pass/ Fail
1	2412	,	2	0.14	30	Pass
6	2437	,	2	0.09	30	Pass
11	2462	r	2	0.43	30	Pass

Note: 1. At finial test to get the worst-case emission at 6Mbps for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Power Output = Power Reading + Cable loss + Attenuator

3. The worse case was recorded

The report refers only to the sample tested and does not apply to the bulk.

This report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 46 of 98

Report No.: TW2107059-01E

Date: 2021-07-28



EUT		Screen Protector Film Cutter		Model	Mini 8	
Mode			802.11n (HT20)	Input Voltage	120V~	
Temperat	ure	24 deg. C,		Humidity	56% RH	
Channel	Frequ (MH	uency z)	Max. Power Output (dBm)		Power Limit (dBm)	Pass/ Fail
1	2412		2	20.04	30	Pass
6	2437			19.12	30	Pass
11	2462			19.95	30	Pass

Note: 1. At finial test to get the worst-case emission at mcs0 of 11n HT20 for CH01, CH06 and CH11

2. The result basic equation calculation as follow:

Power Output = Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT		Screen Protector Film Cutter		Model	Min	i 8
Mode			802.11n (HT40)	Input Voltage	120V~	
Temperat	ure	24 deg. C,		Humidity	56% RH	
Channel	Frequency (MH	uency z)	Max. Powe	er Output (dBm)	Power Limit (dBm)	Pass/ Fail
3	2422			19.02	30	Pass
6	2437			19.24	30	Pass
9	2452			18.77	30	Pass

Note: 1. At finial test to get the worst-case emission at msc0 of 11n HT40 for CH03, CH06 and CH09

2. The result basic equation calculation as follow:

Power Output = Power Reading + Cable loss + Attenuator

3. The worse case was recorded

Report No.: TW2107059-01E


Date: 2021-07-28



Page 47 of 98

9. Power Spectral Density Measurement

9.1 Test Setup



9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm/3kHz.

9.3 Test Procedure

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW = 10 kHz.
- 3. Set the VBW \geq 30 kHz.
- 4. Set the span to 1.5 times the DTS channel bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11. The resulting peak PSD level must be $\leq 8 \text{ dBm/3kHz}$.

Report No.: TW2107059-01E Page 48 of 98

Date: 2021-07-28



9.4Test Result

EUT		Screen Protector File	m Cutter Model		Mini 8	
Mode		802.11b 11Mb	Mbps Input Voltage		120V~	
Temperat	ure	24 deg. C,		Humidity	56% RH	
Channel	F	requency (MHz)		r Spectral Density (dBm/10kHz)	Limit (dBm/3kHz)	Pass/ Fail
1		2412		-6.00	8	Pass
6		2437		-4.40	8	Pass
11		2462	-4.76		8	Pass

EUT		Screen Protector File	m Cutter Model		Mini 8	
Mode		802.11b 1Mb _l	ps	Input Voltage	120V~	
Temperat	ure	24 deg. C,		Humidity	56% RH	
Channel	F	requency (MHz)		r Spectral Density (dBm/10kHz)	Limit (dBm/3kHz)	Pass/ Fail
1		2412		-3.24	8	Pass
6		2437		-4.11	8	Pass
11		2462		-7.55	8	Pass

EUT		Screen Protector Film Cutter		Model	Mini 8	
Mode		802.11g 6Mb _l	os Input Voltage		120V~	
Temperat	ure	24 deg. C,		Humidity	56% RH	
Channel	F	requency (MHz)		r Spectral Density dBm/10kHz)	Limit (dBm/3kHz)	Pass/ Fail
1		2412		-7.74	8	Pass
6		2437		-7.45	8	Pass
11		2462		-6.55	8	Pass

Report No.: TW2107059-01E Page 49 of 98

Date: 2021-07-28



EUT		Screen Protector Film Cutter		Model	Mini 8	
Mode		802.11n HT20 mcs0		Input Voltage	120V~	
Temperat	ure	24 deg. C	,	Humidity	56% RH	
Channel	Fr	requency (MHz)		Spectral Density lBm/10kHz)	Limit (dBm/3kHz)	Pass/ Fail
1		2412	-8.00		8	Pass
6		2437		-7.05	8	Pass
11		2462		-7.84	8	Pass

EUT		Screen Protector Film Cutter		Model	Mini 8	
Mode		802.11n HT40	mcs0	Input Voltage	120V~	
Temperat	ure	24 deg. C	,	Humidity	56% RH	
Channel	Fr	requency (MHz)		Spectral Density lBm/10kHz)	Limit (dBm/3kHz)	Pass/ Fail
3		2422		-11.63	8	Pass
6	2437			-11.94	8	Pass
9	2452		-12.23		8	Pass


Page 50 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



9.5 Photo of Power Spectral Density Measurement

1.802.11b at 11Mbps of CH01




Date: 27.JUL.2021 18:47:05

Page 51 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



2. 802.11b at 11Mbps at CH06




27.JUL.2021 18:48:44 Date:

Page 52 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



3. 802.11b at 11Mbps of CH11




27.JUL.2021 18:49:30 Date:

Page 53 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



4. 802.11b at 1Mbps of CH1



27.JUL.2021 19:01:22 Date:


Page 54 of 98

Report No.: TW2107059-01E

Date: 2021-07-28



5. 802.11b at 1Mbps of CH6



27.JUL.2021 19:00:53 Date:


Page 55 of 98

Report No.: TW2107059-01E

Date: 2021-07-28



6. 802.11b at 1Mbps of CH11




28.JUL.2021 10:48:00 Date:

Page 56 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



7. 802.11g at 6Mbps of CH1



27.JUL.2021 18:59:15 Date:


Page 57 of 98

Report No.: TW2107059-01E

Date: 2021-07-28



8. 802.11g at 6Mbps of CH6



27.JUL.2021 18:56:40 Date:


Page 58 of 98

Report No.: TW2107059-01E

Date: 2021-07-28



9. 802.11g at 6Mbps of CH11



27.JUL.2021 18:54:49 Date:


Page 59 of 98

Report No.: TW2107059-01E

Date: 2021-07-28



10. 802.11n at HT20 of CH01




27.JUL.2021 19:13:32 Date:

Page 60 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



11. 802.11n at HT20 of CH06




27.JUL.2021 19:11:49 Date:

Page 61 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



12. 802.11n at HT20 of CH11




27.JUL.2021 19:06:00 Date:

Page 62 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



13. 802.11n at HT40 of CH01




27.JUL.2021 19:15:35 Date:

Page 63 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



14. 802.11n at HT40 of CH04




27.JUL.2021 19:18:02 Date:

Page 64 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



15. 802.11n at HT40 of CH07




Date: 27.JUL.2021 19:20:25 Report No.: TW2107059-01E

Date: 2021-07-28



Page 65 of 98

10 Out of Band Measurement 10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

10.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

10.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test. (Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector)

For bandage test, the spectrum set as follows: RBW=100, VBW=300 kHz. A conducted measurement used

10.4 Test Result

Please see next pages

Note: For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

Page 66 of 98 Report No.: TW2107059-01E

Date: 2021-07-28




For 802.11b mode

CH01 at 1Mbps

10.4 Band-edge Measurement

EUT	Screen Protector Film Cutter	Model	Mini 8
Mode	Keeping Transmitting	Input Voltage	120V~
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



27.JUL.2021 19:23:43 Date:

Page 67 of 98 Report No.: TW2107059-01E

Date: 2021-07-28




CH11 at 1Mbps

10.4 Band-edge Measurement

EUT	Screen Protector Film Cutter	Model	Mini 8
Mode	Keeping Transmitting	Input Voltage	120V~
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



27.JUL.2021 19:29:44 Date:

Page 68 of 98 Report No.: TW2107059-01E

Date: 2021-07-28




For 802.11b mode

CH01 at 11Mbps

10.4 Band-edge Measurement

EUT	Screen Protector Film Cutter	Model	Mini 8
Mode	Keeping Transmitting	Input Voltage	120V~
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



27.JUL.2021 19:25:46 Date:

Page 69 of 98

Report No.: TW2107059-01E

Date: 2021-07-28




CH11 at 11Mbps

10.4 Band-edge Measurement

EUT	Screen Protector Film Cutter	Model	Mini 8
Mode	Keeping Transmitting	Input Voltage	120V~
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



27.JUL.2021 19:28:39 Date:

Page 70 of 98 Report No.: TW2107059-01E

Date: 2021-07-28




For 802.11g mode

CH01 at 6Mbps

10.4 Band-edge Measurement

EUT	Screen Protector Film Cutter	Model	Mini 8
Mode	Keeping Transmitting	Input Voltage	120V~
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



27.JUL.2021 Date: 19:24:24

Page 71 of 98 Report No.: TW2107059-01E

Date: 2021-07-28




CH11 at 6Mbps

Band-edge Measurement 10.4

EUT	Screen Protector Film Cutter	Model	Mini 8
Mode	Keeping Transmitting	Input Voltage	120V~
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



27.JUL.2021 19:29:15 Date:

Page 72 of 98 Report No.: TW2107059-01E

Date: 2021-07-28




For 802.11n (HT20) mode

CH01 at mcs0

10.4 Band-edge Measurement

EUT	Screen Protector Film Cutter	Model	Mini 8
Mode	Keeping Transmitting	Input Voltage	120V~
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



27.JUL.2021 19:22:24 Date:

Report No.: TW2107059-01E

Date: 2021-07-28




Page 73 of 98

CH11 at mcs0

10.4 Band-edge Measurement

EUT	Screen Protector Film Cutter	Model	Mini 8
Mode	Keeping Transmitting	Input Voltage	120V~
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



27.JUL.2021 Date: 19:30:52

Page 74 of 98 Report No.: TW2107059-01E

Date: 2021-07-28




For 802.11n (HT40) mode

CH03 at msc0

Band-edge and Restricted band Measurement 10.4

EUT	Screen Protector Film Cutter	Model	Mini 8
Mode	Keeping Transmitting	Input Voltage	120V~
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



27.JUL.2021 19:21:38 Date:

Report No.: TW2107059-01E

Date: 2021-07-28




Page 75 of 98

CH09 at msc0

10.4 Band-edge and Restricted band Measurement

EUT	Screen Protector Film Cutter	Model	Mini 8
Mode	Keeping Transmitting	Input Voltage 120V~	
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



27.JUL.2021 19:20:55 Date:

Report No.: TW2107059-01E Page 76 of 98

Date: 2021-07-28



10.5 Restricted band Measurement

EUT	Screen Prot	ector Film Cutter	Model	Mini 8					
Mode	Keeping	Transmitting	Input Voltage	120V~					
Temperature	24	deg. C,	Humidity	56% RH					
Test Result:		Pass	Detector	PK					
		802.11b mode, Low C	Channel, Horizonta	1					
2390	PK (dBμV/m)	48.51	T ::4	$74(dB\mu V/m)$					
	AV (dBμV/m)		Limit	54(dBμV/m)					
	802.11b mode, Vertical								
2390	PK (dBμV/m)	45.58	Limit	74(dBμV/m)					
	AV (dBμV/m)		Limit	54(dBμV/m)					

EUT	Screen Prot	ector Film Cutter	Model	Mini 8				
Mode	Keeping	Transmitting	Input Voltage	120V~				
Temperature	24	deg. C,	Humidity	56% RH				
Test Result:		Pass	Detector	PK				
802.11b mode, High Channel, Horizontal								
2483.5	PK (dBµV/m)	46.85	T,	$74(dB\mu V/m)$				
	AV (dBμV/m)		Limit	54(dBμV/m)				
802.11b mode, High Channel, Vertical								
2483.5	PK (dBµV/m)	44.23	т,	74(dBμV/m)				
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$				

Report No.: TW2107059-01E Page 77 of 98

Date: 2021-07-28



10.5 Restricted band Measurement

EUT	Screen Prot	ector Film Cutter	Model	Mini 8						
Mode	Keeping	Transmitting	Input Voltage	120V~						
Temperature	24	deg. C,	Humidity	56% RH						
Test Result:		Pass	Detector	PK						
		802.11g mode, Low C	Channel, Horizonta	1						
2390	PK (dBµV/m)	49.67	T : :/	$74(dB\mu V/m)$						
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$						
	802.11g mode, Vertical									
2390	PK (dBμV/m)	46.52	Limit	$74(dB\mu V/m)$						
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$						

10.5 Restricted	band Measuremen									
EUT	Screen Prot	ector Film Cutter	Model	Mini 8						
Mode	Keeping	g Transmitting	Input Voltage	120V~						
Temperature	24	deg. C,	Humidity	56% RH						
Test Result:		Pass	Detector	PK						
		802.11g mode, High	Channel, Horizont	al						
2483.5	PK (dBμV/m)	48.82	T ' '4	$74(dB\mu V/m)$						
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$						
	802.11g mode, High Channel, Vertical									
2483.5	PK (dBμV/m)	47.09	T ::4	$74(dB\mu V/m)$						
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$						

Report No.: TW2107059-01E Page 78 of 98

Date: 2021-07-28



10.5 Restricted band Measurement

EUT	Screen Prot	ector Film Cutter	Model	Mini 8					
Mode	Keeping	Transmitting	Input Voltage	120V~					
Temperature	24	deg. C,	Humidity	56% RH					
Test Result:		Pass	Detector	PK					
	802.11n HT20 mode, Low Channel, Horizontal								
2390	PK (dBµV/m)	50.13	T ::4	$74(dB\mu V/m)$					
	AV (dBμV/m)		Limit	54(dBµV/m)					
	802.11n HT20 mode, Low Channel, Vertical								
2390	PK (dBμV/m)	47.96	Limit	74(dBµV/m)					
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$					


EUT	Screen Prot	ector Film Cutter	Model	Mini 8					
Mode	Keeping	Transmitting	Input Voltage	120V~					
Temperature	24	deg. C,	Humidity	56% RH					
Test Result:		Pass	Detector	PK					
802.11n HT20 mode, High Channel, Horizontal									
2483.5	PK (dBµV/m)	49.70	T :!4	$74(dB\mu V/m)$					
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$					
	802.11n HT20 mode, High Channel, Vertical								
2483.5	PK (dBμV/m)	48.12	Limit	74(dBμV/m)					
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$					

Report No.: TW2107059-01E Page 79 of 98

Date: 2021-07-28



EUT	Screen Prot	ector Film Cutter	Model	Mini 8					
Mode	Keeping	Transmitting	Input Voltage	120V~					
Temperature	24	deg. C,	Humidity	56% RH					
Test Result:		Pass	Detector	PK					
	802.11n HT40 mode, Low Channel, Horizontal								
2390	PK (dBμV/m)	52.73	Limit	$74(dB\mu V/m)$					
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$					
	802.11n HT40 mode, Low Channel, Vertical								
2390	PK (dBμV/m)	49.86	I imit	74(dBμV/m)					
	AV (dBμV/m)		Limit	54(dBμV/m)					




No.	Frequency	Results	Factor	Limit	Over	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	Limit (dB)			(cm)		
3	2390.265	52.73	-3.52	74.0	-21.27	Peak	304.00	100	Horizontal	Pass

Page 80 of 98

Report No.: TW2107059-01E






No.	Frequency	Results	Factor	Limit	Over	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	Limit (dB)			(cm)		
3	2390.515	49.86	-3.52	74.0	-24.14	Peak	345.00	100	Vertical	Pass

Page 81 of 98 Report No.: TW2107059-01E

Date: 2021-07-28



EUT	Screen Pro	tector Film Cutter	Model	Mini 8					
Mode	Keeping	g Transmitting	Input Voltage	120V~					
Temperature	24	l deg. C,	Humidity	56% RH					
Test Result:		Pass	Detector	PK					
802.11n HT40 mode, High Channel, Horizontal									
2483.5	PK (dBµV/m)	50.38	T ' '4	$74(dB\mu V/m)$					
	AV (dBμV/m)		Limit	54(dBµV/m)					
802.11n HT40 mode, High Channel, Vertical									
2483.5	PK (dBμV/m)	48.72	Limit	74(dBμV/m)					
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$					




ſ	No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height (cm)	ANT	Verdict
		(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)					
	2	2483.467	50.38	-3.57	74.0	-23.62	Peak	291.00	100	Horizontal	Pass

Page 82 of 98

Report No.: TW2107059-01E





No.	Frequency	Results	Factor	Limit	Over	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	Limit (dB)			(cm)		
2	2483.459	48.72	-3.57	74.0	-25.28	Peak	352.00	100	Vertical	Pass

Report No.: TW2107059-01E

Date: 2021-07-28



Page 83 of 98

11.0 Antenna Requirement

11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2 Antenna Connected construction

PCB antenna used. The gain of 2.5dBi.

Report No.: TW2107059-01E Page 84 of 98

Date: 2021-07-28



12.0 FCC ID Label

FCC ID: 2AVGR-MINI8MINI9

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Page 85 of 98


Report No.: TW2107059-01E

Date: 2021-07-28



13.0 **Photo of testing**

Conducted Emission Test Setup:




Page 86 of 98

Report No.: TW2107059-01E

Date: 2021-07-28



Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2107059-01E

Date: 2021-07-28



Photographs - EUT

Outside View





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Page 88 of 98

Report No.: TW2107059-01E

Date: 2021-07-28



Outside View





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Page 89 of 98

Report No.: TW2107059-01E

Date: 2021-07-28



Outside View



The report refers only to the sample tested and does not apply to the bulk.

This report released in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to

Report No.: TW2107059-01E Page 90 of 98



Outside View




Page 91 of 98

Report No.: TW2107059-01E

Date: 2021-07-28







The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 92 of 98

Report No.: TW2107059-01E



Inside view







Page 93 of 98

Report No.: TW2107059-01E



Inside view





Page 94 of 98

Report No.: TW2107059-01E

Date: 2021-07-28



Inside view







The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2107059-01E Page 95 of 98

Date: 2021-07-28



Inside view




Page 96 of 98

Report No.: TW2107059-01E



Inside view






Page 97 of 98

Report No.: TW2107059-01E



Inside view





Page 98 of 98 Report No.: TW2107059-01E



Inside view



End of the report