


3911 盛和工厂控制号5015752, 柬埔寨工厂控制号5018316

产品标签: 110*80mm

外箱标签: 120*60mm 字高: 2.4mm

字高
2.4mm



COMMERCIAL HORTICULTURE FIXTURE

READ MANUAL BEFORE INSTALLATION
KINDLEGROWLIGHTS.COM

CONFORMS TO UL STD. 1598
CERT. TO CSA STD. CSA C 22.2 #250.0
CONFORMS TO ANSI/CAN/UL STD. 8800
CAN ICES-005-(B)/NMB-005-(B)
FCC ID : 2AVIPK-X2-V2

FC
ETL us
Intertek
5015752

MODEL..... K-X2-V2
WATTAGE..... 780 W
VOLTAGE..... 120-277 Vac
AMPERAGE..... 6.66 A
FREQUENCY..... 50/60 Hz

SUITABLE FOR WET LOCATIONS
CONVIENT AUX EMPLACEMENTS MOUILLÉS
SUITABLE FOR OPERATION IN AMBIENT NOT EXCEEDING 45°C
PEUT ÊTRE UTILISÉ À UNE TEMPÉRATURE AMBIANTE N'EXCÉDANT PAS 45°C
CAUTION – RISK OF FIRE
ATTENTION – RISQUE D'INCENDIE
Not Suitable for Intracanopy Applications
Non applicable aux applications intracavitaires

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) this device must accept any interference received, including interference that may cause undesired operation.

CAUTION: Possibly hazardous optical radiation emitted from this product. Do not stare at operation lamp. May be harmful to the eyes.


CONSULT A QUALIFIED ELECTRICIAN TO ENSURE CORRECT BRANCH CIRCUIT CONDUCTOR

CONSULTER UN ÉLECTRICIEN QUALIFIÉ POUR VOUS ASSURER QUE LES CONDUCTEURS DE LA DÉRIVATION SONT ADÉQUATS

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED

CE PRODUIT DOIT ÊTRE INSTALLÉ SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAÎT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHÉRENTS

字高
2.4mm



COMMERCIAL HORTICULTURE FIXTURE

READ MANUAL BEFORE INSTALLATION
KINDLEGROWLIGHTS.COM

CONFORMS TO UL STD. 1598
CERT. TO CSA STD. CSA C 22.2 #250.0
CONFORMS TO ANSI/CAN/UL STD. 8800
CAN ICES-005-(B)/NMB-005-(B)
FCC ID : 2AVIPK-X2-V2

FC
ETL us
Intertek
5018316

MODEL..... K-X2-V2
WATTAGE..... 780 W
VOLTAGE..... 120-277 Vac
AMPERAGE..... 6.66 A
FREQUENCY..... 50/60 Hz

SUITABLE FOR WET LOCATIONS
CONVIENT AUX EMPLACEMENTS MOUILLÉS
SUITABLE FOR OPERATION IN AMBIENT NOT EXCEEDING 45°C
PEUT ÊTRE UTILISÉ À UNE TEMPÉRATURE AMBIANTE N'EXCÉDANT PAS 45°C
CAUTION – RISK OF FIRE
ATTENTION – RISQUE D'INCENDIE
Not Suitable for Intracanopy Applications
Non applicable aux applications intracavitaires

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) this device must accept any interference received, including interference that may cause undesired operation.

CAUTION: Possibly hazardous optical radiation emitted from this product. Do not stare at operation lamp. May be harmful to the eyes.