



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.249 TEST REPORT

For

DewertOkin Technology Group Co., Ltd.

Room 247, Floor 6, Jiaxing Photovoltaic Science and Innovation Park, 1288 Kanghe Road, Xiuzhou
District, Jiaxing City, Zhejiang Province, China

FCC ID: 2AVJ8-RF42

Report Type: Original Report	Product Type: REMOTE CONTROL
Test Engineer:	Chao Gao <i>Chao Gao</i>
Report Number:	<u>RSHA201014001-00A</u>
Report Date:	<u>2020-10-29</u>
Reviewed By:	Oscar Ye EMC Manager <i>Oscar Ye</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....3

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....3

 OBJECTIVE3

 RELATED SUBMITTAL(S)/GRANT(S).....3

 TEST METHODOLOGY3

 MEASUREMENT UNCERTAINTY4

 TEST FACILITY4

SYSTEM TEST CONFIGURATION.....5

 JUSTIFICATION5

 EUT EXERCISE SOFTWARE5

 SUPPORT EQUIPMENT LIST AND DETAILS5

 EXTERNAL I/O CABLE.....5

 BLOCK DIAGRAM OF TEST SETUP6

SUMMARY OF TEST RESULTS8

TEST EQUIPMENT LIST9

FCC§15.203 - ANTENNA REQUIREMENT.....10

 APPLICABLE STANDARD10

 ANTENNA CONNECTOR CONSTRUCTION10

FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION.....11

 APPLICABLE STANDARD11

 EUT SETUP11

 TEST EQUIPMENT SETUP12

 TEST PROCEDURE12

 CORRECTED AMPLITUDE & MARGIN CALCULATION13

 TEST RESULTS SUMMARY13

 TEST DATA13

FCC §15.215(C) – 20 DB BANDWIDTH TESTING.....20

 APPLICABLE STANDARD20

 TEST PROCEDURE20

 TEST DATA20

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	DewertOkin Technology Group Co., Ltd.
Tested Model:	RF42
Product Type:	REMOTE CONTROL
Power Supply:	DC 4.5V from batteries
RF Function:	2.4G SRD
Operating Band/Frequency:	2403-2480 MHz
Channel Number:	78
Channel Separation:	1 MHz
Antenna Type:	PCB antenna
*Maximum Antenna Gain:	0.0 dBi

Note: The Maximum Antenna Gain was declared by the manufacturer.

All measurement and test data in this report was gathered from production sample serial number: 20201014001. (Assigned by BACL, Kunshan). The EUT was received on 2020-10-14.

Objective

This type approval report is prepared on behalf of *DewertOkin Technology Group Co., Ltd.* in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.249 DXX Grant with FCC ID: 2AVJ8-CB2220.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Justification

Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2403	40	2442
2	2404
...
38	2440	77	2479
39	2441	78	2480

EUT was tested with Channel 1, 40 and 78.

All buttons triggered the same RF parameters (Contain bandwidth, power level, duty cycle).

EUT Exercise Software

No software was used during the test.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/


External I/O Cable

Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup


For Radiated Emissions(Below 1GHz):

Turntable
2m Diameter



For Radiated Emissions(Above 1GHz):

Turntable
2m Diameter



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Not Applicable (See Note)
15.205, §15.209, §15.249	Radiated Emissions& Out of Band Emission	Compliant
§15.215 (c)	20 dB Bandwidth	Compliant

Note: The EUT was powered by batteries.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2019-12-14	2020-12-13
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2017-12-26	2020-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2020-08-14	2021-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2020-08-15	2021-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-04-01	2021-03-31
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2020-07-15	2023-07-14
ETS-LINDGREN	Horn Antenna	3116	2516	2020-01-17	2023-01-16
MICRO-TRONICS	Notch Filter	BRM50702	G024	2020-08-05	2021-08-04
A.H.Systems, inc	Amplifier	PAM-0118P	512	2020-02-20	2021-02-19
SELECTOR	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-12-12	2020-12-11
MICRO-COAX	Coaxial Cable	Cable-11	011	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2020-08-15	2021-08-14
RF Conducted Test					
Rohde & Schwarz	EMI Test Receiver	ESIB26	100146	2019-12-14	2020-12-13
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
DewertOkin	RF Cable	DewertOkin C01	C01	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Antenna Connector Construction

The EUT has a PCB antenna for SRD, which was permanently attached to the EUT, antenna gain is 0.0 dBi, fulfill the requirement of this section, please refer to the EUT photos.

Result: Compliant.

FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION

Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:


Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24GHz-24.25GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.


(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

Test Equipment Setup

The system was investigated from 30 MHz to 25GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V/m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V/m)}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 &15.205 & 15.249.

Test Data

Environmental Conditions

Temperature:	21.2 °C
Relative Humidity:	51 %
ATM Pressure:	101.6 kPa


The testing was performed by Chao Gao on 2020-10-22.

Test Mode: Transmitting

Spurious Emission Test:

30MHz-1GHz:

*Pre-scan with low, middle and high channels of operation in the X, Y and Z axes of orientation, the worst case **low** channel of operation in **Y-axis of orientation** was recorded.*



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
30.035178	21.59	200	H	321.0	-4.6	40.00	18.41
71.963050	8.37	200	H	247.0	-17.2	40.00	31.63
128.909300	13.43	200	V	225.0	-11.4	43.50	30.07
200.075850	16.99	100	V	337.0	-11.5	43.50	26.51
479.551850	17.27	200	V	188.0	-6.5	46.00	28.73
902.843800	24.12	200	V	231.0	0.2	46.00	21.88

1GHz-18GHz


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Y-axis of orientation** was recorded.)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)
 Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)

Low Channel: 2403MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1334.900000	---	22.40	200.0	V	68.0	-17.3	54.00	31.60
1334.900000	31.48	---	200.0	V	68.0	-17.3	74.00	42.52
3648.600000	---	29.70	150.0	V	4.0	-8.3	54.00	24.30
3648.600000	38.17	---	150.0	V	4.0	-8.3	74.00	35.83
4806.000000	40.92	---	200.0	H	26.0	-5.6	74.00	33.08
4806.000000	---	31.94	200.0	H	26.0	-5.6	54.00	22.06
7209.000000	---	34.31	150.0	H	147.0	0.3	54.00	19.69
7209.000000	45.24	---	150.0	H	147.0	0.3	74.00	28.76
11602.900000	---	36.57	150.0	H	198.0	3.0	54.00	17.43
11602.900000	46.50	---	150.0	H	198.0	3.0	74.00	27.50
17807.900000	---	44.78	150.0	H	127.0	8.8	54.00	9.22
17807.900000	53.93	---	150.0	H	127.0	8.8	74.00	20.07

Middle Channel: 2442MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Max Peak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1479.400000	32.28	---	150.0	V	217.0	-16.5	74.00	41.72
1479.400000	---	22.65	150.0	V	217.0	-16.5	54.00	31.35
3247.400000	---	28.97	200.0	V	339.0	-9.5	54.00	25.03
3247.400000	38.11	---	200.0	V	339.0	-9.5	74.00	35.89
4884.000000	41.19	---	150.0	H	333.0	-5.4	74.00	32.81
4884.000000	---	33.53	150.0	H	333.0	-5.4	54.00	20.47
6865.000000	---	34.77	200.0	H	279.0	-0.4	54.00	19.23
6865.000000	43.62	---	200.0	H	279.0	-0.4	74.00	30.38
10718.900000	---	37.21	150.0	H	103.0	2.6	54.00	16.79
10718.900000	46.20	---	150.0	H	103.0	2.6	74.00	27.80
17811.300000	---	44.77	150.0	V	130.0	8.8	54.00	9.23
17811.300000	54.39	---	150.0	V	130.0	8.8	74.00	19.61

High Channel: 2480MHz

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1443.700000	---	23.14	150.0	H	15.0	-16.7	54.00	30.86
1443.700000	31.32	---	150.0	H	15.0	-16.7	74.00	42.68
4960.000000	41.03	---	200.0	H	22.0	-5.3	74.00	32.97
4960.000000	---	34.17	200.0	H	22.0	-5.3	54.00	19.83
7755.800000	46.07	---	150.0	V	231.0	1.4	74.00	27.93
7755.800000	---	36.56	150.0	V	231.0	1.4	54.00	17.44
9668.300000	---	35.63	200.0	V	244.0	2.1	54.00	18.37
9668.300000	45.06	---	200.0	V	244.0	2.1	74.00	28.94
13190.700000	---	39.52	200.0	H	111.0	5.4	54.00	14.48
13190.700000	49.75	---	200.0	H	111.0	5.4	74.00	24.25
17813.000000	54.62	---	150.0	H	51.0	8.8	74.00	19.38
17813.000000	---	45.18	150.0	H	51.0	8.8	54.00	8.82

18GHz-25GHz:


(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case low channel of operation in Y-axis of orientation was recorded)

Horizontal



Date: 22.OCT.2020 22:57:25

Vertical



Date: 22.OCT.2020 23:09:19

Fundamental Test & Restricted Bands Emissions Test:

(Pre-scan in the X, Y and Z axes of orientation, the worst case Y-axis of orientation was recorded.)

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)

Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)

Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	Max Peak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)	Degree			
Low Channel: 2403MHz								
2403.00	86.00	---	150.0	H	41.0	-2.8	114.00	28.00
2403.00	---	85.51	150.0	H	41.0	-2.8	94.00	8.49
2403.00	83.63	---	100.0	V	212.0	-2.8	114.00	30.37
2403.00	---	83.34	100.0	V	212.0	-2.8	94.00	10.66
2400.00	---	42.7	150.0	H	177.0	-2.9	54.00	11.30
2400.00	46.06	---	150.0	H	177.0	-2.9	74.00	27.94
Middle Channel: 2442MHz								
2442.00	83.88	---	200.0	H	244.0	-2.8	114.00	30.12
2442.00	---	83.43	200.0	H	244.0	-2.8	94.00	10.57
2442.00	81.78	---	150.0	V	269.0	-2.8	114.00	32.22
2442.00	---	81.04	150.0	V	269.0	-2.8	94.00	12.96
High Channel: 2480MHz								
2480.00	83.28	---	200.0	H	226.0	-2.5	114.00	30.72
2480.00	---	82.81	200.0	H	226.0	-2.5	94.00	11.19
2480.00	81.06	---	100.0	V	192.0	-2.5	114.00	32.94
2480.00	---	80.70	100.0	V	192.0	-2.5	94.00	13.30
2483.50	47.5	---	150.0	H	339.0	-2.5	74.00	26.50
2483.50	---	43.07	150.0	H	339.0	-2.5	54.00	10.93

FCC §15.215(c) – 20 dB BANDWIDTH TESTING

Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	22.4°C
Relative Humidity:	50%
ATM Pressure:	101.3kPa


The testing was performed by Chao Gao on 2020-10-22.

Test Result: Compliant.


Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2403	1.040
Middle	2442	1.046
High	2480	1.022


Low Channel



Middle Channel



High Channel



Declarations

1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

5: This report cannot be reproduced except in full, without prior written approval of the Company.

6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

******* END OF REPORT *******