

**FCC §15.247 (I) & §1.1310 & §2.1091 - MAXIMUM PERMISSIBLE  
EXPOSURE (MPE)**

**Applicable Standard**

According to subpart 15.247 (i) and subpart 1.1310 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density

**Calculated Formulary:**

Predication of MPE limit at a given distance

S =  $PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

**Calculated Data:**

Test Mode	Frequency Range (MHz)	Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)			
11b	2412	-9.86	0.103	21.48	131.22	20	0.0027	1.0000
	2437	-9.86	0.103	21.34	136.14	20	0.0028	1.0000
	2462	-9.86	0.103	21.17	130.92	20	0.0027	1.0000
11g	2412	-9.86	0.103	18.70	74.13	20	0.0015	1.0000
	2437	-9.86	0.103	18.70	74.13	20	0.0015	1.0000
	2462	-9.86	0.103	18.69	73.96	20	0.0015	1.0000
11n HT20	2412	-9.86	0.103	18.65	73.28	20	0.0015	1.0000
	2437	-9.86	0.103	18.56	71.78	20	0.0015	1.0000
	2462	-9.86	0.103	18.53	71.29	20	0.0015	1.0000

**Conclusion:** The EUT meets exemption requirement - RF exposure evaluation greater than 20cm distance specified in § 2.1091. If the device built into a host as a portable usage, the additional RF exposure evaluation may be required as specified by § 2.1093.