



# FCC Part 15C Measurement and Test Report

For

Hangzhou Sky-Lighting CO., Ltd.

No.161 North Star-Bridge Road. Linping. Hangzhou. Zhejiang. 311100 China

**FCC ID: 2AVJP-DS6SRGBW**

**FCC Rule(s):** FCC Part 15.247  
**Product Description:** LED LAMP  
**Tested Model:** DSST21-AD6S E26 WIFIRGBW  
**Report No.:** WTX20X05026106W  
**Sample Receipt Date:** May.11, 2020  
**Tested Date:** May.11, 2020 to Jun.10, 2020  
**Issued Date:** Jun.10, 2020  
**Tested By:** Jack Huang / Engineer  
**Reviewed By:** Lion Cai / RF Manager  
**Approved & Authorized By:** Silin Chen / Manager  
**Prepared By:**

*Jack Huang*

*Lion Cai*

*Silin Chen*

**Waltek Testing Group (Shenzhen) Co., Ltd.**

1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,  
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Waltek Testing Group (Shenzhen) Co., Ltd.



**TABLE OF CONTENTS**

**1. GENERAL INFORMATION.....4**  
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4  
1.2 TEST STANDARDS.....5  
1.3 TEST METHODOLOGY .....5  
1.4 TEST FACILITY .....5  
1.5 EUT SETUP AND TEST MODE.....6  
1.6 MEASUREMENT UNCERTAINTY .....7  
1.7 TEST EQUIPMENT LIST AND DETAILS .....8

**2. SUMMARY OF TEST RESULTS .....10**

**3. RF EXPOSURE .....11**  
3.1 STANDARD APPLICABLE.....11  
3.2 TEST RESULT.....11

**4. ANTENNA REQUIREMENT .....12**  
4.1 STANDARD APPLICABLE.....12  
4.2 EVALUATION INFORMATION .....12

**5. POWER SPECTRAL DENSITY .....13**  
5.1 STANDARD APPLICABLE.....13  
5.2 TEST PROCEDURE.....13  
5.3 SUMMARY OF TEST RESULTS/PLOTS .....13

**6. DTS BANDWIDTH.....18**  
6.1 STANDARD APPLICABLE.....18  
6.2 TEST PROCEDURE.....18  
6.3 SUMMARY OF TEST RESULTS/PLOTS .....18

**7. RF OUTPUT POWER .....23**  
7.1 STANDARD APPLICABLE.....23  
7.2 TEST PROCEDURE.....23  
7.3 SUMMARY OF TEST RESULTS/PLOTS .....23

**8. FIELD STRENGTH OF SPURIOUS EMISSIONS .....29**  
8.1 STANDARD APPLICABLE.....29  
8.2 TEST PROCEDURE.....29  
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....30  
8.4 SUMMARY OF TEST RESULTS/PLOTS .....30

**9. OUT OF BAND EMISSIONS.....38**  
9.1 STANDARD APPLICABLE.....38  
9.2 TEST PROCEDURE.....38  
9.3 SUMMARY OF TEST RESULTS/PLOTS .....39

**10. CONDUCTED EMISSIONS .....68**  
10.1 TEST PROCEDURE.....68  
10.2 BASIC TEST SETUP BLOCK DIAGRAM.....68  
10.3 TEST RECEIVER SETUP .....68  
10.4 SUMMARY OF TEST RESULTS/PLOTS .....68



## Report version

Version No.	Date of issue	Description
Rev.00	Jun.10, 2020	Original
/	/	/



# 1. GENERAL INFORMATION

## 1.1 Product Description for Equipment Under Test (EUT)

### Client Information

Applicant: Hangzhou Sky-Lighting CO., Ltd.  
 Address of applicant: No.161 North Star-Bridge Road. Linping. Hangzhou.  
 Zhejiang. 311100 China

Manufacturer: Hangzhou Sky-Lighting CO., Ltd.  
 Address of manufacturer: No.161 North Star-Bridge Road. Linping. Hangzhou.  
 Zhejiang. 311100 China

General Description of EUT	
Product Name:	LED LAMP
Trade Name:	SKYING
Model No.:	DSST21-AD6S E26 WIFIRGBW
Adding Model(s):	DSG30-AD6S E26 WIFIRGBW
Rated Voltage:	AC120V 60Hz
Serial Number :	WMBC19AUA00007
Firmware Version:	1.0.5
Hardware Version:	102
<p><i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model DSST21-AD6S E26 WIFIRGBW, but the circuit and the electronic construction do not change, declared by the manufacturer.</i></p>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n-HT20 2422-2452MHz for 802.11n-HT40
RF Output Power:	16.12dBm (Conducted)
Type of Modulation:	DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11 for 802.11b/g/n-HT20 7 for 802.11n-HT40
Channel Separation:	5MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	1.1 dBi

## 1.2 Test Standards

The tests were performed according to following standards:

**FCC Rules Part 15.247:** Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

**558074 D01 15.247 Meas Guidance v05r02:** Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the Fcc rules.

**ANSI C63.10-2013:** American National Standard for Testing Unlicensed Wireless Devices.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

## 1.4 Test Facility

### **Address of the test laboratory**

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

### **FCC – Registration No.: 125990**

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd., has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.



### 1.5 EUT Setup and Test Mode

Use “Wifi Test Tool V1.4.0.exe” and follow the instructions given by the manufacturer, you can start to test. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. Test use the customer default power level, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM3	802.11n-HT20	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM4	802.11n-HT40	Low:2422MHz, Middle:2437MHz,High:2452MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~56 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Accessories Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
AC Cable	/	/	/
Lamp Holder	/	/	/
Notebook	Lenovo	E445	EB12648265



### 1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	±0.42dB
Occupied Bandwidth	Conducted	±1.5%
Power Spectral Density	Conducted	±1.8dB
Conducted Spurious Emission	Conducted	±2.17dB
Conducted Emissions	Conducted	9-150kHz ±3.74dB
		0.15-30MHz ±3.34dB
Transmitter Spurious Emissions	Radiated	30-200MHz ±4.52dB
		0.2-1GHz ±5.56dB
		1-6GHz ±3.84dB
		6-18GHz ±3.92dB


**1.7 Test Equipment List and Details**

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2020-04-28	2021-04-27
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2020-04-28	2021-04-27
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2020-04-28	2021-04-27
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2020-04-28	2021-04-27
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2020-04-28	2021-04-27
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2019-05-05	2021-05-04
SEMT-1042	Horn Antenna	ETS	3117	00086197	2019-05-05	2021-05-04
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2019-05-05	2021-05-04
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2019-05-05	2021-05-04
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2020-04-28	2021-04-27
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2020-04-28	2021-04-27
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2020-04-28	2021-04-27
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2020-04-28	2021-04-27
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2020-04-28	2021-04-27
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2020-04-28	2021-04-27
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2019-05-05	2021-05-04
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2020-04-28	2021-04-27
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2020-04-28	2021-04-27
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2020-04-28	2021-04-27
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2020-03-17	2021-03-16
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2020-03-17	2021-03-16
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2020-03-17	2021-03-16
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2020-03-17	2021-03-16
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2020-03-17	2021-03-16
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2020-03-17	2021-03-16





<b>Software List</b>			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

\*Remark: indicates software version used in the compliance certification testing



## 2. SUMMARY OF TEST RESULTS

---

<b>FCC Rules</b>	<b>Description of Test Item</b>	<b>Result</b>
§2.1091	RF Exposure	Compliant
§15.203;15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable



### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to §1.1307 and §2.1091, the fixed transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

## **4. Antenna Requirement**

---

### **4.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### **4.2 Evaluation Information**

This product has an Integral antenna, fulfill the requirement of this section.



## 5. Power Spectral Density

### 5.1 Standard Applicable

According to 15.247(a)(1)(iii), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 5.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

### 5.3 Summary of Test Results/Plots

Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b_11Mbps	2412	-19.59	8
	2437	-19.60	8
	2462	-20.03	8
802.11g_54Mbps	2412	-20.68	8
	2437	-19.26	8
	2462	-19.81	8
802.11n-HT20_MCS7	2412	-21.75	8
	2437	-20.39	8
	2462	-20.55	8
802.11n-HT40_MCS7	2422	-25.20	8
	2437	-24.63	8
	2452	-24.37	8



Please refer to the following test plots:


<p>802.11b-Low</p>	<p>Ref 10 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -19.59 dBm VSW 10 kHz SWT 3.4 s 2.412780000 GHz</p> <p>10 Offset 1 dB</p> <p>SWR 100 100</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 10.JUN.2020 15:56:34</p>
<p>802.11b-Middle</p>	<p>Ref 10 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -19.60 dBm VSW 10 kHz SWT 3.4 s 2.436340000 GHz</p> <p>10 Offset 1 dB</p> <p>SWR 100 100</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 10.JUN.2020 16:03:12</p>
<p>802.11b-High</p>	<p>Ref 10 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -20.03 dBm VSW 10 kHz SWT 3.4 s 2.461460000 GHz</p> <p>10 Offset 1 dB</p> <p>SWR 100 100</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 10.JUN.2020 16:09:17</p>



<p>802.11g-Low</p>	<p>Ref 10 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -20.68 dBm          VBW 10 kHz SWT 3.4 s 2.412360000 GHz</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 10.JUN.2020 16:16:39</p>
<p>802.11g-Middle</p>	<p>Ref 10 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -19.26 dBm          VBW 10 kHz SWT 3.4 s 2.436760000 GHz</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 10.JUN.2020 16:22:49</p>
<p>802.11g-High</p>	<p>Ref 10 dBm Att 20 dB RBW 3 kHz Marker 1 [T1] -19.81 dBm          VBW 10 kHz SWT 3.4 s 2.462360000 GHz</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 10.JUN.2020 16:29:02</p>




802.11n-HT20-Low




Date: 10.JUN.2020 16:35:21

802.11n-HT20-Middle



Date: 10.JUN.2020 16:41:36

802.11n-HT20-High




Date: 10.JUN.2020 16:48:18






802.11n-HT40-Low




Date: 10.JUN.2020 17:00:27

802.11n-HT40-Middle



Date: 10.JUN.2020 17:12:28

802.11n-HT40-High



Date: 10.JUN.2020 17:25:21



## 6. DTS Bandwidth

### 6.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 6.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2013 Subclause 11.8.1, the test method of DTS Bandwidth as below:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 6.3 Summary of Test Results/Plots

Test Mode	Test Channel MHz	6 dB Bandwidth MHz	Limit kHz
802.11b_11Mbps	2412	10.08	$\geq 500$
	2437	9.60	$\geq 500$
	2462	10.08	$\geq 500$
802.11g_54Mbps	2412	12.60	$\geq 500$
	2437	12.66	$\geq 500$
	2462	15.00	$\geq 500$
802.11n-HT20_MCS7	2412	12.60	$\geq 500$
	2437	12.66	$\geq 500$
	2462	15.06	$\geq 500$
802.11n-HT40_MCS7	2422	31.32	$\geq 500$
	2437	27.72	$\geq 500$
	2452	28.80	$\geq 500$


Please refer to the following test plots:



<p>802.11b-Low</p>	<p>Ref 20 dBm Att 30 dB RBW 100 kHz Delta 1 [T1] 0.27 dB VBW 300 kHz SWT 5 ms 10.08000000 MHz</p> <p>Marker 1 [T1] -4.06 dBm Marker 2 [T1] 2.43 dBm</p> <p>Center 2.412 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 15.MAY.2020 14:08:49</p>
<p>802.11b-Middle</p>	<p>Ref 20 dBm Att 30 dB RBW 100 kHz Delta 1 [T1] 0.51 dB VBW 300 kHz SWT 5 ms -9.60000000 MHz</p> <p>Marker 1 [T1] -2.58 dBm Marker 2 [T1] 3.17 dBm</p> <p>Center 2.437 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 15.MAY.2020 14:09:50</p>
<p>802.11b-High</p>	<p>Ref 20 dBm Att 30 dB RBW 100 kHz Delta 1 [T1] -0.24 dB VBW 300 kHz SWT 5 ms -10.08000000 MHz</p> <p>Marker 1 [T1] -2.18 dBm Marker 2 [T1] 3.07 dBm</p> <p>Center 2.462 GHz 3 MHz/ Span 30 MHz</p> <p>Date: 15.MAY.2020 14:10:58</p>




802.11g-Low




Date: 15.MAY.2020 14:12:04

802.11g-Middle



Date: 15.MAY.2020 14:15:54


802.11g-High



Date: 15.MAY.2020 14:17:46




802.11n-HT20-Low




Date: 15.MAY.2020 14:19:08

802.11n-HT20-Middle



Date: 15.MAY.2020 14:20:16


802.11n-HT20-High



Date: 15.MAY.2020 14:21:14




802.11n-HT40-Low




Date: 15.MAY.2020 14:23:19

802.11n-HT40-Middle



Date: 15.MAY.2020 14:24:29

802.11n-HT40-High



Date: 15.MAY.2020 14:25:23

## 7. RF Output Power

---

### 7.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

### 7.2 Test Procedure

According to the KDB-558074 D01 v05r02 Subclause 8.3.2.2 and ANSI C63.10-2013 Subclause 11.9.2.2, when this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth

- a) Set span to at least 1.5 times the OBW.
- b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
- c) Set VBW  $\geq 3 \times$  RBW.
- d) Number of points in sweep  $\geq 2 \times$  span / RBW. (This gives bin-to-bin spacing  $\leq$  RBW/2, so that narrowband signals are not lost between frequency bins.)
- e) Sweep time = auto.
- f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq 98$  %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run” .
- h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

### 7.3 Summary of Test Results/Plots



Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
802.11b _ 11Mbps	2412	15.25	33.50	1000
	2437	15.11	32.43	1000
	2462	14.69	29.44	1000
802.11g_54Mbps	2412	15.08	32.21	1000
	2437	16.04	40.18	1000
	2462	16.12	40.93	1000
802.11n HT20_MCS7	2412	13.81	24.04	1000
	2437	15.78	37.84	1000
	2462	15.48	35.32	1000
802.11n HT40_MCS7	2422	12.33	17.10	1000
	2437	13.10	20.42	1000
	2452	13.10	20.42	1000

Please refer to the following test plots:






<p>802.11b-Low 11Mbps</p>	<p>Date: 10.JUN.2020 15:35:35</p>
<p>802.11b-Middle 11Mbps</p>	<p>Date: 10.JUN.2020 15:36:04</p>
<p>802.11b-High 11Mbps</p>	<p>Date: 10.JUN.2020 15:36:25</p>



<p>802.11g-Low 54Mbps</p>	<p>Date: 10.JUN.2020 15:37:24</p>
<p>802.11g-Middle 54Mbps</p>	<p>Date: 10.JUN.2020 15:37:51</p>
<p>802.11g-High 54Mbps</p>	<p>Date: 10.JUN.2020 15:38:54</p>




802.11n-HT20-Low  
MCS7




Date: 10.JUN.2020 15:39:49

802.11n-HT20-Middle  
MCS7



Date: 10.JUN.2020 15:40:32

802.11n-HT20-High  
MCS7



Date: 10.JUN.2020 15:41:10



<p>802.11n-HT40-Low MCS7</p>	<p>Date: 10.JUN.2020 15:41:56</p>
<p>802.11n-HT40-Middle MCS7</p>	<p>Date: 10.JUN.2020 15:42:20</p>
<p>802.11n-HT40-High MCS7</p>	<p>Date: 10.JUN.2020 15:42:38</p>

## 8. Field Strength of Spurious Emissions

### 8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz  
 RBW=10KHz,  
 VBW =30KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak

Frequency :30MHz-1GHz  
 RBW=120KHz,  
 VBW=360KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, QP

Frequency :Above 1GHz  
 RBW=1MHz,  
 VBW=3MHz(Peak), 10Hz(AV)  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, AV

### 8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


### 8.4 Summary of Test Results/Plots

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported. All test modes (different data rate and different modulation) are performed, but only the worst case(802.11b\_11 Mbps) is recorded in this report.*



➤ Spurious Emissions Below 1GHz


802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	263.8190	49.65	-10.21	39.44	46.00	-6.56	-	-	peak
2	372.0045	47.49	-7.92	39.57	46.00	-6.43	-	-	peak
3	396.2415	50.11	-7.88	42.23	46.00	-3.77	-	-	peak
4	444.8514	48.06	-8.17	39.89	46.00	-6.11	-	-	peak
5	815.9678	37.59	-3.58	34.01	46.00	-11.99	-	-	peak



802.11b_11Mbps			
Test Channel	Low	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	36.0007	44.87	-15.70	29.17	40.00	-10.83	-	-	peak
2	276.1236	40.54	-9.90	30.64	46.00	-15.36	-	-	peak
3	348.0274	43.10	-7.65	35.45	46.00	-10.55	-	-	peak
4	432.5457	40.34	-8.01	32.33	46.00	-13.67	-	-	peak
5	968.9338	32.21	-0.99	31.22	54.00	-22.78	-	-	peak






802.11b_11Mbps			
Test Channel	Middle	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	276.1236	50.58	-9.90	40.68	46.00	-5.32	-	-	peak
2	348.0274	49.03	-7.65	41.38	46.00	-4.62	-	-	peak
3	396.2415	47.63	-7.88	39.75	46.00	-6.25	-	-	peak
4	432.5457	47.86	-8.01	39.85	46.00	-6.15	-	-	peak
5	815.9678	35.88	-3.58	32.30	46.00	-13.70	-	-	peak




802.11b_11Mbps			
Test Channel	Middle	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	35.8747	43.93	-15.75	28.18	40.00	-11.82	-	-	peak
2	263.8190	40.12	-10.21	29.91	46.00	-16.09	-	-	peak
3	348.0274	41.60	-7.65	33.95	46.00	-12.05	-	-	peak
4	432.5457	44.67	-8.01	36.66	46.00	-9.34	-	-	peak
5	903.3094	31.30	-1.14	30.16	46.00	-15.84	-	-	peak




802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	39.8542	42.68	-14.21	28.47	40.00	-11.53	-	-	peak
2	276.1236	50.49	-9.90	40.59	46.00	-5.41	-	-	peak
3	348.0274	48.97	-7.65	41.32	46.00	-4.68	-	-	peak
4	432.5457	48.24	-8.01	40.23	46.00	-5.77	-	-	peak
5	890.7278	35.08	-1.61	33.47	46.00	-12.53	-	-	peak



802.11b_11Mbps			
Test Channel	High	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	36.0007	44.01	-15.70	28.31	40.00	-11.69	-	-	peak
2	107.8877	40.43	-14.80	25.63	43.50	-17.87	-	-	peak
3	276.1236	39.71	-9.90	29.81	46.00	-16.19	-	-	peak
4	348.0274	42.40	-7.65	34.75	46.00	-11.25	-	-	peak
5	432.5457	45.12	-8.01	37.11	46.00	-8.89	-	-	peak
6	906.4824	31.73	-1.10	30.63	46.00	-15.37	-	-	peak

Remark: '-' Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.



- Spurious Emissions Above 1GHz
- Test Mode: 802.11b\_11Mbps (worst case)

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2412MHz							
4830.157	63.01	-4.50	58.51	74.00	-15.49	H	PK
4830.157	49.17	-4.50	44.67	54.00	-9.33	H	AV
8601.981	55.96	-0.03	55.93	74.00	-18.07	H	PK
8601.981	44.11	-0.03	44.08	54.00	-9.92	H	AV
2410.364	58.16	-9.46	48.70	74.00	-25.30	V	PK
2410.364	51.73	-9.46	42.27	54.00	-11.73	V	AV
4830.157	62.79	-4.50	58.29	74.00	-15.71	V	PK
4830.157	48.60	-4.50	44.10	54.00	-9.90	V	AV
11003.657	53.86	5.02	58.88	74.00	-15.12	V	PK
11031.917	41.87	5.00	46.87	54.00	-7.13	V	AV
Middle Channel-2437MHz							
4879.968	64.44	-4.47	59.97	74.00	-14.03	H	PK
4879.968	50.30	-4.47	45.83	54.00	-8.17	H	AV
8601.981	44.10	-0.03	44.07	54.00	-9.93	H	PK
8624.073	56.18	0.01	56.19	74.00	-17.81	H	AV
1903.706	41.65	-8.61	33.04	54.00	-20.96	V	PK
4259.690	54.05	-5.68	48.37	74.00	-25.63	V	AV
4325.752	42.07	-5.41	36.66	54.00	-17.34	V	PK
8601.981	55.74	-0.03	55.71	74.00	-18.29	V	AV
8601.981	44.07	-0.03	44.04	54.00	-9.96	V	PK
11031.917	54.77	5.00	59.77	74.00	-14.23	V	AV
High Channel-2462MHz							
6604.840	53.86	-2.28	51.58	74.00	-22.42	H	PK
6934.693	41.53	-2.26	39.27	54.00	-14.73	H	AV
8601.981	55.78	-0.03	55.75	74.00	-18.25	H	PK
8601.981	44.21	-0.03	44.18	54.00	-9.82	H	AV
2460.334	53.10	-9.36	43.74	74.00	-30.26	V	PK
2460.334	44.50	-9.36	35.14	54.00	-18.86	V	AV
4270.630	42.39	-5.64	36.75	54.00	-17.25	V	PK
4314.671	54.30	-5.46	48.84	74.00	-25.16	V	AV
8601.981	56.13	-0.03	56.10	74.00	-17.90	V	PK
8601.981	44.12	-0.03	44.09	54.00	-9.91	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

## 9. Out of Band Emissions

---

### 9.1 Standard Applicable

According to §15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 9.2 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2013 Subclause 11.11, the emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2013 Subclause 11.12, the emissions in restricted frequency bands test method as follows:

#### A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.



**B. Antenna-port conducted measurements**

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) VBW  $\geq$  [3  $\times$  RBW].
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

**Table 9—RBW as a function of frequency**

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz


If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

**9.3 Summary of Test Results/Plots**

➤ Radiated test

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal (worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	42.75	-9.66	33.09	54.00	-20.91	Average Detector
	2310.000	52.97	-9.66	43.31	74.00	-30.69	Peak Detector
2	2390.000	52.19	-9.50	42.69	54.00	-11.31	Average Detector
	2390.000	59.97	-9.50	50.47	74.00	-23.53	Peak Detector
3	2412.840	105.78	-9.46	96.32	/	/	Average Detector
	2412.720	111.91	-9.46	102.45	/	/	Peak Detector






802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.250	103.82	-9.36	94.46	/	/	Average Detector
	2462.150	110.57	-9.36	101.21	/	/	Peak Detector
2	2483.500	45.60	-9.31	36.29	54.00	-17.71	Average Detector
	2483.500	55.12	-9.31	45.81	74.00	-28.19	Peak Detector
3	2500.000	41.32	-9.28	32.04	54.00	-21.96	Average Detector
	2500.000	52.45	-9.28	43.17	74.00	-30.83	Peak Detector




802.11g_54Mbps			
Test Channel	Low	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	43.94	-9.66	34.28	54.00	-19.72	Average Detector
		54.82	-9.66	45.16	74.00	-28.84	Peak Detector
2	2390.000	53.44	-9.50	43.94	54.00	-10.06	Average Detector
		69.49	-9.50	59.99	74.00	-14.01	Peak Detector
3	2412.960	103.79	-9.46	94.33	/	/	Average Detector
		112.98	-9.46	103.52	/	/	Peak Detector




802.11g_54Mbps			
Test Channel	High	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.200	101.59	-9.36	92.23	/	/	Average Detector
	2462.900	110.68	-9.36	101.32	/	/	Peak Detector
2	2483.500	47.90	-9.31	38.59	54.00	-15.41	Average Detector
	2483.500	61.26	-9.31	51.95	74.00	-22.05	Peak Detector
3	2500.000	42.27	-9.28	32.99	54.00	-21.01	Average Detector
	2500.000	52.32	-9.28	43.04	74.00	-30.96	Peak Detector


802.11n-HT20_MCS7			
Test Channel	Low	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	44.00	-9.66	34.34	54.00	-19.66	Average Detector
	2310.000	54.19	-9.66	44.53	74.00	-29.47	Peak Detector
2	2390.000	52.91	-9.50	43.41	54.00	-10.59	Average Detector
	2390.000	66.22	-9.50	56.72	74.00	-17.28	Peak Detector
3	2410.920	102.86	-9.46	93.40	/	/	Average Detector
	2410.800	111.44	-9.46	101.98	/	/	Peak Detector




802.11n-HT20_MCS7			
Test Channel	High	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.050	100.42	-9.36	91.06	/	/	Average Detector
	2460.750	118.33	-9.36	108.97	/	/	Peak Detector
2	2483.500	46.55	-9.31	37.24	54.00	-16.76	Average Detector
	2483.500	68.18	-9.31	58.87	74.00	-15.13	Peak Detector
3	2500.000	42.32	-9.28	33.04	54.00	-20.96	Average Detector
	2500.000	61.75	-9.28	52.47	74.00	-21.53	Peak Detector




802.11n-HT40_MCS7			
Test Channel	Low	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	44.13	-9.66	34.47	54.00	-19.53	Average Detector
	2310.000	55.27	-9.66	45.61	74.00	-28.39	Peak Detector
2	2390.000	62.81	-9.50	53.31	54.00	-0.69	Average Detector
	2390.000	79.74	-9.50	70.24	74.00	-3.76	Peak Detector
3	2415.840	98.55	-9.46	89.09	/	/	Average Detector
	2415.560	107.47	-9.46	98.01	/	/	Peak Detector



802.11n-HT40_MCS7			
Test Channel	High	Polarity:	Horizontal (worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2450.650	96.76	-9.38	87.38	/	/	Average Detector
	2449.810	105.68	-9.39	96.29	/	/	Peak Detector
2	2483.500	56.37	-9.31	47.06	54.00	-6.94	Average Detector
	2483.500	73.13	-9.31	63.82	74.00	-10.18	Peak Detector
3	2500.000	44.39	-9.28	35.11	54.00	-18.89	Average Detector
	2500.000	55.74	-9.28	46.46	74.00	-27.54	Peak Detector



➤ Band edge

RBW:100kHz VBW:300kHz

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal (worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit	Remark
					Delta>30dBc	
1	2400.000	63.91	-9.48	54.43	Delta=41.4dBc	Peak Detector
2	2412.600	105.29	-9.46	95.83		Peak Detector






802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit	Remark
					Delta>30dBc	
1	2461.500	103.49	-9.36	94.13	Delta=55.53dBc	Peak Detector
2	2483.500	47.91	-9.31	38.60		Peak Detector




802.11g_54Mbps			
Test Channel	Low	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit	Remark
					Delta>30dBc	
1	2400.000	72.00	-9.48	62.52	Delta=33.02dBc	Peak Detector
2	2413.320	105.00	-9.46	95.54		Peak Detector




802.11g_54Mbps			
Test Channel	High	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit	Remark
					Delta>30dBc	
1	2460.750	101.95	-9.36	92.59	Delta=53.14dBc	Peak Detector
2	2483.500	48.76	-9.31	39.45		Peak Detector




802.11n-HT20_MCS7			
Test Channel	Low	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit	Remark
					Delta>30dBc	
1	2400.000	69.25	-9.48	59.77	Delta=34.71dBc	Peak Detector
3	2413.320	103.94	-9.46	94.48		Peak Detector




802.11n-HT20_MCS7			
Test Channel	High	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit	Remark
					Delta>30dBc	
1	2463.250	101.41	-9.36	92.05	Delta=51.43dBc	Peak Detector
2	2483.500	49.93	-9.31	40.62		Peak Detector




802.11n-HT40_MCS7			
Test Channel	Low	Polarity:	Horizontal (worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit	Remark
					Delta>30dBc	
1	2400.000	66.73	-9.48	57.25	Delta=32.83dBc	Peak Detector
3	2415.840	99.54	-9.46	90.08		Peak Detector



802.11n-HT40_MCS7			
Test Channel	High	Polarity:	Horizontal (worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit	Remark
					Delta>30dBc	
1	2447.010	97.63	-9.39	88.24	Delta=40.84dBc	Peak Detector
2	2483.500	56.71	-9.31	47.40		Peak Detector




➤ Conducted test

802.11b\_11Mbps

Low



Date: 15.MAY.2020 13:40:50




Date: 15.MAY.2020 13:44:16






802.11b\_11Mbps

Middle



Date: 15.MAY.2020 13:45:07




Date: 15.MAY.2020 13:45:23




802.11b\_11Mbps

High



Date: 15.MAY.2020 13:46:52




Date: 15.MAY.2020 13:47:12




802.11g\_54Mbps

Low



Date: 15.MAY.2020 13:49:21




Date: 15.MAY.2020 13:49:44




802.11g\_54Mbps

Middle



Date: 15.MAY.2020 13:53:02




Date: 15.MAY.2020 13:53:28




802.11g\_54Mbps

High



Date: 15.MAY.2020 13:55:18




Date: 15.MAY.2020 13:55:32




802.11n-HT20\_MCS7

Low



Date: 15.MAY.2020 13:56:27




Date: 15.MAY.2020 13:56:42




802.11n-HT20\_MCS7

Middle



Date: 15.MAY.2020 13:58:32




Date: 15.MAY.2020 13:58:48




802.11n-HT20\_MCS7

High



Date: 15.MAY.2020 14:00:33




Date: 15.MAY.2020 14:00:50






802.11n-HT40\_MCS7

Low



Date: 15.MAY.2020 14:02:17




Date: 15.MAY.2020 14:02:42




802.11n-HT40\_MCS7

Middle



Date: 15.MAY.2020 14:03:30




Date: 15.MAY.2020 14:03:43




802.11n-HT40\_MCS7

High



Date: 15.MAY.2020 14:04:27



Date: 15.MAY.2020 14:04:43


## 10. Conducted Emissions

### 10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

### 10.2 Basic Test Setup Block Diagram



### 10.3 Test Receiver Setup


During the conducted emission test, the test receiver was set with the following configurations:

- Start Frequency ..... 150 kHz
- Stop Frequency ..... 30 MHz
- Sweep Speed ..... Auto
- IF Bandwidth..... 10 kHz
- Quasi-Peak Adapter Bandwidth ..... 9 kHz
- Quasi-Peak Adapter Mode ..... Normal

### 10.4 Summary of Test Results/Plots




Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	38.70	9.95	48.65	66.00	-17.35	QP
2	0.1768	37.29	9.95	47.24	64.63	-17.39	QP
3	0.1780	24.93	9.96	34.89	54.58	-19.69	AVG
4	27.0340	20.74	10.98	31.72	50.00	-18.28	AVG
5	29.6140	25.72	11.07	36.79	50.00	-13.21	AVG
6*	29.6900	35.78	11.07	46.85	60.00	-13.15	QP



Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1499	38.55	9.95	48.50	66.00	-17.50	QP
2	0.1780	37.03	9.96	46.99	64.57	-17.58	QP
3	0.1780	25.18	9.96	35.14	54.57	-19.43	AVG
4	0.2180	21.96	9.98	31.94	52.89	-20.95	AVG
5	29.1740	25.84	11.06	36.90	50.00	-13.10	AVG
6*	29.7540	36.53	11.07	47.60	60.00	-12.40	QP

\*\*\*\*\* END OF REPORT \*\*\*\*\*