

RF Exposure Evaluation Report

Product : Handy Tracker
Trade mark : TRC
Model/Type reference : RC2-STD-HDTK02
Serial Number : N/A
Report Number : EED32L00330302
FCC ID : 2AVJS-RC2-STD
Date of Issue : Sep. 27, 2020
Test Standards : 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF
Exposure Guidance v06
Test result : PASS

Prepared for:

TRCare, Inc.

1060 East Meadow Circle, Palo Alto, California 94303, USA

Prepared by:

Centre Testing International Group Co., Ltd.

Hongwei Industrial Zone, Bao'an 70 District,

Shenzhen, Guangdong, China

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by:

Smile Zhong

Reviewed by:

Jok Yang

Smile Zhong

Jok Yang

Approved by:

Sam Chuang

Date:

Sep. 27, 2020

Sam Chuang

Check No.:3096363801



2 Version

Version No.	Date	Description
00	Sep. 27, 2020	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 TEST LOCATION.....	5
4.4 DEVIATION FROM STANDARDS.....	5
4.5 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 SAR EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1 Standard Requirement.....	6
5.1.2 Limits.....	6
5.1.3 EUT RF Exposure.....	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	8

4 General Information

4.1 Client Information

Applicant:	TRCare, Inc.
Address of Applicant:	1060 East Meadow Circle, Palo Alto, California 94303, USA
Manufacturer:	SHENZHEN SIGMAWIT TECHNOLOGY CO., LTD.
Address of Manufacturer:	11th floor, Lingyun Building, DingXin Industrial Area, Honglang North 2nd Road, Bao'an, ShenZhen, China
Factory:	SHENZHEN SIGMAWIT TECHNOLOGY CO., LTD.
Address of Factory:	11th floor, Lingyun Building, DingXin Industrial Area, Honglang North 2nd Road, Bao'an, ShenZhen, China

4.2 General Description of EUT

Product Name:	Handy Tracker
Model No.(EUT):	RC2-STD-HDTK02
Trade Mark:	TRC
Operation Frequency:	2404MHz~2480MHz
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK
Number of Channel:	16
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	Portable production
Test Power Grade:	Default
Test Software of EUT:	XCOM V2.2.exe (manufacturer declare)
Antenna Type:	PCB Antenna
Antenna Gain:	0 dBi
Test Voltage:	120V/60Hz
Max Conducted Peak Output Power:	-0.316dBm
	The Max Conducted Peak Output Power data refer to the report EED32L00330301
Sample Received Date:	Aug. 01, 2020
Sample tested Date:	Aug. 01, 2020 to Sep. 24, 2020
Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.	

4.3 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.4 Deviation from Standards

None.

4.5 Abnormalities from Standard Conditions

None.

4.6 Other Information Requested by the Customer

None.

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

The tune-up power is -0.5 dBm +/- 1dB, therefore the highest tune-up power is
0.5 dBm (1.12 mW) @ 2442 MHz

When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

So,

$$(1.12\text{mW} / 5\text{mm}) * (2.442\text{GHz}^{0.5}) = 0.4$$

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] = 0.4 < 3.0$$

Therefore, standalone SAR measurements are not required for both head and body

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32L00330201 for EUT external and internal photos.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***