

## RF Exposure Evaluation Declaration

**FCC ID:** 2AVK9-30251

**Applicant:** Strong Current Enterprises Limited

**Application Type:** Certification

**Product:** RANGEXTD MVP

**Model No.:** 30251

**FCC Classification:** Digital Transmission System (DTS)

**Test Procedure(s):** KDB 447498 D01 General RF Exposure Guidance v06

Reviewed By:

*Sunny Sun*

( Sunny Sun )

Approved By:

*Robin Wu*

(Robin Wu)



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

## Revision History

| Report No.    | Version | Description    | Issue Date | Note  |
|---------------|---------|----------------|------------|-------|
| 2001RSU020-U2 | Rev. 01 | Initial Report | 02-24-2020 | Valid |
|               |         |                |            |       |

## 1. PRODUCT INFORMATION

### 1.1. Feature of Equipment under Test

|                      |              |
|----------------------|--------------|
| Product Name:        | RANGEXTD MVP |
| Model No.:           | 30251        |
| Wi-Fi Specification: | 802.11b/g/n  |

### 1.2. Product Specification Subjective to this Report

|                     |   |
|---------------------|---|
| Frequency Range:    | 802.11b/g/n-HT20: 2412 ~ 2462MHz<br>802.11n-HT40: 2422 ~ 2452MHz                        |
| Channel Number:     | 802.11b/g/n-HT20: 11<br>802.11n-HT40: 7   |
| Type of Modulation: | 802.11b: DSSS<br>802.11g/n: OFDM  |
| Data Rate:          | 802.11b: 1/2/5.5/11Mbps<br>802.11g: 6/9/12/18/24/36/48/54Mbps<br>802.11n: up to 300Mbps |

### 1.3. Working Frequencies for this report

802.11b/g/n-HT20

| Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|
| 01      | 2412 MHz  | 02      | 2417 MHz  | 03      | 2422 MHz  |
| 04      | 2427 MHz  | 05      | 2432 MHz  | 06      | 2437 MHz  |
| 07      | 2442 MHz  | 08      | 2447 MHz  | 09      | 2452 MHz  |
| 10      | 2457 MHz  | 11      | 2462 MHz  | --      | --        |

802.11n-HT40

| Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|
| 03      | 2422 MHz  | 04      | 2427 MHz  | 05      | 2432 MHz  |
| 06      | 2437 MHz  | 07      | 2442 MHz  | 08      | 2447 MHz  |
| 09      | 2452 MHz  | --      | --        | --      | --        |

#### 1.4. Description of Available Antennas

| Antenna Type     | Frequency Band (MHz) | TX Paths | Max Antenna Gain (dBi) |       | CDD Directional Gain (dBi) |         |
|------------------|----------------------|----------|------------------------|-------|----------------------------|---------|
|                  |                      |          | Ant 0                  | Ant 1 | For Power                  | For PSD |
| Shrapnel Antenna | 2412 ~ 2462          | 2        | 1.5                    | 1.5   | 1.5                        | 4.51    |

Note:

The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated.

For CDD transmissions, directional gain is calculated as follows,  $N_{ANT} = 2$ ,  $N_{SS} = 1$ .

Directional gain =  $G_{ANT\ MAX} + \text{Array Gain}$ , where Array Gain is as follows.

- For power spectral density (PSD) measurements on all devices,

Array Gain =  $10 \log (N_{ANT}/ N_{SS})$  dB = 3.01;

- For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB for  $N_{ANT} \leq 4$ ;

## 2. RF Exposure Evaluation

### 2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range (MHz)                                     | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (Minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/ Control Exposures            |                               |                               |                                     |                          |
| 0.3-3.0   | 614                           | 1.63                          | *100                                | 6                        |
| 3.0-30  | 1842/f                        | 4.89/f                        | *900/f <sup>2</sup>                 | 6                        |
| 30-300  | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300-1,500   | --                            | --                            | f/300                               | 6                        |
| 1,500-100,000   | --                            | --                            | 5                                   | 6                        |
| (B) Limits for General Population/ Uncontrolled Exposures |                               |                               |                                     |                          |
| 0.3-1.34  | 614                           | 1.63                          | *100                                | 30                       |
| 1.34-30   | 824/f                         | 2.19/f                        | *180/f <sup>2</sup>                 | 30                       |
| 30-300  | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1,500   | --                            | --                            | f/1500                              | 30                       |
| 1,500-100,000   | --                            | --                            | 1.0                                 | 30                       |

f= Frequency in MHz

\* = Plane-wave equivalent power density

Calculation Formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

r = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2.2. Test Result of RF Exposure Evaluation

|           |                        |
|-----------|------------------------|
| Product   | RANGEXTD MVP           |
| Test Item | RF Exposure Evaluation |

Antenna Gain: Refer to Clause 1.4 of this report.

| Test Mode   | Frequency Band (MHz) | Maximum Total Average Output Power (dBm) | Power Density at R = 20 cm (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) | Result |
|-------------|----------------------|--|--|-----------------------------|--------|
| 802.11b/g/n | 2412 ~ 2462          | 19.81                                    | 0.0269   | 1                           | Pass   |

The End

## Appendix - EUT Photograph

Refer to "2001RSU020-UE" file.