

FCC/ISED
RF
TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
Kids SmartWatch

ISSUED TO
XPLORA Technologies AS

XPLORA Technologies AS Tangerudvegen 13 2008 Fjerdingsby Norway



Tested by:	Wu Huihui	Report No.:	BL-EC2010017-501
Date	Jul. 14, 2020	EUT Name:	Kids SmartWatch
Approved by:	Wei Yanquan (Chief Engineer)	Model Name:	X5 Play (refer section 2.4)
Date	Jul. 14, 2020	Brand Name:	XPLORA
		Test Standard:	47 CFR Part 2 (10-1-18 Edition) RSS-Gen (Issue 5, March 2019) (Others refer to chapter 3.1)
		FCC ID:	2AVMJX5PE
		ISED Number:	26094-X5P
		Test Conclusion:	Pass
		Test Date:	Jan. 10, 2020 ~ Jul. 02, 2020
		Date of Issue:	Jul. 14, 2020

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Apr. 01, 2020</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Jul. 14, 2020</u>	<u>Added LTE Band 12 and ISED Standards</u>

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION).....	4
1.1	Identification of the Testing Laboratory	4
1.2	Identification of the Responsible Testing Location	4
1.3	Laboratory Condition	4
1.4	Announce.....	5
2	PRODUCT INFORMATION	6
2.1	Applicant Information	6
2.2	Manufacturer Information.....	6
2.3	Factory Information.....	6
2.4	General Description for Equipment under Test (EUT)	6
2.5	Technical Information	7
3	SUMMARY OF TEST RESULTS.....	9
3.1	Test Standards	9
3.2	Test Verdict	10
4	GENERAL TEST CONFIGURATIONS	12
4.1	Test Environments.....	12
4.2	Test Equipment List.....	12
4.3	Test Configurations	14
4.4	Test Setup.....	19
5	TEST ITEMS	21
5.1	Transmitter Radiated Power (EIRP/ERP)	21
5.2	Peak to Average Ratio	24
5.3	Occupied Bandwidth.....	26
5.4	Frequency Stability	28
5.5	Spurious Emission at Antenna Terminals	31

5.6	Band Edge	35
5.7	Field Strength of Spurious Radiation	38
5.8	Receiver Spurious Emissions.....	42
5.9	AC Power-line Conducted Emissions	44
	ANNEX A TEST RESULTS	46
A.1	Transmitter Radiated Power (EIRP/ERP)	46
A.2	Peak to Average Ratio.....	76
A.3	Occupied Bandwidth.....	78
A.4	Frequency Stability	82
A.5	Spurious Emission at Antenna Terminals	90
A.6	Band Edge	96
A.7	Field Strength of Spurious Radiation	102
A.8	Receiver Spurious Emissions.....	104
A.9	AC Power-line Conducted Emissions	108
	ANNEX B TEST SETUP PHOTOS	110
	ANNEX C EUT EXTERNAL PHOTOS	110
	ANNEX D EUT INTERNAL PHOTOS	110

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China.
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China.
Accreditation Certificate	<p>The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1.</p> <p>The laboratory is a testing organization accredited by FCC as an accredited testing laboratory. The designation number is CN1196.</p> <p>The laboratory is a testing organization accredited by American Association for Laboratory Accreditation(A2LA) according to ISO/IEC 17025. The accreditation certificate number is 4344.01.</p> <p>The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.</p>
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20 °C to 35 °C
Ambient Relative Humidity	30 % to 60 %
Ambient Pressure	98 kPa to 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v5.8.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (7) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	XPLORA Technologies AS
Address	XPLORA Technologies AS Tangerudvegen 13 2008 Fjerdingga Norway

2.2 Manufacturer Information

Manufacturer	XPLORA Technologies AS
Address	XPLORA Technologies AS Tangerudvegen 13 2008 Fjerdingga Norway

2.3 Factory Information

Factory	Hefei BOE Vision-electronic Technology Co., Ltd
Address	NO.2177 Dongfang RD, Xinzhan General Pilot Zone, HeFei, Anhui, 230012, P.R. China

2.4 General Description for Equipment under Test (EUT)

EUT Name	Kids SmartWatch
Model Name Under Test	X5 Play
Series Model Name	X5 Play eSIM
Description of Model name differentiation	X5 Play is SIM card, X5 Play eSIM is eSIM card.
Hardware Version	V.0
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Technical Information

All Network and Wireless connectivity for EUT	2G Network GSM/GPRS/EGPRS 850/ 1900 MHz; 3G Network WCDMA/HSDPA/HSUPA Band 2/ 4/ 5; 4G Network FDD LTE Band 2/ 4/ 5/ 7/12; WLAN; Bluetooth; GPS; GLONASS
About the Product	The equipment is Kids Smartwatch, intended for used with information technology equipment.

The requirement for the following technical information of the EUT was tested in this report:

Operating Bands	GSM/GPRS/EGPRS 850/ 1900 MHz WCDMA/HSDPA/HSUPA Band 2/ 4/ 5 FDD LTE Band 2/ 4/ 5/ 7/12	
Modulation Type	GSM/GPRS	GMSK
	EGPRS	8PSK
	WCDMA	QPSK
	HSDPA	QPSK
	/HSUPA	16QAM
	LTE	QPSK
		16QAM
TX Frequency Range	GSM/GPRS/EGPRS 850: 824 MHz ~ 849 MHz GSM/GPRS/EGPRS 1900: 1850 MHz ~ 1910 MHz WCDMA/HSDPA/HSUPA Band 2: 1850 MHz ~ 1910 MHz WCDMA/HSDPA/HSUPA Band 4: 1710 MHz ~ 1755 MHz WCDMA/HSDPA/HSUPA Band 5: 824 MHz ~ 849 MHz FDD LTE Band 2: 1850 MHz ~ 1910 MHz FDD LTE Band 4: 1710 MHz ~ 1755 MHz FDD LTE Band 5: 824 MHz ~ 849 MHz FDD LTE Band 7: 2500 MHz ~ 2570 MHz FDD LTE Band 12: 699 MHz ~ 716 MHz	
Rx Frequency Range	GSM/GPRS/EGPRS 850: 869 MHz ~ 894 MHz GSM/GPRS/EGPRS 1900: 1930 MHz ~ 1990 MHz WCDMA/HSDPA/HSUPA Band 2: 1930 MHz ~ 1990 MHz WCDMA/HSDPA/HSUPA Band 4: 2110 MHz ~ 2155 MHz WCDMA/HSDPA/HSUPA Band 5: 869 MHz ~ 894 MHz FDD LTE Band 2: 1930 MHz ~ 1990 MHz FDD LTE Band 4: 2110 MHz ~ 2155 MHz FDD LTE Band 5: 869 MHz ~ 894 MHz FDD LTE Band 7: 2620 MHz ~ 2690 MHz FDD LTE Band 12: 729 MHz ~ 746 MHz	
Power Class	GSM/GPRS 850: 4 GSM/GPRS 1900: 1 EGPRS 850/1900: E2 WCDMA/HSDPA/HSUPA Band 2: 3	

	WCDMA/HSDPA/HSUPA Band 4: 3 WCDMA/HSDPA/HSUPA Band 5: 3 FDD LTE Band 2: 3 FDD LTE Band 4: 3 FDD LTE Band 5: 3 FDD LTE Band 7: 3 FDD LTE Band 12: 3
Multislot Class	GPRS/EGPRS: 33
Antenna Type	LDS Antenna
Antenna Gain	GSM/GPRS/EGPRS 850: 1 dBi GSM/GPRS/EGPRS 1900: 1 dBi WCDMA/HSDPA/HSUPA Band 2: 1 dBi WCDMA/HSDPA/HSUPA Band 4: 1 dBi WCDMA/HSDPA/HSUPA Band 5: 1 dBi FDD LTE Band 2: 1 dBi FDD LTE Band 4: 1 dBi FDD LTE Band 5: 1 dBi FDD LTE Band 7: 1 dBi FDD LTE Band 12: 1 dBi
The Max RF Output Power (EIRP/ERP)	30.98 dBm

Note 1: The EUT information are declared by manufacturer. For more detailed features description, please refer to the manufacturer's specifications or user's manual.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2 (10-1-18 Edition)	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 22 Subpart H (10-1-18 Edition)	Cellular Radiotelephone Service
3	47 CFR Part 24 Subpart E (10-1-18 Edition)	Broadband PCS
4	47 CFR Part 27 (10-1-18 Edition)	Miscellaneous Wireless Communications Services
5	RSS-Gen Issue5 (March 2019)	General Requirements and Information for the Certification of Radio Apparatus
6	RSS-130 Issue2 (February 2019)	Equipment Operating in the Frequency Bands 617-652 MHz, 663-698 MHz, 698-756 MHz and 777-787 MHz
7	RSS-132 Issue3 (January 2013)	Cellular Telephone Systems Operating in the Bands 824-849 MHz and 869-894 MHz
8	RSS-133 Issue6 (January 2018)	2 GHz Personal Communications Services
9	RSS-139 Issue3 (July 2015)	Advanced Wireless Services (AWS) Equipment Operating in the Bands 1710-1780 MHz and 2110-2180 MHz
10	RSS-199 Issue3 (December 2016)	Broadband Radio Service (BRS) Equipment Operating in the Band 2500-2690 MHz
11	ANSI/TIA-603-E-2016	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
12	KDB 971168 D01 v03r01	Measurement Guidance for Certification of Licensed Digital Transmitters

3.2 Test Verdict

No.	Description	FCC Part No.	ISED Part No.	Test Result	Verdict
1	Conducted RF Output Power	2.1046	RSS-Gen 6.12 RSS-130 4.6 RSS-132 5.4 RSS-133 6.4 RSS-139 6.5 RSS-199 4.4	Reporting only (ANNEX A.1)	Pass
2	Effective (Isotropic) Radiated Power	2.1046 22.913 24.232 27.50	RSS-Gen 6.12 RSS-130 4.6 RSS-132 5.4 RSS-133 6.4 RSS-139 6.5 RSS-199 4.4	ANNEX A.1	Pass
3	Peak to Average Radio	2.1046 24.232(d) 27.50(d)	RSS-130 4.6 RSS-132 5.4 RSS-133 6.4 RSS-139 6.5 RSS-199 4.4	ANNEX A.2	Pass
4	Occupied Bandwidth	2.1049 22.917 24.238 27.53	RSS-Gen 6.7	ANNEX A.3	Pass
5	Frequency Stability	2.1055 22.355 24.235 27.54	RSS-Gen 6.11 RSS-130 4.5 RSS-132 5.3 RSS-133 6.3 RSS-139 6.4 RSS-199 4.3	ANNEX A.4	Pass
6	Spurious Emission at Antenna Terminals	2.1051 22.917 24.238 27.53	RSS-Gen 6.13 RSS-130 4.7 RSS-132 5.5 RSS-133 6.5 RSS-139 6.6 RSS-199 4.5	ANNEX A.5	Pass
7	Band Edge	2.1051 22.917 24.238 27.53	RSS-130 4.7 RSS-132 5.5 RSS-133 6.5 RSS-139 6.6 RSS-199 4.5	ANNEX A.6	Pass
8	Field Strength of Spurious Radiation	2.1053 22.917 24.238 27.53	RSS-Gen 6.13 RSS-130 4.7 RSS-132 5.5 RSS-133 6.5 RSS-139 6.6	ANNEX A.7	Pass

No.	Description	FCC Part No.	ISED Part No.	Test Result	Verdict
			RSS-199 4.5		
9	Receiver Spurious Emissions	N/A	RSS-Gen 7 RSS-132 5.6 RSS-133 6.6	ANNEX A.8	Pass
10	AC Power-line Conducted Emissions	N/A	RSS-Gen 8.8	ANNEX A.9	Pass

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the environmental conditions were within the listed ranges:

Test Voltage of the EUT	NV (Normal Voltage)	DC 3.85 V
	LV (Low Voltage)	DC 3.4 V
	HV (High Voltage)	DC 4.4 V
Test Temperature of the EUT	NT (Normal Temperature)	+25 °C
	LT (Low Temperature)	-30 °C
	HT (High Temperature)	+50 °C

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Software /Firmware Version	Cal. Date	Cal. Due
Conducted Test System						
Test Software 1	R&S	CMUgo	N/A	V2.0.1	N/A	N/A
Test Software 2	R&S	CMWRun	N/A	V1.8.9	N/A	N/A
Test Software 3	BALUN	BL410R	N/A	V2.1.1.38 7	N/A	N/A
Universal Radio Communication Tester	R&S	CMU 200	119280	V5.13	2020.02.19	2021.02.18
Wideband Radio Communication Tester	R&S	CMW 500	127794	V3.5.137	2019.06.13	2020.06.12
Wideband Radio Communication Tester	R&S	CMW 500	120598		2020.06.08	2021.06.07
Spectrum Analyzer	R&S	FSV-30	103118	V3.5.137	2020.02.19	2021.02.18
Spectrum Analyzer	Agilent	E4440A	MY45304434	A.11.21	2019.10.30	2020.10.29
Spectrum Analyzer	Agilent	E4440A	MY46181663	A.11.21	2019.10.30	2020.10.29
Temperature Chamber	AHK	SP20	1412	N/A	2019.06.24	2020.06.23
DC Power Supply	ITECH	IT6863A	6000140106 87210020		2020.06.08	2021.06.07
Power Sensor	Agilent	E9304A H18	MY41497164	N/A	2019.10.30	2020.10.29
Power Splitter	KMW	DCPD-LDC	1305003215	N/A	N/A	N/A
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	N/A	N/A	N/A

Description	Manufacturer	Model	Serial No.	Software /Firmware Version	Cal. Date	Cal. Due
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	N/A	N/A	N/A
Radiated Test System						
Test Software	BALUN	BL410_E	N/A	V16.921	N/A	N/A
Test Antenna-Bi-Log(30 MHz-3 GHz)	Schwarzbeck	VULB 9163	9163-624	N/A	2018.08.22	2020.08.21
Test Antenna-Horn(1-18 GHz)	Schwarzbeck	BBHA 9120D	9120D-1600	N/A	2018.07.11	2020.07.10
Test Antenna-Horn(18-40 GHz)	A-INFO	LB-180400KF	J211060273	N/A	2019.01.05	2021.01.04
Anechoic Chamber	YIHENG	9m*6m*6m	#3	N/A	2018.07.18	2021.07.17
Shielded Enclosure	ChangNing	CN-130701	130703	N/A	N/A	N/A
EMI Receiver	KEYSIGHT	N9038A	MY53220118	A.14.16	2019.10.29	2020.10.28
Spectrum Analyzer	R&S	FSV-30	103118	2.30.SP1	2019.06.13	2020.06.12
					2020.06.08	2021.06.07
Wideband Radio Communication Tester	R&S	CMW 500	127794	V3.2.73	2019.06.13	2020.06.12
					2020.06.08	2021.06.07

4.3 Test Configurations

Test Items	Test Mode	Test Channel		
		LCH	MCH	HCH
Effective (Isotropic) Radiated Power	GSM 850	v	v	v
	GSM 1900	v	v	v
	GPRS 850	v	v	v
	GPRS 1900	v	v	v
	EGPRS 850	v	v	v
	EGPRS 1900	v	v	v
	WCDMA Band 2	v	v	v
	WCDMA Band 4	v	v	v
	WCDMA Band 5	v	v	v
	HSDPA Band 2	v	v	v
	HSDPA Band 4	v	v	v
	HSDPA Band 5	v	v	v
	HSUPA Band 2	v	v	v
	HSUPA Band 4	v	v	v
	HSUPA Band 5	v	v	v
Peak to Average Ratio	WCDMA Band 2	v	v	v
	WCDMA Band 4	v	v	v
	WCDMA Band 5	v	v	v
Occupied Bandwidth	GSM 850	v	v	v
	GSM 1900	v	v	v
	EGPRS 850	v	v	v
	EGPRS 1900	v	v	v
	WCDMA Band 2	v	v	v
	WCDMA Band 4	v	v	v
	WCDMA Band 5	v	v	v
Frequency Stability	GSM 850	v	v	v
	GSM 1900	v	v	v
	GPRS 850	v	v	v
	GPRS 1900	v	v	v
	EGPRS 850	v	v	v
	EGPRS 1900	v	v	v
	WCDMA Band 2	v	v	v
	WCDMA Band 4	v	v	v
	WCDMA Band 5	v	v	v
Spurious Emission at Antenna Terminals	GSM 850	v	v	v
	GSM 1900	v	v	v
	EGPRS 850	v	v	v
	EGPRS 1900	v	v	v
	WCDMA Band 2	v	v	v
	WCDMA Band 4	v	v	v
	WCDMA Band 5	v	v	v

Test Items	Test Mode	Test Channel		
		LCH	MCH	HCH
Band Edge	GSM 850	v	--	v
	GSM 1900	v	--	v
	EGPRS 850	v	--	v
	EGPRS 1900	v	--	v
	WCDMA Band 2	v	--	v
	WCDMA Band 4	v	--	v
	WCDMA Band 5	v	--	v
Field Strength of Spurious Radiation	GSM 850	v	v	v
	GSM 1900	v	v	v
	EGPRS 850	v	v	v
	EGPRS 1900	v	v	v
	WCDMA Band 2	v	v	v
	WCDMA Band 4	v	v	v
	WCDMA Band 5	v	v	v

Note 1: The mark "v" means that this configuration is chosen for testing.

Test Mode	UL Channel	UL Channel No.	UL Frequency (MHz)
GSM/GPRS/EGPRS 850	Low Channel	128	824.2
	Middle Channel	190	836.6
	High Channel	251	848.8
GSM/GPRS/EGPRS 1900	Low Channel	512	1850.2
	Middle Channel	661	1880.0
	High Channel	810	1909.8
WCDMA Band 2	Low Channel	9262	1852.4
	Middle Channel	9400	1880.0
	High Channel	9538	1907.6
WCDMA Band 4	Low Channel	1312	1712.4
	Middle Channel	1412	1732.4
	High Channel	1513	1752.6
WCDMA Band 5	Low Channel	4132	826.4
	Middle Channel	4182	836.4
	High Channel	4233	846.6

LTE Band	Bandwidth (MHz)						Modulation Type		RB#			Test Channel		
	1.4	3	5	10	15	20	QPSK	16-QAM	1	Half	Full	LCH	MCH	HCH
Effective (Isotropic) Radiated Power														
2	v	v	v	v	v	v	v	v	v	v	v	v	v	v
4	v	v	v	v	v	v	v	v	v	v	v	v	v	v
5	v	v	v	v	n	n	v	v	v	v	v	v	v	v
7	n	n	v	v	v	v	v	v	v	v	v	v	v	v
12	v	v	v	v	n	n	v	v	v	v	v	v	v	v
Peak to Average Ratio														
2	--	--	--	--	--	v	v	v	v	--	v	v	v	v
4	--	--	--	--	--	v	v	v	v	--	v	v	v	v
5	--	--	--	v	n	n	v	v	v	--	v	v	v	v
7	n	n	--	--	--	v	v	v	v	--	v	v	v	v
12	--	--	--	v	n	n	v	v	v	--	v	v	v	v
Occupied Bandwidth														
2	v	v	v	v	v	v	v	v	--	--	v	v	v	v
4	v	v	v	v	v	v	v	v	--	--	v	v	v	v
5	v	v	v	v	n	n	v	v	--	--	v	v	v	v
7	n	n	v	v	v	v	v	v	--	--	v	v	v	v
12	v	v	v	v	n	n	v	v	--	--	v	v	v	v
Frequency Stability														
2	--	--	--	v	--	--	v	v	--	--	v	--	v	--
4	--	--	--	v	--	--	v	v	--	--	v	--	v	--
5	--	--	--	v	n	n	v	v	--	--	v	--	v	--
7	n	n	--	v	--	--	v	v	--	--	v	--	v	--
12	--	--	--	v	n	n	v	v	--	--	v	--	v	--
Spurious Emission at Antenna Terminals														
2	v	v	v	v	v	v	v	v	v	--	--	v	v	v
4	v	v	v	v	v	v	v	v	v	--	--	v	v	v
5	v	v	v	v	n	n	v	v	v	--	--	v	v	v
7	n	n	v	v	v	v	v	v	v	--	--	v	v	v
12	v	v	v	v	n	n	v	v	v	--	--	v	v	v
Band Edge														
2	v	v	v	v	v	v	v	v	v	--	v	v	--	v
4	v	v	v	v	v	v	v	v	v	--	v	v	--	v
5	v	v	v	v	n	n	v	v	v	--	v	v	--	v
7	n	n	v	v	v	v	v	v	v	--	v	v	--	v
12	v	v	v	v	n	n	v	v	v	--	v	v	--	v
Field Strength of Spurious Radiation														
2	v	v	v	v	v	v	v	--	v	--	--	--	v	--
4	v	v	v	v	v	v	v	--	v	--	--	--	v	--
5	v	v	v	v	n	n	v	--	v	--	--	--	v	--
7	n	n	v	v	v	v	v	--	v	--	--	--	v	--

LTE Band	Bandwidth (MHz)						Modulation Type		RB#			Test Channel		
	1.4	3	5	10	15	20	QPSK	16-QAM	1	Half	Full	LCH	MCH	HCH
12	v	v	v	v	n	n	v	--	v	--	--	--	v	--

Note 1: The mark "v" means that this configuration is chosen for testing.

Note 2: The mark "n" means that this bandwidth is not supported.

Note 3: The EUT does not support some RB configurations. (for example: ≥ 10 MHz Bandwidth 16QAM mode Full RB and ≥ 15 MHz Bandwidth 16QAM mode Half RB)

Test Mode	UL Channel	Channel Bandwidth (MHz)	UL Channel No.	UL Frequency (MHz)
LTE Band 2	Low Range	1.4	18607	1850.7
		3	18615	1851.5
		5	18625	1852.5
		10	18650	1855
		15	18675	1857.5
		20	18700	1860
	Middle Range	1.4/3/5/10/15/20	18900	1880
	High Range	1.4	19193	1909.3
		3	19185	1908.5
		5	19175	1907.5
		10	19150	1905
		15	19125	1902.5
		20	19100	1900
LTE Band 4	Low Range	1.4	19957	1710.7
		3	19965	1711.5
		5	19975	1712.5
		10	20000	1715
		15	20025	1717.5
		20	20050	1720
	Middle Range	1.4/3/5/10/15/20	20175	1732.5
	High Range	1.4	20393	1754.3
		3	20385	1753.5
		5	20375	1752.5
		10	20350	1750
		15	20325	1747.5
		20	20300	1745
LTE Band 5	Low Range	1.4	20407	824.7
		3	20415	825.5
		5	20425	826.5
		10	20450	829
	Middle Range	1.4/3/5/10	20525	836.5
	High Range	1.4	20643	848.3


Test Mode	UL Channel	Channel Bandwidth (MHz)	UL Channel No.	UL Frequency (MHz)
		3	20635	847.5
		5	20625	846.5
		10	20600	844
LTE Band 7	Low Range	5	20775	2502.5
		10	20800	2505
		15	20825	2507.5
		20	20850	2510
	Middle Range	5/10/15/20	21100	2535
	High Range	5	21425	2567.5
		10	21400	2565
		15	21375	2562.5
		20	21350	2560
LTE Band 12	Low Range	1.4	23017	699.7
		3	23025	700.5
		5	23035	701.5
		10	23060	704
	Middle Range	1.4/3/5/10	23095	707.5
	High Range	1.4	23173	715.3
		3	23165	714.5
		5	23155	713.5
		10	23130	711

Test Items	Test Mode	Test Channel		
		LCH	MCH	HCH
Receiver Spurious Emissions	GSM 850	--	v	--
AC Power-line Conducted Emissions	GSM 850	--	v	--

Note 1: The mark "v" means that this configuration is the worst test mode for Receiver Spurious Emissions and AC Power-line Conducted Emissions measurement.


4.4 Test Setup

4.4.1 For Antenna Port Test




(Diagram 1)

4.4.2 For Frequency Stability Test




(Diagram 2)

4.4.3 For Radiated Test (30 MHz ~ 1 GHz)



(Diagram 3)

4.4.4 For Radiated Test (Above 1 GHz)



(Diagram 4)

5 TEST ITEMS

5.1 Transmitter Radiated Power (EIRP/ERP)

5.1.1 Limit

FCC § 2.1046 & 22.913(a) & 24.232(c) & 27.50(b) & 27.50(c) & 27.50(d) & 27.50(h)

According to FCC section 22.913(a) (5), the Effective Radiated Power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC section 24.232(c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to FCC section 27.50(b) (10), portable stations (hand-held devices) transmitting in the 746-757MHz, 776-788MHz, and 805-806MHz bands are limited to 3 watts ERP.

FCC section 27.50(c) (10), portable stations (hand-held devices) in the 600MHz uplink band and the 698-746MHz band, and fixed and mobile stations in the 600MHz uplink band are limited to 3 watts ERP.

FCC section 27.50(d) (4), fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

(7) Fixed, mobile, and portable (hand-held) stations operating in the 2000-2020 MHz band are limited to 2 watts EIRP.

And FCC section 27.50(h) (2), for mobile and other user stations, mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

RSS-Gen § 6.12 & RSS-130 § 4.6 & RSS-132 § 5.4 & RSS-133 § 6.4 & RSS-139 § 6.5 & RSS-199 § 4.4

According to RSS-130 § 4.6.3, The e.r.p. shall not exceed 30 watts for mobile equipment and outdoor fixed subscriber equipment. The e.r.p. shall not exceed 3 watts for portable equipment and indoor fixed subscriber equipment.

According to RSS-132 § 5.4, the Effective Radiated Power (ERP) for mobile equipment shall not exceed 11.5 watts.

According to RSS-133 § 6.4 (SRSP 510), mobile stations and hand-held portables are limited to 2 watts maximum EIRP.

According to RSS-139 § 6.5, the EIRP for mobile and portable transmitters shall not exceed 1 watt.

According to RSS-199 § 4.4, for mobile subscriber equipment, the EIRP shall not exceed 2 watts.

5.1.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description is used for conducted test, and the section 4.4.3 and 4.4.4 (Diagram 3, 4) test setup description is used for radiated test. The photo of test setup please refer to ANNEX B.

5.1.3 Test Procedure

Description of the Conducted Output Power Measurement

The EUT is coupled to the SS with attenuator through power splitter; the RF load attached to EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. A system simulator is used to establish communication with the EUT, and its parameters are set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The relevant equation for determining the conducted measured value is:

$$\text{Conducted Output Power Value (dBm)} = \text{Measured Value (dBm)} + \text{Path Loss (dB)}$$

where:

Conducted Output Power Value = final conducted measured value in the conducted power test, in dBm;

Measured Value = measured conducted power received by spectrum analyzer or power meter, in dBm;

Path Loss = signal attenuation in the connecting cable between the transmitter and spectrum analyzer or power meter, including external cable loss, in dB;

During the test, the data of Path Loss (dB) is added in the spectrum analyzer or power meter, so Measured Value (dBm) is the final values which contains the data of Path Loss (dB).

For example:

In the conducted output power test, when measured value for GSM850 is 24.7 dBm, and path loss is 8.5 dB, then final conducted output power value is:

$$\text{Conducted Output Power Value (dBm)} = 24.7 \text{ dBm} + 8.5 \text{ dB} = 33.2 \text{ dBm}$$

Description of the Transmitter Radiated Power Measurement

In many cases, the RF output power limits for licensed digital transmission devices is specified in terms of effective radiated power (ERP) or equivalent isotropic radiated power (EIRP). Typically, ERP is specified when the operating frequency is less than or equal to 1 GHz and EIRP is specified when the operating frequency is greater than 1 GHz. Both are determined by adding the transmit antenna gain to the conducted RF output power with the primary difference between the two being that when determining the ERP, the transmit antenna gain is referenced to a dipole antenna (i.e., dBd) whereas when determining the EIRP, the transmit antenna gain is referenced to an isotropic antenna (dBi).

Final measurement calculation as below:

The relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP/EIRP} = P_{\text{Meas}} + GT - LC$$

where:

ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

dBd (ERP)=dBi (EIRP) -2.15 dB

LC = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

For devices utilizing multiple antennas, KDB 662911 provides guidance for determining the effective array transmit antenna gain term to be used in the above equation.

For example:

In the EIRP test, when P_{Meas} value for GSM1900 is 30.2 dBm, LC is 0.6 dB, and GT is -3.4 dB, then final EIRP value is:

EIRP for GSM1900 = 30.2 dBm - 3.4 dBi - 0.6 dB = 26.2 dBm

The relevant equation for determining the ERP/EIRP from the radiated RF output power is:

ERP/EIRP (dBm) = SA Read Value (dBm) + Correction Factor (dB)

where:

ERP/EIRP = effective or equivalent radiated power, in dBm;

SA Read Value = measured transmitter power received by EMI receiver or spectrum analyzer, in dBm;

Correction Factor = total correction factor including cable loss, in dB;

During the test, the data of Correction Factor (dB) is added in the EMI receiver or spectrum analyzer, so SA Read Value (dBm) is the final values which contains the data of Correction Factor (dB).

For example:

In the ERP test, when SA read value for GSM850 is 21dBm, and correction factor is 8dB, then final ERP value for GSM850 is:

ERP (dBm) = 21dBm + 8dB = 29dBm

5.1.4 Test Result

Please refer to ANNEX A.1.

5.2 Peak to Average Ratio

5.2.1 Limit

FCC § 2.1046 & 24.232(d) & 27.50(d)

RSS-130 § 4.6 & RSS-132 § 5.4 & RSS-133 § 6.4 & RSS-139 § 6.5 & RSS-199 § 4.4

In addition, when the transmitter power is measured in terms of average value, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.

According to FCC section 24.232(d), power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with 24.232 (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of § 24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

FCC section 24.232(e), peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

According to FCC section 27.50(d) (5), in measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13dB.

5.2.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description is used for this test. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Here the lowest, middle and highest channels are selected to perform testing to verify the peak-to-average ratio.

According to KDB 971168 D01, there is CCDF procedure for PAPR:

- a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval as follows:
 - 1) for continuous transmissions, set to 1 ms,
 - 2) for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.

e) Record the maximum PAPR level associated with a probability of 0.1%.

Alternate procedure for PAPR:

Use one of the procedures presented in 4.1 to measure the total peak power and record as P_{Pk} . Use one of the applicable procedures presented 4.2 to measure the total average power and record as P_{Avg} . Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$\text{PAPR (dB)} = P_{Pk} (\text{dBm}) - P_{Avg} (\text{dBm}).$$

5.2.4 Test Result

Please refer to ANNEX A.2.

5.3 Occupied Bandwidth

5.3.1 Limit

FCC § 2.1049

RSS-Gen § 6.7

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.

Many of the individual rule parts specify a relative OBW in lieu of the 99% OBW. In such cases, the OBW is defined as the width of the signal between two points, one below the carrier center frequency and on above the carrier center frequency, outside of which all emissions are attenuated by at least X dB below the transmitter power, where the value of X is typically specified as 26.

5.3.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description is used for this test. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The following procedure shall be used for measuring power bandwidth.

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the anticipated OBW).
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- c) Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least $10\log(\text{OBW} / \text{RBW})$ below the reference level.
- d) NOTE—Steps a) through c) may require iteration to adjust within the specified tolerances.
- e) For -26 dB OBW, the dynamic range of the spectrum analyzer at the selected RBW shall be at least 10dB below the target “-X dB down” requirement, e.g. -26 dB OBW, the spectrum analyzer noise floor at the selected RBW shall be 36dB below the reference value.
- f) Set the detection mode to peak, and the trace mode to max hold.
- g) For 99% OBW, use the 99 % power bandwidth function of the spectrum analyzer (if available) and report the measured bandwidth.

If the instrument does not have a 99 % power bandwidth function, the trace data points are to be recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency.

The 99 % power bandwidth is the difference between these two frequencies.

h) For -26 dB OBW, determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).

Determine the “-X dB down amplitude” as equal to (reference value -X). Alternatively, this calculation can be performed by the analyzer by using the marker-delta function.

Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below “-X dB down amplitude” determined in step g). If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.

i) The OBW shall be reported by providing plot(s) of the measuring instrument display. The frequency and amplitude axes and scale shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

j) Change variable modulations, coding, or channel bandwidth settings, then repeat above test procedures.

5.3.4 Test Result

Please refer to ANNEX A.3.

5.4 Frequency Stability

5.4.1 Limit

FCC § 2.1055 & 22.355 & 24.235 & 27.54

RSS-Gen § 6.11 & RSS-130 § 4.5 & RSS-132 § 5.3 & RSS-133 § 6.3 & RSS-139 § 6.4 & RSS-199 § 4.3

FCC § 2.1055 & RSS-Gen § 6.11

The frequency stability shall be measured with variation of ambient temperature as follows:

(1) The temperature is varied from -30°C to +50°C.

(2) Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than 10°C through the range.

The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating and point which shall be specified by the manufacturer.

(3) The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

FCC § 22.355

Except as otherwise provided in this part, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table C-1 of this section.

Table C-1—Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency range (MHz)	Base, fixed (ppm)	Mobile > 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	n/a	n/a
929 to 960	1.5	n/a	n/a
2110 to 2220	10.0	n/a	n/a

FCC § 24.235

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

FCC § 27.54

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

RSS-130 § 4.5

The frequency stability shall be sufficient to ensure that the occupied bandwidth remains within each frequency block range when tested at the temperature and supply voltage variations specified in RSS-Gen.

RSS-132 § 5.3

The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations and ± 1.5 ppm for base stations.

RSS-133 § 6.3

The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations and ± 1.0 ppm for base stations.

RSS-139 § 6.4

The frequency stability shall be sufficient to ensure that the occupied bandwidth stays within the operating frequency block when tested to the temperature and supply voltage variations specified in RSS-Gen.

RSS-199 § 4.3

The frequency stability shall be sufficient to ensure that the occupied bandwidth stays within the operating frequency block when tested to the temperature and supply voltage variations specified in RSS-Gen.

5.4.2 Test Setup

The section 4.4.2 (Diagram 2) test setup description is used for this test. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

1. The EUT is placed in a temperature chamber.
2. The temperature is set to 25°C and allowed to stabilize. After sufficient soak time, the transmitting frequency error is measured.
3. The temperature is increased by not more than 10 degrees, allowed to stabilize and soak, and then repeat the frequency error measurement.
4. Repeat procedure 3 until +50°C and -30°C is reached.
5. Change supply voltage, and repeat measurement until extreme voltage is reached.

5.4.4 Test Result

Please refer to ANNEX A.4.

5.5 Spurious Emission at Antenna Terminals

5.5.1 Limit

FCC § 2.1051 & 22.917(a) & 24.238(a) & 27.53(c) & 27.53(f) & 27.53(g) & 27.53(h) & 27.53(m)

RSS-Gen § 6.13 & RSS-130 § 4.7 & RSS-132 § 5.5 & RSS-133 § 6.5 & RSS-139 § 6.6 & RSS-199 § 4.5

In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

FCC § 22.917(a) & 24.238(a) & RSS-132 § 5.5 & RSS-133 § 6.5

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. This is calculated to be -13 dBm.

FCC § 27.53(c)

For operations in the 746–758 MHz band and the 776–788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746–758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;
- (2) On any frequency outside the 776–788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;
- (3) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $76 + 10 \log(P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

- (6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

FCC § 27.53(f)

For operations in the 746–758 MHz, 775–788 MHz, and 805–806 MHz bands, emissions in the band 1559–1610 MHz shall be limited to - 70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and - 80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

FCC § 27.53(g)

For operations in the 600MHz band and the 698-746MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43+10\log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

FCC § 27.53(h) (1) & RSS-139 § 6.6

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

FCC § 27.53(m) (4) & RSS-199 § 4.5

For mobile digital stations (BRS and EBS stations), the attenuation factor shall be not less than:

- $40+10\log P$ dB (-10 dBm, 100 nW) on all frequencies between the channel edge and 5 MHz from the channel edge.
- $43+10\log P$ dB (-13 dBm, 50 nW) on all frequencies between 5 MHz and X MHz from the channel edge,
- $55+10\log P$ dB (-25 dBm, 3 nW) on all frequencies more than X MHz from the channel edge, where X is the greater of 6 MHz or the actual emission bandwidth (26 dB).

In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

RSS-130 § 4.7

The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10\log_{10}(P)$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.

In addition to the limit outlined above, equipment operating in the frequency bands 746-756 MHz and 777-787 MHz shall also comply with the following restrictions:

(a) The power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least:

- (i) $76 + 10 \log_{10} p$ (watts), dB, for base and fixed equipment and
- (ii) $65 + 10 \log_{10} p$ (watts), dB, for mobile and portable equipment

(b) The e.i.r.p. in the band 1559-1610 MHz shall not exceed -70 dBW/MHz for wideband signal and -80 dBW for discrete emission with bandwidth less than 700 Hz.

5.5.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency blocks a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

1. The EUT is coupled to the system simulator and spectrum analyzer; the RF load attached to EUT antenna terminal is 50Ohm ; the path loss as the factor is calibrated to correct the reading.
2. CMW500 is used to establish communication with the EUT, and its parameters are set to force the EUT transmitting at maximum output power.
3. The RF output of the transmitter is connected to the input of the spectrum analyzer through sufficient attenuation.
4. Spurious emissions are tested with 0.001MHz RBW for frequency less than 150kHz, 0.01MHz RBW for frequency less than 30MHz, 0.1MHz RBW for frequency less than 1GHz, and 1MHz RBW for frequency above 1GHz. And sweep point number are at least 401, referring to following formula.

Sweep point number = Span/RBW

$\text{VBW} = 3 * \text{RBW}$

Detector Mode=mean or average power

5. Record the frequencies and levels of spurious emissions.

5.5.4 Test Result

Please refer to ANNEX A.5.

5.6 Band Edge

5.6.1 Limit

FCC § 2.1051 & 22.917(a) & 24.238(a) & 27.53(c) & 27.53(g) & 27.53(h) & 27.53(m)

RSS-130 § 4.7 & RSS-132 § 5.5 & RSS-133 § 6.5 & RSS-139 § 6.6 & RSS-199 § 4.5

In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

FCC § 22.917(a) & 24.238(a) & RSS-132 § 5.5 & RSS-133 § 6.5

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. This is calculated to be -13 dBm.

FCC § 27.53(c)

For operations in the 746–758 MHz band and the 776–788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746–758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;
- (2) On any frequency outside the 776–788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;
- (3) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $76 + 10 \log(P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

- (6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

FCC § 27.53(g)

For operations in the 600MHz band and the 698-746MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43+10\log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

FCC § 27.53(h) (1) & RSS-139 § 6.6

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

FCC § 27.53(m) (4) & RSS-199 § 4.5

For mobile digital stations (BRS and EBS stations), the attenuation factor shall be not less than:

- $40+10\log P$ dB (-10 dBm, 100 nW) on all frequencies between the channel edge and 5 MHz from the channel edge.
- $43+10\log P$ dB (-13 dBm, 50 nW) on all frequencies between 5 MHz and X MHz from the channel edge,
- $55+10\log P$ dB (-25 dBm, 3 nW) on all frequencies more than X MHz from the channel edge, where X is the greater of 6 MHz or the actual emission bandwidth (26 dB).

In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

RSS-130 § 4.7

The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10\log_{10}(P)$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.

In addition to the limit outlined above, equipment operating in the frequency bands 746 - 756 MHz and 777 - 787 MHz shall also comply with the following restrictions:

- (a) The power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763 - 775 MHz and 793 - 806 MHz shall be attenuated below the transmitter power, P (dBW), by at least:
 - (i) $76 + 10 \log_{10} p$ (watts), dB, for base and fixed equipment and
 - (ii) $65 + 10 \log_{10} p$ (watts), dB, for mobile and portable equipment

(b) The e.i.r.p. in the band 1559-1610 MHz shall not exceed -70 dBW/MHz for wideband signal and -80 dBW for discrete emission with bandwidth less than 700 Hz.

5.6.2 Test Setup

The section 4.4.1 (Diagram 1) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The EUT, which is powered by the Battery, is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading.

1. The EUT is coupled to the system simulator and spectrum analyzer; the RF load attached to EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading.
2. CMW500 is used to establish communication with the EUT, and its parameters are set to force the EUT transmitting at maximum output power.
3. The RF output of the transmitter is connected to the input of the spectrum analyzer through sufficient attenuation.
4. The center of the spectrum analyzer was set to block edge frequency.
5. Band edge are tested with 1%*cBW (RBW), and sweep point number referred to following formula.

$$\text{Sweep point number} = 2 * \text{Span/RBW}$$

$$\text{VBW} = 3 \text{RBW}$$

6. Record the frequencies and levels of spurious emissions.

For mobile and portable stations, on all frequencies between 763–775 MHz and 793–806 MHz, by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment. Since it was not possible to set the resolution bandwidth to 6.25 kHz with the available equipment, a bandwidth of 10 kHz was used instead to show compliance. By using a 10 kHz bandwidth on the spectrum analyzer.

$$10 * \log(10 \text{ kHz} / 6.25 \text{ kHz}) = 2.04 \text{ dB}$$

$$\text{Limit Line} = -35 \text{ dBm} + 2.04 \text{ dB} = -32.96 \text{ dBm}$$

5.6.4 Test Result

Please refer to ANNEX A.6.

5.7 Field Strength of Spurious Radiation

5.7.1 Limit

FCC § 2.1053 & 22.917(a) & 24.238(a) & 27.53(c) & 27.53(f) & 27.53(g) & 27.53(h) & 27.53(m)

RSS-Gen § 6.13 & RSS-130 § 4.7 & RSS-132 § 5.5 & RSS-133 § 6.5 & RSS-139 § 6.6 & RSS-199 § 4.5

FCC § 22.917(a) & 24.238(a) & RSS-132 § 5.5 & RSS-133 § 6.5

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10\log(P)$ dB. This is calculated to be -13 dBm.

FCC § 27.53(c)

For operations in the 746–758 MHz band and the 776–788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746–758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
- (2) On any frequency outside the 776–788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
- (3) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763–775 MHz and 793–805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater.

However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

- (6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

FCC § 27.53(f)

For operations in the 746–758 MHz, 775–788 MHz, and 805–806 MHz bands, emissions in the band 1559–1610 MHz shall be limited to - 70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and - 80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

FCC § 27.53(g)

For operations in the 600MHz band and the 698-746MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43+10\log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

FCC § 27.53(h) (1) & RSS-139 § 6.6

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

FCC § 27.53(m) (4) & RSS-199 § 4.5

For mobile digital stations (BRS and EBS stations), the attenuation factor shall be not less than:

- $40+10\log P$ dB (-10 dBm, 100 nW) on all frequencies between the channel edge and 5 MHz from the channel edge.
- $43+10\log P$ dB (-13 dBm, 50 nW) on all frequencies between 5 MHz and X MHz from the channel edge,
- $55+10\log P$ dB (-25 dBm, 3 nW) on all frequencies more than X MHz from the channel edge, where X is the greater of 6 MHz or the actual emission bandwidth (26 dB).

In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

RSS-130 § 4.7

The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10\log_{10}(P)$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.

In addition to the limit outlined above, equipment operating in the frequency bands 746 - 756 MHz and 777 - 787 MHz shall also comply with the following restrictions:

- (a) The power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763 - 775 MHz and 793 - 806 MHz shall be attenuated below the transmitter power, P (dBW), by at least:
 - (i) $76 + 10 \log_{10} p$ (watts), dB, for base and fixed equipment and
 - (ii) $65 + 10 \log_{10} p$ (watts), dB, for mobile and portable equipment
- (b) The e.i.r.p. in the band 1559 - 1610 MHz shall not exceed -70 dBW/MHz for wideband signal and -80 dBW for

discrete emission with bandwidth less than 700 Hz.

5.7.2 Test Setup

The section 4.4.3 and 4.4.4 (Diagram 3, 4) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

1. On a test site, the EUT shall be placed at 80cm height on a turn table, and in the position close to normal use as declared by the applicant.
2. The test antenna shall be oriented initially for vertical polarization located 3 m from EUT to correspond to the fundamental frequency of the transmitter.
3. The output of the test antenna shall be connected to the measuring receiver and the peak detector is used for the measurement.
4. During the measurement of the EUT, the resolution bandwidth was to 1 MHz and the average bandwidth was set to 1 MHz.
5. The transmitter shall be switched on; the measuring receiver shall be tuned to the frequency of the transmitter under test.
6. The test antenna shall be raised and lowered through the specified range of height until the maximum signal level is detected by the measuring receiver.
7. The transmitter shall be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
8. The test antenna shall be raised and lowered again through the specified range of height until the maximum signal level is detected by the measuring receiver.
9. The maximum signal level detected by the measuring receiver shall be noted.
10. The EUT was replaced by half-wave dipole (824 ~ 849 MHz) or horn antenna (1 850 ~ 1 910 MHz) connected to a signal generator.
11. In necessary, the input attenuator setting on the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
12. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
13. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring received, which is equal to the level noted while the transmitter radiated

power was measured, corrected for the change of input attenuator setting of the measuring receiver.

14. The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.

15. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.

Final measurement calculation as below:

The relevant equation for determining the ERP/EIRP from the radiated RF output power is:

$$\text{ERP/EIRP (dBm)} = \text{SA Read Value (dBm)} + \text{Correction Factor (dB)}$$

where:

ERP/EIRP = effective or equivalent radiated power, in dBm;

SA Read Value = measured transmitter power received by EMI receiver or spectrum analyzer, in dBm;

Correction Factor = total correction factor including cable loss, in dB;

During the test, the data of Correction Factor (dB) is added in the EMI receiver or spectrum analyzer, so SA Read Value (dBm) is the final values which contains the data of Correction Factor (dB).

For example:

In the ERP test, when SA read value for GSM850 is 21dBm, and correction factor is 8dB, then final ERP value for GSM850 is:

$$\text{ERP (dBm)} = 21\text{dBm} + 8\text{dB} = 29\text{dBm}$$

5.7.4 Test Result

Please refer to ANNEX A.7.

5.8 Receiver Spurious Emissions

5.8.1 Limit

RSS-Gen § 7.3/4 & RSS-132 § 5.6 & RSS-133 § 6.6

For emissions at frequencies below 1 GHz, measurements shall be performed using a CISPR quasi-peak detector and the related measurement bandwidth. At frequencies above 1 GHz, measurements shall be performed using a linear average detector with a minimum resolution bandwidth of 1 MHz.

As an alternative to CISPR quasi-peak or average measurements, compliance with the emission limit can be demonstrated using measuring equipment employing a peak detector function properly adjusted for factors such as pulse desensitization, as required, with a measurement bandwidth equal to, or greater than, the applicable CISPR quasi-peak bandwidth or 1 MHz bandwidth, respectively.

Receiver Radiated Limits

Radiated emission measurements shall be performed with the receiver antenna connected to the receiver antenna ports. The search for spurious emissions shall be from the lowest frequency internally generated or used in the receiver (e.g. local oscillator, intermediate or carrier frequency), or 30 MHz, whichever is higher, to at least five times the highest tunable or local oscillator frequency, whichever is higher, without exceeding 40 GHz.

Spurious emissions from receivers shall not exceed the radiated emissions limits shown in Table 2 below.

Table 2 –Receiver radiated emissions limits

Frequency (MHz)	Field Strength (μ V/m at 3 metres)
30 - 88	100
88 - 216	150
216 - 960	200
Above 960	500

Receiver Conducted Limits

If the receiver has a detachable antenna of known impedance, an antenna-conducted spurious emissions measurement is permitted as an alternative to radiated measurement. However, the radiated method is preferred.

The antenna-conducted test shall be performed with the antenna disconnected and with the receiver antenna port connected to a measuring instrument having equal input impedance to that specified for the antenna. The RF cable connecting the receiver under test to the measuring instrument shall also have the same impedance to that specified for the receiver's antenna.

The spurious emissions from the receiver at any discrete frequency, measured at the antenna port by the antenna-conducted method, shall not exceed 2 nW in the frequency range 30-1000 MHz and 5 nW above 1 GHz.

5.8.2 Test Setup

The section 4.4.3 and 4.4.4 (Diagram 3, 4) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The test employing the methods of measurement described in the publication referenced in Section 3(b) (ANSI C63.4);

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

5.8.4 Test Result

Please refer to ANNEX A.8.

5.9 AC Power-line Conducted Emissions

5.9.1 Limit

RSS-Gen § 8.8

For AC power-line conducted emissions, both quasi-peak and average detectors having the characteristics specified in CAN/CSA-CISPR 16-1-1:15 for the 150 kHz to 30 MHz frequency range shall be employed.

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 3, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 3 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Table 3 –AC power-line conducted emissions limits

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ^{Note1}	56 to 46 ^{Note1}
0.5 - 5	56	46
5 - 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

5.9.2 Test Setup

The section 4.4.5 (Diagram 5) test setup description was used for this test. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The test employing the methods of measurement described in the publication referenced in Section 3(b) (ANSI C63.4);

The EUT is connected to the power mains through a LISN which provides $50\ \Omega/50\ \mu\text{H}$ of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.9.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULTS

A.1 Transmitter Radiated Power (EIRP/ERP)

GSM Mode Test Data

Test Band	Test Channel	Conducted Output Peak Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
GSM 850	LCH	31.10	1	-1.15	29.95	0.989	7.00	Pass
	MCH	31.19	1	-1.15	30.04	1.009	7.00	Pass
	HCH	31.26	1	-1.15	30.11	1.026	7.00	Pass
GPRS 850	LCH	30.88	1	-1.15	29.73	0.940	7.00	Pass
	MCH	30.90	1	-1.15	29.75	0.944	7.00	Pass
	HCH	30.99	1	-1.15	29.84	0.964	7.00	Pass
EGPRS 850	LCH	29.32	1	-1.15	28.17	0.656	7.00	Pass
	MCH	29.32	1	-1.15	28.17	0.656	7.00	Pass
	HCH	29.28	1	-1.15	28.13	0.650	7.00	Pass

Test Band	Test Channel	Conducted Output Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
GSM 1900	LCH	29.51	1	30.51	1.125	2.00	Pass
	MCH	29.28	1	30.28	1.067	2.00	Pass
	HCH	29.98	1	30.98	1.253	2.00	Pass
GPRS 1900	LCH	29.24	1	30.24	1.057	2.00	Pass
	MCH	28.96	1	29.96	0.991	2.00	Pass
	HCH	29.65	1	30.65	1.161	2.00	Pass
EGPRS 1900	LCH	27.25	1	28.25	0.668	2.00	Pass
	MCH	27.27	1	28.27	0.671	2.00	Pass
	HCH	27.90	1	28.90	0.776	2.00	Pass

Note 1: For the GPRS and EGPRS mode, all slots were tested and just the worst data were recorded in this table.

Note 2: $ERP/EIRP = P_{Meas} + GT - LC$

$ERP/EIRP$ = effective or equivalent radiated power, respectively (expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

LC = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

$ERP = EIRP - 2.15$; where ERP and $EIRP$ are expressed in consistent units.

Note 3: Set PCL to 5 for GSM/GPRS 850 (power class 4) and 0 for GSM/GPRS 1900 (power class 1).

Set PCL to 8 for EGPRS850 (power class E2) and 2 for EGPRS1900 (power class E2).

GPRS Conducted Output Power

Band	Channel	Conducted Output Peak Power							
		Slot 1 (dBm)	Slot 1 (W)	Slot 2 (dBm)	Slot 2 (W)	Slot 3 (dBm)	Slot 3 (W)	Slot 4 (dBm)	Slot 4 (W)
GPRS 850	LCH	30.88	1.225	29.97	0.993	29.20	0.833	28.24	0.667
	MCH	30.90	1.230	30.00	0.999	29.19	0.830	28.33	0.681
	HCH	30.99	1.256	30.29	1.069	29.41	0.874	28.43	0.696
GPRS 1900	LCH	29.24	0.839	28.01	0.632	26.85	0.484	26.49	0.446
	MCH	28.96	0.787	28.28	0.674	27.24	0.530	26.44	0.440
	HCH	29.65	0.923	28.72	0.744	27.77	0.598	26.98	0.499

EGPRS Conducted Output Power

Band	Channel	Conducted Output Peak Power							
		Slot 1 (dBm)	Slot 1 (W)	Slot 2 (dBm)	Slot 2 (W)	Slot 3 (dBm)	Slot 3 (W)	Slot 4 (dBm)	Slot 4 (W)
EGPRS 850	LCH	29.32	0.855	29.25	0.841	28.74	0.748	26.58	0.455
	MCH	29.32	0.855	29.14	0.819	28.72	0.745	26.47	0.444
	HCH	29.25	0.841	29.28	0.846	28.73	0.747	26.58	0.455
EGPRS 1900	LCH	27.25	0.531	26.20	0.416	25.74	0.375	25.60	0.363
	MCH	27.27	0.533	26.20	0.416	25.75	0.376	25.55	0.359
	HCH	27.90	0.617	26.81	0.479	26.20	0.417	26.23	0.419

WCDMA Mode Test Data

Test Band	Test Channel	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
WCDMA Band 2	LCH	22.17	1	23.17	0.207	2.00	Pass
	MCH	22.38	1	23.38	0.218	2.00	Pass
	HCH	22.27	1	23.27	0.212	2.00	Pass
HSDPA Band 2	LCH	21.13	1	22.13	0.163	2.00	Pass
	MCH	21.40	1	22.40	0.174	2.00	Pass
	HCH	21.31	1	22.31	0.170	2.00	Pass
HSUPA Band 2	LCH	20.85	1	21.85	0.153	2.00	Pass
	MCH	21.05	1	22.05	0.160	2.00	Pass
	HCH	20.93	1	21.93	0.156	2.00	Pass

Test Band	Test Channel	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
WCDMA Band 4	LCH	21.58	1	22.58	0.181	1.00	Pass
	MCH	21.79	1	22.79	0.190	1.00	Pass
	HCH	21.87	1	22.87	0.194	1.00	Pass
HSDPA Band 4	LCH	20.68	1	21.68	0.147	1.00	Pass
	MCH	20.86	1	21.86	0.153	1.00	Pass
	HCH	20.97	1	21.97	0.157	1.00	Pass
HSUPA Band 4	LCH	20.34	1	21.34	0.136	1.00	Pass
	MCH	20.66	1	21.66	0.147	1.00	Pass
	HCH	20.70	1	21.70	0.148	1.00	Pass

Test Band	Test Channel	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
WCDMA Band 5	LCH	20.83	1	-1.15	19.68	0.093	7.00	Pass
	MCH	20.91	1	-1.15	19.76	0.095	7.00	Pass
	HCH	20.92	1	-1.15	19.77	0.095	7.00	Pass
HSDPA Band 5	LCH	19.64	1	-1.15	18.49	0.071	7.00	Pass
	MCH	19.69	1	-1.15	18.54	0.071	7.00	Pass
	HCH	19.75	1	-1.15	18.60	0.072	7.00	Pass
HSUPA Band 5	LCH	19.62	1	-1.15	18.47	0.070	7.00	Pass
	MCH	19.58	1	-1.15	18.43	0.070	7.00	Pass
	HCH	19.75	1	-1.15	18.60	0.072	7.00	Pass

Note 1: For the HSDPA and HSUPA mode, all subtests were tested and just the worst data were recorded in this table.

Note 2: $ERP/EIRP = P_{Meas} + GT - LC$

$ERP/EIRP$ = effective or equivalent radiated power, respectively (expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

LC = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

$ERP = EIRP - 2.15$; where ERP and EIRP are expressed in consistent units.

HSDPA Conducted Output Power

Band	Channel	Conducted Output Average Power							
		Subtest1		Subtest2		Subtest3		Subtest4	
		(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)
HSDPA Band 2	LCH	21.13	0.130	21.13	0.130	20.70	0.117	20.69	0.117
	MCH	21.40	0.138	21.34	0.136	20.85	0.122	20.82	0.121
	HCH	21.31	0.135	21.25	0.133	20.86	0.122	20.83	0.121
HSDPA Band 4	LCH	20.57	0.114	20.68	0.117	20.14	0.103	20.12	0.103
	MCH	20.86	0.122	20.79	0.120	20.30	0.107	20.28	0.107
	HCH	20.97	0.125	20.96	0.125	20.44	0.111	20.44	0.111
HSDPA Band 5	LCH	19.63	0.092	19.64	0.092	19.14	0.082	19.12	0.082
	MCH	19.69	0.093	19.65	0.092	19.25	0.084	19.24	0.084
	HCH	19.75	0.094	19.71	0.094	19.23	0.084	19.32	0.086

HSUPA Conducted Output Power

Band	Channel	Conducted Output Average Power									
		Subtest1		Subtest2		Subtest3		Subtest4		Subtest5	
		(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)
HSUPA Band 2	LCH	20.42	0.110	19.38	0.087	19.90	0.098	19.55	0.090	20.85	0.122
	MCH	20.14	0.103	19.47	0.089	19.69	0.093	19.56	0.090	21.05	0.127
	HCH	20.21	0.105	19.45	0.088	19.68	0.093	19.46	0.088	20.93	0.124
HSUPA Band 4	LCH	19.60	0.091	18.89	0.077	19.09	0.081	18.75	0.075	20.34	0.108
	MCH	20.62	0.115	18.75	0.075	19.50	0.089	19.12	0.082	20.66	0.116
	HCH	20.20	0.105	19.13	0.082	19.68	0.093	19.45	0.088	20.70	0.117
HSUPA Band 5	LCH	19.05	0.080	17.52	0.056	18.32	0.068	18.32	0.068	19.62	0.092
	MCH	19.33	0.086	17.80	0.060	18.37	0.069	18.07	0.064	19.58	0.091
	HCH	19.42	0.087	17.88	0.061	18.64	0.073	17.97	0.063	19.75	0.094

LTE Mode Test Data

Note: The EUT does not support some RB configurations (for example: $\geq 10\text{MHz}$ Bandwidth 16QAM mode Full RB and $\geq 15\text{MHz}$ Bandwidth 16QAM mode Half RB), all supported RB configurations have been tested.

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND2									
1.4 MHz	LCH	QPSK	RB1#0	22.58	1	23.58	0.228	2.00	Pass
			RB1#3	22.61	1	23.61	0.230	2.00	Pass
			RB1#5	22.47	1	23.47	0.222	2.00	Pass
			RB3#0	22.52	1	23.52	0.225	2.00	Pass
			RB3#2	22.57	1	23.57	0.228	2.00	Pass
			RB3#3	22.53	1	23.53	0.225	2.00	Pass
			RB6#0	21.67	1	22.67	0.185	2.00	Pass
	16-QAM	16-QAM	RB1#0	21.37	1	22.37	0.173	2.00	Pass
			RB1#3	21.63	1	22.63	0.183	2.00	Pass
			RB1#5	21.38	1	22.38	0.173	2.00	Pass
			RB3#0	21.24	1	22.24	0.167	2.00	Pass
			RB3#2	21.49	1	22.49	0.177	2.00	Pass
			RB3#3	21.50	1	22.50	0.178	2.00	Pass
			RB6#0	20.52	1	21.52	0.142	2.00	Pass
	MCH	QPSK	RB1#0	22.45	1	23.45	0.221	2.00	Pass
			RB1#3	22.53	1	23.53	0.225	2.00	Pass
			RB1#5	22.40	1	23.40	0.219	2.00	Pass
			RB3#0	22.52	1	23.52	0.225	2.00	Pass
			RB3#2	22.64	1	23.64	0.231	2.00	Pass
			RB3#3	22.59	1	23.59	0.229	2.00	Pass
			RB6#0	21.60	1	22.60	0.182	2.00	Pass
	16-QAM	16-QAM	RB1#0	21.13	1	22.13	0.163	2.00	Pass
			RB1#3	21.23	1	22.23	0.167	2.00	Pass
			RB1#5	21.10	1	22.10	0.162	2.00	Pass
			RB3#0	21.02	1	22.02	0.159	2.00	Pass
			RB3#2	21.04	1	22.04	0.160	2.00	Pass
			RB3#3	20.98	1	21.98	0.158	2.00	Pass
			RB6#0	20.51	1	21.51	0.142	2.00	Pass
	HCH	QPSK	RB1#0	22.43	1	23.43	0.220	2.00	Pass
			RB1#3	22.38	1	23.38	0.218	2.00	Pass
			RB1#5	22.48	1	23.48	0.223	2.00	Pass
			RB3#0	22.54	1	23.54	0.226	2.00	Pass
			RB3#2	22.52	1	23.52	0.225	2.00	Pass
			RB3#3	22.63	1	23.63	0.231	2.00	Pass
			RB6#0	21.50	1	22.50	0.178	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND2									
		16-QAM	RB1#0	21.59	1	22.59	0.182	2.00	Pass
			RB1#3	21.57	1	22.57	0.181	2.00	Pass
			RB1#5	21.43	1	22.43	0.175	2.00	Pass
			RB3#0	21.61	1	22.61	0.182	2.00	Pass
			RB3#2	21.60	1	22.60	0.182	2.00	Pass
			RB3#3	21.72	1	22.72	0.187	2.00	Pass
			RB6#0	20.81	1	21.81	0.152	2.00	Pass
3 MHz	LCH	QPSK	RB1#0	22.47	1	23.47	0.222	2.00	Pass
			RB1#7	22.25	1	23.25	0.211	2.00	Pass
			RB1#14	22.48	1	23.48	0.223	2.00	Pass
			RB8#0	21.41	1	22.41	0.174	2.00	Pass
			RB8#4	21.34	1	22.34	0.171	2.00	Pass
			RB8#7	21.31	1	22.31	0.170	2.00	Pass
			RB15#0	21.43	1	22.43	0.175	2.00	Pass
	MCH	16-QAM	RB1#0	21.28	1	22.28	0.169	2.00	Pass
			RB1#7	21.08	1	22.08	0.161	2.00	Pass
			RB1#14	21.25	1	22.25	0.168	2.00	Pass
			RB8#0	20.16	1	21.16	0.131	2.00	Pass
			RB8#4	20.10	1	21.10	0.129	2.00	Pass
			RB8#7	20.18	1	21.18	0.131	2.00	Pass
			RB15#0	20.32	1	21.32	0.136	2.00	Pass
	HCH	QPSK	RB1#0	22.56	1	23.56	0.227	2.00	Pass
			RB1#7	22.39	1	23.39	0.218	2.00	Pass
			RB1#14	22.36	1	23.36	0.217	2.00	Pass
			RB8#0	21.49	1	22.49	0.177	2.00	Pass
			RB8#4	21.46	1	22.46	0.176	2.00	Pass
			RB8#7	21.41	1	22.41	0.174	2.00	Pass
			RB15#0	21.46	1	22.46	0.176	2.00	Pass
		16-QAM	RB1#0	21.86	1	22.86	0.193	2.00	Pass
			RB1#7	21.55	1	22.55	0.180	2.00	Pass
			RB1#14	21.03	1	22.03	0.160	2.00	Pass
			RB8#0	20.52	1	21.52	0.142	2.00	Pass
			RB8#4	20.60	1	21.60	0.145	2.00	Pass
			RB8#7	20.52	1	21.52	0.142	2.00	Pass
			RB15#0	20.57	1	21.57	0.144	2.00	Pass
	HCH	QPSK	RB1#0	22.76	1	23.76	0.238	2.00	Pass
			RB1#7	22.34	1	23.34	0.216	2.00	Pass
			RB1#14	22.53	1	23.53	0.225	2.00	Pass
			RB8#0	21.37	1	22.37	0.173	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND2									
5 MHz	LCH	16-QAM	RB8#4	21.31	1	22.31	0.170	2.00	Pass
			RB8#7	21.28	1	22.28	0.169	2.00	Pass
			RB15#0	21.41	1	22.41	0.174	2.00	Pass
			RB1#0	21.57	1	22.57	0.181	2.00	Pass
			RB1#7	21.39	1	22.39	0.173	2.00	Pass
			RB1#14	21.63	1	22.63	0.183	2.00	Pass
			RB8#0	20.48	1	21.48	0.141	2.00	Pass
			RB8#4	20.31	1	21.31	0.135	2.00	Pass
			RB8#7	20.28	1	21.28	0.134	2.00	Pass
			RB15#0	20.51	1	21.51	0.142	2.00	Pass
5 MHz	MCH	QPSK	RB1#0	22.06	1	23.06	0.202	2.00	Pass
			RB1#13	22.20	1	23.20	0.209	2.00	Pass
			RB1#24	22.06	1	23.06	0.202	2.00	Pass
			RB12#0	21.25	1	22.25	0.168	2.00	Pass
			RB12#6	21.26	1	22.26	0.168	2.00	Pass
			RB12#13	21.32	1	22.32	0.171	2.00	Pass
			RB25#0	21.28	1	22.28	0.169	2.00	Pass
		16-QAM	RB1#0	20.74	1	21.74	0.149	2.00	Pass
			RB1#13	20.64	1	21.64	0.146	2.00	Pass
			RB1#24	20.70	1	21.70	0.148	2.00	Pass
			RB12#0	20.35	1	21.35	0.136	2.00	Pass
			RB12#6	20.27	1	21.27	0.134	2.00	Pass
			RB12#13	20.43	1	21.43	0.139	2.00	Pass
			RB25#0	20.43	1	21.43	0.139	2.00	Pass
5 MHz	QPSK	16-QAM	RB1#0	22.26	1	23.26	0.212	2.00	Pass
			RB1#13	22.21	1	23.21	0.209	2.00	Pass
			RB1#24	22.23	1	23.23	0.210	2.00	Pass
			RB12#0	21.41	1	22.41	0.174	2.00	Pass
			RB12#6	21.40	1	22.40	0.174	2.00	Pass
			RB12#13	21.41	1	22.41	0.174	2.00	Pass
			RB25#0	21.41	1	22.41	0.174	2.00	Pass
	16-QAM	MCH	RB1#0	20.96	1	21.96	0.157	2.00	Pass
			RB1#13	20.95	1	21.95	0.157	2.00	Pass
			RB1#24	20.88	1	21.88	0.154	2.00	Pass
			RB12#0	20.29	1	21.29	0.135	2.00	Pass
			RB12#6	20.40	1	21.40	0.138	2.00	Pass
			RB12#13	20.38	1	21.38	0.137	2.00	Pass
			RB25#0	20.41	1	21.41	0.138	2.00	Pass
	HCH	QPSK	RB1#0	22.24	1	23.24	0.211	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND2									
10 MHz	LCH	16-QAM	RB1#13	22.46	1	23.46	0.222	2.00	Pass
			RB1#24	22.45	1	23.45	0.221	2.00	Pass
			RB12#0	21.52	1	22.52	0.179	2.00	Pass
			RB12#6	21.38	1	22.38	0.173	2.00	Pass
			RB12#13	21.47	1	22.47	0.177	2.00	Pass
			RB25#0	21.45	1	22.45	0.176	2.00	Pass
			RB1#0	21.02	1	22.02	0.159	2.00	Pass
			RB1#13	20.97	1	21.97	0.157	2.00	Pass
			RB1#24	20.95	1	21.95	0.157	2.00	Pass
			RB12#0	20.61	1	21.61	0.145	2.00	Pass
			RB12#6	20.57	1	21.57	0.144	2.00	Pass
			RB12#13	20.54	1	21.54	0.143	2.00	Pass
			RB25#0	20.46	1	21.46	0.140	2.00	Pass
			RB1#0	22.29	1	23.29	0.213	2.00	Pass
		QPSK	RB1#25	22.34	1	23.34	0.216	2.00	Pass
			RB1#49	22.48	1	23.48	0.223	2.00	Pass
			RB25#0	21.23	1	22.23	0.167	2.00	Pass
			RB25#13	21.23	1	22.23	0.167	2.00	Pass
			RB25#25	21.24	1	22.24	0.167	2.00	Pass
			RB50#0	21.25	1	22.25	0.168	2.00	Pass
			RB1#0	21.36	1	22.36	0.172	2.00	Pass
		16-QAM	RB1#25	21.46	1	22.46	0.176	2.00	Pass
			RB1#49	21.44	1	22.44	0.175	2.00	Pass
			RB25#0	20.42	1	21.42	0.139	2.00	Pass
			RB25#13	20.37	1	21.37	0.137	2.00	Pass
			RB25#25	20.26	1	21.26	0.134	2.00	Pass
			RB1#0	22.24	1	23.24	0.211	2.00	Pass
		QPSK	RB1#25	22.23	1	23.23	0.210	2.00	Pass
			RB1#49	21.44	1	22.44	0.175	2.00	Pass
			RB25#0	21.34	1	22.34	0.171	2.00	Pass
			RB25#13	21.34	1	22.34	0.171	2.00	Pass
			RB25#25	21.34	1	22.34	0.171	2.00	Pass
			RB50#0	21.07	1	22.07	0.161	2.00	Pass
			RB1#0	21.19	1	22.19	0.166	2.00	Pass
		16-QAM	RB1#25	20.97	1	21.97	0.157	2.00	Pass
			RB1#49	20.68	1	21.68	0.147	2.00	Pass
			RB25#0	20.68	1	21.68	0.147	2.00	Pass
			RB25#13	20.58	1	21.58	0.144	2.00	Pass
			RB25#25	22.46	1	23.46	0.222	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND2									
15 MHz	HCH	QPSK	RB1#0	22.27	1	23.27	0.212	2.00	Pass
			RB1#25	21.44	1	22.44	0.175	2.00	Pass
			RB1#49	21.38	1	22.38	0.173	2.00	Pass
			RB25#0	22.29	1	23.29	0.213	2.00	Pass
			RB25#13	22.34	1	23.34	0.216	2.00	Pass
			RB25#25	21.37	1	22.37	0.173	2.00	Pass
			RB50#0	21.47	1	22.47	0.177	2.00	Pass
	16-QAM	16-QAM	RB1#0	21.49	1	22.49	0.177	2.00	Pass
			RB1#25	21.31	1	22.31	0.170	2.00	Pass
			RB1#49	21.27	1	22.27	0.169	2.00	Pass
			RB25#0	20.82	1	21.82	0.152	2.00	Pass
			RB25#13	20.73	1	21.73	0.149	2.00	Pass
			RB25#25	20.80	1	21.80	0.151	2.00	Pass
			RB1#0	22.22	1	23.22	0.210	2.00	Pass
15 MHz	LCH	QPSK	RB1#38	22.36	1	23.36	0.217	2.00	Pass
			RB1#74	22.55	1	23.55	0.226	2.00	Pass
			RB36#0	21.21	1	22.21	0.166	2.00	Pass
			RB36#19	21.26	1	22.26	0.168	2.00	Pass
			RB36#39	21.29	1	22.29	0.169	2.00	Pass
			RB75#0	20.76	1	21.76	0.150	2.00	Pass
			RB1#0	21.33	1	22.33	0.171	2.00	Pass
	MCH	16-QAM	RB1#38	21.41	1	22.41	0.174	2.00	Pass
			RB1#74	21.38	1	22.38	0.173	2.00	Pass
			RB1#0	22.56	1	23.56	0.227	2.00	Pass
			RB1#38	22.23	1	23.23	0.210	2.00	Pass
			RB1#74	22.28	1	23.28	0.213	2.00	Pass
			RB36#0	21.36	1	22.36	0.172	2.00	Pass
			RB36#19	21.31	1	22.31	0.170	2.00	Pass
15 MHz	HCH	QPSK	RB36#39	21.30	1	22.30	0.170	2.00	Pass
			RB75#0	20.74	1	21.74	0.149	2.00	Pass
			RB1#0	20.99	1	21.99	0.158	2.00	Pass
			RB1#38	20.75	1	21.75	0.150	2.00	Pass
			RB1#74	20.67	1	21.67	0.147	2.00	Pass
			RB1#0	22.38	1	23.38	0.218	2.00	Pass
			RB1#38	22.35	1	23.35	0.216	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND2									
		16-QAM	RB75#0	20.75	1	21.75	0.150	2.00	Pass
			RB1#0	22.45	1	23.45	0.221	2.00	Pass
			RB1#38	22.51	1	23.51	0.224	2.00	Pass
			RB1#74	21.88	1	22.88	0.194	2.00	Pass
20 MHz	LCH	QPSK	RB1#0	22.05	1	23.05	0.202	2.00	Pass
			RB1#50	22.53	1	23.53	0.225	2.00	Pass
			RB1#99	22.03	1	23.03	0.201	2.00	Pass
			RB50#0	21.21	1	22.21	0.166	2.00	Pass
			RB50#25	21.32	1	22.32	0.171	2.00	Pass
			RB50#50	21.31	1	22.31	0.170	2.00	Pass
			RB100#0	20.76	1	21.76	0.150	2.00	Pass
	MCH	QPSK	RB1#0	21.33	1	22.33	0.171	2.00	Pass
			RB1#50	21.34	1	22.34	0.171	2.00	Pass
			RB1#99	21.31	1	22.31	0.170	2.00	Pass
			RB1#0	22.56	1	23.56	0.227	2.00	Pass
			RB1#50	22.51	1	23.51	0.224	2.00	Pass
			RB1#99	22.63	1	23.63	0.231	2.00	Pass
			RB50#0	21.49	1	22.49	0.177	2.00	Pass
	HCH	QPSK	RB50#25	21.37	1	22.37	0.173	2.00	Pass
			RB50#50	21.33	1	22.33	0.171	2.00	Pass
			RB100#0	20.75	1	21.75	0.150	2.00	Pass
			RB1#0	21.50	1	22.50	0.178	2.00	Pass
			RB1#50	21.09	1	22.09	0.162	2.00	Pass
			RB1#99	20.92	1	21.92	0.156	2.00	Pass
			RB1#0	22.57	1	23.57	0.228	2.00	Pass
	16-QAM	QPSK	RB1#50	22.4	1	23.40	0.219	2.00	Pass
			RB1#99	22.31	1	23.31	0.214	2.00	Pass
			RB50#0	21.33	1	22.33	0.171	2.00	Pass
			RB50#25	21.44	1	22.44	0.175	2.00	Pass
			RB50#50	21.37	1	22.37	0.173	2.00	Pass
			RB100#0	20.77	1	21.77	0.150	2.00	Pass
			RB1#0	21.05	1	22.05	0.160	2.00	Pass
	16-QAM	QPSK	RB1#50	21.41	1	22.41	0.174	2.00	Pass
			RB1#99	20.93	1	21.93	0.156	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND4									
1.4 MHz	LCH	QPSK	RB1#0	22.31	1	23.31	0.214	1.00	Pass
			RB1#3	22.17	1	23.17	0.207	1.00	Pass
			RB1#5	22.01	1	23.01	0.200	1.00	Pass
			RB3#0	22.07	1	23.07	0.203	1.00	Pass
			RB3#2	22.15	1	23.15	0.207	1.00	Pass
			RB3#3	22.11	1	23.11	0.205	1.00	Pass
			RB6#0	21.09	1	22.09	0.162	1.00	Pass
	16-QAM	16-QAM	RB1#0	20.93	1	21.93	0.156	1.00	Pass
			RB1#3	20.94	1	21.94	0.156	1.00	Pass
			RB1#5	20.82	1	21.82	0.152	1.00	Pass
			RB3#0	21.12	1	22.12	0.163	1.00	Pass
			RB3#2	21.05	1	22.05	0.160	1.00	Pass
			RB3#3	21.03	1	22.03	0.160	1.00	Pass
			RB6#0	20.36	1	21.36	0.137	1.00	Pass
1.4 MHz	MCH	QPSK	RB1#0	22.24	1	23.24	0.211	1.00	Pass
			RB1#3	22.35	1	23.35	0.216	1.00	Pass
			RB1#5	22.21	1	23.21	0.209	1.00	Pass
			RB3#0	22.30	1	23.30	0.214	1.00	Pass
			RB3#2	22.28	1	23.28	0.213	1.00	Pass
			RB3#3	22.31	1	23.31	0.214	1.00	Pass
			RB6#0	21.22	1	22.22	0.167	1.00	Pass
	16-QAM	16-QAM	RB1#0	20.79	1	21.79	0.151	1.00	Pass
			RB1#3	20.80	1	21.80	0.151	1.00	Pass
			RB1#5	21.63	1	22.63	0.183	1.00	Pass
			RB3#0	21.39	1	22.39	0.173	1.00	Pass
			RB3#2	21.49	1	22.49	0.177	1.00	Pass
			RB3#3	21.43	1	22.43	0.175	1.00	Pass
			RB6#0	20.17	1	21.17	0.131	1.00	Pass
1.4 MHz	HCH	QPSK	RB1#0	22.20	1	23.20	0.209	1.00	Pass
			RB1#3	22.32	1	23.32	0.215	1.00	Pass
			RB1#5	22.14	1	23.14	0.206	1.00	Pass
			RB3#0	22.33	1	23.33	0.215	1.00	Pass
			RB3#2	22.38	1	23.38	0.218	1.00	Pass
			RB3#3	22.45	1	23.45	0.221	1.00	Pass
			RB6#0	21.36	1	22.36	0.172	1.00	Pass
	16-QAM	16-QAM	RB1#0	21.24	1	22.24	0.167	1.00	Pass
			RB1#3	21.37	1	22.37	0.173	1.00	Pass
			RB1#5	21.27	1	22.27	0.169	1.00	Pass
			RB3#0	21.58	1	22.58	0.181	1.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND4									
			RB3#2	21.51	1	22.51	0.178	1.00	Pass
			RB3#3	21.45	1	22.45	0.176	1.00	Pass
			RB6#0	20.35	1	21.35	0.136	1.00	Pass
3 MHz	LCH	QPSK	RB1#0	21.91	1	22.91	0.195	1.00	Pass
			RB1#7	21.94	1	22.94	0.197	1.00	Pass
			RB1#14	22.02	1	23.02	0.200	1.00	Pass
			RB8#0	20.93	1	21.93	0.156	1.00	Pass
			RB8#4	20.99	1	21.99	0.158	1.00	Pass
			RB8#7	21.00	1	22.00	0.158	1.00	Pass
			RB15#0	20.94	1	21.94	0.156	1.00	Pass
	16-QAM	16-QAM	RB1#0	20.62	1	21.62	0.145	1.00	Pass
			RB1#7	20.43	1	21.43	0.139	1.00	Pass
			RB1#14	20.59	1	21.59	0.144	1.00	Pass
			RB8#0	19.90	1	20.90	0.123	1.00	Pass
			RB8#4	20.19	1	21.19	0.132	1.00	Pass
			RB8#7	20.09	1	21.09	0.129	1.00	Pass
			RB15#0	20.01	1	21.01	0.126	1.00	Pass
	MCH	QPSK	RB1#0	22.16	1	23.16	0.207	1.00	Pass
			RB1#7	22.01	1	23.01	0.200	1.00	Pass
			RB1#14	22.12	1	23.12	0.205	1.00	Pass
			RB8#0	21.12	1	22.12	0.163	1.00	Pass
			RB8#4	21.13	1	22.13	0.163	1.00	Pass
			RB8#7	21.21	1	22.21	0.166	1.00	Pass
			RB15#0	21.29	1	22.29	0.169	1.00	Pass
	16-QAM	16-QAM	RB1#0	21.44	1	22.44	0.175	1.00	Pass
			RB1#7	21.31	1	22.31	0.170	1.00	Pass
			RB1#14	21.39	1	22.39	0.173	1.00	Pass
			RB8#0	20.17	1	21.17	0.131	1.00	Pass
			RB8#4	20.06	1	21.06	0.128	1.00	Pass
			RB8#7	20.12	1	21.12	0.129	1.00	Pass
			RB15#0	19.97	1	20.97	0.125	1.00	Pass
	HCH	QPSK	RB1#0	22.15	1	23.15	0.207	1.00	Pass
			RB1#7	22.08	1	23.08	0.203	1.00	Pass
			RB1#14	22.24	1	23.24	0.211	1.00	Pass
			RB8#0	21.20	1	22.20	0.166	1.00	Pass
			RB8#4	21.22	1	22.22	0.167	1.00	Pass
			RB8#7	21.26	1	22.26	0.168	1.00	Pass
			RB15#0	21.27	1	22.27	0.169	1.00	Pass
	16-QAM	RB1#0	21.40	1	22.40	0.174	1.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND4									
			RB1#7	21.43	1	22.43	0.175	1.00	Pass
			RB1#14	21.49	1	22.49	0.177	1.00	Pass
			RB8#0	20.30	1	21.30	0.135	1.00	Pass
			RB8#4	20.16	1	21.16	0.131	1.00	Pass
			RB8#7	20.11	1	21.11	0.129	1.00	Pass
			RB15#0	20.26	1	21.26	0.134	1.00	Pass
5 MHz	LCH	QPSK	RB1#0	21.93	1	22.93	0.196	1.00	Pass
			RB1#13	21.91	1	22.91	0.195	1.00	Pass
			RB1#24	21.85	1	22.85	0.193	1.00	Pass
			RB12#0	20.95	1	21.95	0.157	1.00	Pass
			RB12#6	21.06	1	22.06	0.161	1.00	Pass
			RB12#13	21.12	1	22.12	0.163	1.00	Pass
			RB25#0	21.02	1	22.02	0.159	1.00	Pass
	MCH	16-QAM	RB1#0	20.37	1	21.37	0.137	1.00	Pass
			RB1#13	20.41	1	21.41	0.138	1.00	Pass
			RB1#24	20.49	1	21.49	0.141	1.00	Pass
			RB12#0	20.00	1	21.00	0.126	1.00	Pass
			RB12#6	19.76	1	20.76	0.119	1.00	Pass
			RB12#13	20.04	1	21.04	0.127	1.00	Pass
			RB25#0	20.23	1	21.23	0.133	1.00	Pass
	HCH	QPSK	RB1#0	22.01	1	23.01	0.200	1.00	Pass
			RB1#13	22.01	1	23.01	0.200	1.00	Pass
			RB1#24	22.02	1	23.02	0.200	1.00	Pass
			RB12#0	21.25	1	22.25	0.168	1.00	Pass
			RB12#6	21.30	1	22.30	0.170	1.00	Pass
			RB12#13	21.22	1	22.22	0.167	1.00	Pass
			RB25#0	21.28	1	22.28	0.169	1.00	Pass
	16-QAM	16-QAM	RB1#0	20.75	1	21.75	0.150	1.00	Pass
			RB1#13	20.73	1	21.73	0.149	1.00	Pass
			RB1#24	20.66	1	21.66	0.147	1.00	Pass
			RB12#0	20.06	1	21.06	0.128	1.00	Pass
			RB12#6	20.10	1	21.10	0.129	1.00	Pass
			RB12#13	20.04	1	21.04	0.127	1.00	Pass
			RB25#0	20.19	1	21.19	0.132	1.00	Pass
	QPSK	QPSK	RB1#0	22.32	1	23.32	0.215	1.00	Pass
			RB1#13	22.35	1	23.35	0.216	1.00	Pass
			RB1#24	22.54	1	23.54	0.226	1.00	Pass
			RB12#0	21.41	1	22.41	0.174	1.00	Pass
			RB12#6	21.45	1	22.45	0.176	1.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND4									
10 MHz	LCH	16-QAM	RB12#13	21.53	1	22.53	0.179	1.00	Pass
			RB25#0	21.45	1	22.45	0.176	1.00	Pass
			RB1#0	21.03	1	22.03	0.160	1.00	Pass
			RB1#13	20.97	1	21.97	0.157	1.00	Pass
			RB1#24	21.11	1	22.11	0.163	1.00	Pass
			RB12#0	20.29	1	21.29	0.135	1.00	Pass
			RB12#6	20.36	1	21.36	0.137	1.00	Pass
			RB12#13	20.45	1	21.45	0.140	1.00	Pass
			RB25#0	20.37	1	21.37	0.137	1.00	Pass
			RB1#0	22.02	1	23.02	0.200	1.00	Pass
MCH	QPSK	16-QAM	RB1#25	22.09	1	23.09	0.204	1.00	Pass
			RB1#49	22.02	1	23.02	0.200	1.00	Pass
			RB25#0	20.99	1	21.99	0.158	1.00	Pass
			RB25#13	21.06	1	22.06	0.161	1.00	Pass
			RB25#25	21.06	1	22.06	0.161	1.00	Pass
			RB50#0	21.09	1	22.09	0.162	1.00	Pass
			RB1#0	21.08	1	22.08	0.161	1.00	Pass
	QPSK	16-QAM	RB1#25	21.23	1	22.23	0.167	1.00	Pass
			RB1#49	21.28	1	22.28	0.169	1.00	Pass
			RB25#0	20.01	1	21.01	0.126	1.00	Pass
			RB25#13	19.99	1	20.99	0.126	1.00	Pass
			RB25#25	20.00	1	21.00	0.126	1.00	Pass
			RB1#0	22.18	1	23.18	0.208	1.00	Pass
			RB1#25	22.15	1	23.15	0.207	1.00	Pass
HCH	QPSK	16-QAM	RB1#49	21.95	1	22.95	0.197	1.00	Pass
			RB25#0	21.11	1	22.11	0.163	1.00	Pass
			RB25#13	21.23	1	22.23	0.167	1.00	Pass
			RB25#25	21.15	1	22.15	0.164	1.00	Pass
			RB50#0	21.12	1	22.12	0.163	1.00	Pass
			RB1#0	21.55	1	22.55	0.180	1.00	Pass
			RB1#25	21.15	1	22.15	0.164	1.00	Pass
	QPSK	16-QAM	RB1#49	20.97	1	21.97	0.157	1.00	Pass
			RB25#0	20.23	1	21.23	0.133	1.00	Pass
			RB25#13	20.36	1	21.36	0.137	1.00	Pass
			RB25#25	20.28	1	21.28	0.134	1.00	Pass
			RB1#0	22.42	1	23.42	0.220	1.00	Pass
			RB1#25	22.61	1	23.61	0.230	1.00	Pass
			RB1#49	22.59	1	23.59	0.229	1.00	Pass
			RB25#0	21.50	1	22.50	0.178	1.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND4									
15 MHz	LCH	16-QAM	RB25#13	21.50	1	22.50	0.178	1.00	Pass
			RB25#25	21.52	1	22.52	0.179	1.00	Pass
			RB50#0	21.31	1	22.31	0.170	1.00	Pass
			RB1#0	21.25	1	22.25	0.168	1.00	Pass
			RB1#25	21.39	1	22.39	0.173	1.00	Pass
			RB1#49	21.47	1	22.47	0.177	1.00	Pass
		16-QAM	RB25#0	20.45	1	21.45	0.140	1.00	Pass
			RB25#13	20.44	1	21.44	0.139	1.00	Pass
			RB25#25	20.36	1	21.36	0.137	1.00	Pass
			RB1#0	21.94	1	22.94	0.197	1.00	Pass
15 MHz	MCH	QPSK	RB1#38	22.40	1	23.40	0.219	1.00	Pass
			RB1#74	22.35	1	23.35	0.216	1.00	Pass
			RB36#0	21.02	1	22.02	0.159	1.00	Pass
			RB36#19	21.11	1	22.11	0.163	1.00	Pass
			RB36#39	21.11	1	22.11	0.163	1.00	Pass
			RB75#0	20.45	1	21.45	0.140	1.00	Pass
		16-QAM	RB1#0	21.17	1	22.17	0.165	1.00	Pass
			RB1#38	21.13	1	22.13	0.163	1.00	Pass
			RB1#74	21.14	1	22.14	0.164	1.00	Pass
		QPSK	RB1#0	22.12	1	23.12	0.205	1.00	Pass
			RB1#38	22.11	1	23.11	0.205	1.00	Pass
			RB1#74	21.89	1	22.89	0.195	1.00	Pass
			RB36#0	21.17	1	22.17	0.165	1.00	Pass
			RB36#19	21.12	1	22.12	0.163	1.00	Pass
			RB36#39	21.03	1	22.03	0.160	1.00	Pass
			RB75#0	20.32	1	21.32	0.136	1.00	Pass
		16-QAM	RB1#0	21.08	1	22.08	0.161	1.00	Pass
			RB1#38	21.06	1	22.06	0.161	1.00	Pass
			RB1#74	20.89	1	21.89	0.155	1.00	Pass
		QPSK	RB1#0	22.21	1	23.21	0.209	1.00	Pass
			RB1#38	22.29	1	23.29	0.213	1.00	Pass
			RB1#74	22.23	1	23.23	0.210	1.00	Pass
			RB36#0	21.29	1	22.29	0.169	1.00	Pass
			RB36#19	21.31	1	22.31	0.170	1.00	Pass
			RB36#39	21.32	1	22.32	0.171	1.00	Pass
			RB75#0	20.38	1	21.38	0.137	1.00	Pass
		16-QAM	RB1#0	21.75	1	22.75	0.188	1.00	Pass
			RB1#38	21.86	1	22.86	0.193	1.00	Pass
			RB1#74	21.96	1	22.96	0.198	1.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND4									
20 MHz	LCH	QPSK	RB1#0	21.89	1	22.89	0.195	1.00	Pass
			RB1#50	22.28	1	23.28	0.213	1.00	Pass
			RB1#99	22.06	1	23.06	0.202	1.00	Pass
			RB50#0	21.00	1	22.00	0.158	1.00	Pass
			RB50#25	21.20	1	22.20	0.166	1.00	Pass
			RB50#50	21.02	1	22.02	0.159	1.00	Pass
			RB100#0	20.41	1	21.41	0.138	1.00	Pass
	16-QAM	RB1#0	20.46	1	21.46	0.140	1.00	Pass	
		RB1#50	20.76	1	21.76	0.150	1.00	Pass	
		RB1#99	20.58	1	21.58	0.144	1.00	Pass	
	MCH	QPSK	RB1#0	22.53	1	23.53	0.225	1.00	Pass
			RB1#50	22.63	1	23.63	0.231	1.00	Pass
			RB1#99	22.51	1	23.51	0.224	1.00	Pass
			RB50#0	21.24	1	22.24	0.167	1.00	Pass
			RB50#25	21.26	1	22.26	0.168	1.00	Pass
			RB50#50	21.09	1	22.09	0.162	1.00	Pass
			RB100#0	20.40	1	21.40	0.138	1.00	Pass
	16-QAM	RB1#0	21.20	1	22.20	0.166	1.00	Pass	
		RB1#50	21.34	1	22.34	0.171	1.00	Pass	
		RB1#99	21.11	1	22.11	0.163	1.00	Pass	
	HCH	QPSK	RB1#0	22.17	1	23.17	0.207	1.00	Pass
			RB1#50	22.42	1	23.42	0.220	1.00	Pass
			RB1#99	22.36	1	23.36	0.217	1.00	Pass
			RB50#0	21.34	1	22.34	0.171	1.00	Pass
			RB50#25	21.33	1	22.33	0.171	1.00	Pass
			RB50#50	21.34	1	22.34	0.171	1.00	Pass
			RB100#0	20.38	1	21.38	0.137	1.00	Pass
	16-QAM	RB1#0	21.64	1	22.64	0.184	1.00	Pass	
		RB1#50	21.95	1	22.95	0.197	1.00	Pass	
		RB1#99	21.90	1	22.90	0.195	1.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offsets)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND5										
1.4 MHz	LCH	QPSK	RB1#0	22.30	1	-1.15	21.15	0.130	7.00	Pass
			RB1#3	22.46	1	-1.15	21.31	0.135	7.00	Pass
			RB1#5	22.51	1	-1.15	21.36	0.137	7.00	Pass
			RB3#0	22.28	1	-1.15	21.13	0.130	7.00	Pass
			RB3#2	22.28	1	-1.15	21.13	0.130	7.00	Pass
			RB3#3	22.26	1	-1.15	21.11	0.129	7.00	Pass
			RB6#0	21.19	1	-1.15	20.04	0.101	7.00	Pass
	MCH	16-QAM	RB1#0	21.37	1	-1.15	20.22	0.105	7.00	Pass
			RB1#3	21.30	1	-1.15	20.15	0.104	7.00	Pass
			RB1#5	21.29	1	-1.15	20.14	0.103	7.00	Pass
			RB3#0	20.80	1	-1.15	19.65	0.092	7.00	Pass
			RB3#2	21.35	1	-1.15	20.20	0.105	7.00	Pass
			RB3#3	21.34	1	-1.15	20.19	0.104	7.00	Pass
			RB6#0	20.60	1	-1.15	19.45	0.088	7.00	Pass
HCH	QPSK	QPSK	RB1#0	22.08	1	-1.15	20.93	0.124	7.00	Pass
			RB1#3	22.18	1	-1.15	21.03	0.127	7.00	Pass
			RB1#5	22.14	1	-1.15	20.99	0.126	7.00	Pass
			RB3#0	22.11	1	-1.15	20.96	0.125	7.00	Pass
			RB3#2	22.24	1	-1.15	21.09	0.129	7.00	Pass
			RB3#3	22.19	1	-1.15	21.04	0.127	7.00	Pass
			RB6#0	21.04	1	-1.15	19.89	0.097	7.00	Pass
	16-QAM	16-QAM	RB1#0	21.56	1	-1.15	20.41	0.110	7.00	Pass
			RB1#3	21.07	1	-1.15	19.92	0.098	7.00	Pass
			RB1#5	21.31	1	-1.15	20.16	0.104	7.00	Pass
			RB3#0	21.14	1	-1.15	19.99	0.100	7.00	Pass
			RB3#2	21.16	1	-1.15	20.01	0.100	7.00	Pass
			RB3#3	21.09	1	-1.15	19.94	0.099	7.00	Pass
			RB6#0	19.95	1	-1.15	18.80	0.076	7.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offs et)	Conducted Output AV Power (dBm)	Antenn a Gain (dBi)	Antenn a Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND5										
			RB3#2	21.32	1	-1.15	20.17	0.104	7.00	Pass
			RB3#3	21.24	1	-1.15	20.09	0.102	7.00	Pass
			RB6#0	20.23	1	-1.15	19.08	0.081	7.00	Pass
	LCH	QPSK	RB1#0	22.36	1	-1.15	21.21	0.132	7.00	Pass
			RB1#7	22.30	1	-1.15	21.15	0.130	7.00	Pass
			RB1#14	22.30	1	-1.15	21.15	0.130	7.00	Pass
			RB8#0	21.26	1	-1.15	20.11	0.103	7.00	Pass
			RB8#4	21.41	1	-1.15	20.26	0.106	7.00	Pass
			RB8#7	21.39	1	-1.15	20.24	0.106	7.00	Pass
			RB15#0	21.37	1	-1.15	20.22	0.105	7.00	Pass
	3 MHz	16-QAM	RB1#0	21.48	1	-1.15	20.33	0.108	7.00	Pass
			RB1#7	21.50	1	-1.15	20.35	0.108	7.00	Pass
			RB1#14	21.60	1	-1.15	20.45	0.111	7.00	Pass
			RB8#0	20.65	1	-1.15	19.50	0.089	7.00	Pass
			RB8#4	20.74	1	-1.15	19.59	0.091	7.00	Pass
			RB8#7	20.73	1	-1.15	19.58	0.091	7.00	Pass
			RB15#0	20.47	1	-1.15	19.32	0.086	7.00	Pass
	MCH	QPSK	RB1#0	22.16	1	-1.15	21.01	0.126	7.00	Pass
			RB1#7	22.10	1	-1.15	20.95	0.124	7.00	Pass
			RB1#14	22.31	1	-1.15	21.16	0.131	7.00	Pass
			RB8#0	21.16	1	-1.15	20.01	0.100	7.00	Pass
			RB8#4	21.30	1	-1.15	20.15	0.104	7.00	Pass
			RB8#7	21.28	1	-1.15	20.13	0.103	7.00	Pass
			RB15#0	21.27	1	-1.15	20.12	0.103	7.00	Pass
	HCH	16-QAM	RB1#0	21.54	1	-1.15	20.39	0.109	7.00	Pass
			RB1#7	21.33	1	-1.15	20.18	0.104	7.00	Pass
			RB1#14	21.46	1	-1.15	20.31	0.107	7.00	Pass
			RB8#0	20.02	1	-1.15	18.87	0.077	7.00	Pass
			RB8#4	20.05	1	-1.15	18.90	0.078	7.00	Pass
			RB8#7	20.00	1	-1.15	18.85	0.077	7.00	Pass
			RB15#0	20.26	1	-1.15	19.11	0.081	7.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offsets)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND5										
		QAM	RB1#7	21.08	1	-1.15	19.93	0.098	7.00	Pass
			RB1#14	21.27	1	-1.15	20.12	0.103	7.00	Pass
			RB8#0	20.24	1	-1.15	19.09	0.081	7.00	Pass
			RB8#4	20.44	1	-1.15	19.29	0.085	7.00	Pass
			RB8#7	20.38	1	-1.15	19.23	0.084	7.00	Pass
			RB15#0	20.34	1	-1.15	19.19	0.083	7.00	Pass
5 MHz	LCH	QPSK	RB1#0	22.26	1	-1.15	21.11	0.129	7.00	Pass
			RB1#13	22.38	1	-1.15	21.23	0.133	7.00	Pass
			RB1#24	22.32	1	-1.15	21.17	0.131	7.00	Pass
			RB12#0	21.31	1	-1.15	20.16	0.104	7.00	Pass
			RB12#6	21.32	1	-1.15	20.17	0.104	7.00	Pass
			RB12#13	21.37	1	-1.15	20.22	0.105	7.00	Pass
			RB25#0	21.24	1	-1.15	20.09	0.102	7.00	Pass
	MCH	16-QAM	RB1#0	20.91	1	-1.15	19.76	0.095	7.00	Pass
			RB1#13	20.99	1	-1.15	19.84	0.096	7.00	Pass
			RB1#24	20.94	1	-1.15	19.79	0.095	7.00	Pass
			RB12#0	20.37	1	-1.15	19.22	0.084	7.00	Pass
			RB12#6	20.39	1	-1.15	19.24	0.084	7.00	Pass
			RB12#13	20.43	1	-1.15	19.28	0.085	7.00	Pass
			RB25#0	20.55	1	-1.15	19.40	0.087	7.00	Pass
	HCH	QPSK	RB1#0	21.98	1	-1.15	20.83	0.121	7.00	Pass
			RB1#13	22.07	1	-1.15	20.92	0.124	7.00	Pass
			RB1#24	22.18	1	-1.15	21.03	0.127	7.00	Pass
			RB12#0	21.20	1	-1.15	20.05	0.101	7.00	Pass
			RB12#6	21.19	1	-1.15	20.04	0.101	7.00	Pass
			RB12#13	21.29	1	-1.15	20.14	0.103	7.00	Pass
			RB25#0	21.19	1	-1.15	20.04	0.101	7.00	Pass
	16-QAM	16-QAM	RB1#0	21.11	1	-1.15	19.96	0.099	7.00	Pass
			RB1#13	21.25	1	-1.15	20.10	0.102	7.00	Pass
			RB1#24	20.76	1	-1.15	19.61	0.091	7.00	Pass
			RB12#0	20.06	1	-1.15	18.91	0.078	7.00	Pass
			RB12#6	20.13	1	-1.15	18.98	0.079	7.00	Pass
			RB12#13	20.30	1	-1.15	19.15	0.082	7.00	Pass
			RB25#0	20.33	1	-1.15	19.18	0.083	7.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offs et)	Conducted Output AV Power (dBm)	Antenn a Gain (dBi)	Antenn a Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND5										
10 MHz	LCH	16-QAM	RB12#13	21.08	1	-1.15	19.93	0.098	7.00	Pass
			RB25#0	21.01	1	-1.15	19.86	0.097	7.00	Pass
			RB1#0	20.89	1	-1.15	19.74	0.094	7.00	Pass
			RB1#13	20.93	1	-1.15	19.78	0.095	7.00	Pass
			RB1#24	20.98	1	-1.15	19.83	0.096	7.00	Pass
			RB12#0	20.13	1	-1.15	18.98	0.079	7.00	Pass
			RB12#6	20.10	1	-1.15	18.95	0.079	7.00	Pass
	MCH	16-QAM	RB12#13	20.05	1	-1.15	18.90	0.078	7.00	Pass
			RB25#0	20.07	1	-1.15	18.92	0.078	7.00	Pass
			RB1#0	22.25	1	-1.15	21.10	0.129	7.00	Pass
			RB1#25	22.62	1	-1.15	21.47	0.140	7.00	Pass
			RB1#49	22.31	1	-1.15	21.16	0.131	7.00	Pass
			RB25#0	21.39	1	-1.15	20.24	0.106	7.00	Pass
			RB25#13	21.33	1	-1.15	20.18	0.104	7.00	Pass
	HCH	16-QAM	RB25#25	21.18	1	-1.15	20.03	0.101	7.00	Pass
			RB50#0	21.29	1	-1.15	20.14	0.103	7.00	Pass
			RB1#0	21.38	1	-1.15	20.23	0.105	7.00	Pass
			RB1#25	21.32	1	-1.15	20.17	0.104	7.00	Pass
			RB1#49	20.76	1	-1.15	19.61	0.091	7.00	Pass
			RB25#0	20.33	1	-1.15	19.18	0.083	7.00	Pass
			RB25#13	20.25	1	-1.15	19.10	0.081	7.00	Pass
			RB25#25	20.26	1	-1.15	19.11	0.081	7.00	Pass
	QPSK	16-QAM	RB1#0	22.09	1	-1.15	20.94	0.124	7.00	Pass
			RB1#25	22.24	1	-1.15	21.09	0.129	7.00	Pass
			RB1#49	22.23	1	-1.15	21.08	0.128	7.00	Pass
			RB25#0	21.08	1	-1.15	19.93	0.098	7.00	Pass
			RB25#13	21.07	1	-1.15	19.92	0.098	7.00	Pass
			RB25#25	21.23	1	-1.15	20.08	0.102	7.00	Pass
			RB50#0	21.15	1	-1.15	20.00	0.100	7.00	Pass
	QPSK	16-QAM	RB1#0	20.61	1	-1.15	19.46	0.088	7.00	Pass
			RB1#25	20.65	1	-1.15	19.50	0.089	7.00	Pass
			RB1#49	20.77	1	-1.15	19.62	0.092	7.00	Pass
			RB25#0	20.09	1	-1.15	18.94	0.078	7.00	Pass
			RB25#13	20.16	1	-1.15	19.01	0.080	7.00	Pass
			RB25#25	20.31	1	-1.15	19.16	0.082	7.00	Pass
			RB1#0	22.23	1	-1.15	21.08	0.128	7.00	Pass
	QPSK	16-QAM	RB1#25	22.31	1	-1.15	21.16	0.131	7.00	Pass
			RB1#49	22.01	1	-1.15	20.86	0.122	7.00	Pass
			RB25#0	21.10	1	-1.15	19.95	0.099	7.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offs et)	Conducted Output AV Power (dBm)	Antenn a Gain (dBi)	Antenn a Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND5										
16-QAM	RB25#13	RB25#13	21.07	1	-1.15	19.92	0.098	7.00	Pass	
		RB25#25	21.21	1	-1.15	20.06	0.101	7.00	Pass	
		RB50#0	21.12	1	-1.15	19.97	0.099	7.00	Pass	
	RB1#0	RB1#0	21.12	1	-1.15	19.97	0.099	7.00	Pass	
		RB1#25	21.41	1	-1.15	20.26	0.106	7.00	Pass	
		RB1#49	21.05	1	-1.15	19.90	0.098	7.00	Pass	
		RB25#0	20.25	1	-1.15	19.10	0.081	7.00	Pass	
		RB25#13	20.21	1	-1.15	19.06	0.081	7.00	Pass	
		RB25#25	20.35	1	-1.15	19.20	0.083	7.00	Pass	

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND7									
5 MHz	LCH	QPSK	RB1#0	22.12	1	23.12	0.205	2.00	Pass
			RB1#13	22.36	1	23.36	0.217	2.00	Pass
			RB1#24	22.27	1	23.27	0.212	2.00	Pass
			RB12#0	21.37	1	22.37	0.173	2.00	Pass
			RB12#6	21.30	1	22.30	0.170	2.00	Pass
			RB12#13	21.32	1	22.32	0.171	2.00	Pass
			RB25#0	21.23	1	22.23	0.167	2.00	Pass
		16-QAM	RB1#0	20.67	1	21.67	0.147	2.00	Pass
			RB1#13	20.59	1	21.59	0.144	2.00	Pass
			RB1#24	20.63	1	21.63	0.146	2.00	Pass
			RB12#0	20.26	1	21.26	0.134	2.00	Pass
			RB12#6	20.19	1	21.19	0.132	2.00	Pass
			RB12#13	20.12	1	21.12	0.129	2.00	Pass
			RB25#0	20.38	1	21.38	0.137	2.00	Pass
5 MHz	MCH	QPSK	RB1#0	22.01	1	23.01	0.200	2.00	Pass
			RB1#13	22.06	1	23.06	0.202	2.00	Pass
			RB1#24	21.95	1	22.95	0.197	2.00	Pass
			RB12#0	21.08	1	22.08	0.161	2.00	Pass
			RB12#6	21.06	1	22.06	0.161	2.00	Pass
			RB12#13	21.02	1	22.02	0.159	2.00	Pass
			RB25#0	21.01	1	22.01	0.159	2.00	Pass
		16-QAM	RB1#0	20.64	1	21.64	0.146	2.00	Pass
			RB1#13	20.54	1	21.54	0.143	2.00	Pass
			RB1#24	20.53	1	21.53	0.142	2.00	Pass
			RB12#0	20.10	1	21.10	0.129	2.00	Pass
			RB12#6	20.17	1	21.17	0.131	2.00	Pass
			RB12#13	20.11	1	21.11	0.129	2.00	Pass
			RB25#0	20.14	1	21.14	0.130	2.00	Pass
5 MHz	HCH	QPSK	RB1#0	22.13	1	23.13	0.206	2.00	Pass
			RB1#13	22.25	1	23.25	0.211	2.00	Pass
			RB1#24	22.00	1	23.00	0.200	2.00	Pass
			RB12#0	21.16	1	22.16	0.164	2.00	Pass
			RB12#6	21.1	1	22.10	0.162	2.00	Pass
			RB12#13	21.09	1	22.09	0.162	2.00	Pass
			RB25#0	21.11	1	22.11	0.163	2.00	Pass
		16-QAM	RB1#0	20.62	1	21.62	0.145	2.00	Pass
			RB1#13	20.6	1	21.60	0.145	2.00	Pass
			RB1#24	20.57	1	21.57	0.144	2.00	Pass
			RB12#0	20.08	1	21.08	0.128	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND7									
			RB12#6	20.10	1	21.10	0.129	2.00	Pass
			RB12#13	20.10	1	21.10	0.129	2.00	Pass
			RB25#0	20.14	1	21.14	0.130	2.00	Pass
10 MHz	LCH	QPSK	RB1#0	22.70	1	23.70	0.234	2.00	Pass
			RB1#25	22.50	1	23.50	0.224	2.00	Pass
			RB1#49	22.42	1	23.42	0.220	2.00	Pass
			RB25#0	21.41	1	22.41	0.174	2.00	Pass
			RB25#13	21.30	1	22.30	0.170	2.00	Pass
			RB25#25	21.18	1	22.18	0.165	2.00	Pass
			RB50#0	21.20	1	22.20	0.166	2.00	Pass
	MCH	16-QAM	RB1#0	21.54	1	22.54	0.179	2.00	Pass
			RB1#25	21.51	1	22.51	0.178	2.00	Pass
			RB1#49	21.14	1	22.14	0.164	2.00	Pass
			RB25#0	20.42	1	21.42	0.139	2.00	Pass
			RB25#13	20.43	1	21.43	0.139	2.00	Pass
			RB25#25	20.31	1	21.31	0.135	2.00	Pass
	HCH	QPSK	RB1#0	22.24	1	23.24	0.211	2.00	Pass
			RB1#25	22.23	1	23.23	0.210	2.00	Pass
			RB1#49	22.36	1	23.36	0.217	2.00	Pass
			RB25#0	21.09	1	22.09	0.162	2.00	Pass
			RB25#13	21.08	1	22.08	0.161	2.00	Pass
			RB25#25	21.11	1	22.11	0.163	2.00	Pass
			RB50#0	21.14	1	22.14	0.164	2.00	Pass
	16-QAM		RB1#0	21.49	1	22.49	0.177	2.00	Pass
			RB1#25	21.45	1	22.45	0.176	2.00	Pass
			RB1#49	21.45	1	22.45	0.176	2.00	Pass
			RB25#0	20.29	1	21.29	0.135	2.00	Pass
			RB25#13	20.15	1	21.15	0.130	2.00	Pass
			RB25#25	20.17	1	21.17	0.131	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND7									
			RB25#0	20.21	1	21.21	0.132	2.00	Pass
			RB25#13	20.44	1	21.44	0.139	2.00	Pass
			RB25#25	20.31	1	21.31	0.135	2.00	Pass
15 MHz	LCH	QPSK	RB1#0	22.41	1	23.41	0.219	2.00	Pass
			RB1#38	22.14	1	23.14	0.206	2.00	Pass
			RB1#74	22.43	1	23.43	0.220	2.00	Pass
			RB36#0	21.23	1	22.23	0.167	2.00	Pass
			RB36#19	21.12	1	22.12	0.163	2.00	Pass
			RB36#39	21.19	1	22.19	0.166	2.00	Pass
			RB75#0	20.65	1	21.65	0.146	2.00	Pass
	16-QAM	16-QAM	RB1#0	21.47	1	22.47	0.177	2.00	Pass
			RB1#38	21.24	1	22.24	0.167	2.00	Pass
			RB1#74	21.25	1	22.25	0.168	2.00	Pass
	MCH	QPSK	RB1#0	22.46	1	23.46	0.222	2.00	Pass
			RB1#38	22.20	1	23.20	0.209	2.00	Pass
			RB1#74	22.21	1	23.21	0.209	2.00	Pass
			RB36#0	21.19	1	22.19	0.166	2.00	Pass
			RB36#19	21.10	1	22.10	0.162	2.00	Pass
			RB36#39	21.17	1	22.17	0.165	2.00	Pass
			RB75#0	20.64	1	21.64	0.146	2.00	Pass
	16-QAM	16-QAM	RB1#0	20.94	1	21.94	0.156	2.00	Pass
			RB1#38	20.70	1	21.70	0.148	2.00	Pass
			RB1#74	20.60	1	21.60	0.145	2.00	Pass
20 MHz	HCH	QPSK	RB1#0	22.13	1	23.13	0.206	2.00	Pass
			RB1#38	22.21	1	23.21	0.209	2.00	Pass
			RB1#74	22.31	1	23.31	0.214	2.00	Pass
			RB36#0	21.12	1	22.12	0.163	2.00	Pass
			RB36#19	21.28	1	22.28	0.169	2.00	Pass
			RB36#39	21.21	1	22.21	0.166	2.00	Pass
			RB75#0	20.59	1	21.59	0.144	2.00	Pass
		16-QAM	RB1#0	21.17	1	22.17	0.165	2.00	Pass
			RB1#38	21.20	1	22.20	0.166	2.00	Pass
			RB1#74	21.59	1	22.59	0.182	2.00	Pass
	LCH	QPSK	RB1#0	22.14	1	23.14	0.206	2.00	Pass
			RB1#50	22.07	1	23.07	0.203	2.00	Pass
			RB1#99	21.95	1	22.95	0.197	2.00	Pass
			RB50#0	21.26	1	22.26	0.168	2.00	Pass
			RB50#25	21.25	1	22.25	0.168	2.00	Pass
			RB50#50	21.20	1	22.20	0.166	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offset)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	Limit (W)	Verdict
LTE BAND7									
		16-QAM	RB100#0	20.52	1	21.52	0.142	2.00	Pass
			RB1#0	21.29	1	22.29	0.169	2.00	Pass
			RB1#50	21.27	1	22.27	0.169	2.00	Pass
			RB1#99	20.61	1	21.61	0.145	2.00	Pass
	MCH	QPSK	RB1#0	22.52	1	23.52	0.225	2.00	Pass
			RB1#50	22.45	1	23.45	0.221	2.00	Pass
			RB1#99	22.52	1	23.52	0.225	2.00	Pass
			RB50#0	21.18	1	22.18	0.165	2.00	Pass
			RB50#25	21.21	1	22.21	0.166	2.00	Pass
			RB50#50	21.13	1	22.13	0.163	2.00	Pass
			RB100#0	20.54	1	21.54	0.143	2.00	Pass
		16-QAM	RB1#0	21.39	1	22.39	0.173	2.00	Pass
			RB1#50	21.05	1	22.05	0.160	2.00	Pass
			RB1#99	20.98	1	21.98	0.158	2.00	Pass
	HCH	QPSK	RB1#0	22.10	1	23.10	0.204	2.00	Pass
			RB1#50	22.42	1	23.42	0.220	2.00	Pass
			RB1#99	22.20	1	23.20	0.209	2.00	Pass
			RB50#0	21.07	1	22.07	0.161	2.00	Pass
			RB50#25	21.30	1	22.30	0.170	2.00	Pass
			RB50#50	21.24	1	22.24	0.167	2.00	Pass
			RB100#0	20.55	1	21.55	0.143	2.00	Pass
		16-QAM	RB1#0	20.98	1	21.98	0.158	2.00	Pass
			RB1#50	21.05	1	22.05	0.160	2.00	Pass
			RB1#99	20.99	1	21.99	0.158	2.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offsets)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND12										
1.4 MHz	LCH	QPSK	RB1#0	22.76	1	-1.15	21.61	0.145	3.00	Pass
			RB1#3	22.6	1	-1.15	21.45	0.140	3.00	Pass
			RB1#5	22.62	1	-1.15	21.47	0.140	3.00	Pass
			RB3#0	22.71	1	-1.15	21.56	0.143	3.00	Pass
			RB3#2	22.65	1	-1.15	21.50	0.141	3.00	Pass
			RB3#3	22.62	1	-1.15	21.47	0.140	3.00	Pass
			RB6#0	21.73	1	-1.15	20.58	0.114	3.00	Pass
	MCH	16-QAM	RB1#0	21.55	1	-1.15	20.40	0.110	3.00	Pass
			RB1#3	21.51	1	-1.15	20.36	0.109	3.00	Pass
			RB1#5	21.79	1	-1.15	20.64	0.116	3.00	Pass
			RB3#0	21.76	1	-1.15	20.61	0.115	3.00	Pass
			RB3#2	21.69	1	-1.15	20.54	0.113	3.00	Pass
			RB3#3	21.62	1	-1.15	20.47	0.111	3.00	Pass
			RB6#0	20.82	1	-1.15	19.67	0.093	3.00	Pass
HCH	QPSK	QPSK	RB1#0	22.43	1	-1.15	21.28	0.134	3.00	Pass
			RB1#3	22.92	1	-1.15	21.77	0.150	3.00	Pass
			RB1#5	22.91	1	-1.15	21.76	0.150	3.00	Pass
			RB3#0	22.7	1	-1.15	21.55	0.143	3.00	Pass
			RB3#2	22.99	1	-1.15	21.84	0.153	3.00	Pass
			RB3#3	22.91	1	-1.15	21.76	0.150	3.00	Pass
			RB6#0	21.89	1	-1.15	20.74	0.119	3.00	Pass
	16-QAM	16-QAM	RB1#0	22.23	1	-1.15	21.08	0.128	3.00	Pass
			RB1#3	22.27	1	-1.15	21.12	0.129	3.00	Pass
			RB1#5	22.13	1	-1.15	20.98	0.125	3.00	Pass
			RB3#0	21.64	1	-1.15	20.49	0.112	3.00	Pass
			RB3#2	21.98	1	-1.15	20.83	0.121	3.00	Pass
			RB3#3	21.84	1	-1.15	20.69	0.117	3.00	Pass
			RB6#0	20.54	1	-1.15	19.39	0.087	3.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offsets)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND12										
			RB3#2	22.11	1	-1.15	20.96	0.125	3.00	Pass
			RB3#3	21.92	1	-1.15	20.77	0.119	3.00	Pass
			RB6#0	21.05	1	-1.15	19.90	0.098	3.00	Pass
	LCH	QPSK	RB1#0	22.73	1	-1.15	21.58	0.144	3.00	Pass
			RB1#7	22.58	1	-1.15	21.43	0.139	3.00	Pass
			RB1#14	22.72	1	-1.15	21.57	0.144	3.00	Pass
			RB8#0	21.73	1	-1.15	20.58	0.114	3.00	Pass
			RB8#4	21.79	1	-1.15	20.64	0.116	3.00	Pass
			RB8#7	21.67	1	-1.15	20.52	0.113	3.00	Pass
			RB15#0	21.76	1	-1.15	20.61	0.115	3.00	Pass
	3 MHz	16-QAM	RB1#0	21.92	1	-1.15	20.77	0.119	3.00	Pass
			RB1#7	21.75	1	-1.15	20.60	0.115	3.00	Pass
			RB1#14	21.51	1	-1.15	20.36	0.109	3.00	Pass
			RB8#0	21.09	1	-1.15	19.94	0.099	3.00	Pass
			RB8#4	20.73	1	-1.15	19.58	0.091	3.00	Pass
			RB8#7	20.66	1	-1.15	19.51	0.089	3.00	Pass
			RB15#0	20.72	1	-1.15	19.57	0.091	3.00	Pass
	MCH	QPSK	RB1#0	22.61	1	-1.15	21.46	0.140	3.00	Pass
			RB1#7	22.88	1	-1.15	21.73	0.149	3.00	Pass
			RB1#14	22.93	1	-1.15	21.78	0.151	3.00	Pass
			RB8#0	21.75	1	-1.15	20.60	0.115	3.00	Pass
			RB8#4	21.85	1	-1.15	20.70	0.117	3.00	Pass
			RB8#7	21.9	1	-1.15	20.75	0.119	3.00	Pass
			RB15#0	21.81	1	-1.15	20.66	0.116	3.00	Pass
	HCH	16-QAM	RB1#0	21.88	1	-1.15	20.73	0.118	3.00	Pass
			RB1#7	22.17	1	-1.15	21.02	0.126	3.00	Pass
			RB1#14	22.24	1	-1.15	21.09	0.129	3.00	Pass
			RB8#0	20.73	1	-1.15	19.58	0.091	3.00	Pass
			RB8#4	20.95	1	-1.15	19.80	0.095	3.00	Pass
			RB8#7	20.89	1	-1.15	19.74	0.094	3.00	Pass
			RB15#0	20.69	1	-1.15	19.54	0.090	3.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offsets)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND12										
		QAM	RB1#7	21.65	1	-1.15	20.50	0.112	3.00	Pass
			RB1#14	21.66	1	-1.15	20.51	0.112	3.00	Pass
			RB8#0	20.72	1	-1.15	19.57	0.091	3.00	Pass
			RB8#4	20.49	1	-1.15	19.34	0.086	3.00	Pass
			RB8#7	20.62	1	-1.15	19.47	0.089	3.00	Pass
			RB15#0	20.77	1	-1.15	19.62	0.092	3.00	Pass
5 MHz	LCH	QPSK	RB1#0	22.63	1	-1.15	21.48	0.141	3.00	Pass
			RB1#13	22.54	1	-1.15	21.39	0.138	3.00	Pass
			RB1#24	22.59	1	-1.15	21.44	0.139	3.00	Pass
			RB12#0	21.75	1	-1.15	20.60	0.115	3.00	Pass
			RB12#6	21.74	1	-1.15	20.59	0.115	3.00	Pass
			RB12#13	21.72	1	-1.15	20.57	0.114	3.00	Pass
			RB25#0	21.82	1	-1.15	20.67	0.117	3.00	Pass
	MCH	16-QAM	RB1#0	21.24	1	-1.15	20.09	0.102	3.00	Pass
			RB1#13	21.09	1	-1.15	19.94	0.099	3.00	Pass
			RB1#24	21.23	1	-1.15	20.08	0.102	3.00	Pass
			RB12#0	20.78	1	-1.15	19.63	0.092	3.00	Pass
			RB12#6	20.71	1	-1.15	19.56	0.090	3.00	Pass
			RB12#13	20.71	1	-1.15	19.56	0.090	3.00	Pass
			RB25#0	20.86	1	-1.15	19.71	0.094	3.00	Pass
	HCH	QPSK	RB1#0	22.49	1	-1.15	21.34	0.136	3.00	Pass
			RB1#13	22.72	1	-1.15	21.57	0.144	3.00	Pass
			RB1#24	22.8	1	-1.15	21.65	0.146	3.00	Pass
			RB12#0	21.65	1	-1.15	20.50	0.112	3.00	Pass
			RB12#6	21.95	1	-1.15	20.80	0.120	3.00	Pass
			RB12#13	21.85	1	-1.15	20.70	0.117	3.00	Pass
			RB25#0	21.77	1	-1.15	20.62	0.115	3.00	Pass
	16-QAM	16-QAM	RB1#0	21.21	1	-1.15	20.06	0.101	3.00	Pass
			RB1#13	21.32	1	-1.15	20.17	0.104	3.00	Pass
			RB1#24	21.33	1	-1.15	20.18	0.104	3.00	Pass
			RB12#0	20.53	1	-1.15	19.38	0.087	3.00	Pass
			RB12#6	20.85	1	-1.15	19.70	0.093	3.00	Pass
			RB12#13	20.85	1	-1.15	19.70	0.093	3.00	Pass
			RB25#0	20.78	1	-1.15	19.63	0.092	3.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offsets)	Conducted Output AV Power (dBm)	Antenna Gain (dBi)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND12										
10 MHz	LCH	16-QAM	RB12#13	21.63	1	-1.15	20.48	0.112	3.00	Pass
			RB25#0	21.76	1	-1.15	20.61	0.115	3.00	Pass
			RB1#0	21.58	1	-1.15	20.43	0.110	3.00	Pass
			RB1#13	21.11	1	-1.15	19.96	0.099	3.00	Pass
			RB1#24	21.53	1	-1.15	20.38	0.109	3.00	Pass
			RB12#0	20.8	1	-1.15	19.65	0.092	3.00	Pass
			RB12#6	20.6	1	-1.15	19.45	0.088	3.00	Pass
		QPSK	RB12#13	20.51	1	-1.15	19.36	0.086	3.00	Pass
			RB25#0	20.82	1	-1.15	19.67	0.093	3.00	Pass
			RB1#0	22.65	1	-1.15	21.50	0.141	3.00	Pass
	MCH	16-QAM	RB1#25	22.77	1	-1.15	21.62	0.145	3.00	Pass
			RB1#49	22.96	1	-1.15	21.81	0.152	3.00	Pass
			RB25#0	21.72	1	-1.15	20.57	0.114	3.00	Pass
			RB25#13	21.79	1	-1.15	20.64	0.116	3.00	Pass
			RB25#25	21.79	1	-1.15	20.64	0.116	3.00	Pass
			RB50#0	21.82	1	-1.15	20.67	0.117	3.00	Pass
		QPSK	RB1#0	21.79	1	-1.15	20.64	0.116	3.00	Pass
			RB1#25	21.6	1	-1.15	20.45	0.111	3.00	Pass
			RB1#49	22.42	1	-1.15	21.27	0.134	3.00	Pass
	HCH	16-QAM	RB25#0	20.77	1	-1.15	19.62	0.092	3.00	Pass
			RB25#13	20.84	1	-1.15	19.69	0.093	3.00	Pass
			RB25#25	20.79	1	-1.15	19.64	0.092	3.00	Pass
			RB1#0	22.38	1	-1.15	21.23	0.133	3.00	Pass
			RB1#25	22.75	1	-1.15	21.60	0.145	3.00	Pass
			RB1#49	22.74	1	-1.15	21.59	0.144	3.00	Pass
			RB25#0	21.6	1	-1.15	20.45	0.111	3.00	Pass
		QPSK	RB25#13	21.76	1	-1.15	20.61	0.115	3.00	Pass
			RB25#25	21.74	1	-1.15	20.59	0.115	3.00	Pass
			RB50#0	21.65	1	-1.15	20.50	0.112	3.00	Pass
			RB1#0	21.5	1	-1.15	20.35	0.108	3.00	Pass
	16-QAM	QPSK	RB1#25	21.82	1	-1.15	20.67	0.117	3.00	Pass
			RB1#49	22.23	1	-1.15	21.08	0.128	3.00	Pass
			RB25#0	20.59	1	-1.15	19.44	0.088	3.00	Pass
		QPSK	RB25#13	20.82	1	-1.15	19.67	0.093	3.00	Pass
			RB25#25	20.83	1	-1.15	19.68	0.093	3.00	Pass
	HCH	QPSK	RB1#0	22.57	1	-1.15	21.42	0.139	3.00	Pass
			RB1#25	22.8	1	-1.15	21.65	0.146	3.00	Pass
			RB1#49	22.26	1	-1.15	21.11	0.129	3.00	Pass
			RB25#0	21.7	1	-1.15	20.55	0.114	3.00	Pass

Test BW	Test Channel	Test Mode	Test RB (Size#Offs et)	Conducted Output AV Power (dBm)	Antenn a Gain (dBi)	Antenn a Gain (dBd)	ERP (dBm)	ERP (W)	Limit (W)	Verdict
LTE BAND12										
16-QAM	RB25#13	RB25#13	21.77	1	-1.15	20.62	0.115	3.00	Pass	
		RB25#25	21.58	1	-1.15	20.43	0.110	3.00	Pass	
		RB50#0	21.66	1	-1.15	20.51	0.112	3.00	Pass	
	RB1#0	RB1#0	22.02	1	-1.15	20.87	0.122	3.00	Pass	
		RB1#25	22.09	1	-1.15	20.94	0.124	3.00	Pass	
		RB1#49	21.94	1	-1.15	20.79	0.120	3.00	Pass	
		RB25#0	20.59	1	-1.15	19.44	0.088	3.00	Pass	
		RB25#13	20.77	1	-1.15	19.62	0.092	3.00	Pass	
		RB25#25	20.53	1	-1.15	19.38	0.087	3.00	Pass	

A.2 Peak to Average Ratio

Note 1: For average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB. For GSM, GPRS and EGPRS, there are peak power to demonstrate compliance, PAR measurements are not required.

Note 2: Test plots please refer to the document "Annex No.: BL-EC2010017-501 Data Part 1.pdf".

Note 3: The EUT does not support some RB configurations. (for example: $\geq 10\text{MHz}$ Bandwidth 16QAM mode Full RB and $\geq 15\text{MHz}$ Bandwidth 16QAM mode Half RB)

WCDMA Mode Test Data

Test Band	Test Channel	Peak to Average Ratio (dB)	Limit (dB)	Refer to Plot ^{Note2}	Verdict
Band 2	LCH	3.04	13	1.1	Pass
	MCH	2.99	13	1.2	Pass
	HCH	3.01	13	1.3	Pass
Band 4	LCH	3.25	13	2.1	Pass
	MCH	2.81	13	2.2	Pass
	HCH	3.16	13	2.3	Pass
Band 5	LCH	2.78	13	3.1	Pass
	MCH	3.04	13	3.2	Pass
	HCH	3.01	13	3.3	Pass

LTE Mode Test Data

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Peak to Average Ratio (dB)	Limit (dB)	Refer to Plot ^{Note2}	Verdict
LTE Band 2	20 MHz	LCH	QPSK	RB1#0	4.09	13	4.1	Pass
				RB100#0	4.38	13	4.2	Pass
			16-QAM	RB1#0	4.67	13	4.3	Pass
		MCH	QPSK	RB1#0	3.51	13	4.4	Pass
				RB100#0	4.41	13	4.5	Pass
			16-QAM	RB1#0	4.52	13	4.6	Pass
		HCH	QPSK	RB1#0	3.91	13	4.7	Pass
				RB100#0	4.35	13	4.8	Pass
			16-QAM	RB1#0	4.78	13	4.9	Pass
LTE Band 4	20 MHz	LCH	QPSK	RB1#0	4.67	13	5.1	Pass
				RB100#0	4.58	13	5.2	Pass
			16-QAM	RB1#0	5.62	13	5.3	Pass
		MCH	QPSK	RB1#0	3.86	13	5.4	Pass
				RB100#0	4.26	13	5.5	Pass
			16-QAM	RB1#0	4.46	13	5.6	Pass
		HCH	QPSK	RB1#0	3.48	13	5.7	Pass
				RB100#0	4.52	13	5.8	Pass
			16-QAM	RB1#0	4.52	13	5.9	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Peak to Average Ratio (dB)	Limit (dB)	Refer to Plot ^{Note2}	Verdict
LTE Band 5	10 MHz	LCH	QPSK	RB1#0	3.30	13	6.1	Pass
				RB50#0	3.77	13	6.2	Pass
			16-QAM	RB1#0	3.97	13	6.3	Pass
		MCH	QPSK	RB1#0	3.54	13	6.4	Pass
				RB50#0	4.14	13	6.5	Pass
			16-QAM	RB1#0	4.32	13	6.6	Pass
		HCH	QPSK	RB1#0	3.80	13	6.7	Pass
				RB50#0	4.17	13	6.8	Pass
			16-QAM	RB1#0	4.75	13	6.9	Pass
LTE Band 7	20 MHz	LCH	QPSK	RB1#0	3.71	13	7.1	Pass
				RB100#0	4.58	13	7.2	Pass
			16-QAM	RB1#0	4.78	13	7.3	Pass
		MCH	QPSK	RB1#0	3.25	13	7.4	Pass
				RB100#0	4.23	13	7.5	Pass
			16-QAM	RB1#0	4.17	13	7.6	Pass
		HCH	QPSK	RB1#0	4.32	13	7.7	Pass
				RB100#0	4.41	13	7.8	Pass
			16-QAM	RB1#0	5.22	13	7.9	Pass
LTE Band 12	10 MHz	LCH	QPSK	RB1#0	3.53	13	8.1	Pass
				RB50#0	5.02	13	8.2	Pass
			16-QAM	RB1#0	4.31	13	8.3	Pass
		MCH	QPSK	RB1#0	4.63	13	8.4	Pass
				RB50#0	4.93	13	8.5	Pass
			16-QAM	RB1#0	5.52	13	8.6	Pass
		HCH	QPSK	RB1#0	4.62	13	8.7	Pass
				RB50#0	4.10	13	8.8	Pass
			16-QAM	RB1#0	5.54	13	8.9	Pass

A.3 Occupied Bandwidth

Note 1: All modes were tested, but only the typical data were reported in this report.

Note 2: Test plots please refer to the document “Annex No.:BL-EC2010017-501 Data Part 2.pdf”.

Note 3: The EUT does not support some RB configurations. (for example: ≥ 10 MHz Bandwidth 16QAM mode Full RB and ≥ 15 MHz Bandwidth 16QAM mode Half RB)

GSM and WCDMA Mode Test Data

Test Band	Test Channel	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
GSM 850	LCH	0.25	0.31	1.1
	MCH	0.25	0.31	1.2
	HCH	0.25	0.31	1.3
GSM 1900	LCH	0.24	0.31	2.1
	MCH	0.24	0.30	2.2
	HCH	0.24	0.30	2.3
EGPRS 850	LCH	0.25	0.31	3.1
	MCH	0.25	0.31	3.2
	HCH	0.25	0.31	3.3
EGPRS 1900	LCH	0.25	0.31	4.1
	MCH	0.24	0.30	4.2
	HCH	0.25	0.31	4.3
WCDMA Band 2	LCH	4.12	4.73	5.1
	MCH	4.12	4.72	5.2
	HCH	4.12	4.74	5.3
WCDMA Band 4	LCH	4.12	4.71	6.1
	MCH	4.12	4.75	6.2
	HCH	4.12	4.72	6.3
WCDMA Band 5	LCH	4.13	4.74	7.1
	MCH	4.12	4.74	7.2
	HCH	4.12	4.73	7.3

LTE Mode Test Data

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 2	1.4 MHz	LCH	QPSK	RB6#0	1.09	1.30	8.1
			16-QAM	RB6#0	1.09	1.30	8.2
		MCH	QPSK	RB6#0	1.09	1.32	8.3
			16-QAM	RB6#0	1.09	1.32	8.4
		HCH	QPSK	RB6#0	1.09	1.27	8.5
			16-QAM	RB6#0	1.09	1.29	8.6
	3 MHz	LCH	QPSK	RB15#0	2.70	2.99	8.7
			16-QAM	RB15#0	2.70	3.01	8.8
		MCH	QPSK	RB15#0	2.70	3.00	8.9
			16-QAM	RB15#0	2.70	3.00	8.10
		HCH	QPSK	RB15#0	2.70	2.98	8.11
			16-QAM	RB15#0	2.70	3.01	8.12
	5 MHz	LCH	QPSK	RB25#0	4.51	5.02	8.13
			16-QAM	RB25#0	4.50	5.00	8.14
		MCH	QPSK	RB25#0	4.50	5.03	8.15
			16-QAM	RB25#0	4.51	5.02	8.16
		HCH	QPSK	RB25#0	4.49	5.01	8.17
			16-QAM	RB25#0	4.51	5.03	8.18
	10 MHz	LCH	QPSK	RB50#0	8.97	9.86	8.19
		MCH	QPSK	RB50#0	8.86	9.97	8.20
		HCH	QPSK	RB50#0	8.94	9.86	8.21
	15 MHz	LCH	QPSK	RB75#0	13.41	14.66	8.22
		MCH	QPSK	RB75#0	13.44	14.72	8.23
		HCH	QPSK	RB75#0	13.36	14.69	8.24
	20 MHz	LCH	QPSK	RB100#0	17.89	19.50	8.25
		MCH	QPSK	RB100#0	17.88	19.43	8.26
		HCH	QPSK	RB100#0	17.80	19.37	8.27
Band 4	1.4 MHz	LCH	QPSK	RB6#0	1.08	1.28	9.1
			16-QAM	RB6#0	1.10	1.30	9.2
		MCH	QPSK	RB6#0	1.09	1.31	9.3
			16-QAM	RB6#0	1.09	1.26	9.4
		HCH	QPSK	RB6#0	1.10	1.26	9.5
			16-QAM	RB6#0	1.09	1.30	9.6
	3 MHz	LCH	QPSK	RB15#0	2.70	2.99	9.7
			16-QAM	RB15#0	2.70	2.99	9.8
		MCH	QPSK	RB15#0	2.70	2.98	9.9
			16-QAM	RB15#0	2.71	2.98	9.10
		HCH	QPSK	RB15#0	2.71	3.00	9.11
			16-QAM	RB15#0	2.69	2.99	9.12

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 4	5 MHz	LCH	QPSK	RB25#0	4.51	4.99	9.13
	5 MHz	LCH	16-QAM	RB25#0	4.50	4.98	9.14
		MCH	QPSK	RB25#0	4.49	5.02	9.15
			16-QAM	RB25#0	4.51	5.02	9.16
		HCH	QPSK	RB25#0	4.50	5.02	9.17
			16-QAM	RB25#0	4.50	5.06	9.18
	10 MHz	LCH	QPSK	RB50#0	8.96	9.88	9.19
		MCH	QPSK	RB50#0	8.93	9.87	9.20
		HCH	QPSK	RB50#0	8.96	9.91	9.21
	15 MHz	LCH	QPSK	RB75#0	13.43	14.67	9.22
		MCH	QPSK	RB75#0	13.37	14.67	9.23
		HCH	QPSK	RB75#0	13.41	14.72	9.24
	20 MHz	LCH	QPSK	RB100#0	17.85	19.29	9.25
		MCH	QPSK	RB100#0	17.84	19.38	9.26
		HCH	QPSK	RB100#0	17.92	19.57	9.27
Band 5	1.4 MHz	LCH	QPSK	RB6#0	1.09	1.40	10.1
			16-QAM	RB6#0	1.09	1.31	10.2
		MCH	QPSK	RB6#0	1.10	1.31	10.3
			16-QAM	RB6#0	1.09	1.31	10.4
		HCH	QPSK	RB6#0	1.09	1.31	10.5
			16-QAM	RB6#0	1.10	1.30	10.6
	3 MHz	LCH	QPSK	RB15#0	2.71	3.01	10.7
			16-QAM	RB15#0	2.71	3.01	10.8
		MCH	QPSK	RB15#0	2.70	2.99	10.9
			16-QAM	RB15#0	2.70	2.99	10.10
		HCH	QPSK	RB15#0	2.70	3.00	10.11
			16-QAM	RB15#0	2.70	3.01	10.12
	5 MHz	LCH	QPSK	RB25#0	4.52	5.05	10.13
			16-QAM	RB25#0	4.51	5.01	10.14
		MCH	QPSK	RB25#0	4.50	5.01	10.15
			16-QAM	RB25#0	4.51	5.02	10.16
		HCH	QPSK	RB25#0	4.50	4.98	10.17
			16-QAM	RB25#0	4.51	5.02	10.18
	10 MHz	LCH	QPSK	RB50#0	8.97	9.97	10.19
		MCH	QPSK	RB50#0	8.94	9.87	10.20
		HCH	QPSK	RB50#0	8.93	9.83	10.21
Band 7	5 MHz	LCH	QPSK	RB25#0	4.51	5.00	11.1
			16-QAM	RB25#0	4.49	4.95	11.2
		MCH	QPSK	RB25#0	4.49	5.05	11.3
			16-QAM	RB25#0	4.50	5.02	11.4

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Measured 99% Occupied Bandwidth (MHz)	Measured -26 dB Occupied Bandwidth (MHz)	Refer to Plot ^{Note2}
Band 12	10 MHz	HCH	QPSK	RB25#0	4.49	4.99	11.5
			16-QAM	RB25#0	4.50	5.02	11.6
		LCH	QPSK	RB50#0	8.96	9.92	11.7
			MCH	QPSK	RB50#0	8.97	9.95
			HCH	QPSK	RB50#0	8.94	9.89
	15 MHz	LCH	QPSK	RB75#0	13.46	14.76	11.10
			MCH	QPSK	RB75#0	13.46	14.82
		HCH	QPSK	RB75#0	13.39	14.70	11.12
	20 MHz	LCH	QPSK	RB100#0	17.92	19.60	11.13
		MCH	QPSK	RB100#0	17.87	19.33	11.14
		HCH	QPSK	RB100#0	17.88	19.40	11.15
	1.4 MHz	LCH	QPSK	RB6#0	1.09	1.32	12.1
			16-QAM	RB6#0	1.09	1.31	12.2
		MCH	QPSK	RB6#0	1.09	1.29	12.3
			16-QAM	RB6#0	1.09	1.27	12.4
		HCH	QPSK	RB6#0	1.1	1.32	12.5
			16-QAM	RB6#0	1.09	1.33	12.6
		LCH	QPSK	RB15#0	2.7	2.98	12.7
			16-QAM	RB15#0	2.7	2.97	12.8
		MCH	QPSK	RB15#0	2.7	2.98	12.9
			16-QAM	RB15#0	2.7	2.99	12.10
		HCH	QPSK	RB15#0	2.71	3	12.11
			16-QAM	RB15#0	2.7	3.03	12.12
	5 MHz	LCH	QPSK	RB25#0	4.52	5.01	12.13
			16-QAM	RB25#0	4.51	5.01	12.14
		MCH	QPSK	RB25#0	4.5	4.96	12.15
			16-QAM	RB25#0	4.52	5.01	12.16
		HCH	QPSK	RB25#0	4.51	4.96	12.17
			16-QAM	RB25#0	4.52	5.08	12.18
	10 MHz	LCH	QPSK	RB50#0	9.02	10.06	12.19
		MCH	QPSK	RB50#0	8.97	9.85	12.20
		HCH	QPSK	RB50#0	8.91	9.76	12.21

A.4 Frequency Stability

GSM 850

Test Conditions		Frequency Deviation						Verdict	
Power (VDC)	Temperature (°C)	LCH 824.2 MHz		MCH 836.6 MHz		HCH 848.8 MHz			
		Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)		
3.85	-30	17.98	±2060.5	13.50	±2091.5	7.88	±2122	Pass	
	-20	13.40		8.59		4.36			
	-10	11.30		10.07		10.36			
	0	12.46		5.84		10.20			
	+10	15.69		4.78		10.49			
	+20	15.43		12.62		3.75			
	+25	13.43		7.65		7.65			
	+30	11.40		8.52		4.84			
	+40	10.23		5.62		12.33			
	+50	11.91		6.36		6.52			
3.4	+25	10.91		5.91		4.78			
4.4	+25	11.24		2.81		12.04			

GSM 1900

Test Conditions		Frequency Deviation						Verdict	
Power (VDC)	Temperature (°C)	LCH 1850.2 MHz		MCH 1880 MHz		HCH 1909.8 MHz			
		Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)		
3.85	-30	-3.94	±4625.5	11.75	±4700.0	-11.07	±4774.5	Pass	
	-20	10.91		5.71		6.94			
	-10	-9.65		13.62		10.11			
	0	13.88		7.94		-11.33			
	+10	7.72		6.94		-11.95			
	+20	11.17		12.91		15.53			
	+25	7.78		8.46		-12.75			
	+30	10.72		6.62		9.40			
	+40	13.50		12.88		8.85			
	+50	11.46		8.85		10.82			
3.4	+25	8.59		-5.94		-12.43			
4.4	+25	12.72		7.52		-13.75			

GPRS 850

Test Conditions		Frequency Deviation						Verdict	
Power (VDC)	Temperature (°C)	LCH 824.2 MHz		MCH 836.6 MHz		HCH 848.8 MHz			
		Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)		
3.85	-30	14.63	±2060.5	6.33	±2091.5	8.23	±2122	Pass	
	-20	16.92		14.24		13.27			
	-10	23.25		19.60		18.69			
	0	16.40		13.01		18.24			
	+10	22.12		29.25		18.85			
	+20	20.50		23.02		19.05			
	+25	27.70		29.02		20.95			
	+30	21.60		29.09		18.21			
	+40	27.15		24.18		19.40			
	+50	22.31		23.41		16.98			
	3.4	+25		22.44		17.47			
	4.4	+25		19.40		20.79			

GPRS 1900

Test Conditions		Frequency Deviation						Verdict	
Power (VDC)	Temperature (°C)	LCH 1850.2 MHz		MCH 1880 MHz		HCH 1909.8 MHz			
		Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)		
3.85	-30	-12.82	±4625.5	-28.77	±4700.0	-19.79	±4774.5	Pass	
	-20	-19.31		14.72		14.27			
	-10	22.02		23.63		31.38			
	0	23.50		7.88		31.45			
	+10	26.31		23.99		24.89			
	+20	26.57		21.44		25.18			
	+25	28.57		24.80		27.93			
	+30	22.02		23.50		28.44			
	+40	27.12		23.57		21.86			
	+50	23.99		23.31		24.99			
	3.4	+25		22.50		26.02			
	4.4	+25		23.57		18.95			

EGPRS 850

Test Conditions		Frequency Deviation						Verdict	
Power (VDC)	Temperature (°C)	LCH 824.2 MHz		MCH 836.6 MHz		HCH 848.8 MHz			
		Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)		
3.85	-30	31.38	±2060.5	19.44	±2091.5	19.63	±2122	Pass	
	-20	27.67		30.25		21.05			
	-10	26.89		21.02		21.53			
	0	25.67		30.54		18.53			
	+10	30.19		24.67		19.57			
	+20	26.57		20.31		20.11			
	+25	26.28		31.19		19.31			
	+30	24.21		27.83		19.57			
	+40	25.89		32.64		18.69			
	+50	22.89		23.21		19.21			
	3.4	+25		28.31		19.57			
	4.4	+25		19.98		20.05			

EGPRS 1900

Test Conditions		Frequency Deviation						Verdict	
Power (VDC)	Temperature (°C)	LCH 1850.2 MHz		MCH 1880 MHz		HCH 1909.8 MHz			
		Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)	Value (Hz)	Limits (Hz)		
3.85	-30	17.14	±4625.5	20.73	±4700.0	15.11	±4774.5	Pass	
	-20	13.30		14.92		18.76			
	-10	18.76		15.46		14.82			
	0	17.56		15.95		20.73			
	+10	13.01		12.14		13.82			
	+20	12.49		10.62		17.11			
	+25	17.40		17.40		14.08			
	+30	11.30		14.92		15.05			
	+40	8.46		13.62		15.72			
	+50	14.17		14.66		19.31			
	3.4	+25		16.47		16.30			
	4.4	+25		23.37		11.04			

WCDMA Band 2

Test Conditions		Frequency Deviation						Verdict	
Power (VDC)	Temperature (°C)	LCH		MCH		HCH			
		1852.4 MHz	Value (Hz)	1880 MHz	Value (Hz)	Limits (Hz)	1907.6 MHz		
3.85	-30	5.38	±4631	0.25	±4700	0.25	-5.41	±4769	
	-20	4.42		-1.10		-1.10	-5.79		
	-10	2.37		-1.30		-1.30	-5.82		
	0	1.84		-1.41		-1.41	-5.88		
	+10	1.24		-1.65		-1.65	-5.41		
	+20	1.92		-1.70		-1.70	-5.47		
	+25	0.62		-2.06		-2.06	-5.15		
	+30	1.27		-1.83		-1.83	-4.89		
	+40	0.83		-2.64		-2.64	-5.10		
	+50	0.27		-1.92		-1.92	-5.01		
	3.4	+25		-2.90		-2.90	-4.37		
	4.4	+25		-2.22		-2.22	-4.09		

WCDMA Band 4

Test Conditions		Frequency Deviation						Verdict	
Power (VDC)	Temperature (°C)	LCH		MCH		HCH			
		1712.4 MHz	Value (Hz)	1732.4 MHz	Value (Hz)	Limits (Hz)	1752.6 MHz		
3.85	-30	1.35	±4281	-0.46	±4331	-0.46	-2.37	±4381.5	
	-20	0.65		-0.32		-0.32	-2.22		
	-10	1.29		-0.69		-0.69	-2.59		
	0	1.04		-0.76		-0.76	-2.10		
	+10	1.30		-0.54		-0.54	-1.82		
	+20	1.02		-0.97		-0.97	-2.60		
	+25	-0.04		-1.09		-1.09	-2.29		
	+30	0.95		-0.57		-0.57	-2.22		
	+40	0.71		-0.67		-0.67	-2.05		
	+50	0.55		-0.46		-0.46	-1.95		
	3.4	+25		-1.32		-1.32	-1.89		
	4.4	+25		-0.87		-0.87	-2.29		

WCDMA Band B5

Test Conditions		Frequency Deviation						Verdict	
Power (VDC)	Temperature (°C)	LCH		MCH		HCH			
		826.4 MHz	Value (Hz)	836.4 MHz	Value (Hz)	846.6 MHz	Value (Hz)		
3.85	-30	6.37	±2066	-1.94	±2091	-5.83	±2116.5	Pass	
	-20	3.08		-1.88		-4.47			
	-10	2.60		-2.70		-2.88			
	0	0.48		-3.10		-2.27			
	+10	-0.13		-2.92		-2.35			
	+20	-0.38		-3.70		-1.17			
	+25	0.06		-2.72		-1.14			
	+30	-0.94		-2.99		-0.12			
	+40	-1.77		-2.50		0.38			
	+50	-2.76		-2.95		1.54			
	3.4	+25		-2.92		0.14			
	4.4	+25		-3.10		1.32			

LTE Band 2 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict	
Power (VDC)	Temperature (°C)	MCH 1880 MHz			
		Value (Hz)	Limits (Hz)		
3.85	-30	-4.18	±4700	Pass	
	-20	-4.42			
	-10	-3.79			
	0	-3.81			
	+10	-4.12			
	+20	-2.03			
	+25	-3.26			
	+30	-4.22			
	+40	-3.18			
	+50	-4.59			
	3.4	+25			
4.4	+25	-3.83			

LTE Band 4 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict	
Power (VDC)	Temperature (°C)	MCH 1732.5 MHz			
		Value (Hz)	Limits (Hz)		
3.85	-30	0.03	±4331.25	Pass	
	-20	-1.20			
	-10	-0.73			
	0	0.41			
	+10	0.07			
	+20	1.50			
	+25	-0.01			
	+30	0.57			
	+40	-1.24			
	+50	0.84			
	3.4	+25			
4.4	+25	0.72			

LTE Band 5 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict	
Power (VDC)	Temperature (°C)	MCH			
		Value (Hz)	Limits (Hz)		
3.85	-30	-0.20	± 2091.25	Pass	
	-20	-0.66			
	-10	-1.23			
	0	-0.30			
	+10	-0.16			
	+20	-2.19			
	+25	-0.56			
	+30	-0.33			
	+40	-0.64			
	+50	-0.49			
	3.4	0.17			
4.4	+25	-1.07			

LTE Band 7 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict	
Power (VDC)	Temperature (°C)	MCH			
		Value (Hz)	Limits (Hz)		
3.85	-30	-1.26	± 6337.5	Pass	
	-20	-3.12			
	-10	-3.75			
	0	-3.45			
	+10	-5.01			
	+20	-5.06			
	+25	-4.33			
	+30	-3.62			
	+40	-5.01			
	+50	-2.85			
	3.4	-4.63			
4.4	+25	-1.96			

LTE Band 12 QPSK 10 MHz

Test Conditions		Frequency Deviation		Verdict	
Power (VDC)	Temperature (°C)	MCH			
		2535 MHz	Value (Hz)		
3.85	-30	-5.66	±6337.5	Pass	
	-20	-2.70			
	-10	-3.06			
	0	-1.06			
	+10	-3.07			
	+20	-2.76			
	+25	-2.05			
	+30	-3.77			
	+40	-2.39			
	+50	-1.65			
3.4	+25	-0.70			
4.4	+25	-0.91			

A.5 Spurious Emission at Antenna Terminals

Note 1: GSM and EGPRS modes have been verified, and only the worst data with different bandwidth for LTE are shown here.

Note 2: The frequencies of verdict which are marked by "N/A" should be ignored because they are UE carrier frequency.

Note 3: Test plots please refer to the document "Annex No.:BL-EC2010017-501 Data Part 3.pdf".

GSM and WCDMA Mode Test Verdict

Test Band	Test Channel	Refer to Plot ^{Note3}	Verdict
GSM 850	LCH	1.1	Pass
	MCH	1.2	Pass
	HCH	1.3	Pass
GSM 1900	LCH	2.1	Pass
	MCH	2.2	Pass
	HCH	2.3	Pass
EGPRS 850	LCH	3.1	Pass
	MCH	3.2	Pass
	HCH	3.3	Pass
EGPRS 1900	LCH	4.1	Pass
	MCH	4.2	Pass
	HCH	4.3	Pass
WCDMA Band 2	LCH	5.1	Pass
	MCH	5.2	Pass
	HCH	5.3	Pass
WCDMA Band 4	LCH	6.1	Pass
	MCH	6.2	Pass
	HCH	6.2	Pass
WCDMA Band 5	LCH	7.1	Pass
	MCH	7.2	Pass
	HCH	7.3	Pass

LTE Mode Test Verdict

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
Band 2	1.4 MHz	LCH	QPSK	RB1#0	8.1	Pass
			16-QAM	RB1#0	8.2	Pass
	MCH	QPSK	RB1#0	8.3	Pass	
		16-QAM	RB1#0	8.4	Pass	
	HCH	QPSK	RB1#0	8.5	Pass	
		16-QAM	RB1#0	8.6	Pass	
	3 MHz	LCH	QPSK	RB1#0	8.7	Pass
			16-QAM	RB1#0	8.8	Pass
	MCH	QPSK	RB1#0	8.9	Pass	
		16-QAM	RB1#0	8.10	Pass	
	HCH	QPSK	RB1#0	8.11	Pass	
		16-QAM	RB1#0	8.12	Pass	
	5 MHz	LCH	QPSK	RB1#0	8.13	Pass
			16-QAM	RB1#0	8.14	Pass
	MCH	QPSK	RB1#0	8.15	Pass	
		16-QAM	RB1#0	8.16	Pass	
	HCH	QPSK	RB1#0	8.17	Pass	
		16-QAM	RB1#0	8.18	Pass	
	10 MHz	LCH	QPSK	RB1#0	8.19	Pass
			16-QAM	RB1#0	8.20	Pass
	MCH	QPSK	RB1#0	8.21	Pass	
		16-QAM	RB1#0	8.22	Pass	
	HCH	QPSK	RB1#0	8.23	Pass	
		16-QAM	RB1#0	8.24	Pass	
	15 MHz	LCH	QPSK	RB1#0	8.25	Pass
			16-QAM	RB1#0	8.26	Pass
	MCH	QPSK	RB1#0	8.27	Pass	
		16-QAM	RB1#0	8.28	Pass	
	HCH	QPSK	RB1#0	8.29	Pass	
		16-QAM	RB1#0	8.30	Pass	
	20 MHz	LCH	QPSK	RB1#0	8.31	Pass
			16-QAM	RB1#0	8.32	Pass
	MCH	QPSK	RB1#0	8.33	Pass	
		16-QAM	RB1#0	8.34	Pass	
	HCH	QPSK	RB1#0	8.35	Pass	
		16-QAM	RB1#0	8.36	Pass	

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
Band 4	1.4 MHz	LCH	QPSK	RB1#0	9.1	Pass
			16-QAM	RB1#0	9.2	Pass
		MCH	QPSK	RB1#0	9.3	Pass
			16-QAM	RB1#0	9.4	Pass
		HCH	QPSK	RB1#0	9.5	Pass
			16-QAM	RB1#0	9.6	Pass
	3 MHz	LCH	QPSK	RB1#0	9.7	Pass
			16-QAM	RB1#0	9.8	Pass
		MCH	QPSK	RB1#0	9.9	Pass
			16-QAM	RB1#0	9.10	Pass
		HCH	QPSK	RB1#0	9.11	Pass
			16-QAM	RB1#0	9.12	Pass
	5 MHz	LCH	QPSK	RB1#0	9.13	Pass
			16-QAM	RB1#0	9.14	Pass
		MCH	QPSK	RB1#0	9.15	Pass
			16-QAM	RB1#0	9.16	Pass
		HCH	QPSK	RB1#0	9.17	Pass
			16-QAM	RB1#0	9.18	Pass
	10 MHz	LCH	QPSK	RB1#0	9.19	Pass
			16-QAM	RB1#0	9.20	Pass
		MCH	QPSK	RB1#0	9.21	Pass
			16-QAM	RB1#0	9.22	Pass
		HCH	QPSK	RB1#0	9.23	Pass
			16-QAM	RB1#0	9.24	Pass
	15 MHz	LCH	QPSK	RB1#0	9.25	Pass
			16-QAM	RB1#0	9.26	Pass
		MCH	QPSK	RB1#0	9.27	Pass
			16-QAM	RB1#0	9.28	Pass
		HCH	QPSK	RB1#0	9.29	Pass
			16-QAM	RB1#0	9.30	Pass
	20 MHz	LCH	QPSK	RB1#0	9.31	Pass
			16-QAM	RB1#0	9.32	Pass
		MCH	QPSK	RB1#0	9.33	Pass
			16-QAM	RB1#0	9.34	Pass
		HCH	QPSK	RB1#0	9.35	Pass
			16-QAM	RB1#0	9.36	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
Band 5	1.4 MHz	LCH	QPSK	RB1#0	10.1	Pass
			16-QAM	RB1#0	10.2	Pass
		MCH	QPSK	RB1#0	10.3	Pass
			16-QAM	RB1#0	10.4	Pass
		HCH	QPSK	RB1#0	10.5	Pass
		HCH	16-QAM	RB1#0	10.6	Pass
	3 MHz	LCH	QPSK	RB1#0	10.7	Pass
			16-QAM	RB1#0	10.8	Pass
		MCH	QPSK	RB1#0	10.9	Pass
			16-QAM	RB1#0	10.10	Pass
		HCH	QPSK	RB1#0	10.11	Pass
			16-QAM	RB1#0	10.12	Pass
	5 MHz	LCH	QPSK	RB1#0	10.13	Pass
			16-QAM	RB1#0	10.14	Pass
		MCH	QPSK	RB1#0	10.15	Pass
			16-QAM	RB1#0	10.16	Pass
		HCH	QPSK	RB1#0	10.17	Pass
			16-QAM	RB1#0	10.18	Pass
	10 MHz	LCH	QPSK	RB1#0	10.19	Pass
			16-QAM	RB1#0	10.20	Pass
		MCH	QPSK	RB1#0	10.21	Pass
			16-QAM	RB1#0	10.22	Pass
		HCH	QPSK	RB1#0	10.23	Pass
			16-QAM	RB1#0	10.24	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
Band 7	5 MHz	LCH	QPSK	RB1#0	11.1	Pass
			16-QAM	RB1#0	11.2	Pass
		MCH	QPSK	RB1#0	11.3	Pass
			16-QAM	RB1#0	11.4	Pass
		HCH	QPSK	RB1#0	11.5	Pass
			16-QAM	RB1#0	11.6	Pass
	10 MHz	LCH	QPSK	RB1#0	11.7	Pass
			16-QAM	RB1#0	11.8	Pass
		MCH	QPSK	RB1#0	11.9	Pass
			16-QAM	RB1#0	11.10	Pass
		HCH	QPSK	RB1#0	11.11	Pass
			16-QAM	RB1#0	11.12	Pass
	15 MHz	LCH	QPSK	RB1#0	11.13	Pass
			16-QAM	RB1#0	11.14	Pass
		MCH	QPSK	RB1#0	11.15	Pass
			16-QAM	RB1#0	11.16	Pass
		HCH	QPSK	RB1#0	11.17	Pass
			16-QAM	RB1#0	11.18	Pass
	20 MHz	LCH	QPSK	RB1#0	11.19	Pass
			16-QAM	RB1#0	11.20	Pass
		MCH	QPSK	RB1#0	11.21	Pass
			16-QAM	RB1#0	11.22	Pass
		HCH	QPSK	RB1#0	11.23	Pass
		HCH	16-QAM	RB1#0	11.24	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
Band 12	1.4 MHz	LCH	QPSK	RB1#0	12.1	Pass
			16-QAM	RB1#0	12.2	Pass
		MCH	QPSK	RB1#0	12.3	Pass
			16-QAM	RB1#0	12.4	Pass
		HCH	QPSK	RB1#0	12.5	Pass
		HCH	16-QAM	RB1#0	12.6	Pass
	3 MHz	LCH	QPSK	RB1#0	12.7	Pass
			16-QAM	RB1#0	12.8	Pass
		MCH	QPSK	RB1#0	12.9	Pass
			16-QAM	RB1#0	12.10	Pass
		HCH	QPSK	RB1#0	12.11	Pass
			16-QAM	RB1#0	12.12	Pass
	5 MHz	LCH	QPSK	RB1#0	12.13	Pass
			16-QAM	RB1#0	12.14	Pass
		MCH	QPSK	RB1#0	12.15	Pass
			16-QAM	RB1#0	12.16	Pass
		HCH	QPSK	RB1#0	12.17	Pass
			16-QAM	RB1#0	12.18	Pass
	10 MHz	LCH	QPSK	RB1#0	12.19	Pass
			16-QAM	RB1#0	12.20	Pass
		MCH	QPSK	RB1#0	12.21	Pass
			16-QAM	RB1#0	12.22	Pass
		HCH	QPSK	RB1#0	12.23	Pass
			16-QAM	RB1#0	12.24	Pass

A.6 Band Edge

Note 1: Test plots please refer to the document "Annex No.:BL-EC2010017-501 Data Part 4.pdf".

GSM and WCDMA Mode Test Verdict

Test Band	Test Channel	Refer to Plot ^{Note1}	Verdict
GSM 850	LCH	1.1	Pass
	HCH	1.2	Pass
GSM 1900	LCH	2.1	Pass
	HCH	2.2	Pass
EGPRS 850	LCH	3.1	Pass
	HCH	3.2	Pass
EGPRS 1900	LCH	4.1	Pass
	HCH	4.2	Pass
WCDMA Band 2	LCH	5.1	Pass
	HCH	5.2	Pass
WCDMA Band 4	LCH	6.1	Pass
	HCH	6.2	Pass
WCDMA Band 5	LCH	7.1	Pass
	HCH	7.2	Pass

LTE Mode Test Verdict

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band2	1.4 MHz	LCH	QPSK	RB1#0	8.1	Pass
				RB6#0	8.2	Pass
		HCH	QPSK	RB1#0	8.3	Pass
				RB6#0	8.4	Pass
		LCH	QPSK	RB1#5	8.5	Pass
				RB6#0	8.6	Pass
		HCH	16-QAM	RB1#5	8.7	Pass
				RB6#0	8.8	Pass
	3 MHz	LCH	QPSK	RB1#0	8.9	Pass
				RB15#0	8.10	Pass
		HCH	16-QAM	RB1#0	8.11	Pass
				RB15#0	8.12	Pass
		LCH	QPSK	RB1#14	8.13	Pass
				RB15#0	8.14	Pass
		HCH	16-QAM	RB1#14	8.15	Pass
				RB15#0	8.16	Pass
	5 MHz	LCH	QPSK	RB1#0	8.17	Pass
				RB25#0	8.18	Pass
		HCH	16-QAM	RB1#0	8.19	Pass
				RB25#0	8.20	Pass
		LCH	QPSK	RB1#24	8.21	Pass
				RB25#0	8.22	Pass
		HCH	16-QAM	RB1#24	8.23	Pass
				RB25#0	8.24	Pass
	10 MHz	LCH	QPSK	RB1#0	8.25	Pass
				RB50#0	8.26	Pass
		HCH	16-QAM	RB1#0	8.27	Pass
				RB1#49	8.28	Pass
		LCH	QPSK	RB50#0	8.29	Pass
				RB1#49	8.30	Pass
		HCH	16-QAM	RB1#0	8.31	Pass
				RB75#0	8.32	Pass
	15 MHz	LCH	QPSK	RB1#0	8.33	Pass
				RB1#74	8.34	Pass
		HCH	16-QAM	RB1#74	8.35	Pass
				RB1#74	8.36	Pass
		LCH	QPSK	RB1#0	8.37	Pass
				RB100#0	8.38	Pass
		HCH	16-QAM	RB1#0	8.39	Pass
				RB1#99	8.40	Pass
			QPSK	RB100#0	8.41	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band4	1.4 MHz	LCH	16-QAM	RB1#99	8.42	Pass
			QPSK	RB1#0	9.1	Pass
				RB6#0	9.2	Pass
			16-QAM	RB1#0	9.3	Pass
		HCH		RB6#0	9.4	Pass
		QPSK	RB1#5	9.5	Pass	
			RB6#0	9.6	Pass	
		16-QAM	RB1#5	9.7	Pass	
	3 MHz		LCH		RB6#0	9.8
		QPSK	RB1#0	9.9	Pass	
			RB15#0	9.10	Pass	
		16-QAM	RB1#0	9.11	Pass	
			HCH		RB15#0	9.12
		QPSK	RB1#14	9.13	Pass	
			RB15#0	9.14	Pass	
		16-QAM	RB1#14	9.15	Pass	
			RB15#0	9.16	Pass	
	5 MHz	LCH	QPSK	RB1#0	9.17	Pass
				RB25#0	9.18	Pass
			16-QAM	RB1#0	9.19	Pass
				RB25#0	9.20	Pass
		HCH	QPSK	RB1#24	9.21	Pass
				RB25#0	9.22	Pass
			16-QAM	RB1#24	9.23	Pass
				RB25#0	9.24	Pass
	10 MHz	LCH	QPSK	RB1#0	9.25	Pass
				RB50#0	9.26	Pass
			16-QAM	RB1#0	9.27	Pass
		HCH	QPSK	RB1#49	9.28	Pass
				RB50#0	9.29	Pass
			16-QAM	RB1#49	9.30	Pass
	15 MHz	LCH	QPSK	RB1#0	9.31	Pass
				RB75#0	9.32	Pass
			16-QAM	RB1#0	9.33	Pass
		HCH	QPSK	RB1#74	9.34	Pass
				RB75#0	9.35	Pass
			16-QAM	RB1#74	9.36	Pass
	20 MHz	LCH	QPSK	RB1#0	9.37	Pass
				RB100#0	9.38	Pass
		16-QAM	RB1#0	RB1#0	9.39	Pass
		HCH	QPSK	RB1#99	9.40	Pass
				RB100#0	9.41	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
Band5	1.4 MHz	LCH	16-QAM	RB1#99	9.42	Pass
			QPSK	RB1#0	10.1	Pass
				RB6#0	10.2	Pass
			16-QAM	RB1#0	10.3	Pass
		HCH		RB6#0	10.4	Pass
		QPSK	RB1#5	10.5	Pass	
			RB6#0	10.6	Pass	
		16-QAM	RB1#5	10.7	Pass	
	3 MHz		LCH		RB6#0	10.8
		QPSK	RB1#0	10.9	Pass	
			RB15#0	10.10	Pass	
		16-QAM	RB1#0	10.11	Pass	
			HCH		RB15#0	10.12
		QPSK	RB1#14	10.13	Pass	
			RB15#0	10.14	Pass	
		16-QAM	RB1#14	10.15	Pass	
	10 MHz		LCH		RB15#0	10.16
		QPSK	RB1#0	10.17	Pass	
			RB25#0	10.18	Pass	
		16-QAM	RB1#0	10.19	Pass	
			HCH		RB25#0	10.20
		QPSK	RB1#24	10.21	Pass	
			RB25#0	10.22	Pass	
		16-QAM	RB1#24	10.23	Pass	
			LCH		RB25#0	10.24
		QPSK	RB1#0	10.25	Pass	
			RB50#0	10.26	Pass	
		16-QAM	RB1#0	10.27	Pass	
Band7	5 MHz	LCH	QPSK	RB1#49	10.28	Pass
				RB50#0	10.29	Pass
			16-QAM	RB1#49	10.30	Pass
		HCH		RB1#0	11.1	Pass
		QPSK	RB25#0	11.2	Pass	
			RB1#0	11.3	Pass	
			RB25#0	11.4	Pass	
		HCH	QPSK	RB1#24	11.5	Pass
				RB25#0	11.6	Pass
			16-QAM	RB1#24	11.7	Pass
				RB25#0	11.8	Pass
	10 MHz	LCH	QPSK	RB1#0	11.9	Pass
				RB50#0	11.10	Pass
			16-QAM	RB1#0	11.11	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
15 MHz	15 MHz	HCH	QPSK	RB1#49	11.12	Pass
				RB50#0	11.13	Pass
				RB1#49	11.14	Pass
	20 MHz	LCH	QPSK	RB1#0	11.15	Pass
				RB75#0	11.16	Pass
			16-QAM	RB1#0	11.17	Pass
	20 MHz	HCH	QPSK	RB1#74	11.18	Pass
				RB75#0	11.19	Pass
			16-QAM	RB1#74	11.20	Pass
		LCH	QPSK	RB1#0	11.21	Pass
				RB100#0	11.22	Pass
			16-QAM	RB1#0	11.23	Pass
Band 12	1.4 MHz	LCH	QPSK	RB1#0	12.1	Pass
				RB6#0	12.2	Pass
			16-QAM	RB1#0	12.3	Pass
				RB6#0	12.4	Pass
	3 MHz	HCH	QPSK	RB1#5	12.5	Pass
				RB6#0	12.6	Pass
		16-QAM	QPSK	RB1#5	12.7	Pass
				RB6#0	12.8	Pass
	5 MHz	LCH	QPSK	RB1#0	12.9	Pass
				RB15#0	12.10	Pass
			16-QAM	RB1#0	12.11	Pass
				RB15#0	12.12	Pass
		HCH	QPSK	RB1#14	12.13	Pass
				RB15#0	12.14	Pass
			16-QAM	RB1#14	12.15	Pass
				RB15#0	12.16	Pass
	10 MHz	LCH	QPSK	RB1#0	12.17	Pass
				RB25#0	12.18	Pass
			16-QAM	RB1#0	12.19	Pass
				RB25#0	12.20	Pass
		HCH	QPSK	RB1#24	12.21	Pass
				RB25#0	12.22	Pass
			16-QAM	RB1#24	12.23	Pass
				RB25#0	12.24	Pass
		LCH	QPSK	RB1#0	12.25	Pass
				RB50#0	12.26	Pass
			16-QAM	RB1#0	12.27	Pass

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note1}	Verdict
		HCH	QPSK	RB1#49	12.28	Pass
				RB50#0	12.29	Pass
			16-QAM	RB1#49	12.30	Pass

A.7 Field Strength of Spurious Radiation

Note 1: GSM and EGPRS modes have been verified, only the worst data with different transmit bandwidth for LTE are shown here.

Note 2: The frequencies of verdict which are marked by "N/A" should be ignored because they are UE carrier frequency.

Note 3: Test plots please refer to the document "Annex No.:BL-EC2010017-501 Data Part 5.pdf".

GSM and WCDMA Mode Test Verdict


Test Band	Test Channel	Refer to Plot ^{Note3}	Verdict
GSM 850	LCH	1.1	Pass
	MCH	1.2	Pass
	HCH	1.3	Pass
GSM 1900	LCH	2.1	Pass
	MCH	2.2	Pass
	HCH	2.3	Pass
EGPRS 850	LCH	3.1	Pass
	MCH	3.2	Pass
	HCH	3.3	Pass
EGPRS 1900	LCH	4.1	Pass
	MCH	4.2	Pass
	HCH	4.3	Pass
WCDMA Band 2	LCH	5.1	Pass
	MCH	5.2	Pass
	HCH	5.3	Pass
WCDMA Band 4	LCH	6.1	Pass
	MCH	6.2	Pass
	HCH	6.3	Pass
WCDMA Band 5	LCH	7.1	Pass
	MCH	7.2	Pass
	HCH	7.3	Pass

LTE Mode Test Verdict

Test Band	Test Bandwidth	Test Channel	Test Mode	Test RB (Size#Offset)	Refer to Plot ^{Note3}	Verdict
Band 2	1.4 MHz	MCH	QPSK	RB1#0	8.1	Pass
	3 MHz	MCH	QPSK	RB1#0	8.2	Pass
	5 MHz	MCH	QPSK	RB1#0	8.3	Pass
	10 MHz	MCH	QPSK	RB1#0	8.4	Pass
	15 MHz	MCH	QPSK	RB1#0	8.5	Pass
	20 MHz	MCH	QPSK	RB1#0	8.6	Pass
Band 4	1.4 MHz	MCH	QPSK	RB1#0	9.1	Pass
	3 MHz	MCH	QPSK	RB1#0	9.2	Pass
	5 MHz	MCH	QPSK	RB1#0	9.3	Pass
	10 MHz	MCH	QPSK	RB1#0	9.4	Pass
	15 MHz	MCH	QPSK	RB1#0	9.5	Pass
	20 MHz	MCH	QPSK	RB1#0	9.6	Pass
Band 5	1.4 MHz	MCH	QPSK	RB1#0	10.1	Pass
	3 MHz	MCH	QPSK	RB1#0	10.2	Pass
	5 MHz	MCH	QPSK	RB1#0	10.3	Pass
	10 MHz	MCH	QPSK	RB1#0	10.4	Pass
Band 7	5 MHz	MCH	QPSK	RB1#0	11.1	Pass
	10 MHz	MCH	QPSK	RB1#0	11.2	Pass
	15 MHz	MCH	QPSK	RB1#0	11.3	Pass
	20 MHz	MCH	QPSK	RB1#0	11.4	Pass
Band 12	1.4 MHz	MCH	QPSK	RB1#0	12.1	Pass
	3 MHz	MCH	QPSK	RB1#0	12.2	Pass
	5 MHz	MCH	QPSK	RB1#0	12.3	Pass
	10 MHz	MCH	QPSK	RB1#0	12.4	Pass


A.8 Receiver Spurious Emissions

Note: Only the worst test results were recorded in this report.




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	36.547	29.33	-26.67	40.0	-10.67	Peak	73.00	100	Vertical	Pass
2	67.103	29.77	-26.96	40.0	-10.23	Peak	55.00	100	Vertical	Pass
3	110.510	32.62	-25.79	43.5	-10.88	Peak	166.00	100	Vertical	Pass
4	199.992	22.70	-25.81	43.5	-20.80	Peak	148.00	100	Vertical	Pass
5	450.010	22.33	-20.34	46.0	-23.67	Peak	207.00	100	Vertical	Pass
6	856.440	25.72	-11.79	46.0	-20.28	Peak	95.00	200	Vertical	Pass

30MHz to 1GHz, ANT H




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	32.182	23.51	-28.00	40.0	-16.49	Peak	154.00	100	Horizontal	Pass
2	66.132	22.51	-26.46	40.0	-17.49	Peak	164.00	200	Horizontal	Pass
3	113.662	22.41	-26.41	43.5	-21.09	Peak	217.00	100	Horizontal	Pass
4	199.992	23.10	-25.81	43.5	-20.40	Peak	44.00	200	Horizontal	Pass
5	345.492	22.28	-21.83	46.0	-23.72	Peak	83.00	100	Horizontal	Pass
6	742.465	24.38	-13.86	46.0	-21.62	Peak	358.00	100	Horizontal	Pass

1GHz to 18GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1346.500	42.22	-15.70	74.0	-31.78	Peak	215.00	100	Vertical	Pass
1**	1346.500	24.68	-15.70	54.0	-29.32	AV	215.00	100	Vertical	Pass
2	2069.000	45.34	-13.38	74.0	-28.66	Peak	266.00	100	Vertical	Pass
2**	2069.000	28.59	-13.38	54.0	-25.41	AV	266.00	100	Vertical	Pass
3	2863.500	49.11	-9.76	74.0	-24.89	Peak	357.00	100	Vertical	Pass
3**	2863.500	32.06	-9.76	54.0	-21.94	AV	357.00	100	Vertical	Pass
4	5861.000	49.14	-0.71	74.0	-24.86	Peak	1.00	100	Vertical	Pass
4**	5861.000	33.78	-0.71	54.0	-20.22	AV	1.00	100	Vertical	Pass
5	9315.500	52.80	4.53	74.0	-21.20	Peak	275.00	100	Vertical	Pass
5**	9315.500	43.29	4.53	54.0	-10.71	AV	275.00	100	Vertical	Pass
6	14480.000	58.63	11.82	74.0	-15.37	Peak	136.00	100	Vertical	Pass
6**	14480.000	47.00	11.82	54.0	-7.00	AV	136.00	100	Vertical	Pass


1GHz to 18GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1309.000	40.02	-15.83	74.0	-33.98	Peak	354.00	100	Horizontal	Pass
1**	1309.000	24.74	-15.83	54.0	-29.26	AV	354.00	100	Horizontal	Pass
2	2231.500	46.45	-12.50	74.0	-27.55	Peak	7.00	100	Horizontal	Pass
2**	2231.500	29.33	-12.50	54.0	-24.67	AV	7.00	100	Horizontal	Pass
3	3584.000	44.07	-5.51	74.0	-29.93	Peak	231.00	100	Horizontal	Pass
3**	3584.000	27.67	-5.51	54.0	-26.33	AV	231.00	100	Horizontal	Pass
4	5190.000	47.79	-2.40	74.0	-26.21	Peak	-1.00	100	Horizontal	Pass
4**	5190.000	30.78	-2.40	54.0	-23.22	AV	-1.00	100	Horizontal	Pass
5	9307.250	52.47	4.59	74.0	-21.53	Peak	51.00	100	Horizontal	Pass
5**	9307.250	42.92	4.59	54.0	-11.08	AV	51.00	100	Horizontal	Pass
6	14524.000	58.61	11.74	74.0	-15.39	Peak	140.00	100	Horizontal	Pass
6**	14524.000	47.33	11.74	54.0	-6.67	AV	140.00	100	Horizontal	Pass


A.9 AC Power-line Conducted Emissions

Note: Only the worst test results were recorded in this report.



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.320	50.67	11.40	90.71	-40.04	Peak	L	Pass
1**	0.320	38.18	11.40	77.71	-39.53	AV	L	Pass
2	0.380	51.78	11.46	89.28	-37.50	Peak	L	Pass
2**	0.380	45.14	11.46	76.28	-31.14	AV	L	Pass
3	0.760	51.52	11.20	87.00	-35.48	Peak	L	Pass
3**	0.760	40.14	11.20	74.00	-33.86	AV	L	Pass
4	1.266	50.55	11.22	87.00	-36.45	Peak	L	Pass
4**	1.266	38.31	11.22	74.00	-35.69	AV	L	Pass
5	8.098	46.72	11.04	87.00	-40.28	Peak	L	Pass
5**	8.098	38.72	11.04	74.00	-35.28	AV	L	Pass

N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.450	46.74	11.36	56.88	-10.14	Peak	N	Pass
1**	0.450	29.03	11.36	46.88	-17.85	AV	N	Pass
2	0.888	47.06	11.23	56.00	-8.94	Peak	N	Pass
2**	0.888	25.65	11.23	46.00	-20.35	AV	N	Pass
3	1.290	47.14	11.28	56.00	-8.86	Peak	N	Pass
3**	1.290	24.19	11.28	46.00	-21.81	AV	N	Pass
4	2.056	41.09	11.17	56.00	-14.91	Peak	N	Pass
4**	2.056	22.39	11.17	46.00	-23.61	AV	N	Pass
5	2.526	40.57	11.15	56.00	-15.43	Peak	N	Pass
5**	2.526	21.50	11.15	46.00	-24.50	AV	N	Pass
6	17.936	36.37	11.42	60.00	-23.63	Peak	N	Pass
6**	17.936	22.23	11.42	50.00	-27.77	AV	N	Pass

ANNEX B TEST SETUP PHOTOS

Please refer to the document "BL-EC2010017-AR.PDF".

ANNEX C EUT EXTERNAL PHOTOS

Please refer to the document "BL-EC2010017-AW.PDF".

ANNEX D EUT INTERNAL PHOTOS

Please refer to the document "BL-EC2010017-AI.PDF".

--END OF REPORT--