

RF EXPOSURE EVALUATION

Equipment under test: Blue Connect Module

FCC ID number: 2AVPG-MCX

Test report reference: RRA-100-19-105909-2-A

MPE calculation

These equations are generally accurate in the far field of an antenna but will over predict power density in the near field, where they could be used for making a “worst case” prediction.

$$S = PG/4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units e.g. mW)

G = power gain of the antenna in the direction of interest relative to the isotropic radiator

R = distance to the centre of radiation of the antenna (appropriate units e.g. cm)

Or

$$S = EIRP/4\pi R^2$$

Where $EIRP$ = equivalent isotropically radiated power

Calculation:

(Calculated for max. EIRP)

EIRP: +1.61 dBm (1.449 mW)

Calculated at distance of 20 cm:

Power density = 0.000288 mW/cm²

Limit:

0.608mW/cm² is the reference level for G exposure according to Rule part 1.1310 (e)

Ed.	Date	Modified page(s)	Written by		Technical Verification and Quality Approval	
			Name	Visa	Name	Visa
0	12/03/2020	Creation	F. LHEUREUX (Test technician)		B. Pellerin Radio Technical Manager	



Siège Social : Emitech - 3, rue des Coudriers - Z.A. de l'Observatoire - 78180 MONTIGNY LE BX - France
 Siret : 344 545 645 00022 - Tél. : 33 (0)1 30 57 55 55 - Fax : 33 (0)1 30 43 74 48 - E-mail : contact@emitech.fr - URL : www.emitech.fr
 S.A. au capital de 1 560 000 € - R.C.S. VERSAILLES 344 545 645 - APE 7112B