

Test report no.: Prüfbericht-Nr.:	CN237HC2 004	Order No.: Auftragsnr.:	168444544	Page 1 of 11 Seite 1 von 11	
Client reference no.: Kunden-Referenz-Nr.:	N/A	Order date: Auftragsdatum:	2023-09-15		
Client: Auftraggeber:	Vestel Elektronik Sanayi ve Ticaret A.S. Organize Sanayi Bolgesi, 45030 Manisa TURKEY				
Test item: Prüfgegenstand:	17WFM26Y WI-FI + BT combo module				
Identification / Type no.: Bezeichnung / Typ-Nr.:	17WFM26Y				
Order content: Auftrags-Inhalt:	Test Report				
Test specification Prüfgrundlage:	47 CFR FCC Part 2.1091 RSS-102 Issue 5				
Date of sample receipt: Wareneingangsdatum:	2023-09-20	Please refer to Photo Document			
Test sample no: Prüfmuster-Nr.:	A003554099-001				
Testing period: Prüfzeitraum:	2023-09-25 - 2023-11-15				
Place of testing: Ort der Prüfung:	Refer to section 2.1				
Testing laboratory: Prüflaboratorium:	TÜV Rheinland (Shenzhen) Co., Ltd.				
Test result*: Prüfergebnis*:	Pass				
tested by: geprüft von:			authorized by: genehmigt von:		
Date: 2023-12-20 Datum:	Signed by: Bell Hu		Issue date: 2023-12-20 Ausstellungsdatum:	Signed by: Jonathan Li	
Position / Stellung:	Expert/Sachverständige(r)		Position / Stellung:	Expert/Sachverständige(r)	
Other: Sonstiges:	FCC ID: 2AVQS-17WFM26Y, IC: 25888-17WFM26Y, HVIN: V2.0, PMN: 17WFM26Y WI-FI + BT combo module				
Condition of the test item at delivery: Zustand des Prüfgegenstandes bei Anlieferung:			Test item complete and undamaged Prüfmuster vollständig und unbeschädigt		
* Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested * Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet					
This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark. <i>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</i>					

V05

Test report no.: CN237HC2 004
Prüfbericht-Nr.:

Page 2 of 11
Seite 2 von 11

Remarks
Anmerkungen

- | | |
|----------|--|
| 1 | <p>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</p> <p><i>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</i></p> |
| 2 | <p>As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.</p> <p><i>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.</i></p> |
| 3 | <p>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</p> <p><i>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</i></p> |
| 4 | <p>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</p> <p><i>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</i></p> |

Prüfbericht - Nr.: CN224AD0 004
Test Report No.:

Seite 3 von 11
Page 3 of 11

TEST SUMMARY

3.1.1 RF EXPOSURE COMPLIANCE

RESULT: Pass

CONTENTS

1.	TEST SITES.....	5
1.1	TEST FACILITIES	5
1.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS	5
1.3	TRACEABILITY	5
1.4	CALIBRATION.....	5
1.5	LOCATION OF ORIGINAL DATA	5
1.6	STATUS OF FACILITY USED FOR TESTING	5
2.	GENERAL PRODUCT INFORMATION	6
2.1	GENERAL DESCRIPTION	6
2.2	RATING AND SYSTEM DETAILS	6
3.	TEST RESULTS	8
3.1	TRANSMITTER REQUIREMENTS & TEST SUITES.....	8
3.1.1	RF Exposure Compliance.....	8
3.1.1.1	FCC Part 1.1310, Part 2.1091	9
3.1.1.2	RSS-102 Exemption Limits for Routine Evaluation – RF Exposure Evaluation	10
4.	LIST OF TABLES.....	11

1. TEST SITES

1.1 TEST FACILITIES

TÜV Rheinland (Shenzhen) Co., Ltd.

Address: No. 362 Huanguan Road Middle, Longhua District, Shenzhen 518110, P.R. China

FCC Registration No.: 694916

ISED Wireless Device Testing Laboratory: 25069

1.2 LIST OF TEST AND MEASUREMENT INSTRUMENTS

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing				
Equipment	Manufacturer	Model	Serial No.	Cal. until
Wireless Connectivity Tester	R&S	CMW270	101375	2022-08-09
Signal Analyzer	R&S	FSV 40	101441	2022-08-09

1.3 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

1.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

1.5 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendixes of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

1.6 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. facility located at No. 362 Huanguan Road Middle, Longhua District, Shenzhen 518110, P.R. China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

2. GENERAL PRODUCT INFORMATION

2.1 GENERAL DESCRIPTION

The Product is WI-FI + BT combo module, which supports Bluetooth, 2.4GHz Wi-Fi 802.11 b/g/n and 5GHz Wi-Fi 802.11a/b/g/n/ac wireless technology.

For details refer to the User Manual, Technical Description and Circuit Diagram.

2.2 RATING AND SYSTEM DETAILS

Table 2: Rating of EUT

General Information of EUT	Value
Kind of Equipment:	17WFM26Y WI-FI + BT combo module
Type Designation:	17WFM26Y
FCC ID:	2AVQS-17WFM26Y
IC:	25888-17WFM26Y
HVIN:	V2.0
Operating Voltage:	DC 5V
Antenna Type:	Integral Antennas
Antenna Gain:	Wi-Fi Antenna 1#: Max gain 3.4dBi for 2.4GHz Wi-Fi Max gain 2.97dBi for 5GHz Wi-Fi U-NII-1 and U-NII-2A Max gain 3.69dBi for 5GHz Wi-Fi U-NII-2C Max gain 2.89dBi for 5GHz Wi-Fi U-NII-3 Wi-Fi Antenna 2#: Max gain 2.14dBi for 2.4GHz Wi-Fi Max gain 3.7dBi for 5GHz Wi-Fi U-NII-1 and U-NII-2A Max gain 3.68dBi for 5GHz Wi-Fi U-NII-2C Max gain 2.83dBi for 5GHz Wi-Fi U-NII-3 BT Antenna #: Max gain 0.29dBi for Bluetooth As for MIMO mode for Antenna 1# and Antenna 2#, Cyclic Delay Diversity mode Employed.
Technical Specification of Bluetooth (Dual Mode)	
Operating Frequency:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Channel Number:	79 channels, BDR & EDR 40 channels, BLE
Channel Separation:	1MHz (for EDR & BDR), 2MHz (for BLE)
Technical Specification of Wi-Fi 802.11 b/g/n	
Operating Frequency:	2412 - 2462 MHz for 802.11b/g/n(HT20) 2422 - 2452 MHz for 802.11n(HT40)
Type of Modulation:	DSSS(DBPSK/DQPSK/CCK)

Prüfbericht - Nr.: CN237HC2 004

Test Report No.:

Seite 7 von 11

Page 7 of 11

	OFDM(BPSK/QPSK/16QAM/64QAM)
Data Rate:	1/2/5.5/11 Mbps for 802.11b 6/9/12/18/24/36/48/54 Mbps for 802.11g MCS0 ~ MCS7 for 802.11n
Channel Number:	11 channels for 802.11b/g/n(HT20) 7 channels for 802.11n(HT40)
Channel Separation:	5 MHz
MIMO and SISO mode:	SISO for 802.11b/g, MIMO and SISO for 802.11n, no beamforming.
Technical Specification of Wi-Fi 802.11 a/n/ac	
Operating Frequency:	5180-5320MHz, 5500-5700MHz, 5745-5825MHz
Type of Modulation:	OFDM(BPSK/QPSK/16QAM/64QAM/256QAM)
Operating Modes:	802.11 a/n20/n40/ac20/ac40/ac80
Channel Separation	5 MHz
MIMO and SISO mode:	SISO for 802.11a, MIMO and SISO for 802.11n/ac, no beamforming.

3. Test Results

3.1 Transmitter Requirements & Test Suites

3.1.1 RF Exposure Compliance

RESULT:**Pass**

Test standard	:	RSS-102 Issue 5 FCC Part 1.1091
Limit	:	Table 1 of 47 CFR FCC Part 1.1310 Section 2.5.2 of RSS-102 Issue 5
Kind of test site	:	Shielded room

This device is mobile device, and the applicant declares that the minimum separation distance is greater than 20cm. Therefore MPE measurement or computational modelling should be used to determine compliance.

MPE Calculation is based on the conducted power, and considering maximum power and Antenna gain. The following formula is used to MPE evaluation.

$$Pd = \frac{P_{out} * G}{4R^2\pi}$$

Where

P_d = power density in mW/cm² or W/m²

P_{out} = output power to antenna in mW or W

G_{num} = Antenna gain in numeric

π = 3.14159

R = Distance between observation point and the center of radiator in cm or m

3.1.1.1 FCC Part 1.1310, Part 2.1091

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

Table 3: Test Results of RF Exposure Calculations for FCC, Stand-alone mode

Operating Mode	Max. EIRP incl. tune-up (dBm)	Distance (cm)	MPE (mW/cm ²)	Limit (mW/cm ²)	Verdict
Bluetooth	7.00	20	0.001	1.0	Pass
2.4GHz Wi-Fi	23.00	20	0.040	1.0	Pass
5GHz Wi-Fi	22.00	20	0.032	1.0	Pass

Table 4: Test Results of RF Exposure Calculations for FCC, Simultaneous mode

Co-location Mode	Sum of the MPE ratios	Limit	Verdict
2.4GHz Wi-Fi+ Bluetooth	0.040/1+0.001/1<1.0	1.0	Pass
5GHz Wi-Fi+ Bluetooth	0.032/1+0.001/1<1.0	1.0	Pass

3.1.1.2 RSS-102 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Table 5: Test Results of RF Exposure Calculations for ISED, Stand-alone

Operating Mode	Max. EIRP incl. tune-up (dBm)	Distance (cm)	Maximum EIRP (W)	Threshold power (W)	Verdict
Bluetooth	7.00	20	0.005	2.68	Pass
2.4GHz Wi-Fi	23.00	20	0.200	2.70	Pass
5GHz Wi-Fi	22.00	20	0.158	4.52	Pass

Note: The maximum EIRP much lower than the threshold power in section 2.5.2, thus compliant.

Table 6: Test Results of RF Exposure Calculations for ISED, Simultaneous mode

Co-location Mode	Sum of the ratios	Limit	Verdict
2.4GHz Wi-Fi+ Bluetooth	$0.200/2.70 + 0.005/2.68 < 1.0$	1.0	Pass
5GHz Wi-Fi+ Bluetooth	$0.158/4.52 + 0.005/2.68 < 1.0$	1.0	Pass

4. List of Tables

Table 1: List of Test and Measurement Equipment	5
Table 2: Rating of EUT	6
Table 3: Test Results of RF Exposure Calculations for FCC, Stand-alone mode	9
Table 4: Test Results of RF Exposure Calculations for FCC, Simultaneous mode.....	9
Table 5: Test Results of RF Exposure Calculations for ISED, Stand-alone	10
Table 6: Test Results of RF Exposure Calculations for ISED, Simultaneous mode.....	10