



element

Athena GTX, Inc.


HsPro

FCC 1.1307:2023

802.11b/g/n

Bluetooth Low Energy

Report: AGTX0071.0 Rev.01, Issue Date: October 19, 2023



This report must not be used to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the U.S. Government. This Report shall not be reproduced, except in full without written approval of the laboratory.

TABLE OF CONTENTS



Section	Page Number
Certificate of Evaluation	3
Revision History	4
Accreditations.....	5
Facilities	6
Product Description	7
Exposure Condition.....	8
Exemption From RF Exposure Evaluation	9
Appendix	12
End of Report.....	17



CERTIFICATE OF EVALUATION

Last Date of Evaluation: October 16, 2023
Athena GTX, Inc.
EUT: HsPro

RF Exposure Evaluation

Standards

Specification	Method
FCC 1.1307:2023	FCC 1.1307:2023

Results

Method Clause	Description	Applied	Results	Comments
(b)(3)(ii)(B)	Exemption From RF Exposure Evaluation	Yes	Pass	N/A

Deviations From Evaluation Standards

None

Approved By:

Donald Facteau, Process Architect

Product compliance is the responsibility of the client; therefore, the tests and equipment modes of operation represented in this report were agreed upon by the client, prior to testing. The results of this test pertain only to the sample(s) tested. The specific description is noted in each of the individual sections of the test report supporting this certificate of test. This report reflects only those tests from the referenced standards shown in the certificate of test. It does not include inspection or verification of labels, identification, marking or user information. As indicated in the Statement of Work sent with the quotation, Element's standard process is to always use the latest published version of the test methods even when earlier versions are cited in the test specification. Issuance of a purchase order was de facto acceptance of this approach. Otherwise, the client would have advised Element in writing of the specific version of the test methods they wanted applied to the subject testing

REVISION HISTORY



Revision Number	Description	Date (yyyy-mm-dd)	Page Number
01	Corrected limits applied to assessment tables	2023-10-19	11

ACCREDITATIONS AND AUTHORIZATIONS



United States

FCC - Designated by the FCC as a Telecommunications Certification Body (TCB). Certification chambers, Open Area Test Sites, and conducted measurement facilities are listed with the FCC.

A2LA - Each laboratory is accredited by A2LA to ISO / IEC 17025, and as a product certifier to ISO / IEC 17065 which allows Element to certify transmitters to FCC and IC specifications.

Canada

ISED - Recognized by Innovation, Science and Economic Development Canada as a Certification Body (CB) and as a CAB for the acceptance of test data.

European Union

European Commission – Recognized as an EU Notified Body validated for the EMCD and RED Directives.

United Kingdom

BEIS – Recognized by the UK as an Approved Body under the UK Radio Equipment and UK EMC Regulations.

Australia/New Zealand

ACMA - Recognized by ACMA as a CAB for the acceptance of test data.

Korea

MSIT / RRA - Recognized by KCC's RRA as a CAB for the acceptance of test data.

Japan

VCCI - Associate Member of the VCCI. Conducted and radiated measurement facilities are registered.

Taiwan

BSMI – Recognized by BSMI as a CAB for the acceptance of test data.

NCC - Recognized by NCC as a CAB for the acceptance of test data.

Singapore

IDA – Recognized by IDA as a CAB for the acceptance of test data.

Israel

MOC – Recognized by MOC as a CAB for the acceptance of test data.

Hong Kong

OFCA – Recognized by OFCA as a CAB for the acceptance of test data.

Vietnam

MIC – Recognized by MIC as a CAB for the acceptance of test data.

SCOPE

For details on the Scopes of our Accreditations, please visit:

[California](#)

[Minnesota](#)

[Oregon](#)


[Texas](#)

[Washington](#)

FACILITIES



California Labs OC01-17 41 Tesla Irvine, CA 92618 (949) 861-8918	Minnesota Labs MN01-11 9349 W Broadway Ave. Brooklyn Park, MN 55445 (612) 638-5136	Oregon Labs EV01-12 6775 NE Evergreen Pkwy #400 Hillsboro, OR 97124 (503) 844-4066	Texas Labs TX01-09 3801 E Plano Pkwy Plano, TX 75074 (469) 304-5255	Washington Labs NC01-05 19201 120 th Ave NE Bothell, WA 98011 (425) 984-6600
A2LA				
Lab Code: 3310.04	Lab Code: 3310.05	Lab Code: 3310.02	Lab Code: 3310.03	Lab Code: 3310.06
Innovation, Science and Economic Development Canada				
2834B-1, 2834B-3	2834E-1, 2834E-3	2834D-1	2834G-1	2834F-1
BSMI				
SL2-IN-E-1154R	SL2-IN-E-1152R	SL2-IN-E-1017	SL2-IN-E-1158R	SL2-IN-E-1153R
VCCI				
A-0029	A-0109	A-0108	A-0201	A-0110
Recognized Phase I CAB for ISED, ACMA, BSMI, IDA, KCC/RRA, MIC, MOC, NCC, OFCA				
US0158	US0175	US0017	US0191	US0157



PRODUCT DESCRIPTION



Client and Equipment Under Evaluation Information

Company Name:	Athena GTX, Inc.
Address:	5900 NW 86th Street
City, State, Zip:	Johnston, IA 50131
Evaluation Requested By:	Sean Mahoney
EUT:	HsPro
Date of Evaluation:	10/19/2023

Information Provided by the Party Requesting the Evaluation

Functional Description of the Equipment:

HsPro Series system is a physiological status monitor that has three components: HsPro (The central Hub with SpO2 and Pulse Rate Sensors), Anteros (Environmental Sensors) and EchoXT Heart Rate and Temperature Sensors). The HsPro is the subject of this submission and is attached to users by an arm strap on the bicep.

HsPro connects to applicable Bluetooth Low Energy (BLE) accessories while sending environmental and user physiological data through wireless radio communications from the HsPro device to an HsPro viewer on a PC, Android, or iOS device.

NOTE up to two BLE modules will be co-transmitting with a Wi-Fi radio module.

Objective:

To demonstrate compliance with FCC Requirements for RF exposure for 1.1307 RF exempt devices

RF EXPOSURE CONDITION



The following RF Exposure conditions were used for the assessment documented in this report:	
Intended Use	Portable
Location on Body (if applicable)	Limb
How is the Device Used	Device is used at a distance less than 20cm from the user.
Radios Contained in the Same Host Device	802.11b/g/n Bluetooth Low Energy
Simultaneous Transmitting Radios	802.11b/g/n, Bluetooth Low Energy
Body Worn Accessories	Cloth arm-band
Environment	General Population/Uncontrolled Exposure

EXEMPTION FROM RF EXPOSURE EVALUATION



OVERVIEW

With respect to the limits on human exposure to RF emissions provided in 47 CFR §1.1310, if equipment can be shown to qualify for an exemption pursuant to 47 CFR §1.1307(b)(3), an evaluation is not required.

COMPLIANCE WITH FCC 1.1310

Per 1.1307(b)(3), (i) For single RF sources (*i.e.*, any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

- (A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);
- (B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th}(mW) = \begin{cases} ERP_{20\text{ cm}}(d/20\text{ cm})^x & d \leq 20\text{ cm} \\ ERP_{20\text{ cm}} & 20\text{ cm} < d \leq 40\text{ cm} \end{cases}$$

Where

$$x = -\log_{10}\left(\frac{60}{ERP_{20\text{ cm}}\sqrt{f}}\right) \text{ and } f \text{ is in GHz};$$

And

$$ERP_{20\text{ cm}}(mW) = \begin{cases} 2040f & 0.3\text{ GHz} \leq f < 1.5\text{ GHz} \\ 3060 & 1.5\text{ GHz} \leq f \leq 6\text{ GHz} \end{cases}$$

- (C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

TABLE 1 TO §1.1307(b)(3)(i)(C)—SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R ² .
1.34-30	3,450 R ² /f ² .
30-300	3.83 R ² .
300-1,500	0.0128 R ² f.
1,500-100,000	19.2R ² .

EXEMPTION FROM RF EXPOSURE EVALUATION



(ii) For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for P_{th} , including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$ = the exemption threshold power (P_{th}) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i .

ERP_j = the ERP of fixed, mobile, or portable RF source j .

$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

$Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure\ Limit_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k , as applicable from §1.1310

The relationship between EIRP and ERP is:

$$ERP\ (dBm) = EIRP\ (dBm) - 2.14\ dB$$

Where EIRP is the sum of the conducted power (dBm) and the antenna gain (dBi).

EXEMPTION FROM RF EXPOSURE EVALUATION



ASSESSMENT

The exemption from RF exposure evaluation is summarized in the following table(s):

Radio	Transmit Frequency (MHz)	Conducted Output Power	Power Tolerance (dB)	Duty Cycle	Antenna Assembly Gain (dBi)	Minimum Separation Distance (cm)	Calculated Radiated Exposure Power (mW) ERP	Calculated Conducted Exposure Power (mW dBm)	Limit (mW)	Ratio
802.11b/g/n: XB2B-WFWT-001	2412	26.81 dBm	0.0	0.9%	1.5	1.4991	3.8	4.4	22.4	0.20
Max Ratio										0.20

The information in the table above was obtained from:

The rated value was used in these calculations. From client supplied information and maximum output power (worst-case) listed on the grant. FCC ID: 2AVRK-XBS6BTH.

Radio	Transmit Frequency (MHz)	Conducted Output Power	Power Tolerance (dB)	Duty Cycle	Antenna Assembly Gain (dBi)	Minimum Separation Distance (cm)	Calculated Radiated Exposure Power (mW) ERP	Calculated Conducted Exposure Power (mW dBm)	Limit (mW)	Ratio
Bluetooth Low Energy: BMD-301 #2	2402	4 dBm	0.0	0.9%	2.5	0.90969	0.0	0.0	8.7	0.00
Bluetooth Low Energy: BMD-301 #1	2402	4 dBm	0.0	0.9%	2.5	0.90969	0.0	0.0	8.7	0.00
Max Ratio										0.00

The information in the table above was obtained from:

The rated value was used in these calculations. From client supplied information. FCC ID: 2AVRK-BMD301.

Duty Cycle Information:

Device transmits 1 packet (5680 bytes) at a minimum data rate of 1 Mbps every 5 seconds during normal operation.

As stated by Sean Mahoney, VP of Engineering & Regulatory Affairs, 10 October 2023


Sum of Maximum Ratios	Limit	Compliant
0.20	1	Yes

Evaluator: Chuck Heller


Appendix

Addendum to the RF Exposure Report Information


Co-location Separation: 16.022 mm




Antenna – Skin Separation: Wi-Fi XBEE: 14.99 mm



BLE-0: 9.10 mm



BLE-1: 0.475in (12.07 mm)



Host Accessory Materials (surround antenna): Armband made of bamboo-based memory foam, polyester/micro-modal/merino wool mesh fabric, thermoplastic polyurethane (TPU) grommets, and polyethylene terephthalate (rPET) lining.

Live Data mode transmits 1 packet every 5 seconds.

Historical Data Mode requests previous live data packets that were missed, for up to 3 packets every 5 seconds in addition to the 1 Live Data packet.

Live Data Mode Duty Cycle:

Packet size: 1420 bytes (max)

Data Rate: 802.11b at 1 Mbps to 11 Mbps, and 802.11n at 6.5 Mbps – 72.22 Mbps

Packet Transmit Time (at 1Mbps): 11.4 ms

Worst Case Duty Cycle Calculation: 1420 bytes = 11360 bits

At the slowest rates for each radio over a 5 second interval:

HsPro		Wi-Fi		Xbee			
Max Calc				Minimum			
Bytes/Sec	bits/Byte	bits/sec	Sec	Duty Cycle/Sec		Typical Power (dBm)	FCC Peak (dBm)
1420	8	1000000	2.3E-3	0.227%	b	16	26.81
		6000000	378.7E-6	0.038%	g	16	28.52
		6500000	349.5E-6	0.035%	n	15	28.75

Historical Data Mode + Live Data Duty Cycle:

Packet size: 1420 bytes (max)

Data Rate: 802.11b at 1 Mbps to 11 Mbps, and 802.11n at 6.5 Mbps – 72.22 Mbps

Packet Transmit Time (at 1Mbps): 45.4 ms

Worst Case Duty Cycle Calculation (4 packets max per 5 sec): 5680 bytes = 45,440 bits

At the slowest rates for each radio over a 5 second interval:

Worst Case History + Live (4 x Max Calc)

HsPro	Wi-Fi	Xbee Minimum					Typical	FCC Peak
			Bytes/Sec	bits/Byte	bits/sec	Sec	Duty Cycle/Sec	Power (dBm)
5680	8	1000000	9.1E-3	0.909%	b	16	26.81	
		6000000	1.5E-3	0.151%	g	16	28.52	
		6500000	1.4E-3	0.140%	n	15	28.75	

HsPro BLE-0	Xbee Minimum	5 Sec Transmission Interval				Typical	FCC Peak
		Bytes/Sec	bits/Byte	bits/sec	Sec	Duty Cycle/Sec	Power (dBm)
5680	8	1000000	9.1E-3	0.909%	350		4
		1000000	9.1E-3	0.909%	300		4
		1000000	9.1E-3	0.909%	301		4

HsPro BLE-1	Xbee Minimum	300 Sec Tx Interval (every 5 min)				Typical	FCC Peak
		Bytes/Sec	bits/Byte	bits/sec	Sec	Duty Cycle/Sec	Power (dBm)
1	8	1000000	26.7E-9	0.000%	350		4
		1000000	26.7E-9	0.000%	300		4
		1000000	26.7E-9	0.000%	301		4

End of Test Report