

Athena-GTX, Inc. addendum

FCC ID: 2AVRK-XBS6BTH is configured in a specific singular modular use configuration, this addendum is created to support changes. Information in this addendum is designed to replace FCC publication 996369 related information on *Digi XBee Wi-Fi RF Module User Guide Rev W*, except where specifically stated.

FCC publication 996369 related information

In publication 996369 section D03, the FCC requires information concerning a module to be presented by OEM manufacturers. This section assists in answering or fulfilling these requirements.

2.1 General

No requirements are associated with this section.

2.2 List of applicable FCC rules

This module conforms to FCC Part 15.247.

2.3 Summarize the specific operational use conditions

For the XBee Wi-Fi RF Module, see FCC approved antenna (2.4 GHz) identified in section 2.7 of this addendum.

Once integrated with the Host Device, the Wi-Fi module will communicate (TX/RX) using 2.4 GHz at the nominal power setting (16 dBM), duty cycle <14.1 %. Modules will be in portable use, <20 cm proximity to user's body.

Users are not permitted to modify antenna or alter pre-defined Host or Module configuration settings, outside of connecting and disconnect other devices.

2.4 Limited module procedures

Not applicable.

2.5 Trace antenna designs

Not applicable.

2.6 RF exposure considerations

See conditions in Section 2.3 above that allow for use <20cm proximity to the user's body.

2.7 Antennas

For XBee, only P/N: A24-QI monopole (Integrated Whip) antenna is approved to be used for this module.

2.8 Label and compliance information

A physical label stating "Contains FCC ID: 2AVRK- XBS6BTH", shall be used on the outside of the enclosure of the host product.

Note, the label 'phrase' will be a single line on the host product.



2.9 Information on test modes and additional testing requirements

Devices shall be reviewed under configured max operational settings (standard use) for SAR, Spurious Radiated Emissions. Unintentional Radiators is also required for review, however, due to setting requirements (RF modules disabled), only Athena GTX Inc. is permitted to configure a test unit for this mode.

When testing for all, except for Unintentional Radiators, both Wi-Fi modules must be tested after a connection with a partnering WLAN device is established and information is transmitting.

Antenna power, duty cycle, and transmission rate cannot be altered from approved settings, see RF Exposure report for technical information.

2.10 Additional testing, Part 15 Subpart B disclaimer

Not applicable, see this section in original Digi XBee Wi-Fi RF Module User Guide Rev W or greater.