



FCC TEST REPORT

FCC ID: 2AVRV-DG3200

On Behalf of

DP AUDIO VIDEO LLC

32inch Rollable Smart Touchscreen TV

Model No.: DG3200RTV, OR3200RTV, WH32pro, CR3200RTV

Prepared for : DP AUDIO VIDEO LLC
Address : 1001 Gayley Avenue P.O Box 24857, Los Angeles, CA, USA 90024


Prepared By : Shenzhen PSI Testing Co., Ltd.
Address : 1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road,
Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Report Number : psi2404032-C01-R01
Date of Receipt : April 11, 2024
Date of Test : April 11, 2024-May 15, 2024
Date of Report : May 15, 2024
Version Number : V0

TABLE OF CONTENTS

Description	Page
1. Summary Of Standards And Results.....	6
1.1. Description of Standards and Results	6
2. General Information.....	7
2.1. Description of Device (EUT).....	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details	8
2.4. Block Diagram of connection between EUT and simulators	8
2.5. Test Mode Description	8
2.6. Test Conditions	9
2.7. Test Facility	9
2.8. Measurement Uncertainty	9
2.9. Test Equipment List	10
3. Maximum Peak Output Power	11
3.1. Limit.....	11
3.2. Test Procedure	11
3.3. Test Setup.....	11
3.4. Test Result.....	11
4. Bandwidth	12
4.1. Limit.....	12
4.2. Test Procedure	12
4.3. Test Result.....	12
5. Carrier Frequency Separation	23
5.1. Limit.....	23
5.2. Test Procedure	23
5.3. Test Result.....	23
6. Number Of Hopping Channel	25
6.1. Limit.....	25
6.2. Test Procedure	25
6.3. Test Result.....	25
7. Dwell Time	27
7.1. Test limit.....	27
7.2. Test Procedure	27
7.3. Test Result.....	27
8. Out-of-band Emissions	37
8.1. Test Limits.....	37
8.2. Test Procedure	37
8.3. Test Setup.....	37
8.4. Test Results	37
9. Radiated Emissions.....	59
9.1. Limit.....	59
9.2. Block Diagram of Test setup.....	60
9.3. Test Procedure	61

9.4. Test Results	61
10. Band Edge Test.....	69
10.1. Block Diagram of Test Setup	69
10.2. Test Limit	69
10.3. Test Procedure	69
10.4. Test Results	70
11. Power Line Conducted Emissions.....	73
11.1. Block Diagram of Test Setup	73
11.2. Limit.....	73
11.3. Test Procedure	73
11.4. Test Results	74
12. Antenna Requirements	77
12.1. Limit.....	77
12.2. Result	77
13. Photos of test setup	78
14. Photos of EUT	78



TEST REPORT DECLARATION

Applicant : DP AUDIO VIDEO LLC

Address : 1001 Gayley Avenue P.O Box 24857, Los Angeles, CA, USA 90024

Manufacturer : Shenzhen Weihejia Electronics Technology Co.,LTD

Address : Block 102, Building 9, Xihu Industrial park, Xikeng community, Yuanshan street,
Longgang district, Shenzhen

EUT Description : 32inch Rollable Smart Touchscreen TV

(A) Model No. : DG3200RTV, OR3200RTV, WH32pro, CR3200RTV


(B) Trademark : DURAGO, ORCATV, CORE INNOVATIONS

Measurement Standard Used:

**FCC Rules and Regulations Part 15 Subpart C Section 15.247,
ANSI C63.10-2013**

The device described above is tested by Shenzhen PSI Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen PSI Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC Part 15C requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen PSI Testing Co., Ltd.

Tested by (name + signature).....: Felix Pang
Test Engineer 

Approved by (name + signature).....: Simple Guan
Project Manager 

Date of issue.....: May 15, 2024

Revision History

Revision	Issue Date	Revisions	Revised By
V0	May 15, 2024	Initial released Issue	Felix Pang



1. Summary Of Standards And Results

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1)	P
Bandwidth	FCC Part 15:15.247(a)(1)	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1)	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)	P
Dwell Time	FCC Part 15: 15.247(a)(1)	P
Radiated Spurious Emission	FCC Part 15: 15.209 FCC Part 15: 15.205	P
Out-of-band Emissions	FCC Part 15: 15.247(d)	P
Radiated Band Edge Emission	FCC Part 15: 15.247(d)	P
Power Line Conducted Emissions	FCC Part 15: 15.207	P
Antenna requirement	FCC Part 15: 15.203	P
Note: 1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable. 4. Conclusion determination rules of this report: Unless there are clear provisions on measurement uncertainty in the standard or customer requirements, decision by actual test data without considering measurement uncertainty. 5. Measurement method usage KDB 558074 D01 15.247 Meas Guidance v05r02.		

2. General Information

2.1. Description of Device (EUT)

Description/PMN : 32inch Rollable Smart Touchscreen TV
Model : DG3200RTV, OR3200RTV, WH32pro, CR3200RTV
Diff : There is no difference except the name of the model. All tests are made with the DG3200RTV model.
Test Voltage : DC 18V from adapter, DC 12.8V from battery

Radio Technology : Bluetooth V5.0 EDR

Operation frequency : 2402MHz-2480MHz

Modulation : GFSK, $\pi/4$ -DQPSK, 8DPSK

Channel No. : 79 Channels

Channel Separation : 1MHz

Antenna Type : Internal antenna, Maximum Gain is 2.64dBi.

Software version : V1.0

Hardware version : V1.0

Note : Antenna information is provided by applicant.
Testing lab is not responsible for the accuracy of the information.


2.2. Accessories of Device (EUT)

Accessories	: POWER ADAPTER
Manufacturer	: N/A
Model	: BCT180600-157ED
Input	: 100-240V~ Max 1.6A 50/60Hz
Output	: DC 18.0V/6.0A

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number
1	N/A	N/A	N/A	N/A

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

The test software used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
GFSK / Pi/4-DQPSK/ 8DPSK Carrier Tx Mode	CH0	2402
	CH39	2441
	CH78	2480
GFSK / Pi/4-DQPSK/ 8DPSK hopping on Tx Mode	CH0 to CH78	2402 to 2480
GFSK / Pi/4-DQPSK/ 8DPSK hopping off Tx Mode	CH0	2402
	CH39	2441
	CH78	2480

2.6. Test Conditions

Items	Required
Temperature range:	15-35℃
Humidity range:	25-75%
Pressure range:	86-106kPa

2.7. Test Facility

Shenzhen PSI Testing Co., Ltd.

1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

September 13, 2023 File on Federal Communication Commission

Registration Number: 916281

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.17dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	2.74dB(Polarize: V)
	2.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 18GHz)	4.29dB(Polarize: V)
	4.82dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31 dB(Polarize: V)
	4.30 dB(Polarize: H)
Uncertainty for radio frequency	48.24KHz
Uncertainty for conducted RF Power	0.41dB
Occupied Bandwidth	968Hz
Conducted Spurious Emission	1.26dB

2.9. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2022.12.20	3 Year
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2023.12.19	1 Year
3.	L.I.S.N.#1	Rohde&Schwarz	ENV216	102282	/	2023.12.19	1 Year
4.	L.I.S.N.#2	RFT	NNB111	13835240	/	2023.12.19	1 Year
5.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2023.04.03	2 Year
6.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2022.12.26	2 Year
7.	Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101648	3.70	2023.12.19	1 Year
8.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2022.12.26	2 Year
9.	Amplifier	SKET	LAPA_01G1 8G-45dB	SK20220329 01	/	2023.12.19	1 Year
10.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2022.12.25	2 Year
11.	Amplifier	SKET	LNPA_0118 G-45	SK20200108 01	/	2023.12.19	1 Year
12	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.0 2-1111533-F z	/	2023.12.19	1 Year
13	RF Sensor Unit	Tachoy	TR1029-2	20220428P0 08	/	2023.12.19	1 Year
14	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2023.12.19	1 Year
15	Temp. & Humid Chamber	Auchno	9606	/	/	2023.12.19	1 Year
16	Regulated DC Power Supply	Xinouhua	ADC120V10 A	2022112516 38		2023.12.19	1 Year
For Test Software Information							
Item	Software Name	Manufacturer			Version		
RE	EZ_EMC	Farad			PSI-3A1		
CE	EZ_EMC	Farad			PSI-3A1		
RF	RTS	TACHOY			V1.0.0		

3. Maximum Peak Output Power

3.1. Limit


Please refer FCC part 15.247 & RSS-247.

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W.

3.2. Test Procedure

The transmitter output is connected to the RF Power meter. The Power meter is set to the peak power detection.

3.3. Test Setup



3.4. Test Result

Condition	Antenna	Modulation	Frequency (MHz)	Max. Conducted Power(dBm)	Max. Conducted Power(mW)	Limit(mW)	Result
NVNT	ANT1	1-DH1	2402.00	4.33	2.71	1000	Pass
NVNT	ANT1	1-DH1	2441.00	6.35	4.32	1000	Pass
NVNT	ANT1	1-DH1	2480.00	5.80	3.80	1000	Pass
NVNT	ANT1	2-DH1	2402.00	4.03	2.53	125	Pass
NVNT	ANT1	2-DH1	2441.00	6.12	4.09	125	Pass
NVNT	ANT1	2-DH1	2480.00	5.94	3.93	125	Pass
NVNT	ANT1	3-DH1	2402.00	5.70	3.71	125	Pass
NVNT	ANT1	3-DH1	2441.00	7.62	5.78	125	Pass
NVNT	ANT1	3-DH1	2480.00	7.42	5.53	125	Pass

4. Bandwidth

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in RSS-GEN, FCC Section 15.247(a)(1), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result

Condition	Antenna	Modulation	Frequency (MHz)	-20dB BW(MHz)	if larger than CFS
NVNT	ANT1	1-DH1	2402.00	0.805	No
NVNT	ANT1	1-DH1	2441.00	0.803	No
NVNT	ANT1	1-DH1	2480.00	0.798	No
NVNT	ANT1	2-DH1	2402.00	1.110	Yes
NVNT	ANT1	2-DH1	2441.00	1.113	Yes
NVNT	ANT1	2-DH1	2480.00	1.111	Yes
NVNT	ANT1	3-DH1	2402.00	1.180	Yes
NVNT	ANT1	3-DH1	2441.00	1.180	Yes
NVNT	ANT1	3-DH1	2480.00	1.183	Yes

-20dB_Bandwidth_NVNT_ANT1_1-DH1_2402**-20dB_Bandwidth_NVNT_ANT1_1-DH1_2441**

-20dB_Bandwidth_NVNT_ANT1_1-DH1_2480**-20dB_Bandwidth_NVNT_ANT1_2-DH1_2402**

-20dB_Bandwidth_NVNT_ANT1_2-DH1_2441**-20dB_Bandwidth_NVNT_ANT1_2-DH1_2480**

-20dB_Bandwidth_NVNT_ANT1_3-DH1_2402**-20dB_Bandwidth_NVNT_ANT1_3-DH1_2441**

-20dB_Bandwidth_NVNT_ANT1_3-DH1_2480

Condition	Antenna	Modulation	Frequency (MHz)	99%BW(MHz)
NVNT	ANT1	1-DH1	2402.00	0.847
NVNT	ANT1	1-DH1	2441.00	0.848
NVNT	ANT1	1-DH1	2480.00	0.848
NVNT	ANT1	2-DH1	2402.00	1.071
NVNT	ANT1	2-DH1	2441.00	1.071
NVNT	ANT1	2-DH1	2480.00	1.070
NVNT	ANT1	3-DH1	2402.00	1.130
NVNT	ANT1	3-DH1	2441.00	1.129
NVNT	ANT1	3-DH1	2480.00	1.130

99%_Occupied_Bandwidth_NVNT_ANT1_1-DH1_2402



99%_Occupied_Bandwidth_NVNT_ANT1_1-DH1_2441



99%_Occupied_Bandwidth_NVNT_ANT1_1-DH1_2480



99%_Occupied_Bandwidth_NVNT_ANT1_2-DH1_2402



99%_Occupied_Bandwidth_NVNT_ANT1_2-DH1_2441




99%_Occupied_Bandwidth_NVNT_ANT1_2-DH1_2480



99%_Occupied_Bandwidth_NVNT_ANT1_3-DH1_2402



99%_Occupied_Bandwidth_NVNT_ANT1_3-DH1_2441



99%_Occupied_Bandwidth_NVNT_ANT1_3-DH1_2480



5. Carrier Frequency Separation

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

5.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 100kHz RBW and 300kHz VBW.

5.3. Test Result

Condition	Antenna	Modulation	Frequency(MHz)	Hopping NO.0 (MHz)	Hopping NO.1 (MHz)	Carrier Frequencies Separation(MHz)	Limit(MHz)	Result
NVNT	ANT1	1-DH1	2441.00	2440.996	2442.037	1.04	0.804	Pass
NVNT	ANT1	2-DH1	2441.00	2440.996	2441.995	1.00	0.742	Pass
NVNT	ANT1	3-DH1	2441.00	2440.999	2441.998	1.00	0.789	Pass

Carrier_Frequencies_Separation_(Hopping)_NVNT_ANT1_1-DH1_Hopping



Carrier_Frequencies_Separation_(Hopping)_NVNT_ANT1_2-DH1_Hopping



Carrier_Frequencies_Separation_(Hopping)_NVNT_ANT1_3-DH1_Hopping



6. Number Of Hopping Channel

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 75 channels,
For all other frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels


6.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.


6.3. Test Result

Condition	Antenna	Modulation	Hopping Num	Limit	Result
NVNT	ANT1	1-DH1	79	75	Pass
NVNT	ANT1	2-DH1	79	15	Pass
NVNT	ANT1	3-DH1	79	15	Pass

Number_of_Hopping_Channel_(Hopping)_NVNT_ANT1_1-DH1_Hopping



Number_of_Hopping_Channel_(Hopping)_NVNT_ANT1_2-DH1_Hopping



Number_of_Hopping_Channel_(Hopping)_NVNT_ANT1_3-DH1_Hopping



7. Dwell Time

7.1. Test limit

Please refer FCC part 15.247 & RSS-247.

Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channel employed.

7.2. Test Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
5. Repeat above procedures until all frequency measured were complete.
6. The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$
7. Dwell Time = Pulse Time * Hops Number

7.3. Test Result

Condition	Antenna	Packet Type	Pulse Time(ms)	Hops	Dwell Time(ms)	Limit(s)	Result
NVNT	ANT1	1-DH1	0.407	320.00	130.240	0.40	Pass
NVNT	ANT1	2-DH1	0.393	319.00	125.367	0.40	Pass
NVNT	ANT1	3-DH1	0.393	317.00	124.581	0.40	Pass
NVNT	ANT1	1-DH3	1.663	159.00	264.417	0.40	Pass
NVNT	ANT1	1-DH5	2.911	110.00	320.210	0.40	Pass
NVNT	ANT1	2-DH3	1.645	172.00	282.940	0.40	Pass
NVNT	ANT1	2-DH5	2.893	100.00	289.300	0.40	Pass
NVNT	ANT1	3-DH3	1.645	169.00	278.005	0.40	Pass
NVNT	ANT1	3-DH5	2.893	100.00	289.300	0.40	Pass

The screenshot displays the Agilent Spectrum Analyzer - Sweep SA interface. The main window shows a frequency spectrum plot with a yellow signal trace. Key parameters are visible:

- Center Freq:** 2.441000000 GHz
- Ref Offset:** 4.08 dB
- Ref:** 21.16 dBm
- Trig Delay:** 500.0 μs
- Trig:** Video
- #Avg Type:** RMS
- PNO:** Fast
- IFGain:** Low
- Atten:** 28 dB
- ΔMkr1:** 407.0 μs
- Log Scale:** 10 dB/div
- Span:** 0 Hz
- Res BW:** 1.0 MHz
- #VBW:** 1.0 MHz
- Sweep:** 10.00 ms (30001 pts)

The right sidebar contains various controls and settings:


- Frequency:** 2.441000000 GHz
- Auto Tune**
- Start Freq:** 2.441000000 GHz
- Stop Freq:** 2.441000000 GHz
- CF Step:** 1.000000 MHz
- Freq Offset:** 0 Hz

The bottom section shows a table of measurement results:


MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	Δ2	t	(Δ)	407.0 μs	(Δ)	-17.87 dBm		
2	F	t		499.0 μs				

The screenshot displays an Agilent Spectrum Analyzer interface. The main plot shows a signal at 2.441 GHz with a span of 0 Hz. The signal is represented by a yellow trace. A green marker is visible at 13.64 s. The plot is labeled with 'Ref Offset 4.08 dB' and 'Ref 24.08 dBm'. The right-hand side of the screen features a control panel with various settings, including 'Auto Tune', 'Center Freq', 'Start Freq', 'Stop Freq', 'CF Step', 'Auto', 'Freq Offset', and 'Span 0 Hz'. The bottom status bar shows 'MSG' and 'STATUS'.


Dwell_Time_(Hopping)_NVNT_ANT1_2-DH1_2441_One_Burst_Time




Dwell_Time_(Hopping)_NVNT_ANT1_2-DH1_2441_Accumulated




Dwell_Time_(Hopping)_NVNT_ANT1_3-DH1_2441_One_Burst_Time




Dwell_Time_(Hopping)_NVNT_ANT1_3-DH1_2441_Accumulated



Dwell_Time_(Hopping)_NVNT_ANT1_1-DH3_2441_One_Burst_Time



Dwell_Time_(Hopping)_NVNT_ANT1_1-DH3_2441_Accumulated



Agilent Spectrum Analyzer - Sweep SA

Center Freq 2.441000000 GHz

Ref Offset 4.08 dB
Ref 21.16 dBm

ΔMkr1 1.645 ms
15.40 dB

10 dB/div
Log

X₂

1Δ2

TRIG LVL

Center 2.441000000 GHz

Res BW 1.0 MHz

#VBW 1.0 MHz

Span 0 Hz

Sweep 10.00 ms (30001 pts)

Mkr	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	Δ2	1	t	(Δ)	1.645 ms (Δ)	15.40 dB		
2	F	1	t		499.0 μs	-29.22 dBm		
3								
4								
5								
6								
7								
8								
9								
10								
11								

MISG

STATUS

Agilent Spectrum Analyzer - Swept SA

RL RF 50 Ω AC SENSE:PULSE ALIGN:OFF 06:38:13 PM Apr 20, 2024

Center Freq 2.441000000 GHz PNO: Fast Trg: Free Run #Avg Type: RMS
IFGain:Low Atten: 30 dB TYPE: W W W W W W W W
DET: P N N N N N

Ref Offset 4.08 dB
Ref 24.08 dBm


Mkr1 4.172 s
1.91 dBm

10 dB/div
Log


Center 2.441000000 GHz Span 0 Hz
Res BW 1.0 MHz #VBW 1.0 MHz Sweep 31.60 s (30001 pts)

MSG STATUS


Dwell_Time_(Hopping)_NVNT_ANT1_2-DH5_2441_One_Burst_Time




Dwell_Time_(Hopping)_NVNT_ANT1_2-DH5_2441_Accumulated




Dwell_Time_(Hopping)_NVNT_ANT1_3-DH3_2441_One_Burst_Time




Dwell_Time_(Hopping)_NVNT_ANT1_3-DH3_2441_Accumulated



Dwell_Time_(Hopping)_NVNT_ANT1_3-DH5_2441_One_Burst_Time



Dwell_Time_(Hopping)_NVNT_ANT1_3-DH5_2441_Accumulated



8. Out-of-band Emissions

8.1. Test Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in FCC Part 15.209(a) is not required.

8.2. Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, band edge and out-of-band emissions.

8.3. Test Setup



8.4. Test Results

PASS.


The test results are listed in next pages.

Band Edge: Pass

1_Reference_Level_NVNT_ANT1_1-DH1_2402




2_Bandedge_NVNT_ANT1_1-DH1_2402



1_Reference_Level_Hopping_NVNT_ANT1_1-DH1_Hopping




2_Band_Edge_(Hopping)_NVNT_ANT1_1-DH1_Hopping



1_Reference_Level_NVNT_ANT1_1-DH1_2480




2_Bandedge_NVNT_ANT1_1-DH1_2480



1_Reference_Level_Hopping_NVNT_ANT1_1-DH1_Hopping




2_Band_Edge_(Hopping)_NVNT_ANT1_1-DH1_Hopping




1_Reference_Level_NVNT_ANT1_2-DH1_2402




2_Bandedge_NVNT_ANT1_2-DH1_2402



1_Reference_Level_Hopping_NVNT_ANT1_2-DH1_Hopping



2_Band_Edge_(Hopping)_NVNT_ANT1_2-DH1_Hopping




1_Reference_Level_NVNT_ANT1_2-DH1_2480




2_Bandedge_NVNT_ANT1_2-DH1_2480




1_Reference_Level_Hopping_NVNT_ANT1_2-DH1_Hopping




2_Band_Edge_(Hopping)_NVNT_ANT1_2-DH1_Hopping




1_Reference_Level_NVNT_ANT1_3-DH1_2402




2_Bandedge_NVNT_ANT1_3-DH1_2402



1_Reference_Level_Hopping_NVNT_ANT1_3-DH1_Hopping




2_Band_Edge_(Hopping)_NVNT_ANT1_3-DH1_Hopping



1_Reference_Level_NVNT_ANT1_3-DH1_2480




2_Bandedge_NVNT_ANT1_3-DH1_2480



1_Reference_Level_Hopping_NVNT_ANT1_3-DH1_Hopping



2_Band_Edge_(Hopping)_NVNT_ANT1_3-DH1_Hopping




Conducted spurious emission: Pass

1_Reference_Level_NVNT_ANT1_1-DH1_2402




2_Spurious_Emissions_NVNT_ANT1_1-DH1_2402



1_Reference_Level_NVNT_ANT1_1-DH1_2441




2_Spurious_Emissions_NVNT_ANT1_1-DH1_2441



1_Reference_Level_NVNT_ANT1_1-DH1_2480




2_Spurious_Emissions_NVNT_ANT1_1-DH1_2480



1_Reference_Level_NVNT_ANT1_2-DH1_2402




2_Spurious_Emissions_NVNT_ANT1_2-DH1_2402



1_Reference_Level_NVNT_ANT1_2-DH1_2441




2_Spurious_Emissions_NVNT_ANT1_2-DH1_2441




1_Reference_Level_NVNT_ANT1_2-DH1_2480




2_Spurious_Emissions_NVNT_ANT1_2-DH1_2480



1_Reference_Level_NVNT_ANT1_3-DH1_2402




2_Spurious_Emissions_NVNT_ANT1_3-DH1_2402



1_Reference_Level_NVNT_ANT1_3-DH1_2441




2_Spurious_Emissions_NVNT_ANT1_3-DH1_2441



1_Reference_Level_NVNT_ANT1_3-DH1_2480



2_Spurious_Emissions_NVNT_ANT1_3-DH1_2480



9. Radiated Emissions

9.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)


15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	


Note: The peak limit is 20 dB higher than the average limit

9.2. Block Diagram of Test setup


9.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



9.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



9.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

9.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 10 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and simulator
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 :2013on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

9.4. Test Results


We have scanned from 9kHz to the 10th harmonic of the EUT's highest frequency.

Detailed information please see the following page.

From 9KHz to 30MHz:	
Test Date : 2024.05.15	Temperature : 26℃
Test Engineer : Felix Pang	Humidity : 54%
Test Mode : GFSK mode	
Test Results : PASS	
Note:	The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

From 30MHz to 1000MHz:	
Test Date : 2024.05.15	Temperature : 26℃
Test Engineer : Felix Pang	Humidity : 54%
Test Mode : GFSK mode	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. All modes have been tested, and only worst data of GFSK mode, Channel 2402MHz (AC 120V/ 60Hz) was listed in this report.




Polarization: Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	42.9374	19.39	13.51	32.90	40.00	-7.10	QP
2	63.3688	18.96	11.79	30.75	40.00	-9.25	QP
3 *	207.1226	29.34	10.28	39.62	43.50	-3.88	QP
4	345.2924	23.29	14.81	38.10	46.00	-7.90	QP
5	690.7745	17.31	21.85	39.16	46.00	-6.84	QP
6	966.8126	19.40	25.26	44.66	54.00	-9.34	QP

Note: Level = Reading + Factor Margin = Level - Limit

Polarization: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	100.8897	20.06	9.62	29.68	43.50	-13.82	QP
2	138.0844	16.11	12.70	28.81	43.50	-14.69	QP
3 *	207.1245	30.98	10.28	41.26	43.50	-2.24	QP
4	275.8816	18.84	13.14	31.98	46.00	-14.02	QP
5	345.2924	20.98	14.81	35.79	46.00	-10.21	QP
6	966.8126	22.15	25.26	47.41	54.00	-6.59	QP

Note: Level = Reading + Factor Margin = Level - Limit

From 1GHz to 25GHz:	
Test Date : 2024.05.15	Temperature : 26℃
Test Engineer : Felix Pang	Humidity : 54%
Test Mode : GFSK, $\pi/4$ DQPSK, 8DPSK mode	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.


Test Mode : GFSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	86.05	-27.27	58.78	74.00	-15.22	Peak
2	4804	V	63.14	-27.27	35.87	54.00	-18.13	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	79.90	-27.27	52.63	74.00	-21.37	Peak
6	4804	H	73.85	-27.27	46.58	54.00	-7.42	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : GFSK TX Mid								
1	4882	V	85.92	-27.79	58.13	74.00	-15.87	Peak
2	4882	V	64.42	-27.79	36.63	54.00	-17.37	Avg
3	7323	--	--	--	--	--	--	--
4	9764	--	--	--	--	--	--	--
5	4882	H	84.08	-27.79	56.29	74.00	-17.71	Peak
6	4882	H	70.39	-27.79	42.60	54.00	-11.40	Avg
7	7323	--	--	--	--	--	--	--
8	9764	--	--	--	--	--	--	--
Test Mode : GFSK TX High								
1	4960	V	84.27	-28.30	55.97	74.00	-18.03	Peak
2	4960	V	70.65	-28.30	42.35	54.00	-11.65	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	80.31	-28.30	52.01	74.00	-21.99	Peak
6	4960	H	72.47	-28.30	44.17	54.00	-9.83	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

Test Mode : $\pi/4$ DQPSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	82.90	-27.27	55.63	74.00	-18.37	Peak
2	4804	V	64.36	-27.27	37.09	54.00	-16.91	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	81.25	-27.27	53.98	74.00	-20.02	Peak
6	4804	H	71.10	-27.27	43.83	54.00	-10.17	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : $\pi/4$ DQPSK TX Mid								
1	4882	V	85.40	-27.79	57.61	74.00	-16.39	Peak
2	4882	V	64.63	-27.79	36.84	54.00	-17.16	Avg
3	7323	--	--	--	--	--	--	--
4	9764	--	--	--	--	--	--	--
5	4882	H	84.32	-27.79	56.53	74.00	-17.47	Peak
6	4882	H	71.03	-27.79	43.24	54.00	-10.76	Avg
7	7323	--	--	--	--	--	--	--
8	9764	--	--	--	--	--	--	--
Test Mode : $\pi/4$ DQPSK TX High								
1	4960	V	85.88	-28.30	57.58	74.00	-16.42	Peak
2	4960	V	68.46	-28.30	40.16	54.00	-13.84	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	82.32	-28.30	54.02	74.00	-19.98	Peak
6	4960	H	73.48	-28.30	45.18	54.00	-8.82	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

Test Mode : 8DPSK TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4804	V	82.52	-27.27	55.25	74.00	-18.75	Peak
2	4804	V	63.52	-27.27	36.25	54.00	-17.75	Avg
3	7206	--	--	--	--	--	--	--
4	9608	--	--	--	--	--	--	--
5	4804	H	82.33	-27.27	55.06	74.00	-18.94	Peak
6	4804	H	72.18	-27.27	44.91	54.00	-9.09	Avg
7	7206	--	--	--	--	--	--	--
8	9608	--	--	--	--	--	--	--
Test Mode : 8DPSK TX Mid								
1	4882	V	85.53	-27.79	57.74	74.00	-16.26	Peak
2	4882	V	64.90	-27.79	37.11	54.00	-16.89	Avg
3	7323	--	--	--	--	--	--	--
4	9764	--	--	--	--	--	--	--
5	4882	H	84.24	-27.79	56.45	74.00	-17.55	Peak
6	4882	H	73.68	-27.79	45.89	54.00	-8.11	Avg
7	7323	--	--	--	--	--	--	--
8	9764	--	--	--	--	--	--	--
Test Mode : 8DPSK TX High								
1	4960	V	83.39	-28.30	55.09	74.00	-18.91	Peak
2	4960	V	68.53	-28.30	40.23	54.00	-13.77	Avg
3	7440	--	--	--	--	--	--	--
4	9920	--	--	--	--	--	--	--
5	4960	H	81.23	-28.30	52.93	74.00	-21.07	Peak
6	4960	H	71.71	-28.30	43.41	54.00	-10.59	Avg
7	7440	--	--	--	--	--	--	--
8	9920	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

10. Band Edge Test

10.1. Block Diagram of Test Setup



10.2. Test Limit

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

10.3. Test Procedure

Refer to ANSI C 63.10, Clause 6.10.

All restriction band and non- restriction band have been tested, only worse case is reported.

10.4. Test Results

Test Date	: 2024.05.15	Temperature	: 26°C
Test Engineer	: Felix Pang	Humidity	: 54%
Test Results	: PASS		


Frequency Range : 2310MHz~2410MHz								
Test Mode : GFSK TX 2402MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	73.01	-21.62	51.39	74.00	-22.61	Peak
2	2390	H	--	-21.62	--	54.00	--	Avg
3	2400	H	77.13	-26.08	51.05	74.00	-22.95	Peak
4	2400	H	--	-26.08	--	54.00	--	Avg
1	2390	V	67.56	-21.62	45.94	74.00	-28.06	Peak
2	2390	V	--	-21.62	--	54.00	--	Avg
3	2400	V	79.01	-26.08	52.93	74.00	-21.07	Peak
4	2400	V	--	-26.08	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : GFSK TX 2480MHz								
1	2483.5	H	75.24	-25.84	49.40	74.00	-24.60	Peak
2	2483.5	H	--	-25.84	--	54.00	--	Avg
1	2483.5	V	73.20	-25.84	47.36	74.00	-26.64	Peak
2	2483.5	V	--	-25.84	--	54.00	--	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

Frequency Range : 2310MHz~2410MHz								
Test Mode : $\pi/4$ DQPSK TX 2402MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	73.32	-21.62	51.70	74.00	-22.30	Peak
2	2390	H	--	-21.62	--	54.00	--	Avg
3	2400	H	76.41	-26.08	50.33	74.00	-23.67	Peak
4	2400	H	--	-26.08	--	54.00	--	Avg
1	2390	V	70.68	-21.62	49.06	74.00	-24.94	Peak
2	2390	V	--	-21.62	--	54.00	--	Avg
3	2400	V	77.64	-26.08	51.56	74.00	-22.44	Peak
4	2400	V	--	-26.08	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : $\pi/4$ DQPSK TX 2480MHz								
1	2483.5	H	73.59	-25.84	47.75	74.00	-26.25	Peak
2	2483.5	H	--	-25.84	--	54.00	--	Avg
1	2483.5	V	72.82	-25.84	46.98	74.00	-27.02	Peak
2	2483.5	V	--	-25.84	--	54.00	--	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

Frequency Range : 2310MHz~2410MHz								
Test Mode : 8DPSK TX 2402MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	70.87	-21.62	49.25	74.00	-24.75	Peak
2	2390	H	--	-21.62	--	54.00	--	Avg
3	2400	H	76.76	-26.08	50.68	74.00	-23.32	Peak
4	2400	H	--	-26.08	--	54.00	--	Avg
1	2390	V	67.95	-21.62	46.33	74.00	-27.67	Peak
2	2390	V	--	-21.62	--	54.00	--	Avg
3	2400	V	79.48	-26.08	53.40	74.00	-20.60	Peak
4	2400	V	--	-26.08	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : 8DPSK TX 2480MHz								
1	2483.5	H	75.27	-25.84	49.43	74.00	-24.57	Peak
2	2483.5	H	--	-25.84	--	54.00	--	Avg
1	2483.5	V	74.39	-25.84	48.55	74.00	-25.45	Peak
2	2483.5	V	--	-25.84	--	54.00	--	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

11. Power Line Conducted Emissions

11.1. Block Diagram of Test Setup



11.2. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.


11.3. Test Procedure

- (1) The EUT was placed on a non-metallic table, 10cm above the ground plane.
- (2) Setup the EUT and simulator as shown in 11.1
- (3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on conducted Emission test.
- (4) The bandwidth of test receiver is set at 10KHz.
- (5) The frequency range from 150 KHz to 30MHz is checked.

11.4. Test Results

Test Date	: 2024.04.18	Temperature	: 26°C
Test Engineer	: Felix Pang	Humidity	: 54%
Test Mode	: GFSK mode		
Test Results	: PASS		
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out. 4. All modes have been tested, and only worst data of GFSK mode, Channel 2402MHz (AC 120V/ 60Hz) was listed in this report.		


Polarization: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1620	42.49	9.94	52.43	65.36	-12.93	QP	P
2	0.1620	22.20	9.94	32.14	55.36	-23.22	AVG	P
3	0.1900	42.09	9.95	52.04	64.04	-12.00	QP	P
4	0.1900	22.17	9.95	32.12	54.04	-21.92	AVG	P
5	0.2700	39.44	9.98	49.42	61.12	-11.70	QP	P
6	0.2700	35.76	9.98	45.74	51.12	-5.38	AVG	P
7	0.4260	37.41	9.70	47.11	57.33	-10.22	QP	P
8	0.4260	32.48	9.70	42.18	47.33	-5.15	AVG	P
9	0.4620	38.43	9.80	48.23	56.66	-8.43	QP	P
10 *	0.4620	32.46	9.80	42.26	46.66	-4.40	AVG	P
11	0.6300	36.27	9.60	45.87	56.00	-10.13	QP	P
12	0.6300	24.74	9.60	34.34	46.00	-11.66	AVG	P

Note: Level = Reading + Factor Margin = Level - Limit

Polarization: N



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.2779	39.90	9.98	49.88	60.88	-11.00	QP	P
2	0.2779	35.92	9.98	45.90	50.88	-4.98	AVG	P
3	0.4580	38.09	9.79	47.88	56.73	-8.85	QP	P
4 *	0.4580	32.38	9.79	42.17	46.73	-4.56	AVG	P
5	0.6500	35.72	9.55	45.27	56.00	-10.73	QP	P
6	0.6500	28.72	9.55	38.27	46.00	-7.73	AVG	P
7	0.8180	34.47	9.42	43.89	56.00	-12.11	QP	P
8	0.8180	25.51	9.42	34.93	46.00	-11.07	AVG	P
9	0.9980	32.61	9.41	42.02	56.00	-13.98	QP	P
10	0.9980	20.77	9.41	30.18	46.00	-15.82	AVG	P
11	1.1980	32.12	9.41	41.53	56.00	-14.47	QP	P
12	1.1980	21.51	9.41	30.92	46.00	-15.08	AVG	P

Note: Level = Reading + Factor Margin = Level - Limit

12. Antenna Requirements

12.1.Limit

For intentional device, according to FCC 47 CFR Section 15.203 and RSS-GEN, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

12.2.Result

The EUT antenna is internal antenna. It complies with the standard requirement.



13.Photos of test setup

Reference to the **appendix I Test Setup Photo** for details.

14.Photos of EUT

Reference to the **appendix II external photos** and **appendix III internal photos** for details.

----- END OF REPORT-----

