



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V05
Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20220901608E -04
Applicant: DP Audio Video LLC
Address of Applicant: 920 Malcolm Ave Los Angeles 90024 California United States
Equipment Under Test (EUT):
EUT Name: 55"4K SMART LED TV
Model No.: DRPTV550SM
Test Model No.: DRPTV550SM
Brand Name: DuraPro
FCC ID: 2AVRVDRPTV550SM
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
447498 D04 Interim General RF Exposure Guidance v01
Date of Receipt: 2022-09-13
Date of Test: 2022-09-13 to 2022-09-28
Date of Issue: 2022-10-12
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: _____

Lewis Zhou

(Lewis Zhou)

Reviewed By: _____

Timo Lei

(Timo Lei)

Approved By: _____

Jack Ai

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20220901608E -04	Rev.01	Initial report	2022-10-12

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BT CLASSIC	4
3.4 GENERAL DESCRIPTION OF 2.4G WIFI CLASSIC	5
3.5 GENERAL DESCRIPTION OF 5G WIFI CLASSIC	5
4 MPE EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 <i>Limits</i>	6
4.1.2 <i>Test Procedure</i>	6
4.1.3 <i>EUT RF Exposure</i>	7

3 General Information

3.1 Client Information

Applicant:	DP Audio Video LLC
Address of Applicant:	920 Malcolm Ave Los Angeles 90024 California United States
Manufacturer:	DP Audio Video LLC
Address of Manufacturer:	920 Malcolm Ave Los Angeles 90024 California United States
Factory:	Ganzhou City Mosws Electronics Ltd
Address of Factory:	SOUTH OF JINLINGXI ROAD, EAST OF QIFENGSAN ROAD, GANZHOU DEVELOPMENT AREA GANZHOU CITY, JIANGXI PROVINCE, CHINA

3.2 General Description of EUT

Product Name:	55"4K SMART LED TV
Model No.:	DRPTV550SM
Test Model No.:	DRPTV550SM
Trade Mark:	DuraPro
Software Version:	23-03.10.23
Hardware Version:	LT-2874WV6.2
EUT Power Supply:	Power by AC 120V/60Hz

3.3 General Description of BT Classic

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps/3Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Antenna Type:	Metal antenna
Antenna Gain:	2dBi

3.4 General Description of 2.4G WIFI Classic

Operation Frequency:	2412MHz~2462MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps IEEE for 802.11n(HT40) : 13.5Mbps/27Mbps/40.5Mbps/54Mbps/81Mbps/108Mbps/121.5Mbps/135Mbps
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Antenna Type:	Metal antenna
Antenna Gain:	ANT1= 2.58 dBi,ANT2= 2.58 dBi.

3.5 General Description of 5G WIFI Classic

Operation Frequency:	5150MHz ~5250 MHz
Type of Modulation:	OFDM
Number of Channel:	IEEE 802.11a/n/ac(20M): 5150MHz ~5250MHz/ 4 channel IEEE 802.11n/ac(40M): 5150MHz ~5250MHz/ 2 channel IEEE 802.11ac(80M): 5150MHz ~5250MHz/ 1 channel
Channel Separation:	5MHz
Operation Frequency:	IEEE 802.11a/n/ac(20M): 5150MHz ~5250 MHz IEEE802.11n/ac(40M): 5150MHz ~5250 MHz IEEE802.11ac(80M): 5150MHz ~5250 MHz
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Antenna Type:	Metal antenna
Antenna Gain:	ANT1= 0.97 dBi, ANT2= 0.97 dBi.

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator. For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave Dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For BT Classic

Measurement Data

GFSK mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(2402MHz)	1.7	1.5±1	2.5	0.35	1.08
Middle(2441MHz)	2.84	3.0±1	4.0	1.85	1.53
Highest(2480MHz)	2.05	2.0±1	3.0	0.85	1.22
π/4DQPSK mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(2402MHz)	1.2	1.0±1	2.0	-0.15	0.97
Middle(2441MHz)	3.4	3.5±1	4.5	2.35	1.72
Highest(2480MHz)	2.8	3.0±1	4.0	1.85	1.53
8DPSK mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(2402MHz)	1.08	1.0±1	2.0	0.35	1.08
Middle(2441MHz)	3.16	3.0±1	4.0	1.85	1.53
Highest(2480MHz)	1.99	2.0±1	3.0	0.85	1.22

Note: 1) Refer to report No. CQASZ20220901608E -01 for EUT test Max Conducted Peak Output Power value.
2) EUT's Bluetooth module is more than 20cm away from the human body.

2) For 2.4G WIFI Classic

Measurement Data

Ant1:

11B mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(2412MHz)	10.77	10.5±1	11.5	9.35	8.61
Middle(2437MHz)	11.54	11.5±1	12.5	10.35	10.84
Highest(2462MHz)	11.61	11.5±1	12.5	10.35	10.84
11G mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(2412MHz)	10.6	10.5±1	11.5	9.35	8.61
Middle(2437MHz)	11.41	11.5±1	12.5	10.35	10.84
Highest(2462MHz)	11.26	11.5±1	12.5	10.35	10.84
11N20 mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(2412MHz)	10.48	10.5±1	11.5	9.35	8.61
Middle(2437MHz)	11.64	11.5±1	12.5	10.35	10.84
Highest(2462MHz)	11.78	11.5±1	12.5	10.35	10.84
11N40 mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(2422MHz)	11.14	11.0±1	12.0	9.85	9.66
Middle(2437MHz)	11.42	11.5±1	12.5	10.35	10.84
Highest(2452MHz)	11.16	11.0±1	12.0	9.85	9.66

Ant2:

11B mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(2412MHz)	10.46	10.5±1	11.5	9.35	8.61
Middle(2437MHz)	11.37	11.5±1	12.5	10.35	10.84
Highest(2462MHz)	11.44	11.5±1	12.5	10.35	10.84
11G mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(2412MHz)	10.43	10.5±1	11.5	9.35	8.61
Middle(2437MHz)	11.25	11.0±1	12.0	9.85	9.66
Highest(2462MHz)	11.32	11.0±1	12.0	9.85	9.66
11N20 mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(2412MHz)	10.26	10.0±1	11.0	8.85	7.67
Middle(2437MHz)	11.13	11.0±1	12.0	9.85	9.66
Highest(2462MHz)	11.21	11.0±1	12.0	9.85	9.66
11N40 mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(2422MHz)	10.63	10.5±1	11.5	9.35	8.61
Middle(2437MHz)	10.99	11.0±1	12.0	9.85	9.66
Highest(2452MHz)	10.98	11.0±1	12.0	9.85	9.66

Note: 1) Refer to report No. CQASZ20220901608E -02 for EUT test Max Conducted Peak Output Power value.
2) EUT's 2.4G WIFI module is more than 20cm away from the human body.

3) For 5G WIFI Classic

Measurement Data

Ant1:

11A mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(5180MHz)	9.85	10.0±1	11.0	8.85	7.67
Middle(5200MHz)	9.2	9.0±1	10.0	7.85	6.10
Highest(5240MHz)	9.08	9.0±1	10.0	7.85	6.10
11N20 mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(5180MHz)	10.83	10.5±1	11.5	9.35	8.61
Middle(5200MHz)	10.08	10.0±1	11.0	8.85	7.67
Highest(5240MHz)	9.72	9.5±1	10.5	8.35	6.84
11N40 mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(5190MHz)	10.55	10.5±1	11.5	9.35	8.61
Highest(5230MHz)	9.15	9.0±1	10.0	7.85	6.10
11AC20 mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(5180MHz)	10.84	11.0±1	12.0	9.85	9.66
Middle(5200MHz)	9.97	10.0±1	11.0	8.85	7.67
Highest(5240MHz)	9.5	9.5±1	10.5	8.35	6.84

11AC40 mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(5190MHz)	5.62	5.5±1	6.5	4.35	2.72
Highest(5230MHz)	3.75	3.5±1	4.5	2.35	1.72

11AC80 mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Middle(5210MHz)	8.8	8.5±1	9.5	7.35	5.43

Ant2:

11A mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(5180MHz)	6.96	7.0±1	8.0	5.85	3.85
Middle(5200MHz)	5.76	5.5±1	6.5	4.35	2.72
Highest(5240MHz)	2.63	2.5±1	3.5	1.35	1.36
11N20 mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(5180MHz)	6.82	6.5±1	7.5	5.35	3.43
Middle(5200MHz)	5.56	5.5±1	6.5	4.35	2.72
Highest(5240MHz)	2.56	2.5±1	3.5	1.35	1.36
11N40 mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(5190MHz)	1.57	1.5±1	2.5	0.35	1.08
Highest(5230MHz)	-0.57	-0.5±1	0.5	-1.65	0.68
11AC20 mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(5180MHz)	6.8	6.5±1	7.5	5.35	3.43
Middle(5200MHz)	5.63	5.5±1	6.5	4.35	2.72
Highest(5240MHz)	5.19	5.0±1	6.0	3.85	2.43

11AC40 mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Lowest(5190MHz)	2.92	3.0±1	4.0	1.85	1.53
Highest(5230MHz)	0.9	1.0±1	2.0	-0.15	0.97

11AC80 mode					
Test channel	EIRP(dBm)	Tune up tolerance (dBm)	Maximum tune-up Power (dBm)	ERP	
				(dBm)	(mW)
Middle(5210MHz)	0.17	0±1	1.0	-1.15	0.77

Note: 1) Refer to report No. CQASZ20220901608E -03 for EUT test Max Conducted Peak Output Power value.
2) EUT's 5G WIFI module is more than 20cm away from the human body.

Result:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

WIFI Ant1+WIFI Ant2+BT=10.84/3060+10.84/3060+1.72/3060=0.01≤1

*** END OF REPORT ***