



EMI TEST REPORT

Test Report No.: 14541001H-B

Customer	DAIHATSU MOTOR CO., LTD.
Description of EUT	Keyfree system
Model Number of EUT	DH19C-3
FCC ID	2AVSADH19C-3
Test Regulation	FCC Part 15 Subpart B
Test Result	Complied (Refer to SECTION 3)
Issue Date	November 17, 2022
Remarks	-

Representative test engineer

Kiyoshiro Okazaki
Engineer

Approved by

Tsubasa Takayama
Leader



CERTIFICATE 5107.02

- The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.
 There is no testing item of "Non-accreditation".

Report Cover Page - Form-ULID-003532 (DCS:13-EM-F0429) Issue# 21.0

ANNOUNCEMENT

- This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- The results in this report apply only to the sample tested. (Laboratory was not involved in sampling.)
- This sample tested is in compliance with the limits of the above regulation.
- The test results in this test report are traceable to the national or international standards.
- This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
- This test report covers EMC technical requirements. It does not cover administrative issues such as Manual or non-EMC test related Requirements. (if applicable)
- The all test items in this test report are conducted by UL Japan, Inc. Ise EMC Lab.
- The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan, Inc. has been accredited.
- The information provided from the customer for this report is identified in SECTION 1.
- For test report(s) referred in this report, the latest version (including any revisions) is always referred.

REVISION HISTORY

Original Test Report No.: 14541001H-B

Revision	Test Report No.	Date	Page Revised Contents
- (Original)	14541001H-B	November 17, 2022	-

Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	GPS	Global Positioning System
AAN	Asymmetric Artificial Network	Hori.	Horizontal
AC	Alternating Current	ICES	Interference-Causing Equipment Standard
AM	Amplitude Modulation	I/O	Input/Output
AMN	Artificial Mains Network	IEC	International Electrotechnical Commission
Amp, AMP	Amplifier	IEEE	Institute of Electrical and Electronics Engineers
ANSI	American National Standards Institute	IF	Intermediate Frequency
Ant, ANT	Antenna	ILAC	International Laboratory Accreditation Conference
AP	Access Point	ISED	Innovation, Science and Economic Development Canada
ASK	Amplitude Shift Keying	ISN	Impedance Stabilization Network
Atten., ATT	Attenuator	ISO	International Organization for Standardization
AV	Average	JAB	Japan Accreditation Board
BPSK	Binary Phase-Shift Keying	LAN	Local Area Network
BR	Bluetooth Basic Rate	LCL	Longitudinal Conversion Loss
BT	Bluetooth	LIMS	Laboratory Information Management System
BT LE	Bluetooth Low Energy	LISN	Line Impedance Stabilization Network
BW	BandWidth	MRA	Mutual Recognition Arrangement
C.F	Correction Factor	N/A	Not Applicable
Cal Int	Calibration Interval	NIST	National Institute of Standards and Technology
CAV	CISPR AV	NS	No signal detect.
CCK	Complementary Code Keying	NSA	Normalized Site Attenuation
CDN	Coupling Decoupling Network	OBW	Occupied BandWidth
Ch., CH	Channel	OFDM	Orthogonal Frequency Division Multiplexing
CISPR	Comite International Special des Perturbations Radioelectriques	PER	Packet Error Rate
Corr.	Correction	PK	Peak
CPE	Customer premise equipment	PLT	long-term flicker severity
CW	Continuous Wave	POHC(A)	Partial Odd Harmonic Current
DBPSK	Differential BPSK	Pol., Pola.	Polarization
DC	Direct Current	PR-ASK	Phase Reversal ASK
DET	Detector	PST	short-term flicker severity
D-factor	Distance factor	QAM	Quadrature Amplitude Modulation
Dmax	maximum absolute voltage change during an observation period	QP	Quasi-Peak
DQPSK	Differential QPSK	QPSK	Quadrature Phase Shift Keying
DSSS	Direct Sequence Spread Spectrum	r.m.s., RMS	Root Mean Square
DUT	Device Under Test	RBW	Resolution BandWidth
EDR	Enhanced Data Rate	RE	Radio Equipment
e.i.r.p., EIRP	Equivalent Isotropically Radiated Power	REV	Reverse
EM clamp	Electromagnetic clamp	RF	Radio Frequency
EMC	ElectroMagnetic Compatibility	RFID	Radio Frequency Identifier
EMI	ElectroMagnetic Interference	RNSS	Radio Navigation Satellite Service
EMS	ElectroMagnetic Susceptibility	RSS	Radio Standards Specifications
EN	European Norm	Rx	Receiving
e.r.p., ERP	Effective Radiated Power	SINAD	Ratio of (Signal + Noise + Distortion) to (Noise + Distortion)
ETSI	European Telecommunications Standards Institute	S/N	Signal to Noise ratio
EU	European Union	SA, S/A	Spectrum Analyzer
EUT	Equipment Under Test	SG	Signal Generator
Fac.	Factor	SVSWR	Site-Voltage Standing Wave Ratio
FCC	Federal Communications Commission	THC(A)	Total Harmonic Current
FHSS	Frequency Hopping Spread Spectrum	THD(%)	Total Harmonic Distortion
FM	Frequency Modulation	TR, T/R	Test Receiver
Freq.	Frequency	Tx	Transmitting
FSK	Frequency Shift Keying	VBW	Video BandWidth
Fund	Fundamental	Vert.	Vertical
FWD	Forward	WLAN	Wireless LAN
GFSK	Gaussian Frequency-Shift Keying	xDSL	Generic term for all types of DSL technology
GNSS	Global Navigation Satellite System		(DSL: Digital Subscriber Line)

CONTENTS

PAGE

SECTION 1: Customer information	5
SECTION 2: Equipment under test (EUT).....	5
SECTION 3: Test specification, procedures & results	7
SECTION 4: Operation of EUT during testing.....	10
SECTION 5: Radiated Emission.....	13
APPENDIX 1: Test data	15
Radiated Emission	15
APPENDIX 2: Test instruments	19
APPENDIX 3: Photographs of test setup.....	20
Radiated Emission	20
Worst Case Position.....	24

SECTION 1: Customer information

Company Name	DAIHATSU MOTOR CO., LTD.*
Address	1-1, Momozono 2-Chome, Ikeda-shi, Osaka, 563-8651, Japan
Telephone Number	+81-72-754-5619
Contact Person	Kouji Ozawa

***Remarks:**

DAIHATSU MOTOR CO., LTD. designates DENSO CORPORATION and TOKAI RIKA CO., LTD. as manufacturer of the product (Keyfree system).

The information provided from the customer is as follows;

- Customer, Description of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer Information
- SECTION 2: Equipment Under Test (EUT) other than the Receipt Date and Test Date
- SECTION 4: Operation of EUT during testing

* The laboratory is exempted from liability of any test results affected from the above information in SECTION 2 and 4.

SECTION 2: Equipment under test (EUT)

2.1 Identification of EUT

Description	Keyfree system
Model Number	DH19C-3
Serial Number	Refer to SECTION 4.2
Condition	Production prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	No Modification by the test lab
Receipt Date	October 24, 2022
Test Date	November 1, 2022

2.2 Product Description

General Specification

Rating	System: DC 12.0 V Internal: DC 12.0 V (Transmitter) / DC 5.0 V (Receiver)
Clock frequency (ies) in the system	8 MHz (CPU), 33.6 MHz (RF IC)

Radio Specification

[Transmitter part]

Radio Type	LF Transmitter
Frequency of Operation	125 kHz
Modulation	ASK (A1D)
Antenna type	LF Antenna (Outside D) LF Antenna (Outside P) LF Antenna (Outside B) LF Antenna (Inside Fr) LF Antenna (Inside Mi) LF Antenna (Inside Rr) Immobilizer Antenna
Antenna Specification	LF antenna: Ferrite antenna coil Immobilizer antenna: Loop antenna coil

[Receiver part]

Frequency of Operation	433.92 MHz (Keyfree) 433.90 MHz (TPMS)
Intermediate frequency	525 kHz (Keyfree) 1.05 MHz (TPMS)
Modulation	FSK (F1D)
Type of receiving system	Super-heterodyne
Antenna Specification	Internal antenna (Inverted F antenna)

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification	FCC Part 15 Subpart B The latest version on the first day of the testing period
Title	FCC 47CFR Part15 Radio Frequency Device Subpart B Unintentional Radiators

3.2 Procedures and results

Item	Test Procedure	Limits	Deviation	Worst margin	Result	Remarks
Conducted emission	FCC: ANSI C63.4: 2014 7. AC power - line conducted emission measurements	FCC:Part 15 Subpart B 15.107(a)	N/A	-	N/A	*1)
	ISED: RSS-Gen 7.1	ISED: RSS-Gen 7.2				
Radiated emission	FCC: ANSI C63.4: 2014 8. Radiated emission measurements	FCC: Part 15 Subpart B 15.109(a)	N/A	8.57 dB 136.220 MHz, Vertical, QP	Complied a)	-
	ISED: RSS-Gen 7.1	ISED: RSS-Gen 7.3				
Antenna Terminal	FCC: ANSI C63.4: 2014 12. Measurement of unintentional radiators other than ITE	FCC: Part 15 Subpart B 15.111(a)	N/A	-	N/A	*2)
	ISED: - RSS-Gen 7.1	ISED: RSS-Gen 7.4				

* Note: UL Japan, Inc.'s EMI Work Procedure: Work Instructions-ULID-003591.

*1) The test is not applicable since the EUT is not the device that is designed to be connected to the public utility (AC) power line.

*2) The receiving antenna (of this EUT) is installed inside the EUT and cannot be removed (permanently attached). Therefore, Radiated emission test was performed.

a) Refer to APPENDIX 1 (data of Radiated Emission)

3.3 Addition to standard

No addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

Measurement uncertainty is not taken into account when stating conformity with a specified requirement.

Note: When margins obtained from test results are less than the measurement uncertainty, the test results may exceed the limit.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k = 2$.

Radiated emission

Measurement distance	Frequency range		Uncertainty (+/-)
3 m	30 MHz to 200 MHz	Horizontal	4.8 dB
		Vertical	5.0 dB
	200 MHz to 1000 MHz	Horizontal	5.1 dB
		Vertical	6.2 dB
10 m	30 MHz to 200 MHz	Horizontal	4.8 dB
		Vertical	4.8 dB
	200 MHz to 1000 MHz	Horizontal	5.0 dB
		Vertical	5.0 dB
3 m	1 GHz to 6 GHz	Test Receiver	5.0 dB
		Spectrum analyzer	4.9 dB
	6 GHz to 18 GHz	Test Receiver	5.3 dB
		Spectrum analyzer	5.2 dB
1 m	10 GHz to 26.5 GHz	Spectrum analyzer	5.5 dB
	26.5 GHz to 40 GHz	Spectrum analyzer	5.4 dB
0.5 m	26.5 GHz to 40 GHz	Spectrum analyzer	5.4 dB
10 m	1 GHz to 18 GHz	Test Receiver	5.3 dB

3.5 Test Location

UL Japan, Inc. Ise EMC Lab.

*A2LA Certificate Number: 5107.02 / FCC Test Firm Registration Number: 884919

ISED Lab Company Number: 2973C / CAB identifier: JP0002

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 Japan

Telephone: +81-596-24-8999

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room	3 m
No.3 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room	3 m
No.4 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.5 measurement room	6.4 x 6.4 x 3.0	6.4 x 6.4	-	-
No.6 shielded room	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room	3.1 x 5.0 x 2.7	3.1 x 5.0	-	-
No.9 measurement room	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.10 shielded room	3.8 x 2.8 x 2.8	3.8 x 2.8	-	-
No.11 measurement room	4.0 x 3.4 x 2.5	N/A	-	-
No.12 measurement room	2.6 x 3.4 x 2.5	N/A	-	-
Large Chamber	16.9 x 22.1 x 10.17	16.9 x 22.1	-	10 m
Small Chamber	5.3 x 6.69 x 3.59	5.3 x 6.69	-	-

3.6 Test data, Test instruments, and Test set up

Refer to APPENDIX.

SECTION 4: Operation of EUT during testing

4.1 Operating Mode(s)


Mode	Remarks
Mode 1: Keyfree Receiving mode	-
Mode 2: TPMS Receiving mode	
*EUT was set by the software as follows; Software: DN-2390005080-04.S	

*The test signal level was confirmed to be sufficient to stabilize the local oscillator of the EUT.

* It was confirmed by using checker that the EUT receives the signal from the transmitter (pair of EUT).

4.2 Configuration and peripherals

Mode 1



* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.


Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Body ECU	DH19C-3	No.778	DENSO CORPORATION	EUT
B	LF Antenna (Outside D)	DH19C-3	No.778-1	TOKAI RIKA CO., LTD.	-
C	LF Antenna (Outside P)	DH19C-3	No.778-2	TOKAI RIKA CO., LTD.	-
D	LF Antenna (Outside B)	DH19C-3	No.778-3	TOKAI RIKA CO., LTD.	-
E	LF Antenna (Inside Fr)	DH19C-3	No.778-4	TOKAI RIKA CO., LTD.	-
F	LF Antenna (Inside Rr)	DH19C-3	No.778-5	TOKAI RIKA CO., LTD.	-
G	LF Antenna (Inside Mi)	DH19C-3	No.778-6	TOKAI RIKA CO., LTD.	-
H	Evaluation Bench	-	No.20	DENSO CORPORATION	-
I	LED	-	-	-	-
J	LED	-	-	-	-
K	Immobilizer Antenna	DH19C-3	No.778	TOKAI RIKA CO., LTD.	-
L	Smart Key	DH19C-3	No.778	DENSO CORPORATION	-

List of cables used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	DC Cable	3.0	Unshielded	Unshielded	-
2	Antenna Cable (AND)	3.0	Unshielded	Unshielded	-
3	Antenna Cable (ANP)	3.0	Unshielded	Unshielded	-
4	Antenna Cable (ANB)	3.0	Unshielded	Unshielded	-
5	Antenna Cable (ANF)	3.0	Unshielded	Unshielded	-
6	Antenna Cable (ANR)	3.0	Unshielded	Unshielded	-
7	Antenna Cable (ANM)	3.0	Unshielded	Unshielded	-
8	Signal Cable (CN-C)	3.0	Unshielded	Unshielded	-
9	Signal Cable (CN-K)	3.0	Unshielded	Unshielded	-
10	Signal Cable (CN-M)	3.0	Unshielded	Unshielded	-
11	Signal Cable (CN-P)	3.0	Unshielded	Unshielded	-
12	DC Cable	3.0	Unshielded	Unshielded	-
13	Signal Cable	0.5	Unshielded	Unshielded	-
14	Signal Cable	0.5	Unshielded	Unshielded	-
15	Antenna Cable	3.0	Unshielded	Unshielded	-

Mode 2



* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Body ECU	DH19C-3	No.779	DENSO CORPORATION	EUT
B	LF Antenna (Outside D)	DH19C-3	No.778-1	TOKAI RIKA CO., LTD.	-
C	LF Antenna (Outside P)	DH19C-3	No.778-2	TOKAI RIKA CO., LTD.	-
D	LF Antenna (Outside B)	DH19C-3	No.778-3	TOKAI RIKA CO., LTD.	-
E	LF Antenna (Inside Fr)	DH19C-3	No.778-4	TOKAI RIKA CO., LTD.	-
F	LF Antenna (Inside Rr)	DH19C-3	No.778-5	TOKAI RIKA CO., LTD.	-
G	LF Antenna (Inside Mi)	DH19C-3	No.778-6	TOKAI RIKA CO., LTD.	-
H	Immobilizer Antenna	DH19C-3	No.778-1	TOKAI RIKA CO., LTD.	-
I	TPMS bench	DH19T-3	202204110008	DENSO CORPORATION	-
J	TPMS Antenna	-	No.1	-	-
K	Bench	-	-	DENSO CORPORATION	-
L	AC Adapter	ATS065-P240	-	K&C CORPORATION	-

List of cables used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	DC Cable	3.0	Unshielded	Unshielded	-
2	Antenna Cable (AND)	3.0	Unshielded	Unshielded	-
3	Antenna Cable (ANP)	3.0	Unshielded	Unshielded	-
4	Antenna Cable (ANB)	3.0	Unshielded	Unshielded	-
5	Antenna Cable (ANF)	3.0	Unshielded	Unshielded	-
6	Antenna Cable (ANR)	3.0	Unshielded	Unshielded	-
7	Antenna Cable (ANM)	3.0	Unshielded	Unshielded	-
8	Signal cable	1.5	Unshielded	Unshielded	-
9	DC Cable	1.5	Unshielded	Unshielded	-
10	AC Cable	1.8	Unshielded	Unshielded	-
11	DC Cable	0.8	Unshielded	Unshielded	-
12	Signal Cable	1.0	Shielded	Shielded	-
13	DC Cable	1.5	Unshielded	Unshielded	-
14	Antenna Cable	3.0	Unshielded	Unshielded	-

SECTION 5: Radiated Emission

5.1 Operating environment

Date	See data
Test place	See data
Temperature	See data
Humidity	See data
Test engineer	See data

5.2 Test configuration

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane.

The EUT was set on the edge of the tabletop.

Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

Photographs of the set up are shown in APPENDIX 3

5.3 Test conditions

Frequency range	30 MHz to 200 MHz (Biconical antenna) 200 MHz to 1000 MHz (Logperiodic antenna) 1000 MHz to 2000 MHz (Horn antenna)
Test distance	3 m
EUT position	Table top
EUT operation mode	See Clause 4.1

5.4 Test procedure

The height of the measuring antenna varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver.

The radiated emission measurements were made with the following detector function of the Test Receiver.

For above 1 GHz, test antenna was aimed at the EUT for receiving the maximum signal and always kept within the illumination area of the 3 dB beamwidth of the antenna.


Frequency	Below 1GHz	Above 1GHz *1)
Instrument used	Test Receiver	Test Receiver
IF Bandwidth	QP: BW 120 kHz	PK: BW 1 MHz, CAV: BW 1 MHz

*1) The measurement data was adjusted to a 3 m distance using the following Distance Factor.

Distance Factor: See Figure 1.

Figure 1: Test Setup


Below 1 GHz



x : Center of turn table

Test Distance: 3 m

1 GHz to 2 GHz



r : Radius of an outer periphery of EUT

x : Center of turn table

Distance Factor: $20 \times \log(3.30 \text{ m}^*/3.0 \text{ m}) = 0.83 \text{ dB}$
* Test Distance: $(3 + \text{SVSWR Volume} / 2) - r = 3.30 \text{ m}$

SVSWR Volume: 2 m
(SVSWR Volume has been calibrated based on CISPR 16-1-4.)
 $r = 0.7 \text{ m}$

- The noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

5.5 Test result

Summary of the test results: Pass

The limit is rounded down to one decimal place.


The test result is rounded off to one or two decimal places, so some differences might be observed.

APPENDIX 1: Test data

Radiated Emission

Test place Ise EMC Lab.
Semi Anechoic Chamber No.4
Date November 1, 2022
Temperature / Humidity 22 deg. C / 46 % RH
Engineer Kiyoshiro Okazaki
 (Below 1 GHz)
Mode Mode 1

Limit : FCC_Part 15 Subpart B(15.109)_Class B



No.	Freq. [MHz]	Reading	Ant Foc [dB/m]	Loss [dB]	Gain [dB]	Result	Limit	Margin	Pola [H/V]	Height [cm]	Angle [deg]	Ant. Type	Comment
		[dBuV]				[QP]	[QP]						
1	53.545	23.70	9.77	7.34	32.09	8.72	40.00	31.28	Hori.	364	171	BA	
2	65.872	35.10	6.69	7.49	32.09	17.19	40.00	22.81	Hori.	294	196	BA	
3	116.605	40.50	12.42	8.00	32.05	28.87	43.50	14.63	Hori.	298	198	BA	
4	251.729	33.10	11.95	9.07	32.02	22.10	46.00	23.90	Hori.	183	197	LA23	
5	277.997	38.30	13.33	9.26	32.02	28.87	46.00	17.13	Hori.	153	356	LA23	
6	433.395	31.70	16.29	10.28	32.18	26.09	46.00	19.91	Hori.	100	24	LA23	
7	36.541	32.90	16.05	7.11	32.10	23.96	40.00	16.04	Vert.	100	134	BA	
8	52.555	46.00	10.11	7.33	32.09	31.35	40.00	8.65	Vert.	100	295	BA	
9	65.872	45.80	6.69	7.49	32.09	27.89	40.00	12.11	Vert.	100	293	BA	
10	106.585	45.30	11.15	7.91	32.06	32.30	43.50	11.20	Vert.	100	89	BA	
11	210.390	42.20	11.20	8.77	32.00	30.17	43.50	13.33	Vert.	100	73	LA23	
12	277.997	30.90	13.33	9.26	32.02	21.47	46.00	24.53	Vert.	100	1	LA23	
13	433.395	21.10	16.29	10.28	32.18	15.49	46.00	30.51	Vert.	100	0	LA23	

CHART: WITH FACTOR

ANT TYPE: - 30 MHz: LOOP, 30 MHz - 200 MHz: BICONICAL, 200 MHz - 1000 MHz: LOGPERIODIC, 1000 MHz - : HORN


CALCULATION: RESULT = READING + ANT FACTOR + LOSS(CABLE + ATT) - GAIN(AMP)

Except for the above table: adequate margin data below the limits.

Radiated Emission

Test place Ise EMC Lab.
Semi Anechoic Chamber No.4
Date November 1, 2022
Temperature / Humidity 22 deg. C / 46 % RH
Engineer Kiyoshiro Okazaki
 (Above 1 GHz)
Mode Mode 1

Limit : FCC_Part 15 Subpart B(15.109)_Class B



No.	Freq. [MHz]	Reading		Ant.Fac [dB/m]	Loss [dB]	Gain [dB]	Result		Limit		Margin		Pola. [H/V]	Height [cm]	Angle [deg]	Ant. Type	Comment
		(AV) [dBuV]	(PK) [dBuV]				(AV) [dBuV/m]	(PK) [dBuV/m]	(AV) [dBuV/m]	(PK) [dBuV/m]	(AV) [dB]	(PK) [dB]					
1	1560.007	36.60	46.60	24.95	2.91	33.39	31.07	41.07	53.90	73.90	22.83	32.83	Hori.	100	354	H2 1	
2	1560.007	34.90	45.70	24.95	2.91	33.39	29.37	40.17	53.90	73.90	24.53	33.73	Vert.	100	14	H2 1	

CHART: WITH FACTOR

ANT TYPE: - 30 MHz: LOOP, 30 MHz - 200 MHz: BICONICAL, 200 MHz - 1000 MHz: LOGPERIODIC, 1000 MHz -: HORN


CALCULATION: RESULT = READING + ANT FACTOR + LOSS(CABLE + D-factor) - GAIN(AMP)

Except for the above table: adequate margin data below the limits.

Radiated Emission

Test place Ise EMC Lab.
Semi Anechoic Chamber No.4
Date November 1, 2022
Temperature / Humidity 22 deg. C / 46 % RH
Engineer Kiyoshiro Okazaki
 (Below 1 GHz)
Mode Mode 2

Limit : FCC_Part 15 Subpart B(15.109)_Class B



No.	Freq. [MHz]	Reading	Ant.Fac [dB/m]	Loss [dB]	Gain [dB]	Result	Limit	Margin	Pola. [H/V]	Height [cm]	Angle [deg]	Ant. Type	Comment
		[dBuV]				[QP]	[QP]	[QP]					
1	83.638	35.90	7.45	7.69	32.08	18.96	40.00	21.04	Hori.	206	2	BA	
2	136.220	42.90	14.19	8.18	32.04	33.23	43.50	10.27	Hori.	223	29	BA	
3	152.318	35.00	15.07	8.32	32.03	26.36	43.50	17.14	Hori.	230	87	BA	
4	191.262	27.70	16.39	8.62	32.01	20.70	43.50	22.80	Hori.	183	80	BA	
5	432.850	33.60	16.28	10.27	32.18	27.97	46.00	18.03	Hori.	155	213	LA23	
6	650.001	31.20	19.27	11.40	32.45	29.42	46.00	16.58	Hori.	141	3	LA23	
7	83.638	35.20	7.45	7.69	32.08	18.26	40.00	21.74	Vert.	100	279	BA	
8	136.220	44.60	14.19	8.18	32.04	34.93	43.50	8.57	Vert.	100	254	BA	
9	152.318	42.20	15.07	8.32	32.03	33.56	43.50	9.94	Vert.	100	252	BA	
10	191.262	33.10	16.39	8.62	32.01	26.10	43.50	17.40	Vert.	100	257	BA	
11	432.850	35.20	16.28	10.27	32.18	29.57	46.00	16.43	Vert.	100	59	LA23	
12	650.001	28.60	19.27	11.40	32.45	26.82	46.00	19.18	Vert.	100	6	LA23	

CHART: WITH FACTOR

ANT TYPE: - 30 MHz: LOOP, 30 MHz - 200 MHz: BICONICAL, 200 MHz - 1000 MHz: LOGPERIODIC, 1000 MHz :-
HORN


CALCULATION: RESULT = READING + ANT FACTOR + LOSS(CABLE + ATT) - GAIN(AMP)

Except for the above table: adequate margin data below the limits.

Radiated Emission

Test place Ise EMC Lab.
Semi Anechoic Chamber No.4
Date November 1, 2022
Temperature / Humidity 22 deg. C / 46 % RH
Engineer Kiyoshiro Okazaki
 (Above 1 GHz)
Mode Mode 2

Limit : FCC_Part 15 Subpart B(15.109)_Class B



No.	Freq. [MHz]	Reading		Ant.Fac [dB/m]	Loss [dB]	Gain [dB]	Result		Limit		Margin		Pola. [H/V]	Height [cm]	Angle [deg]	Ant. Type	Comment
		(AV) [dBuV]	(PK) [dBuV]				(AV) [dBuV/m]	(PK) [dBuV/m]	(AV) [dBuV/m]	(PK) [dBuV/m]	(AV) [dB]	(PK) [dB]					
1	1439.996	30.40	44.30	25.37	2.61	33.71	24.67	38.77	53.90	73.90	29.03	35.13	Horiz.	100	354	H2 1	
2	1439.996	30.80	44.30	25.37	2.81	33.71	25.27	38.77	53.90	73.90	28.63	35.13	Vert.	100	3	H2 1	

CHART: WITH FACTOR

ANT TYPE: - 30 MHz: LOOP, 30 MHz - 200 MHz: BICONICAL, 200 MHz - 1000 MHz: LOGPERIODIC, 1000 MHz - : HORN

CALCULATION: RESULT = READING + ANT FACTOR + LOSS(CABLE + D-factor) - GAIN(AMP)

Except for the above table: adequate margin data below the limits.

APPENDIX 2: Test instruments

Test equipment

Test Item	Local ID	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
RE	COTS-MEMI-02	178648	EMI measurement program	TSJ (Techno Science Japan)	TEPTO-DV	-	-	-
RE	KBA-05	141198	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	VHA9103+ BBA9106	2513	05/14/2022	12
RE	MAEC-04	142011	AC4_Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	05/22/2022	24
RE	MAEC-04-SVSWR	142017	AC4_Semi Anechoic Chamber(SVSWR)	TDK	Semi Anechoic Chamber 3m	DA-10005	04/12/2021	24
RE	MAT-34	141331	Attenuator(6dB)	TME	UFA-01	-	02/25/2022	12
RE	MCC-217	141393	Microwave Cable	Junkosha	MWX221	1604S254(1 m)/1608S088(5 m)	08/02/2022	12
RE	MCC-50	141397	Coaxial Cable	UL Japan	-	-	11/03/2021	12
RE	MHA-21	141508	Horn Antenna 1-18GHz	Schwarzbeck Mess-Elektronik OHG	BBHA9120D	557	05/20/2022	12
RE	MJM-29	142230	Measure	KOMELON	KMC-36	-	-	-
RE	MLA-23	141267	Logperiodic Antenna (200-1000MHz)	Schwarzbeck Mess-Elektronik OHG	VUSLP9111B	9111B-192	09/21/2022	12
RE	MMM-10	141545	DIGITAL HiTESTER	HIOKI E.E. CORPORATION	3805	51201148	01/16/2022	12
RE	MOS-15	141562	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	0010	01/10/2022	12
RE	MPA-12	141581	MicroWave System Amplifier	Keysight Technologies Inc	83017A	00650	10/05/2022	12
RE	MPA-14	141583	Pre Amplifier	SONOMA INSTRUMENT	310	260833	04/04/2022	12
RE	MTR-10	141951	EMI Test Receiver	Rohde & Schwarz	ESR26	101408	07/25/2022	12

*Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item:

RE: Radiated emission