FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Report No.: RSZ200220001-00A

Limits for General Population/Uncontrolled Exposure							
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)			
0.3-1.34	614	1.63	*(100)	30			
1.34-30	824/f	2.19/f	$*(180/f^2)$	30			
30-300	27.5	0.073	0.2	30			
300-1500	/	/	f/1500	30			
1500-100,000	/	/	1.0	30			

f = frequency in MHz

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \le 1$$

FCC Part 15.247 Page 12 of 37

^{* =} Plane-wave equivalent power density

Wi-Fi Modular 1

Report No.: RSZ200220001-00A

Frequency	Antenna Gain		Tune up conducted power		Evaluation Distance	Power Density	MPE Limit
(MHz)	(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm^2)	(mW/cm ²)
2412-2462	2.05	1.60	21	125.89	20	0.040	1
5150-5250	2.2	1.66	16	39.81	20	0.013	1
5725-5850	2.2	1.66	16	39.81	20	0.013	1

Wi-Fi Modular 2

Frequency	Antenna Gain		Tune up conducted power		Evaluation Distance	Power Density	MPE Limit
(MHz)	(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm^2)	(mW/cm ²)
2412-2462	4.5	2.82	30	1000	20	0.561	1
5150-5250	2.2	1.66	16	39.81	20	0.013	1
5725-5850	2.2	1.66	16	39.81	20	0.013	1

Note: 1. the tune up conducted power was declared by the applicant 2. For the same modular, the 2.4G Wi-Fi can't transmit at the same time with the 5G Wi-Fi. 3. In normal condition, the two modules are working independently.

Simultaneous transmitting consideration:

The ratio=MPE $_{Modular\ 1}$ /limit+MPE $_{Modular\ 2}$ /limit=0.040+0.561=0.601 < 1.0, so simultaneous exposure is not required.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

FCC Part 15.247 Page 13 of 37