



MPE REPORT

FCC ID: 2AVTT-XR50A

Date of issue: June 28, 2020

| | |
|---------------------|---|
| Report number: | MTi19111507-13E2 |
| Sample description: | 2.4G WIFI module |
| Model(s): | XR-50A |
| Applicant: | Shenzhen Jixin intelligence Co., Ltd |
| Address: | A505 Room, Business Building, Suojia Science Park, Xixiang, Baoan District, Shenzhen |
| Date of test: | Jan. 14, 2020 to June 28, 2020 |

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>



| TEST RESULT CERTIFICATION | |
|----------------------------------|--|
| Applicant's name: | Shenzhen Jixin intelligence Co., Ltd |
| Address: | A505 Room, Business Building, Suojia Science Park, Xixiang, Baoan District, Shenzhen |
| Manufacture's name: | Shenzhen Jixin intelligence Co., Ltd |
| Address: | A505 Room, Business Building, Suojia Science Park, Xixiang, Baoan District, Shenzhen |
| Product name: | 2.4G WIFI module |
| Trademark: | N/A |
| Model and/or type reference . : | XR-50A |
| Serial model | N/A |
| RF exposure procedures | KDB 447498 D01 v06 |

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Danny Xu

June 28, 2020

Reviewed by:

Leo Su

June 28, 2020

Approved by:

Tom Xue

June 28, 2020

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposure | | | | |
| 0.3-3.0 | 614 | 1.63 | *100 | 6 |
| 3.0-30 | 1842/f | 4.89/f | *300/f ² | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1,500 | | | f/300 | 6 |
| 1,500-100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *100 | 30 |
| 1.34-30 | 824/f | 2.19/f | *180/f ² | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1,500 | | | f/1500 | 30 |
| 1,500-100,000 | | | 1.0 | 30 |

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm(20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

WIFI:

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

Power density limited: 1mW/ cm²

Antenna Type: PCB Antenna;

Antenna gain: 2dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(2/10)}=1.58$

| Channel Freq. (MHz) | modulation | conducted power (dBm) | Tune-up power (dBm) | Max | | Antenna Gain Numeric | Evaluation result at 20cm Power density(mW/cm ²) | Power density Limits (mW/cm ²) |
|---------------------|-------------|-----------------------|---------------------|---------------|---------|----------------------|--|--|
| | | | | tune-up power | | | | |
| | | | | (dBm) | (mW) | | | |
| 2412 | 802.11b | 16.93 | 16±1 | 17 | 50.1187 | 1.58 | 0.01575 | 1 |
| 2437 | | 16.60 | 16±1 | 17 | 50.1187 | 1.58 | 0.01575 | 1 |
| 2462 | | 16.16 | 16±1 | 17 | 50.1187 | 1.58 | 0.01575 | 1 |
| 2412 | 802.11g | 14.89 | 15±1 | 16 | 39.8107 | 1.58 | 0.01251 | 1 |
| 2437 | | 14.84 | 15±1 | 16 | 39.8107 | 1.58 | 0.01251 | 1 |
| 2462 | | 14.57 | 15±1 | 16 | 39.8107 | 1.58 | 0.01251 | 1 |
| 2412 | 802.11n H20 | 15.08 | 15±1 | 16 | 39.8107 | 1.58 | 0.01251 | 1 |
| 2437 | | 14.97 | 15±1 | 16 | 39.8107 | 1.58 | 0.01251 | 1 |
| 2462 | | 14.54 | 15±1 | 16 | 39.8107 | 1.58 | 0.01251 | 1 |

Conclusion:

For the max result: $0.01575 \leq 1.0$ for 1g SAR, No SAR is required.

----END OF REPORT----