



FCC TEST REPORT

Test report
On Behalf of

Enping City Yongyue Electroacoustic Equipment factory

For
Wireless microphone

Model No.: KX620, KX621, KX622, KX6512C, KX6515C, KX6515D,
KX623, KX801

FCC ID: 2AVUT-KX620

Prepared for : Enping City Yongyue Electroacoustic Equipment factory
The 2nd Foor workshop of workshop No. C5-1, Zone 2, Industrial park, enping
City, Guangdong Province, China

Prepared By : Shenzhen HUAK Testing Technology Co., Ltd.
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,
Bao'an District, Shenzhen City, China

Date of Test: Feb. 27, 2020 ~ Mar. 05, 2020

Date of Report: Mar. 05, 2020

Report Number: HK2003050245-E



TEST RESULT CERTIFICATION

Applicant's name : Enping City Yongyue Electroacoustic Equipment factory
Address : The 2nd Foor workshop of workshop No. C5-1, Zone 2, Industrial park, enping City, Guangdong Province, China
Manufacture's Name : Enping City Yongyue Electroacoustic Equipment factory
Address : The 2nd Foor workshop of workshop No. C5-1, Zone 2, Industrial park, enping City, Guangdong Province, China

Product description

Trade Mark : superadd
Product name : Wireless microphone
Model and/or type reference : KX620, KX621, KX622, KX6512C, KX6515C, KX6515D, KX623, KX801
Standards : FCC Rules and Regulations Part 15 Subpart C Section 15.236
ANSI C63.4: 2014

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test :

Date (s) of performance of tests : Feb. 27, 2020 ~ Mar. 05, 2020

Date of Issue : Mar. 05, 2020

Test Result : **Pass**


Testing Engineer : 

(Gary Qian)

Technical Manager : 

(Eden Hu)

Authorized Signatory :



(Jason Zhou)



TABLE OF CONTENTS

1	TEST SUMMARY.....	4
1.1	<i>TEST PROCEDURES AND RESULTS</i>	4
1.2	<i>TEST FACILITY</i>	4
1.3	<i>Measurement Uncertainty.....</i>	4
2	GENERAL INFORMATION.....	5
2.1	<i>GENERAL DESCRIPTION OF EUT</i>	5
2.2	<i>Carrier Frequency of Channels</i>	6
2.3	<i>Operation of EUT during testing</i>	6
2.4	<i>DESCRIPTION OF TEST SETUP.....</i>	7
2.5	<i>Description of Support Units</i>	7
3	TEST RESULTS AND MEASUREMENT DATA	9
3.1	<i>CONDUCTED EMISSIONS TEST</i>	9
3.2	<i>RADIATED EMISSION TEST</i>	12
3.4	<i>Conducted Output Power.....</i>	17
3.5	<i>OCCUPIED BANDWIDTH MEASUREMENT.....</i>	18
3.5	<i>Necessary bandwidth.....</i>	20
3.6	<i>FREQUENCY STABILITY.....</i>	23
4	PHOTOGRAPH OF TEST	25
5	PHOTOGRAPH OF EUT.....	27



1 TEST SUMMARY

1.1 TEST PROCEDURES AND RESULTS

Requirement	CFR 47 Section	Result
Conducted Emission	15.207	PASS
Conducted Peak Output Power	15.236(d)(1)	PASS
Occupied Bandwidth Emission	15.236(f)(2)	PASS
Radiated Spurious Emission	15.236(g)	PASS
Frequency Stability	15.236(f)(3)	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

1.2 TEST FACILITY

Test Firm : Shenzhen HUAK Testing Technology Co., Ltd.

Address 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China

1.3 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 2.56\text{dB}$
2	RF power, conducted	$\pm 0.12\text{dB}$
3	Spurious emissions, conducted	$\pm 0.11\text{dB}$
4	All emissions, radiated(<1G)	$\pm 3.92\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.28\text{dB}$
6	Temperature	$\pm 0.1^\circ\text{C}$
7	Humidity	$\pm 1.0\%$



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Wireless microphone
Model Name	KX620
Serial No.	KX621, KX622, KX6512C, KX6515C, KX6515D, KX623, KX801
Model Difference	All model's the function, software and electric circuit are the same, only with a product color and model named different. Test sample model: KX620
Trade Mark	superadd
FCC ID	2AVUT-KX620
Hardware Version:	ZR-PD206-V01
Software Version:	ZH8605-V05_R3
Operation frequency	561.6MHz –578.6MHz
Number of Channels	35
Antenna Type	Internal antenna
Antenna Gain	-3dBi
Modulation Type	FM
Power Source	DC 5V from USB or DC 3.7V from Battery



2.2 Carrier Frequency of Channels

Channel	Frequency	Channel	Frequency
0	561.6	18	570.6
1	562.1	19	571.1
2	562.6	20	571.6
3	563.1	21	572.1
4	563.6	22	572.6
5	564.1	23	573.1
6	564.6	24	573.6
7	565.1	25	574.1
8	565.6	26	574.6
9	566.1	27	575.1
10	566.6	28	575.6
11	567.1	29	576.1
12	567.6	30	576.6
13	568.1	31	577.1
14	568.6	32	577.6
15	569.1	33	578.1
16	569.6	34	578.6
17	570.1		

2.3 Operation of EUT during testing

Operating Mode

The mode is used: **Transmitting mode**

Low Channel: CH00: 561.6MHz


Middle Channel: CH15:570.1MHz

High Channel: CH31:578.6MHz



2.4 DESCRIPTION OF TEST SETUP

Operation of EUT during conducted testing and Radiationtesting:



Operation of EUT Above 1GHz Radiationtesting:



Adapter information

Model: HW-059200CHQ

Input: 100~240V, 50/60Hz, 0.5A

Output: 5VDC, 2A

2.5 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Description	Model No.	Manufacturer	Remark	Certificate
/	/	/	/	/
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.



2.6 MEASUREMENT INSTRUMENTS LIST

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	R&S	ENV216	HKE-002	Dec. 26, 2019	1 Year
2.	Receiver	R&S	ESCI 7	HKE-010	Dec. 26, 2019	1 Year
3.	RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 26, 2019	1 Year
4.	Spectrum analyzer	R&S	FSP40	HKE-025	Dec. 26, 2019	1 Year
5.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 26, 2019	1 Year
6.	Preamplifier	Schwarzbeck	BBV 9743	HKE-006	Dec. 26, 2019	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESCI 7	HKE-010	Dec. 26, 2019	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	HKE-012	Dec. 26, 2019	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB 1519B	HKE-014	Dec. 26, 2019	1 Year
10.	Horn Antenna	Schwarzbeck	9120D	HKE-013	Dec. 26, 2019	1 Year
11.	Pre-amplifier	EMCI	EMC051845SE	HKE-015	Dec. 26, 2019	1 Year
12.	Pre-amplifier	Agilent	83051A	HKE-016	Dec. 26, 2019	1 Year
13.	EMI Test Software EZ-EMC	Tonscend	JS1120-B Version	HKE-083	Dec. 26, 2019	N/A
14.	Power Sensor	Agilent	E9300A	HKE-086	Dec. 26, 2019	1 Year
15.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 26, 2019	1 Year
16.	Signal generator	Agilent	N5182A	HKE-029	Dec. 26, 2019	1 Year
17.	Signal Generator	Agilent	83630A	HKE-028	Dec. 26, 2019	1 Year
18.	Shielded room	Shiel Hong	4*3*3	HKE-039	Dec. 26, 2019	1 Year
19.	Power Meter	R&S	NRVD	SEL0069	Dec. 26, 2019	1 Year
20	High Gain Antenna	Schwarzbeck	LB-180400KF	HKE-054	Dec. 26, 2019	1 Year

3 TEST RESULTS AND MEASUREMENT DATA

3.1 CONDUCTED EMISSIONS TEST


LIMIT

According to FCC CFR Title 47 Part 15 Subpart C Section 15.207 and RSS Gen 8.8, AC Power Line Conducted Emissions Limits for Licence-Exempt Radio Apparatus as below:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION




TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.

7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Test Specification: Line




Suspected List									
NO.	Freq. [MHz]	Level [dB μ V]	Factor [dB]	Limit [dB μ V]	Margin [dB]	Reading [dB μ V]	Detector	Type	
1	0.1815	44.66	10.06	64.42	19.76	34.60	PK	L	
2	0.6900	45.93	10.05	56.00	10.07	35.88	PK	L	
3	1.1130	43.84	10.08	56.00	12.16	33.76	PK	L	
4	1.4640	42.78	10.10	56.00	13.22	32.68	PK	L	
5	8.2770	38.09	10.13	60.00	21.91	27.96	PK	L	
6	14.5680	36.77	9.95	60.00	23.23	26.82	PK	L	

Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor

Test Specification: Neutral



Suspected List

NO.	Freq. [MHz]	Level [dB μ V]	Factor [dB]	Limit [dB μ V]	Margin [dB]	Reading [dB μ V]	Detector	Type
1	0.1770	44.34	10.05	64.63	20.29	34.29	PK	N
2	0.6945	44.89	10.05	56.00	11.11	34.84	PK	N
3	1.1130	42.99	10.08	56.00	13.01	32.91	PK	N
4	1.4190	42.29	10.11	56.00	13.71	32.18	PK	N
5	6.8865	35.81	10.20	60.00	24.19	25.61	PK	N
6	12.3450	37.28	9.98	60.00	22.72	27.30	PK	N

Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor

3.2 RADIATED EMISSION TEST


Limit

Emissions within the band from one megahertz below to one megahertz above the carrier frequency shall comply with the emission mask in §8.3 of ETSI EN 300 422-1 V1.4.2 (2011-08).


Emissions outside of this band shall comply with the limits specified in section 8.4 of ETSI EN 300 422-1 V1.4.2 (2011-08).

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10KHz	RBW=120KHz	RBW=1MHz
VBW =30KHz	VBW=300KHz	VBW=3MHz
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold
Detector function = QP	Detector function = QP	Detector function = RMS


Test Procedure

1. The setup of EUT is according with per TIA/EIA Standard 603 and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable.

TEST RESULTS

Below 1GHz Test Results:(Show only the worst test results)

Antenna polarity: H




Suspected List

NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Polarity
1	75.3475	-59.40	-56.11	-36.00	20.11	3.29	Horizontal
2	99.1125	-61.16	-60.36	-54.00	6.36	0.80	Horizontal
3	148.340	-64.25	-61.90	-36.00	25.90	2.35	Horizontal
4	188.110	-58.12	-59.85	-36.00	23.85	-1.73	Horizontal
5	292.142	-62.22	-59.24	-54.00	5.24	2.98	Horizontal
6	563.115	1.38	6.72	-36.00	-42.72	5.34	Horizontal

Factor=Antenna Factor+ Cable loss, Margin=Limit- Result.

Antenna polarity: V



Suspected List

NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Polarity
1	32.9100	-68.53	-66.61	-36.00	30.61	1.92	Vertical
2	75.5900	-58.35	-62.08	-36.00	26.08	-3.73	Vertical
3	107.1115	-68.49	-57.49	-54.00	3.49	11.00	Vertical
4	180.835	-64.84	-68.23	-36.00	32.23	-3.39	Vertical
5	364.650	-63.88	-62.16	-54.00	8.16	1.72	Vertical
6	563.1115	1.11	5.51	-36.00	-41.51	4.40	Vertical

Factor=Antenna Factor+ Cable loss, Margin=Limit- Result.

Remark:

- (1) Measuring frequencies from 9 KHz to the 1 GHz, Radiated emission test from 9KHz to 30MHz was verified, and no any emission was found except system noise floor.
- (2) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.

Harmonics and Spurious Emissions

Frequency Range (9 kHz-30MHz)

Frequency (MHz)	Level@3m (dB μ V/m)	Limit@3m (dB μ V/m)
--	--	--
--	--	--
--	--	--
--	--	--

Note: 1. Emission Level=Reading+ Cable loss+ Antenna factor-Amp factor

2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement



ABOVE 1GHz Test Results:
Transmitting at 561.6MHz

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1123.20	-35.34	-5.81	-41.15	-30	-11.15	Horizontal
1123.20	-36.01	-5.81	-41.82	-30	-11.82	Vertical
1684.80	-33.67	-6.06	-39.73	-30	-9.73	peak
1684.80	-34.14	-5.81	-39.95	-30	-9.95	Horizontal

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Transmitting at 570.1MHz

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1140.20	-38.52	-5.81	-44.33	-30	-14.33	Horizontal
1140.20	-37.93	-5.81	-43.74	-30	-13.74	Vertical
1710.30	-36.33	-6.06	-42.39	-30	-12.39	peak
1710.30	-34.34	-5.81	-40.15	-30	-10.15	Horizontal

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Transmitting at 578.6MHz

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	
1157.20	-38.35	-5.81	-44.16	-30	-14.16	Horizontal
1157.20	-37.86	-5.81	-43.67	-30	-13.67	Vertical
1735.80	-34.36	-6.06	-40.42	-30	-10.42	peak
1735.80	-35.11	-5.81	-40.92	-30	-10.92	Horizontal

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.




3.4 Conducted Output Power

Limit

According to FCC 15.236(d)(1), for low power auxiliary station operating in the 470-608, and 614-698 MHz bands, In the bands allocated and assigned for broadcast television and in the 600 MHz service band: 50 mW EIRP

TEST CONFIGURATION



Test Procedure:

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Test Results:

Test Channel	frequency (MHz)	Conducted Output Power (dBm)	ANT Gain (dBi)	EIRP (dBm)	Limit (dBm)	Result
CH00	561.6	-7.36	-3	-10.36	17	PASS
CH15	570.1	-6.36	-3	-9.36		PASS
CH31	578.6	-6.32	-3	-9.32		PASS



3.5 OCCUPIED BANDWIDTH MEASUREMENT

Limit


According to FCC 15.236(f)(2), The operating frequency within a permissible band of operation as defined in paragraph (c) must comply with the following requirements.

- (1) The frequency selection shall be offset from the upper or lower band limits by 25 kHz or an integral multiple thereof.
- (2) One or more adjacent 25 kHz segments within the assignable frequencies may be combined to form a channel whose maximum bandwidth shall not exceed 200 kHz. The operating bandwidth shall not exceed 200 kHz.

Emissions within the band from one megahertz below to one megahertz above the carrier frequency shall comply with the emission mask in Section 8.3 of ETSI EN 300 422-1 V1.4.2 (2011-08) (incorporated by reference, see §15.38). Emissions outside this band shall comply with the limit specified at the edges of the

ETSI mask

TEST CONFIGURATION




Test Procedure:

According to TIA-603 for additional Test Set-Up procedures, the occupied bandwidth of emission was measured with a Spectrum Analyzer connected to the antenna terminal while EUT was operating in 2.5 kHz tone at an input level 16 dB greater than that necessary to produce 50 percent modulation. Then mark the -26 dB Bandwidth and record it.


Test Results:

Test Channel	frequency (MHz)	-20 Bandwidth (kHz)	99% Bandwidth (kHz)	Limit (kHz)	Result
CH00	561.6	130.9	114.97	200	PASS
CH15	570.1	124.6	110.80		PASS
CH31	578.6	126.8	108.92		PASS



3.5 Necessary bandwidth

Limit




Standard Applicable

According to §15.236 (g) Emissions within the band from one megahertz below to one megahertz above the carrier frequency shall comply with the emission mask in §8.3 of ETSI EN 300 422-1 V1.4.2 (2011-08), Electromagnetic compatibility and Radio spectrum Matters (ERM); Wireless microphones in the 25 MHz to 3GHz frequency range; Part 1: Technical characteristics and methods of measurement. Emissions outside of this band shall comply with the limits specified in section 8.4 of ETSI EN 300 422-1 V1.4.2 (2011-08).

According to ETSI EN 300 422-2 V2.1.1 section 8.3, the transmitter output spectrum shall be within the mask defined in the following figure.

TEST CONFIGURATION



Test Procedure:

The arrangement of test equipment as shown in figure B.1 shall be used. Note that the noise meter conforms to (quasi peak) without weighting filter (flat).

With the Low Frequency (LF) audio signal generator set to 500 Hz, the audio input level to the DUT shall be adjusted to 8 dB below the limiting threshold (-8 dB (lim)) as declared by the manufacturer.

The corresponding audio output level from the demodulator shall be measured and recorded.

The input impedance of the noise meter shall be sufficiently high to avoid more than 0,1 dB change in input level when the meter is switched between input and output.

The audio input level shall be increased by 20 dB, i.e. to +12 dB (lim), and the corresponding change in output level shall be measured.

It shall be checked that the audio output level has increased by ≤ 10 dB.

If this condition is not met, the initial audio input level shall be increased from -8 dB (lim) in 1 dB steps until the above condition is fulfilled, and the input level recorded in the test report. This level replaces the value derived from the manufacturer's declaration and is defined as -8 dB (lim).

Measure the input level at the transmitter required to give +12 dB (lim).

The LF generator shall be replaced with the weighted noise source to Recommendation ITU-R BS.559-2 [i.3], band-limited to 15 kHz as described in IEC 60244-13 [2], and the level shall be adjusted such that the measured input to the transmitter corresponds to +12 dB (lim).

If the transmitter incorporates any ancillary coding or signalling channels (e.g. pilot-tones), these shall be enabled prior to any spectral measurements.

If the transmitter incorporates more than one audio input, e.g. stereo systems, the second and subsequent channels shall be simultaneously driven from the same noise source, attenuated to a level of -6 dB (lim).

- centre frequency: fc: Transmitter (Tx) nominal frequency;
- dispersion (Span): fc - 1 MHz to fc + 1 MHz;
- Resolution BandWidth (RBW): 1 kHz;
- Video BandWidth (VBW): 1 kHz;
- detector: Peak hold.

Test Result






570.1MHz



578.6MHz



3.6 FREQUENCY STABILITY


Limit

±50ppm

Standard Applicable

According to FCC 15.236(f)(3), The frequency tolerance of the carrier signal shall be maintained within ±0.005% of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. Battery operated equipment shall be tested using a new battery.

TEST CONFIGURATION



Test Procedure:

1. Setup the configuration of the ambient temperature from -20°C to 50°C with sufficient time. And measure the different power of the EUT with an artificial power from highest to end point voltage.
2. Set frequency counter center frequency to the right frequency needs to be measured band.

Test Result

Test frequency (MHz)	Test Conditions		Measure Frequency (MHz)	Frequency Error		Limit ppm	Result
	Voltage (V)	Temperatur e (°C)		(MHz)	ppm		
561.6MHz	N	N	561.6036	0.0036	6.41	±50ppm	PASS
		L	561.5793	-0.0207	-36.86		
		H	561.6050	0.005	8.90		
	L	N	561.5850	-0.015	-26.71		
		L	561.5977	-0.0023	-4.10		
		H	561.6027	0.0027	4.81		
	H	N	561.5871	-0.0129	-22.97		
		L	561.5843	-0.0157	-27.96		
		H	561.5832	-0.0168	-29.91		




Test frequency	Test Conditions		Measure Frequency	Frequency Error		Limit	Result
	(MHz)	Voltage (V)		(MHz)	ppm		
570.1MHz	N	N	570.0966	-0.0034	-5.96	±50ppm	PASS
		L	570.0876	-0.0124	-21.75		
		H	570.0957	-0.0043	-7.54		
	L	N	570.1110	0.011	19.29		
		L	570.1113	0.0113	19.82		
		H	570.0949	-0.0051	-8.95		
	H	N	570.0972	-0.0028	-4.91		
		L	570.0867	-0.0133	-23.33		
		H	570.0861	-0.0139	-24.38		

Test frequency	Test Conditions		Measure Frequency	Frequency Error		Limit	Result
	(MHz)	Voltage (V)		(MHz)	ppm		
578.6MHz	N	N	578.6087	0.0087	15.04	±50ppm	PASS
		L	578.5986	-0.0014	-2.42		
		H	578.5801	-0.0199	-34.39		
	L	N	578.5863	-0.0137	-23.68		
		L	578.6086	0.0086	14.86		
		H	578.6172	0.0172	29.73		
	H	N	578.5790	-0.021	-36.29		
		L	578.6180	0.018	31.11		
		H	578.6169	0.0169	29.21		

4 PHOTOGRAPH OF TEST

Radiated Emission



Conducted Emission





5 PHOTOGRAPH OF EUT

Reference to the reporter : ANNEX A of external photos and ANNEX B of internal photos

-----End of test report-----