

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Wireless microphone
Model Name	KX620
FCC ID	2AVUT-KX620

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR.}$

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

According to the follow transmitter output power (P_t) formula :

$$P_t = -6.32 \text{ dBm} = 0.23 \text{ mW}$$

The result for RF exposure evaluation

$$\text{SAR} = (0.23 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{0.5786(\text{GHz})}] = 0.034 < 3.0 \text{ for 1-g SAR}$$

4. CONCLUSION

The SAR evaluation is not required.