



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V04
Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No. : CQASZ20210300010EX-02

Applicant: Han Promotion Limited

Address of Applicant: Rm.18 & 20, Blk 1, 12/F, Golden Ind. Bldg., 16-26 Kwai Tak Street, Kwai Chung, N.T. Hong Kong

Manufacturer: Han Promotion Limited

Address of Manufacturer: Rm.18 & 20, Blk 1, 12/F, Golden Ind. Bldg., 16-26 Kwai Tak Street, Kwai Chung, N.T. Hong Kong

Equipment Under Test (EUT):

Product: Light Up Wireless Power Bank

All Model No.: PB004

Test Model No.: PB004

Brand Name: N/A

FCC ID: 2AVVH-PB004

Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB 680106 D01 RF Exposure wireless charging base App V03

Date of Test: Mar. 05, 2021 to Mar. 11, 2020

Date of Issue: Mar. 11, 2020

Test Result : **PASS**

Tested By:

Jun Li

(Jun Li)

Reviewed By:

Ares Liu

(Ares Liu)

Approved By:

Sheek Luo

(Sheek luo)



1 Version

Revision History Of Report

| Report No. | Version | Description | Issue Date |
|-----------------------|---------|----------------|---------------|
| CQASZ20210300010EX-02 | Rev.01 | Initial report | Mar. 11, 2020 |

2 Contents

| | |
|----------------------------------------------------|----------|
| 1 VERSION | 2 |
| 2 CONTENTS | 3 |
| 3 GENERAL INFORMATION | 4 |
| 3.1 CLIENT INFORMATION..... | 4 |
| 3.2 GENERAL DESCRIPTION OF EUT..... | 4 |
| 3.3 TEST ENVIRONMENT..... | 4 |
| 3.4 DESCRIPTION OF SUPPORT UNITS..... | 5 |
| 3.5 TEST LOCATION..... | 5 |
| 3.6 TEST FACILITY..... | 5 |
| 3.7 EQUIPMENT LIST..... | 5 |
| 4 RF EXPOSURE EVALUATION | 6 |
| 4.1 RF EXPOSURE COMPLIANCE REQUIREMENT..... | 6 |
| 4.1.1 <i>Limits</i> | 6 |
| 4.1.2 <i>Test Procedure</i> | 6 |
| 4.1.3 <i>Test Setup</i> | 7 |
| 4.1.4 <i>Test Results</i> | 7 |
| APPENDIX A: PHOTOGRAPHS OF TEST SETUP | 9 |

3 General Information

3.1 Client Information

| | |
|--------------------------|-----------------------------------------------------------------------------------------------|
| Applicant: | Han Promotion Limited |
| Address of Applicant: | Rm.18 & 20, Blk 1, 12/F, Golden Ind. Bldg., 16-26 Kwai Tak Street, Kwai Chung, N.T. Hong Kong |
| Manufacturer: | Han Promotion Limited |
| Address of Manufacturer: | Rm.18 & 20, Blk 1, 12/F, Golden Ind. Bldg., 16-26 Kwai Tak Street, Kwai Chung, N.T. Hong Kong |

3.2 General Description of EUT

| | |
|-------------------------------|--------------------------------------------------------------------------------------------------------------|
| Product Name: | Light Up Wireless Power Bank |
| Test Model No.: | PB004 |
| Trade Mark: | N/A |
| Hardware Version: | V1.0 |
| Software Version: | / |
| Operation Frequency: | 129.5kHz |
| Modulation Type: | MSK |
| Antenna Type: | Loop coil antenna |
| Antenna Gain: | 0 dBi |
| Wireless charger Information: | Capacity:3500mAh Input: 5V $\overline{=}$ 2.1A(Max) Output: 5W(Wireless) 5V $\overline{=}$ 2.0A(Wired) |

Note:

For more details features description, please refer to the manufacture's specifications or the usermanual.

3.3 Test environment

| | |
|--------------------------------------------------------------------------------------------------|---------------------------------------------|
| Operating Environment: | |
| Temperature: | 25.0 °C |
| Humidity: | 53 % RH |
| Atmospheric Pressure: | 1010mbar |
| Test Mode: | |
| Mode b | Wireless charging Mode at 5V(Full load) |
| Mode c | Wireless charging Mode at 5V(Half load) |
| Mode d | Wireless charging Mode at 5V(Null load) |
| Mode e | Wireless charging mode -5W |
| Mode f | Output: 5V $\overline{=}$ 2.0A(5W-wireless) |
| Note: The mode f was the worst case and only the data of the worst case record in this report | |

3.4 Description of Support Units

The EUT has been tested with associated equipment below.

| Description | Manufacturer | Model No. | emark | FCC certification |
|-----------------------------|-------------------------------------|-------------------|--------------------------|-------------------|
| Adapter | SHENZHEN FUJIA APPLIANCE CO.,LTD | FJ-SW1260502500UN | Provide by laboratory | sdoc |
| Wireless electronic Load | - | - | Provide by laboratory | - |
| | | | | |

3.5 Test location

Shenzhen Huaxia Testing Technology Co., Ltd,

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

3.6 Test Facility

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

3.7 Equipment list

| Test Equipment | Manufacturer | Model No. | Instrument No. | Calibration Date | Calibration Due Date |
|-----------------------------|-------------------------------------------|-----------|----------------|------------------|----------------------|
| Broadband Field Meter | Narda Safety Test Solutions GmbH | NBM-520 | SB9873 | 2020/10/18 | 2021/10/17 |
| Magnetic field probe | HIOKI | 3470 | SB9058/04 | 2020/12/14 | 2021/12/13 |

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the nvironment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|----------------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures | | | | |
| 0.3–3.0 | 614 | 1.63 | *(100) | 6 |
| 3.0–30 | 1842/f | 4.89/f | *(900/f ²) | 6 |
| 30–300 | 61.4 | 0.163 | 1.0 | 6 |
| 300–1500 | | | f/300 | 6 |
| 1500–100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1500 | | | f/1500 | 30 |
| 1500–100,000 | | | 1.0 | 30 |

Note 1: f = frequency in MHz ; *Plane-wave equivalent power density


Note 2: For the applicable limit, see FCC 1.1310, 680106 D01 RF Exposure Wireless Charging Apps v03 Note 3: Emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m. A KDB inquiry is required to determine the applicable exposure limits below 100 kHz.

Note 4: The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit .

4.1.2 Test Procedure

For devices designed for typical desktop applications, such a wireless charging pads, RF exposure evaluation should be conducted assuming a user separation distance of 20 cm(Top) and 15cm(Edge). E and H field strength measurements or numerical modeling may be used to demonstrate compliance. Measurements should be made from all sides and the top of the primary/client pair, with the 20 cm(Top) and 15cm(Edge) measured from the center of the probe(s) to the edge of the device.

4.1.3 Test Setup



Note: Position A: Front of EUT; Position B: Left of EUT; Position C: back of EUT; Position D: Right of EUT; Position E: Top of EUT(20 cm measure distance);

4.1.4 Test Results

The EUT does comply with item 5 KDB680106 D01 v03.

(1) Power transfer frequency is less than 1 MHz.

(Conform)

(2) Output power from each primary coil is less than or equal to 15 watts.

(Conform)

(3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.

(Conform)

(4) Client device is placed directly in contact with the transmitter.

(Conform)

(5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).

(Conform)

(6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

(Conform)

Test condition: Mode f

E-field strength test result:


| Frequency Range | Probe Position A (V/m) | Probe Position B (V/m) | Probe Position C (V/m) | Probe Position D (V/m) | Probe Position E (V/m) | Limit (V/m) |
|-----------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------|
| 129.5kHz | 1.62 | 0.58 | 1.03 | 0.87 | 1.68 | 614 |

H-field strength test result:

| Frequency Range | Probe Position A (A/m) | Probe Position B (A/m) | Probe Position C (A/m) | Probe Position D (A/m) | Probe Position E (A/m) | Limit (A/m) |
|-----------------|------------------------|------------------------|------------------------|------------------------|------------------------|-------------|
| 129.5kHz | 0.41 | 0.52 | 0.38 | 0.47 | 0.39 | 1.63 |

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Test Model No.: PB004



----END OF REPORT----